

# **A Revision of CROSS Security: Proofs and Attacks for Multi-Round Fiat-Shamir Signatures**

---

Edoardo Signorini

Joint work with Michele Battagliola, Federico Pintore, Riccardo Longo, and Giovanni Tognolini

CrypTO Conference 2025 - May 23, 2025

## The scheme:

- Code-based signature scheme.
- Second round candidate in NIST *on-ramp* standardization call.
- Zero-Knowledge protocol + Fiat-Shamir transform.
- Well-known protocol based on decoding random oracle (with **restricted** errors).
- Standard optimization techniques.
- Competitive public-keys size and fast execution.



cross-crypto.com

## The scheme:

- Code-based signature scheme.
- Second round candidate in NIST *on-ramp* standardization call.
- Zero-Knowledge protocol + Fiat-Shamir transform.
- Well-known protocol based on decoding random oracle (with **restricted** errors).
- Standard optimization techniques.
- Competitive public-keys size and fast execution.



cross-crypto.com

## Our contribution:


- Formal security proof for CROSS.
  - EUF-CMA security of Fiat-Shamir transform for special-sound multi-round proofs.
- Novel forgery attack.
  - Improves upon previous attack by Kales and Zaverucha.<sup>1</sup>
  - Security loss up to 24% in worst case.

---

<sup>1</sup>Kales and Zaverucha. "An Attack on Some Signature Schemes Constructed from Five-Pass Identification Schemes". CANS 20.

## (Multi-Round) Interactive Proofs

A binary relation is a set  $R = \{(x, w)\}$  of statement-witness pairs.



### Goal


Prove the knowledge of a witness  $w$  for a public statement  $x$ .

### Digital Signature

We can obtain a digital signature by applying the Fiat-Shamir transform.


# Fiat-Shamir Transform

Transform any public-coin interactive proof into a *non-interactive* proof in the random oracle model.



# Fiat-Shamir Transform

Transform any public-coin interactive proof into a *non-interactive* proof in the random oracle model.



**Idea:** replace the challenge from the verifier with the output of a **random oracle** on the current transcript (add a message to obtain a signature-scheme).

## Completeness

Honest provers (almost) always succeed in convincing a verifier.

## Zero-knowledge

No information about  $w$  is revealed. Usually enough to prove **Honest-Verifier Zero-Knowledge**.

## Knowledge Soundness

Given a dishonest prover  $P^*$  with a success probability greater than the **knowledge error**  $\kappa$ , it is always possible to efficiently extract a witness from  $P^*$ .

## Completeness

Honest provers (almost) always succeed in convincing a verifier.

## Zero-knowledge

No information about  $w$  is revealed. Usually enough to prove **Honest-Verifier Zero-Knowledge**.

## Knowledge Soundness

Given a dishonest prover  $P^*$  with a success probability greater than the **knowledge error**  $\kappa$ , it is always possible to efficiently extract a witness from  $P^*$ .

Knowledge soundness is hard to prove in general and is often implied by the simpler notion of **special soundness**.

## Special Soundness

There is an extracting algorithm which can compute a witness given enough accepting transcript relative to a true statement.




## **Fixed-Weight Repetition of Multi-Round Interactive Proofs**

---

# Parallel Repetition

Many protocols have large knowledge error  $\kappa \approx 1/2$ .


- To build digital signatures, we need the knowledge error to be negligible.



# Parallel Repetition

Many protocols have large knowledge error  $\kappa \approx 1/2$ .


- To build digital signatures, we need the knowledge error to be negligible.
- We can **reduce** the knowledge error of  $\Pi$  by considering the  $t$ -fold parallel repetition  $\Pi^t$  of the protocol.



# Parallel Repetition

Many protocols have large knowledge error  $\kappa \approx 1/2$ .

- To build digital signatures, we need the knowledge error to be negligible.
- We can **reduce** the knowledge error of  $\Pi$  by considering the  $t$ -fold parallel repetition  $\Pi^t$  of the protocol.



## Theorem<sup>2</sup>

If  $\Pi$  is special-sound and has knowledge error  $\kappa$ , then  $\Pi^t$  has knowledge error  $\kappa^t$ .

<sup>2</sup>Attema and Fehr. "Parallel Repetition of  $(\mathbf{r}_1, \dots, \mathbf{r}_\mu)$ -Special-Sound Multi-round Interactive Proofs". CRYPTO 2022, Part I.

- When we build signature schemes from interactive protocols, the size of the signature is typically dominated by the length of the responses.
- Some challenges may be matched by much smaller responses.

# Fixed-Weight Repetition

- When we build signature schemes from interactive protocols, the size of the signature is typically dominated by the length of the responses.
- Some challenges may be matched by much smaller responses.

There is a standard optimization for this scenario:

## $(t, \omega)$ -Fixed-Weight Repetition

Repeat the protocol  $t$  times, with the last challenge sampled from a space with a fixed large weight  $\omega$  of favorable challenges.



Fewer large responses to be sent  $\implies$  smaller signature.



More repetitions  $\implies$  less efficient signing and verification.

# Fixed-Weight Repetition

- When we build signature schemes from interactive protocols, the size of the signature is typically dominated by the length of the responses.
- Some challenges may be matched by much smaller responses.

There is a standard optimization for this scenario:

## $(t, \omega)$ -Fixed-Weight Repetition

Repeat the protocol  $t$  times, with the last challenge sampled from a space with a fixed large weight  $\omega$  of favorable challenges.



Fewer large responses to be sent  $\implies$  smaller signature.



More repetitions  $\implies$  less efficient signing and verification.

## Theorem<sup>3</sup>

The  $(t, \omega)$ -fixed-weight repetition of a special-sound multi-round interactive proof  $\Pi$  is knowledge sound.

---

<sup>3</sup>Battagliola, Longo, Pintore, S., and Tognolini. Security of Fixed-Weight Repetitions of Special-Sound Multi-Round Proofs.

## Theorem

The Fiat-Shamir transform of a knowledge-sound interactive proof is EUFCMA secure.

## Key steps in the proof:

1. Prove security against impersonation under passive attack
2. Show that this implies EUFCMA security with a security loss of at most  $\binom{Q}{\mu}$ .
  - $Q$  is the number of signature queries.
  - $2\mu + 1$  is the number of rounds.

Since the fixed-weight repetition of a special-sound protocol is knowledge sound, we can apply this result to CROSS.



## **Attacking the Parallel Repetition**

---

Critical property required for the attack:

- An adversary can win by guessing **only one** of the two challenges.
- Somewhat surprising but true for most protocols.

Critical property required for the attack:

- An adversary can win by guessing **only one** of the two challenges.
- Somewhat surprising but true for most protocols.

Can be formalized with the notion of **Piecewise Simulatability**:

- Stronger property than HVZK.
- Split the simulator in two algorithms.
- Allows one of the two challenges to be randomly chosen, while the simulator can choose the other challenge and produce a valid transcript.


## The Kales-Zaverucha Attack

In the signature, the lack of interaction and piecewise simulatability can be exploited to split the attack in two **independent** phases:

# The Kales-Zaverucha Attack

In the signature, the lack of interaction and piecewise simulatability can be exploited to split the attack in two **independent** phases:


1. Generates new commitment until  $t^*$  first challenges  $a_i$  are correctly guessed.



# The Kales-Zaverucha Attack

In the signature, the lack of interaction and piecewise simulatability can be exploited to split the attack in two **independent** phases:


1. Generates new commitment until  $t^*$  first challenges  $\alpha_i$  are correctly guessed.
2. Generates responses  $\text{rsp}_1$  until the second challenges  $\beta_i$  are correctly guessed for the remaining  $t - t^*$  repetitions.



# The Kales-Zaverucha Attack

In the signature, the lack of interaction and piecewise simulatability can be exploited to split the attack in two **independent** phases:

1. Generates new commitment until  $t^*$  first challenges  $\alpha_i$  are correctly guessed.
2. Generates responses  $\text{rsp}_1$  until the second challenges  $\beta_i$  are correctly guessed for the remaining  $t - t^*$  repetitions.




# The Kales-Zaverucha Attack

In the signature, the lack of interaction and piecewise simulatability can be exploited to split the attack in two **independent** phases:

1. Generates new commitment until  $t^*$  first challenges  $\alpha_i$  are correctly guessed.
2. Generates responses  $\text{rsp}_1$  until the second challenges  $\beta_i$  are correctly guessed for the remaining  $t - t^*$  repetitions.

Compute final responses  $\text{rsp}_2$ .





## **Attacking the Fixed-Weight Repetition**

---

In the following we will restrict to  $q^2$ -interactive proofs. In particular  $|\text{Ch}[1]| = q$  and  $|\text{Ch}[2]| = 2$ .

# Intuition

In the following we will restrict to  $q2$ -interactive proofs. In particular  $|\text{Ch}[1]| = q$  and  $|\text{Ch}[2]| = 2$ .

## Previous strategy:

- CROSS adapted KZ's attack by taking extra advantage of the fixed-weight challenge of the second round.
  - The second challenge is guessed with the same weight as the actual challenge.

Example with  $t = 10, \omega = 9$ :




In the following we will restrict to  $q2$ -interactive proofs. In particular  $|\text{Ch}[1]| = q$  and  $|\text{Ch}[2]| = 2$ .

**Previous strategy:**

- CROSS adapted KZ's attack by taking extra advantage of the fixed-weight challenge of the second round.
  - The second challenge is guessed with the same weight as the actual challenge.

Example with  $t = 10, \omega = 9$ :



In the following we will restrict to  $q2$ -interactive proofs. In particular  $|\text{Ch}[1]| = q$  and  $|\text{Ch}[2]| = 2$ .

## Previous strategy:

- CROSS adapted KZ's attack by taking extra advantage of the fixed-weight challenge of the second round.
  - The second challenge is guessed with the same weight as the actual challenge.
- This strategy is optimal **only** when  $\omega \approx t/2$ .

Example with  $t = 10, \omega = 9$ :

	First $t^*$ rounds				Last $t - t^*$ rounds					
Guessed $\beta$	1	1	0	1	1	1	1	1	1	1
Actual $\beta$	1	0	1	1	1	1	1	1	1	1

In the following we will restrict to  $q^2$ -interactive proofs. In particular  $|\text{Ch}[1]| = q$  and  $|\text{Ch}[2]| = 2$ .

## Previous strategy:

- CROSS adapted KZ's attack by taking extra advantage of the fixed-weight challenge of the second round.
  - The second challenge is guessed with the same weight as the actual challenge.
- This strategy is optimal **only** when  $\omega \approx t/2$ .

## Improved strategy:

- Select **at least**  $\omega^* \geq \omega$  positions where attacker expects the special challenge.
- When  $\omega \approx t$ , choosing more than  $\omega$  positions gives better results.
  - Making mistakes in a few positions is more efficient than trying to guess perfectly.

Example with  $t = 10, \omega = 9, \omega^* = 10$ :

	First $t^*$ rounds				Last $t - t^*$ rounds					
Guessed $\beta$	1	1	0	1	1	1	1	1	1	1
Actual $\beta$	1	0	1	1	1	1	1	1	1	1
Improved $\beta$	1	1	1	1	1	1	1	1	1	1

Two phases in our improved attack:

1. Try to guess the first challenges  $\alpha_i$  for at least  $t^*$  parallel executions.
2. Try to guess the second challenge for remaining **fixed-weight** executions.
  - **Key improvement:** Select  $\omega^* \geq \omega$  positions for the fixed-weight element.

Still requires *piecewise simulatability* (similar to Kales-Zaverucha attack).

Two phases in our improved attack:

1. Try to guess the first challenges  $\alpha_i$  for at least  $t^*$  parallel executions.
2. Try to guess the second challenge for remaining **fixed-weight** executions.
  - **Key improvement:** Select  $\omega^* \geq \omega$  positions for the fixed-weight element.

Still requires *piecewise simulatability* (similar to Kales-Zaverucha attack).

## Choosing attack parameters:

- The choice of  $t^*$  depends on the size of the challenge sets.
  - Ideally, phase 1 should have a similar cost to phase 2.
- The choice of  $\omega^*$  depends on the choice of  $\omega$  relative to  $t$ .
  - The attack is most effective for very unbalanced parameters.



## Impact on CROSS Parameters

Significant security reduction for *balanced* and *small* parameter sets!

Parameter Set		$t$	$\omega$	Forgery Cost	Loss
CROSS-R-SDP 1	balanced	252	212	120	6%
	small	960	938	97	24%
CROSS-R-SDP 3	balanced	398	340	180	6%
	small	945	907	156	19%
CROSS-R-SDP 5	balanced	507	427	241	6%
	small	968	912	217	15%
CROSS-R-SDP(G) 1	balanced	243	206	123	4%
	small	871	850	108	15%
CROSS-R-SDP(G) 3	balanced	255	176	190	1%
	small	949	914	168	13%
CROSS-R-SDP(G) 5	balanced	356	257	253	1%
	small	996	945	229	11%

Detailed cost analysis: <https://github.com/edoars/revise-cross-parameters>.

## Main results:

- Proved **EUFCMA** security of CROSS.
- Presented a novel forgery attack for the fixed-weight repetition of q2-identification schemes.
- Showed significant security reductions for CROSS parameter sets.
  - *Fast* variant:  $\omega \approx t/2$ , maintains security.
  - *Balanced* and *small* variants:  $\omega$  close to  $t$ , vulnerable.
  - For *small* variant, security loss up to 24%.

## Implications:

- Fixed-weight parameters for CROSS re-chosen for round 2.
- The underlying hard problem is **not affected**.

## Future work:

- Proving optimality of our attack.
- Investigating alternative schemes with different security properties (e.g., **early abort**).

Full paper:



ia.cr/2025/127

**Thank You!**