

# Distributed autonomous encirclement of a wheeled robot formation with collision avoidance

Castioni Edoardo

232250

edoardo.castioni@studenti.unitn.com

Pranzo Massimiliano

233174

massimiliano.pranzo@studenti.unitn.com

Intelligent Distributed Systems  
04 December 2023




**UNIVERSITÀ  
DI TRENTO**  
Dipartimento di  
Ingegneria Industriale



# Table of contents

- Context and goal explanation
- Robot equipment
- Robot localization
- Voronoi tessellation
- Motion control
- Final simulation and results
- Conclusions

# Context and goal explanation




- Goal: Moving target encirclement
- Solution:
  - Localization
  - Exchange information
  - Motion control

# Robot equipment


- Robot: moving circular entity with encumbrance  $\delta$
- Dynamics:
  - Linear  $\bar{x}_{R,i+1} = \bar{x}_{R,i} + \bar{u}_i + \bar{v}_i$
  - Unicycle 
$$\begin{bmatrix} \bar{x}_R \\ \theta_R \end{bmatrix}_{i+1} = \begin{bmatrix} \bar{x}_R \\ \theta_R \end{bmatrix}_i + \begin{bmatrix} \cos(\theta_R) & 0 \\ \sin(\theta_R) & 0 \\ 0 & 1 \end{bmatrix}_i \bar{u}_i + \bar{v}_i$$
- Sensors:
  - GPS:  $\sigma = 3 [m]$
  - Stereo camera / Relative distance sensor:  $\sigma = 0.3 [m]$
  - $R_{\text{com}} = R_{\text{cam}} = 12 [m]$

# Robot localization

## Extended Kalman filter



## Distributed WLS




# Voronoi tessellation


The voronoi cell considers:

- Uncertainty on robot localization (self and reciprocal)
- Robot encumbrance

Voronoi explanation




Initial scenario




# Motion control – High level

- It defines a goal position for the low level control
- Target search: random search of the target
- Target reaching
- Keeping equidistance




Formation control function



Iteration: 1



# Motion control – Low level



Linear Dynamics

$$\bar{x}_{R,i+1} = \bar{x}_{R,i} + \min(k_p (\bar{x}_{R,i} - \bar{x}_D), v_{MAX}) \Delta t$$



Unicycle Dynamics

$$v = \min(k_p \|\bar{x}_R - \bar{x}_D\|, v_{MAX}) \cos(\gamma_m)$$



$$\omega = \min(k_p |\gamma_M|, \omega_{MAX}) \cdot \begin{cases} 1 & (\alpha_D \geq \theta_R \wedge \gamma_M < \pi) \\ -1 & (\alpha_D < \theta_R \wedge \gamma_M > \pi) \\ \text{otherwise} & \end{cases} \vee$$



# Final simulation and results



# Extra results



# Conclusions

- Performed tasks:
  - Localization
  - Information distribution
  - Voronoi tessellation and Motion control
- Improvements:
  - Increase localization accuracy with distributed SLAM
  - Model Predictive Control to enhance the non linear trajectory
  - Environment - adaptive formation function