

Computer Graphics Formulae

Edoardo Riggio

February 1, 2022

Computer Graphics - SA. 2021
Computer Science
Università della Svizzera Italiana, Lugano

Contents

1	Vectors	2
1.1	Dot Product	2
1.2	Cross Product	2
1.3	Magnitude	2
2	Rays and Objects	2
2.1	Ray	2
2.2	Ray-Sphere Intersection	2
2.3	Ray-Cone Intersection	2
2.4	Ray-Triangle Intersection	3
3	Illumination	3
3.1	Diffuse Reflection	3
3.2	Ambient Illumination	3
3.3	Specular Reflection	4
3.4	Blinn-Phong Specular Reflection	4
3.5	Distance Attenuation	4
3.6	Phong Lighting Model	4
3.7	Gamma Correction and Tone Mapping	5
4	Transformations	5
4.1	Translation	5
4.2	Shear	5
4.3	Scale	5
4.4	Rotation	5
4.5	Normal	6
5	Advanced	6
5.1	Snell's Law	6
5.2	Reflection	6
5.3	Refraction	6
5.4	Fresnel Effect	7
6	Transformation Pipeline	7
6.1	Vectors	7
6.2	Viewing Matrix	7
6.3	Projection Matrix	7
7	Texture Pipeline	7
7.1	Normal Mapping	7
7.2	Tangent Space	8

1 Vectors

1.1 Dot Product

$$\langle a, b \rangle = \sum_{i=1}^3 a_i b_i$$

1.2 Cross Product

$$a \times b = \begin{bmatrix} a_2 b_3 - a_3 b_2 \\ a_3 b_1 - a_1 b_3 \\ a_1 b_2 - a_2 b_1 \end{bmatrix}$$

1.3 Magnitude

$$|a| = \sqrt{\sum_{i=1}^3 a_i^2}$$

2 Rays and Objects

2.1 Ray

$$\gamma(t) = o + dt$$

2.2 Ray-Sphere Intersection

$$\begin{aligned} a &= \langle c, d \rangle \\ D &= \sqrt{\|c\|^2 - \langle c, d \rangle^2} \\ t_{1,2} &= \langle c, d \rangle \pm \sqrt{r^2 - D^2} \end{aligned}$$

Where c is the vector from the eye to the center of the sphere, d is the viewing direction, and r is the ray of the circle.

2.3 Ray-Cone Intersection

$$\begin{aligned} a &= d_x^2 + d_z^2 - d_y^2 \\ b &= 2(d_x o_x - d_z o_z - d_y o_y) \\ c &= o_x^2 + o_z^2 - o_y^2 \end{aligned}$$

$$t_{1,2} = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

Where d is the view direction, and o is the position of the eye.

2.4 Ray-Triangle Intersection

$$p = \begin{bmatrix} x \\ y \\ z \end{bmatrix}$$

$$p_i = \begin{bmatrix} x_i \\ y_i \\ z_i \end{bmatrix}$$

$$n = (p_2 - p_1) \times (p_3 - p_1)$$

$$n_i = (p_{i+1} - p) \times (p_{i-1} - p)$$

$$W = \frac{\|n\|}{2}$$

$$w_i = \frac{\|n_i\|}{2} \cdot \text{sign}(\langle n_i, n \rangle)$$

$$\lambda_1(p) = \frac{w_1}{W} \quad \lambda_2(p) = \frac{w_2}{W} \quad \lambda_3(p) = \frac{w_3}{W}$$

Where $\lambda_1(p)$, $\lambda_2(p)$ and $\lambda_3(p)$ are the three barycentric coordinates.

3 Illumination

3.1 Diffuse Reflection

$$I_d = \rho_d \cdot \langle n, l \rangle \cdot I$$

Where ρ_d is the diffuse coefficient, n is the normal vector of the point, l is the vector pointing to the light source, and I is the intensity of the light.

3.2 Ambient Illumination

$$I_a = \rho_a \cdot I$$

Where ρ_a is the ambient coefficient, and I is the ambient light intensity.

3.3 Specular Reflection

$$r = 2n \cdot \langle n, l \rangle - l$$

$$I_s = \rho_s \cdot \langle r, v \rangle^k \cdot I$$

Where n is the normal vector of the point, l is the vector pointing to the light source, ρ_s is the reflection coefficient, r is the reflection ray, v is the viewing direction, k is the shininess of the object, and I is the intensity of the light source.

3.4 Blinn-Phong Specular Reflection

$$h = \frac{1}{2}(l + v)$$

$$I_s = \rho_s \cdot \langle n, h \rangle^{4k} \cdot I$$

Where l is the vector pointing to the light source, v is the viewing direction, ρ_s is the reflection coefficient, n is the normal of the point, h is the bisection vector, k is the shininess of the object, and I is the intensity of the light source.

3.5 Distance Attenuation

$$att(r) = \frac{1}{a_1 + a_2 r + a_3 r^2}$$

Where r is the ray of light, and a_1 , a_2 and a_3 are constant values.

3.6 Phong Lighting Model

$$I = I_e + \rho_a \cdot I_a + \sum_{j=1}^n (\rho_d \cdot \langle n, l_j \rangle + \rho_s \cdot \langle n, h_j \rangle^{4k}) \cdot I_j \cdot att(||l_j||) \cdot s_j(p)$$

Where I_e is the self-emitting intensity, ρ_a is the diffuse coefficient, I_a is the ambient intensity, ρ_d is the diffuse coefficient, n is the normal vector, l is the vector pointing to the light source, ρ_s is the specular coefficient, h is the bisection vector, v is the direction vector, k is the shininess, I_j is the intensity of the j -th light source, and $s_j(p)$ indicates if the point p indicates whether the point is in shadow or not - 1 p is not in shadow, 0 p is in shadow.

3.7 Gamma Correction and Tone Mapping

$$I_{in} = \max((\alpha \cdot I^\beta)^{\frac{1}{\gamma}}, 1.0)$$

Where I_{in} is the input for our display, I is the intensity computed by the Phong model, γ is the gamma coefficient, and α and β are the tone mapping coefficients.

4 Transformations

4.1 Translation

$$T = \begin{bmatrix} 1 & 0 & 0 & t_x \\ 0 & 1 & 0 & t_y \\ 0 & 0 & 1 & t_z \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

4.2 Shear

$$S_{yz} = \begin{bmatrix} 1 & 0 & 0 & 0 \\ d_y & 1 & 0 & 0 \\ d_z & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \quad S_{xz} = \begin{bmatrix} 1 & d_x & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & d_z & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$
$$S_{xy} = \begin{bmatrix} 1 & 0 & d_x & 0 \\ 0 & 1 & d_y & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

4.3 Scale

$$S = \begin{bmatrix} s_x & 0 & 0 & 0 \\ 0 & s_y & 0 & 0 \\ 0 & 0 & s_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

4.4 Rotation

$$R_x = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos \alpha & -\sin \alpha & 0 \\ 0 & \sin \alpha & \cos \alpha & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \quad R_y = \begin{bmatrix} \cos \alpha & 0 & \sin \alpha & 0 \\ 0 & 1 & 0 & 0 \\ -\sin \alpha & 0 & \cos \alpha & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

$$R_z = \begin{bmatrix} \cos \alpha & -\sin \alpha & 0 & 0 \\ \sin \alpha & \cos \alpha & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

4.5 Normal

$$\begin{aligned} n_{new} &= Mn \\ n_{new} &= (M^{-1})^T n \end{aligned}$$

Where M is the transformation matrix. The first equation is used in the case that the transformation preserves angles, otherwise we use the second equations.

5 Advanced

5.1 Snell's Law

$$\frac{\sin \Theta_1}{\sin \Theta_2} = \frac{\delta_1}{\delta_2} = \frac{v_1}{v_2}$$

Where δ is the index of refraction of the medium, and v is the velocity of light in the medium.

5.2 Reflection

$$r = i - 2n \cdot \langle n, i \rangle$$

Where r is the reflection vector, i is the viewing direction, and n is the normal of the point.

5.3 Refraction

$$\begin{aligned} a &= n \cdot \langle n, i \rangle \\ b &= i - a \\ \beta &= \frac{\delta_1}{\delta_2} \\ \alpha &= \sqrt{1 + (1 - \beta^2) \frac{\|b\|^2}{\|a\|^2}} \\ r &= \alpha a + \beta b \end{aligned}$$

Where n is the normal of the vector, i is the viewing direction, and δ is the index of refraction of the medium.

5.4 Fresnel Effect

$$F_{Rl} = \frac{1}{2} \left(\left(\frac{\delta_2 \cos \Theta_1 - \delta_1 \cos \Theta_2}{\delta_2 \cos \Theta_1 + \delta_1 \cos \Theta_2} \right)^2 + \left(\frac{\delta_1 \cos \Theta_1 - \delta_2 \cos \Theta_2}{\delta_1 \cos \Theta_1 + \delta_2 \cos \Theta_2} \right)^2 \right)$$

$$F_{Rf} = 1 - F_{Rl}$$

6 Transformation Pipeline

6.1 Vectors

$$eye = VP$$

$$z' = \frac{VPN}{||VPN||}$$

$$x' = \frac{VUP \times z'}{||VUP|| \times |z'|}$$

$$y' = z' \times x'$$

Where VP is the camera position, VPN is the view plane normal, and VUP is the view up vector

6.2 Viewing Matrix

$$VM = \begin{bmatrix} -x^T & - & -x'^T \cdot eye \\ -y^T & - & -y'^T \cdot eye \\ -z^T & - & -z'^T \cdot eye \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

6.3 Projection Matrix

$$PM = \begin{bmatrix} \frac{1}{r} & 0 & 0 & 0 \\ 0 & \frac{1}{t} & 0 & 0 \\ 0 & 0 & \frac{-2}{f-n} & -\frac{f+n}{f-n} \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

7 Texture Pipeline

7.1 Normal Mapping

$$n_{new} = \begin{bmatrix} n_x \\ n_y \\ n_z \end{bmatrix} = 2 \begin{bmatrix} R \\ G \\ B \end{bmatrix} - \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix}$$

7.2 Tangent Space

$$p_i - p_j = \langle (u_i - u_j), T \rangle + \langle (v_i - v_j), B \rangle$$

$$T = T - \langle N, T \rangle \cdot N$$

$$B = N \times T$$

Where T is the tangent, B is the bitangent, and N is the normal to the point.