


# New goodies in v7.6

- Scalability enhancements (always...)
- File Transfer enhancements
- Grid/Cloud Universe enhancements
- Hierarchical Accounting Groups
- Keyboard detection on Vista/Win7
  - Just put "KBDD" in `Daemon_List`
- Sizeable amount of "Snow Leopard" work...

# Extreme-Makeover - Build system edition!



Thanks Tim, the  
nightmares  
finally stopped



Packaging via CPack, MSI via WiX

# New ClassAds are now in Condor!

- > Library in v7.5 / v7.6
  - Nothing user visible changes (we hope)... well, almost nothing
  - Logan's DAG Priority ?  
 $+JobPrio = DAGManJobId * 100 + NumRestarts$
- > Developers are ready & eager to take leverage new ads in next dev series - but are users ready? Are YOU ready?

# Scalability

## > Everywhere

- DaemonCore optimizations
- Compiler optimizations enabled

## > Schedd

- Shadow recycling
- Reduced fsync frequency (was a disk killer!)
- Daemoncore optimizations
- Reduced protocol overhead between shadows and the schedd
- Asynchronous matchmaking(schedd would be unresponsive for  $O(10s)$ )


## > Collector

- Moving to new classads - richer semantics and about 20% faster
- Optimized classad insertion and removal

## > Grid


- Cream batching

# # of Cores managed by one Condor schedd: 60k



# CHEP 2010 Paper

(slides at <http://tinyurl.com/3nrawrw>)



“Condor  
FASTBALL!”

## An update on the scalability limits of the Condor batch system

D Bradley<sup>1</sup>, T St Clair<sup>1</sup>, M Farrellee<sup>1</sup>, Z Guo<sup>1</sup>, M Livny<sup>1</sup>, I Sfiligoi<sup>2</sup>,  
T Tannenbaum<sup>1</sup>

<sup>1</sup>University of Wisconsin, Madison, WI, USA


<sup>2</sup>University of California, San Diego, La Jolla, CA, USA

E-mail: [dan@hep.wisc.edu](mailto:dan@hep.wisc.edu)



# One Schedd: Maximum sustained job completion rate


(120k subsecond jobs, 'ideal' disk conditions)



# Time spent in the schedd during negotiation

(same test... 1K jobs matched to 10K slot pool)

Schedd responsiveness improvement very noticeable, does other work





# Condor File Transfer Hooks

- By default moves files between submit and execute hosts (shadow and starter).
- **File Transfer Hooks** - can have URLs grab files from anywhere
  - Globus Online, HDFS, all the usual like http:// ...
- New - works for both stage-in and stage-out
- New - now works in VM Universe!
  - **file://** URLs can be used to allow VM disk image files to be pre-staged on execute nodes

# Contribution Modules

<https://condor-wiki.cs.wisc.edu/index.cgi/wiki?p=ContribModules>

- Quill, Stork, Aviary, DBQ, Remote Condor, QMF Management

And LISP, Todd,  
(L I S P) !



# Directory transfer

- Transfer of directories is now supported
- Just list them along with other files to be transferred

transfer\_input\_files = input.txt,scripts,libs

transfer\_output\_files = output.txt,images


# Directory transfer

- When output is auto-detected (i.e. `transfer_output_files` not specified), directories are *ignored*.
- This behavior may change in future versions.

# Directory transfer

- > Works in Condor-C and non-grid universes.
- > Does not currently work for Globus jobs.


# Hierarchical Group Quotas



GROUP\_QUOTA\_physics = 700  
GROUP\_QUOTA\_physics.string\_theory = 100  
GROUP\_QUOTA\_physics.particle\_physics = 600  
GROUP\_QUOTA\_physics.particle\_physics.CMS = 200  
GROUP\_QUOTA\_physics.particle\_physics.ATLAS = 200  
GROUP\_QUOTA\_physics.particle\_physics.CDF = 100

group.sub-  
group.sub-sub-  
group...

# Hierarchical Group Quotas



Groups configured to accept surplus will share it in proportion to their quota.

Here, unused particle physics surplus is shared by ATLAS and CDF.

GROUP\_ACCEPT\_SURPLUS\_physics.particle\_physics.ATLAS = true  
GROUP\_ACCEPT\_SURPLUS\_physics.particle\_physics.CDF = true

# Changed behavior: AUTOREGROUP

- > GROUP\_AUTOREGROUP is not identical to behavior prior to 7.5.6
- > Now it is equivalent to GROUP\_ACCEPT\_SURPLUS
- > Sharing between users in different groups determined by group quotas, *not* user priorities.



# Network Port Usage

- Condor v7.4 needs a lot of open network ports for incoming connections
  - Schedd:  $5 + 5 * \text{NumRunningJobs}$
  - Startd:  $5 + 5 * \text{NumSlots}$
- Not a pleasant firewall situation.
- CCB can make the schedd or the startd (but not both) turn these into outgoing ports instead of incoming

Have Condor listen on just *one*  
port per machine



# condor\_shared\_port

- All daemons on a machine can share one incoming port
  - Simplifies firewall or port forwarding config
  - Improves scalability
  - Running now on both Unix and Windows

USE\_SHARED\_PORT = True

DAEMON\_LIST = ... SHARED\_PORT


# Death to Locks!

## > LOCK\_DEBUG\_LOG\_TO\_APPEND

- Defaults to False on Unix
- Relies on Posix O\_APPEND semantics
- Big gain w/ many running jobs
- Only will lock on rotation

## > CREATE\_LOCKS\_ON\_LOCAL\_DISK

- Defaults to True
- Lock files for event logs to /tmp
- Relief for event logs in user home directories (aka on NFS)
- Next step: only lock on rotation



# Deltacloud Grid Type

- Project sponsored by Red Hat and Apache
- Has its own simple protocol
- Translates requests into protocol of target cloud service
  - Many protocols supported
  - Wider reach than EC2 protocol (e.g. GoGrid, Rackable, RHEV, ...)

# Igor's Talk Last Year...

Condor-G basically insecure!

- It takes a lot of trust to use Condor
  - At least 2 GTN...
- If any ...  
your ...
  - And ...  
... that! You have to log in, right?
- The ... that vanilla Condor  
is much more secure
  - Condor team tells me remote admins can only  
access/modify files in the submit directory

**Fixed!**



Madison, Apr 2010

Igor Sfiligoi

16



# DAGMan

- Condor\_hold/condor\_remove of DAGMan job now works correctly (7.5.6).
- \$MAX\_RETRIES for script argument (7.5.6).
- A bunch of new config macros to match existing condor\_submit\_dag command-line arguments (7.5.6).
- Condor\_hold/condor\_remove of DAGMan job now works correctly (7.5.6).
- Jobstate.log file (7.5.5).
- Node status file (7.5.4).
- The new configuration variable DAGMAN\_MAX\_JOB\_HOLDS specifies the maximum number of times a DAG node job is allowed to go on hold (7.5.4).
- Category throttles in splices can be overridden by higher levels in the DAG splicing structure (7.5.3).
- Lazy creation of submit files for nested DAGs (7.5.2).

Dag-  
WINNING!

