

Adaptive Thresholding Techniques

EECS5330

Image Analysis and Computer Vision

Edris Amin

Kris Armstrong



Overview

Image Binarization


- Global Thresholding
 - applied to the entire image
 - global thresholding has difficulty with images that have:
 - changes in illumination
 - scanning errors
 - low resolution
 - complex documents(mixed text and graphics)
- Variable Thresholding
 - any method that uses more than one threshold for the image
- Adaptive Thresholding
 - uses a local neighborhood to calculate the threshold for each pixel

Binarization Using Thresholding

- Basics
 - Global thresholding.



- Adaptive thresholding



Adaptive Thresholding

- Otsu's Algorithm

- Select Threshold level T
- 2 Sets of pixels S_o, S_b
- Weight & variance
object & background
- Variances: within-set
between-set, total
- Select Threshold for maximum
between-set vs within-set ratio

$$W_o = \sum_{i=1}^T p(i); \quad W_b = \sum_{i=T+1}^L p(i); \quad W_b = 1 - W_o$$

$$\mu_o = \sum_{i=1}^T \frac{ip(i)}{W_o}; \quad \mu_b = \sum_{i=T+1}^L \frac{ip(i)}{W_b}; \quad \mu_T = W_o\mu_o + W_b\mu_b$$

$$\sigma_o^2 = \sum_{i=1}^T \frac{(1 - \mu_o)^2 p(i)}{W_o}; \quad \sigma_b^2 = \sum_{i=T+1}^L \frac{(1 - \mu_b)^2 p(i)}{W_b}$$

$$\sigma_W^2 = \omega_o \sigma_o^2 + \omega_b \sigma_b^2 \quad \sigma_B^2 = \omega_o (\mu_o - \mu_T)^2 + \omega_b (\mu_b - \mu_T)^2$$

$$\sigma_T^2 = \sum_{i=1}^L (i - \mu_T)^2 p(i) \quad \eta = \max_{1 \leq T \leq L} \frac{\sigma_B^2}{\sigma_W^2}$$

- Niblack's Algorithm

- Choose a square scanner
 - size: $b \times b$
- Apply thresholding within square
 -


$$m(x, y) = \frac{1}{b^2} \sum_j \sum_i f(i, j) \quad \sigma^2(x, y) = \frac{1}{b^2} \sum_j \sum_i (m(x, y) - f(i, j))^2$$

$$T(x, y) = m(x, y) + k * \sigma^2(x, y)$$

Adaptive Thresholding

- **Bernsen's Method**

- A classic method that others use for comparison
- Finds threshold of the center pixel, $T(i,j)$, of a $n \times m$ set of pixels by calculating the mean of the maximum and the minimum value of the pixels in the window
- $T(i,j) = 0.5 * \{\max[c(i + x, j + y)] + \min[c(i + x, j + y)]\}$ where x,y iterate over all pixels in the window
- $b(x,y) = 1$ if $[c(i,j) - T(i,j)] > 0$
0 otherwise



Arial,14,italic



Local_Bernsen, S=0.078

Adaptive Thresholding


- **Sauvola Method**

- a hybrid method that adapts the threshold window to either text or graphic types.
- divide the image into small windows and use TD to determine the type of threshold to use
- $TD = [2P(i,j) - [P(i-1,j) + P(i,j-1)]]$ over every $p(i,j)$
- For graphics use:
 - calculate a weighting system based on local histograms
 - use weights to determine the threshold for each pixel
- For text use: (modified Niblack)
 - $T(i,j) = m(i,j) + \{1 + k[\text{var}(i,j) / (R - 1)]\}$
 - R = the dynamic range of the standard deviation


Adaptive Thresholding

- Gato's Method


- Wiener applied Smoothing background



- Binary image using Sauvola's algorithm



- Background image select threshold d



- Apply Thresholding

- $T(i,j) = 1$ for $\{ \text{background}(i,j) - \text{image}(i,j) \} > d$

Adaptive Thresholding

Comparison of Techniques

J. Sauvola, M. Pietikäinen / Pattern Recognition 33 (2000) 225–236

233

Result images and ranked benchmarking evaluation results




Fig. 12. Visual and numeric results on the comparison algorithms applied to illuminated, textual images.

A New Method

[Yu-Ting Pai, et. al.]

- Problems with current Adaptive Thresholding methods
 - Recursive → Time + Memory + Computation

- Fusion

- Smoothing
- Select box size
- Segment Image
- Threshold segments


- Computational Complexity

- M x N size, L levels, b block size

Otsu: $MN + 7L^2 + 5L - 12$

Niblack: $(4b^2 + 3)MN$

Fusion: $N(M-1)$



References

B. Gatos, I. Pratikakis, S.J. Perantonis

"Adaptive degraded document image binarization"

Sept. 2005 The Journal of the Pattern Recognition Society

Yu-Ting Pai, Yi-Fan Chang, Shanq-Jang Ruan

"Adaptive thresholding algorithm: Efficient computation technique based on intelligent block detection for degraded document images"

2010 The Journal of the Pattern Recognition Society

R.C. Gonzales, R.E. Woods

Digital Image Processing Third Edition

2008 Prentice Hall

References

- J. Brensen "Dynamic Thresholding of Gray Level Images," ICPR'86 Proc. Intl. Patt. Recog., pp 1251-1255 (1986)
- J. Sauvalo and M. Pietaksinen, "Adaptive Document Image Binarization," Pattern Recog., 33 pp.225 - 236 (2000)
- N. B. Venkateswarluh and R.D. Boyle, "New segmentation techniques for document images," Image Vis. comput. 13 pp. 573 - 583 (1995)