



Beige / Beige

Taupé / Taupe

Ficha Técnica Technical Specifications Piso Gres / Gres Floor Tile

Formato / Size:

55 x 55 cm / 22" x 22"

54 x 54 cm Rectificado / 21,2" x 21,2" Rectified

[Link: Pasta blanca vs. Pasta Roja](#)



	Separación de boquilla / Grout separation	4 mm sin rect. / 2 mm rect.			
	P.E.I.	2 (Tráfico: Medio)			
	Tono y Textura Mezclada / Shade and Texture Mixture	Alto / High			
	Resistencia al ataque químico / Chemical Resistance	Conforme / Compliant	A.S.T.M. C650		
	Coeficiente Dinámico de Fricción / DCOF	≥ 0.42	A.S.T.M. C1028		
	Absorción de agua / Water absorption	3 - 7 %	A.S.T.M. C373		
	MOHS	5 - 8	A.S.T.M. C1028		
	Resistencia a la flexión / Breaking Strength	≥ 250kg / 551 lbs	ISO 10545-4		
	Resistencia al shock térmico / Thermal Shock Resistance	Conforme / Compliant	A.S.T.M. C484		
	Resistencia a helada / Frost Resistance	Conforme / Compliant	A.S.T.M. C1026		
	Resistencia a las manchas / Stain Resistance	Conforme / Compliant	A.S.T.M. C1378		
	Resistencia a la abrasión / Abrasion Resistance	Conforme / Compliant	ANSI A137		
	Información de Embalaje / Packaging Information	FORMATO / SIZE	PZS-CAJA / PCS-BOX	M ² -CAJA / FT ² -BOX	KG-CAJA / LBS-BOX
		55 x 55 cm 22" x 22"	5	1.5 / 16.14	29.90 / 65.91

Cesantoni S.A. de C.V. certifica que los resultados anteriores fueron obtenidos en análisis de laboratorio elaborado por el departamento de Control de Calidad. Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.