

Architectural Specification — TIGRA



Line Array

The loudspeaker shall be a self-powered, linear, low-distortion, line array loudspeaker. Its transducers shall include one 4-inch diaphragm compression driver coupled to a constant-directivity horn through a manifold, and two 10-inch long-excursion cone drivers.

The loudspeaker shall incorporate internal processing and a 2-channel class-D amplifier. Protection circuits shall include TruPower limiting. The analog audio input shall be electronically balanced with a 10 k Ω impedance and accept a nominal 0 dBV (1.0 V rms) signal. Analog audio connectors shall be Neutrik XLR 3-pin TOP (True Outdoor Protection) airtight female input with male loop output with captive sealing caps. The digital audio input format shall be Milan AVB (avnu.org). The connectors shall be two Neutrik RJ45 etherCON TOP (True Outdoor Protection) airtight network inputs with captive sealing caps.

Performance specifications for a typical production unit shall be as follows, measured at 1/3-octave resolution:

- For all models, the operating frequency range shall be 55 Hz – 16 kHz.
- TIGRA-L: The maximum sound level shall be 146 dB measured in free-field at 4 m referred to 1 m using noise. In accordance with AES75-2022, the following maximum linear sound levels shall be measured in free-field at 4 m, referred to 1 m: 122 dBz, 140.5 dBzpk, with an RMS input level of +4 dBV.
- TIGRA-W: The maximum sound level shall be 145 dB, measured in free-field at 4 m referred to 1 m using noise. In accordance with AES75-2022, the following maximum linear sound levels shall be measured in free-field at 4 m, referred to 1 m: 121 dBz, 139.5 dBzpk, with an RMS input level of +3 dBV.

The internal power supply shall perform EMI filtering, soft current turn-on, and surge suppression. Power requirements shall be nominal 100-240V~, 50-60Hz. Power shall be 550 W maximum long-term continuous (>10 seconds). The AC power connector shall be a Neutrik powerCON® TRUE1 Chassis Connector NAC3PX-TRUE1 sealed power connector.

Components shall be mounted in an optimally tuned, vented enclosure constructed of premium multi-ply birch and coated with a slightly textured black finish. The enclosure shall include end frames with captive GuideALinks for linking units in vertical arrays at splay angles from 0.5° to 10°. The front protective grille shall be powder-coated stamped steel. Dimensions shall be 33.92 in (862 mm) wide, 12.76 in (324 mm) high, and 22.25 in (565 mm) deep. Weight shall be 120 lb (54 kg). The IP rating shall be IP55 when connected to cables terminated with Neutrik powerCON® TRUE1 cable connectors or when the connector sealing caps are in place.

The 85° coverage medium-format line array loudspeaker shall be the Meyer Sound TIGRA-L.

The 110° coverage medium-format line array loudspeaker shall be the Meyer Sound TIGRA-W.

Meyer Sound Laboratories, Inc. +1 510 486.1166
2832 San Pablo Avenue meyersound.com/contact
Berkeley, CA 94702 meyersound.com

Architectural Specification — TIGRA
PN: 18.336.140.01 C 2605
Copyright © 2026
All Rights Reserved