

Operating Instructions — USW-210P



Subwoofer



[Safety Instructions — Meyer Sound
Products](#)



[Safety Instructions — QuickFly
Rigging](#)

The USW-210P compact narrow subwoofer provides robust, extended low-frequency response for installed sound applications that require convincing bass impact from a slender, low-profile loudspeaker. Its dual-driver configuration permits a narrow form factor that fits into restricted architectural spaces to produce output levels equal to or exceeding systems with single 12-inch (or larger) drivers. Its slanted connector panel enables flush-mounting the cabinet against wall surfaces, reducing required installation depth to 12 inches (30.5 cm), including connectors.

The USW-210P subwoofer is ideal for installations requiring high performance and versatility along with an appealing, discreet aesthetic appearance. The USW-210P integrates easily with other Meyer Sound loudspeaker systems, such as CAL™ and ULTRA Series loudspeakers.

The USW-210P has an operating frequency range of 30–140 Hz with a linear peak SPL of 126 dB (measured in half-space at 4 m and referred to 1m using M-noise). The long skinny bass reflex cabinet employs the same port design as Meyer Sound's flagship 1100-LFC low-frequency control element for high efficiency and low port distortion.



USW-210P Slanted Connector Panel

Meyer Sound Laboratories, Inc. +1 510 486.1166
2832 San Pablo Avenue meyersound.com/contact
Berkeley, CA 94702 meyersound.com

Operating Instructions — USW-210P
Copyright © 2026
All Rights Reserved