LPI 109.2 - Persistent network configuration

Curs 2021 - 2022

ASIX M01-ISO 109 Networking Fundamentals

Persistent network configuration

Description

Key concepts:
- ❏ Understand basic TCP/IP host configuration.
- ❏ Configure ethernet and wi-fi network using NetworkManager.
- ❏ Awareness of systemd-networkd.

Commands and files:
- ❏ /etc/hostname
- ❏ /etc/hosts
- ❏ /etc/nsswitch.conf
- ❏ /etc/resolv.conf
- ❏ nmcli
- ❏ hostnamectl
- ❏ ifup
- ❏ ifdown

TCP/IP Configuration

Configuration:
- ● interficies
  - ○ eth0 enp1s0 (wired)
  - ○ wlp0s0 (wifi)
  - ○ loopback lo 127.0.0.1
  - ○ virtual VM bridges virbr0
- ● IP address / Mask
- ● gateway
- ● Resolver DNS

Interfaces

The main purpose of a network interface is to provide a route through which local data can be sent and remote data can be received. The the operating system uses the loopback interface when it needs to establish a connection with itself

Transmission Control Protocol (TCP) provides connection-oriented service between two applications exchanging data. To configure a network port, or interface, on legacy systems, use the ifconfig command.

This command is used for the following functions:
- Assigning static IP address
- Viewing current network configuration
- Setting the netmask
- Setting the broadcast address
- Enable/disable network interfaces

```
ifconfig [INTERFACE] [OPTIONS]
```

- ifconfig
- ifconfig device
- ifconfig device IP netmask mask [broadcast brd]

Fedora home example:
```
$ ifconfig
br-38fb360b0b9f: flags=4099<UP,BROADCAST,MULTICAST>  mtu 1500
        inet 192.168.49.1  netmask 255.255.255.0  broadcast 192.168.49.255
        ether 02:42:4c:8f:03:67  txqueuelen 0  (Ethernet)
        RX packets 0  bytes 0 (0.0 B)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 0  bytes 0 (0.0 B)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

docker0: flags=4099<UP,BROADCAST,MULTICAST>  mtu 1500
        inet 172.17.0.1  netmask 255.255.0.0  broadcast 172.17.255.255
        inet6 fe80::42:a1ff:fe60:ffcc  prefixlen 64  scopeid 0x20<link>
        ether 02:42:a1:60:ff:cc  txqueuelen 0  (Ethernet)
        RX packets 18127  bytes 952046 (929.7 KiB)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 29020  bytes 61685421 (58.8 MiB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

enp1s0: flags=4099<UP,BROADCAST,MULTICAST>  mtu 1500
        ether c0:18:50:14:97:b3  txqueuelen 1000  (Ethernet)
        RX packets 0  bytes 0 (0.0 B)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 0  bytes 0 (0.0 B)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING>  mtu 65536
        inet 127.0.0.1  netmask 255.0.0.0
        inet6 ::1  prefixlen 128  scopeid 0x10<host>
        loop  txqueuelen 1000  (Local Loopback)
        RX packets 48  bytes 5307 (5.1 KiB)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 48  bytes 5307 (5.1 KiB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

virbr0: flags=4099<UP,BROADCAST,MULTICAST>  mtu 1500
        inet 192.168.122.1  netmask 255.255.255.0  broadcast 192.168.122.255
        ether 52:54:00:6c:e0:04  txqueuelen 1000  (Ethernet)
        RX packets 289  bytes 26902 (26.2 KiB)
        RX errors 0  dropped 0  overruns 0  frame 0
```

```
        TX packets 396  bytes 50583 (49.3 KiB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

wlp0s20f3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500
        inet 192.168.1.45  netmask 255.255.255.0  broadcast 192.168.1.255
        inet6 fe80::2062:d7b2:5a59:f895  prefixlen 64  scopeid 0x20<link>
        ether 84:1b:77:00:78:c8  txqueuelen 1000  (Ethernet)
        RX packets 1241115  bytes 1771487246 (1.6 GiB)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 551534  bytes 75079937 (71.6 MiB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0
```

```
$ ifconfig lo
lo: flags=73<UP,LOOPBACK,RUNNING>  mtu 65536
        inet 127.0.0.1  netmask 255.0.0.0
        inet6 ::1  prefixlen 128  scopeid 0x10<host>
        loop  txqueuelen 1000  (Local Loopback)
        RX packets 48  bytes 5307 (5.1 KiB)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 48  bytes 5307 (5.1 KiB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

$ ifconfig enp1s0
enp1s0: flags=4099<UP,BROADCAST,MULTICAST>  mtu 1500
        ether c0:18:50:14:97:b3  txqueuelen 1000  (Ethernet)
        RX packets 0  bytes 0 (0.0 B)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 0  bytes 0 (0.0 B)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0
```

```
$ sudo ifconfig eth0 up

$ sudo ifconfig eth0 192.168.1.3

$ sudo ifconfig eth0 netmask 255.255.255.192

$ sudo ifconfig eth0 broadcast 192.168.1.63

$ sudo ifconfig eth0 down
```

ip address

Debian example:

```
pue@debian:~$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen
1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
       valid_lft forever preferred_lft forever
2: ens3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP group
default qlen 1000
    link/ether 52:54:00:b3:03:02 brd ff:ff:ff:ff:ff:ff
    inet 172.16.5.2/24 brd 172.16.5.255 scope global dynamic noprefixroute ens3
       valid_lft 2985sec preferred_lft 2985sec
    inet6 fe80::5054:ff:feb3:302/64 scope link noprefixroute
       valid_lft forever preferred_lft forever
3: docker0: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1500 qdisc noqueue state DOWN group
default
    link/ether 02:42:55:12:02:45 brd ff:ff:ff:ff:ff:ff
    inet 172.17.0.1/16 brd 172.17.255.255 scope global docker0
       valid_lft forever preferred_lft forever
```

nmcli device

```
# nmcli device
DEVICE   TYPE         STATE           CONNECTION
ens3     ethernet   conectado   Wired connection 1
docker0  bridge        sin gestión   --
lo       loopback   sin gestión   --
```

Setting the hostname

The hostname is used to identify the system by applications such as web servers:
- /etc/hostname
- /etc/sysconfig/network (legacy)

hostname command

- hostname [-s -f]
- short hostname / FQDN Fully Qualified Domain Name
- setting the hostname using the hostname command results in a change that is only persistent until the next system boot.

```
$ hostname
localhost.localdomain

$ hostname
buster-64
```

hostnamectl command

Systemd systems use an alternative to the hostname command, the hostnamectl command. provides additional categories for hostnames; static, pretty, and transient:

Static:
A static hostname is limited to [a-z], [0-9], hyphen -, and period . characters (no spaces i.e., localhost or ndg-server). This hostname is stored in the /etc/hostname file. Static hostnames can be set by a user.

Pretty:
Hostname can be in a human-readable format using any valid UTF-8 characters and can include special characters (i.e., Sarah's Laptop or Joe's Home PC).

Transient:
The transient hostname is a dynamic hostname usually set by the kernel to localhost by default. A dynamic hostname can be modified if needed. The transient hostname can be modified by DHCP or mDNS at runtime.

Hostnames can be up to 64 characters, but it is recommended that static and transient hostnames are limited to only 7 bit ASCII lowercase characters with no spaces or dots and conforming to strings acceptable for DNS domain names.

- hostnamectl
- hostnamectl status
- hostnamectl set-hostname

If neither the --pretty nor --transient option is used, then all three hostname types will be set to the given name. To set the static hostname, but not the pretty and transient names, the option --static should be used instead. In all cases, only the static hostname is stored in the /etc/hostname file.

```
$ hostnamectl
   Static hostname: localhost.localdomain
         Icon name: computer-laptop
           Chassis: laptop
        Machine ID: f8bff953853f56b4963ed3aa06461c80
           Boot ID: 022e36fa92be4213a4ea82fa4eb8d128
  Operating System: Fedora 32 (Workstation Edition)
       CPE OS Name: cpe:/o:fedoraproject:fedora:32
            Kernel: Linux 5.11.22-100.fc32.x86_64
      Architecture: x86-64
```

```
$ sudo hostnamectl set-hostname mylaptop

$ hostname
mylaptop

$ sudo hostnamectl set-hostname mylaptop.edt.org

$ hostname
mylaptop.edt.org

$ hostname -s
mylaptop

$ cat /etc/hostname
mylaptop.edt.org
```

Configuring DNS

- static (files) : /etc/hosts
- dinàmic (dns): /etc/resolv.conf
- /etc/nsswitch

The DNS (Domain Name System) is the mapping table for the internet, allowing any computer or device to access by using a name instead of an IP address. The DNS implementation is based on a distributed database of network names and IP addresses and query interfaces to retrieve information.

/etc/hosts

- static hostnames resolution

```
$ cat /etc/hosts
127.0.0.1   localhost localhost.localdomain localhost4 localhost4.localdomain4
::1         localhost localhost.localdomain localhost6 localhost6.localdomain6
192.168.122.28  centos20
172.17.0.1      ldap.edt.org
```

/etc/resolv.conf

- The /etc/resolv.conf file is the configuration file for DNS resolvers (the client DNS part). The information in this file is normally set up by network initialization scripts.

- The configuration directives used in this file are:
    - nameserver
        - IP address of the name server that the resolver will use
        - Maximum of 3 servers can be listed
    - domain
        - Domain name to be used locally
    - search
        - Search list to be used for hostname lookup
    - sortlist
        - Allow addresses to be sorted
        - The list is specified by IP addresses and optionally the netmask
    - options
        - Used to modify the resolver's internal variables using certain keywords
        - E.g. attempts: 3 will set the retry count for querying the name servers to 3

```
$ cat /etc/resolv.conf
# Generated by NetworkManager
search Home edt.org
nameserver 80.58.61.250
nameserver 80.58.61.254
```

/etc/nsswitch

The Name Service Switch (NSS) is used by the system administrator to specify which name information source (i.e., local files, LDAP, etc.) to use for different categories (i.e., passwd, shadow, hosts, etc.), and in which order the sources are searched.

The /etc/nsswitch.conf file is used to store the information used for name service switching. It is a text file with columns that contain the following information:
- Database name
- Lookup order of sources
- Actions permitted for the lookup result

Example fragment of /etc/nsswitch

```
passwd:     sss files systemd
shadow:     files sss
group:      sss files systemd

#hosts:     db files nisplus nis dns
hosts:      files mdns4_minimal [NOTFOUND=return] dns myhostname
```

By changing the order of the name services listed for a particular database, like hosts, the administrator could change whether the local /etc/hosts file is consulted before or after the DNS servers listed in /etc/resolv.conf.

```
hosts:       files dns
```

```
hosts:        dns files
```

```
hosts: dns [NOTFOUND=return] files
```

Routing Table

Routing tables are used by the kernel to store information about how to reach a network directly or indirectly. The route and ip route command is used to view, as well as update, the IP routing table.

Static routes in the kernel's routing table can be set using the route or ip route commands.

route command

Destination   Destination host or network
Gateway   IP address of the gateway
               0.0.0.0 means "no route, broadcast on this network"
Genmask   Subnet mask for the destination network
               Set to 0.0.0.0 for the default route
Flags   Values include C (cache entry), G (use gateway) and U (up)
Metric   Number of hops to the target, used as a measure of distance
Ref   Number of references to this route; this is not used in Linux
Use   Count of lookups done for this route
Iface   Interface to use for sending packets for this route

```
$ route
Kernel IP routing table
Destination     Gateway         Genmask         Flags Metric Ref    Use Iface
default         _gateway        0.0.0.0         UG    600    0        0 wlp0s20f3
172.17.0.0      0.0.0.0         255.255.0.0     U     0      0        0 docker0
192.168.1.0     0.0.0.0         255.255.255.0   U     600    0        0 wlp0s20f3
192.168.49.0    0.0.0.0         255.255.255.0   U     0      0        0 br-38fb360b0b9f
192.168.122.0   0.0.0.0         255.255.255.0   U     0      0        0 virbr0
```

```
$ sudo route add -net 192.56.78.0 netmask 255.255.255.0 gw 192.168.1.1 dev eth0
```

```
$ sudo route add default gw 192.168.1.1

$ sudo route del -net 192.56.78.0 netmask 255.255.255.0 gw 192.168.1.1 dev eth0

$ sudo route del default gw 192.168.1.1
```

Network Interfaces

The term network interface refers to the point of connection between a computer and a network. It can be implemented in either hardware or software. The network interface card (NIC) is an example of the hardware interface, while the loopback interface (127.0.0.1) is an example of the software interface.

Examine network interface information:

```
$ lspci  -v -s 01:00.0
01:00.0 Ethernet controller: Realtek Semiconductor Co., Ltd. RTL8111/8168/8411 PCI
Express Gigabit Ethernet Controller (rev 15)
        Subsystem: Lenovo Device 3852
        Flags: bus master, fast devsel, latency 0, IRQ 16
        I/O ports at 2000 [size=256]
        Memory at 81304000 (64-bit, non-prefetchable) [size=4K]
        Memory at 81300000 (64-bit, non-prefetchable) [size=16K]
        Capabilities: <access denied>
        Kernel driver in use: r8169
        Kernel modules: r8169

$ modinfo r8169
filename:
/lib/modules/5.11.22-100.fc32.x86_64/kernel/drivers/net/ethernet/realtek/r8169.ko.xz
firmware:       rtl_nic/rtl8125b-2.fw
firmware:       rtl_nic/rtl8125a-3.fw
...

$ lsmod | grep r8169
r8169                 102400  0

$ lshw -c network
        description: Ethernet interface
        product: RTL8111/8168/8411 PCI Express Gigabit Ethernet Controller
        vendor: Realtek Semiconductor Co., Ltd.
        physical id: 0
        bus info: pci@0000:01:00.0
        logical name: enp1s0
        version: 15
        serial: c0:18:50:14:97:b3
        capacity: 1Gbit/s
        width: 64 bits
        clock: 33MHz
        capabilities: bus_master cap_list ethernet physical tp mii 10bt 10bt-fd 100bt
100bt-fd 1000bt-fd autonegotiation
        configuration: autonegotiation=on broadcast=yes driver=r8169
driverversion=5.11.22-100.fc32.x86_64 firmware=rtl8168h-2_0.0.2 02/26/15 latency=0
link=no multicast=yes port=twisted pair
        resources: irq:16 ioport:2000(size=256) memory:81304000-81304fff
memory:81300000-81303fff

$ dmesg | grep r8169
[    7.685183] libphy: r8169: probed
[    7.685348] r8169 0000:01:00.0 eth0: RTL8168h/8111h, c0:18:50:14:97:b3, XID 541, IRQ
```

```
129
[    7.685352] r8169 0000:01:00.0 eth0: jumbo features [frames: 9194 bytes, tx
checksumming: ko]
[    7.780189] r8169 0000:01:00.0 enp1s0: renamed from eth0
[   12.117117] Generic FE-GE Realtek PHY r8169-100:00: attached PHY driver
(mii_bus:phy_addr=r8169-100:00, irq=IGNORE)
[   12.282200] r8169 0000:01:00.0 enp1s0: Link is Down
```

Device information:

RX errors	Number of received packets which were damaged
RX dropped	Number of packets dropped due to reception errors
RX overruns	Number of received packets which experienced data overrun
RX frame	Number of received packets which experienced frame errors
TX errors	Number of packets which experienced data transmission errors
TX dropped	Number of packets dropped due to transmission errors
TX overruns	Number of transmitted packets which experienced data overrun
TX carriers	Number of transmitted packets which experienced loss of carriers
TX collisions	Number of transmitted packets which experienced Ethernet collisions possibly due to network congestion

```
$ ifconfig enp1s0
enp1s0: flags=4099<UP,BROADCAST,MULTICAST>  mtu 1500
        ether c0:18:50:14:97:b3  txqueuelen 1000  (Ethernet)
        RX packets 0  bytes 0 (0.0 B)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 0  bytes 0 (0.0 B)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

$ ip -s a show enp1s0
2: enp1s0: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1500 qdisc fq_codel state DOWN group
default qlen 1000
    link/ether c0:18:50:14:97:b3 brd ff:ff:ff:ff:ff:ff
    RX: bytes  packets  errors  dropped overrun mcast
    0          0        0       0       0       0
    TX: bytes  packets  errors  dropped carrier collsns
    0          0        0       0       0       0
```

Interface Names

Older Linux distributions named ethernet network interfaces as eth0, eth1, etc., numbered according to the order in which the kernel identifies the devices. The wireless interfaces were named wlan0, wlan1, etc. This naming convention, however, does not clarify which specific ethernet port matches with the interface eth0, for example. Depending on how the hardware was detected, it was even possible for two network interfaces to swap names after a reboot.

In Linux distributions that use the systemd naming scheme, all interface names start with a two-character prefix that signifies the interface type:

en	Ethernet
ib	InfiniBand
sl	Serial line IP (slip)
wl	Wireless local area network (WLAN)
ww	Wireless wide area network (WWA

From higher to lower priority, the following rules are used by the operating system to name and number the network interfaces:

1. Name the interface after the index provided by the BIOS or by the firmware of embedded devices, e.g. eno1.
2. Name the interface after the PCI express slot index, as given by the BIOS or firmware, e.g. ens1.
3. Name the interface after its address at the corresponding bus, e.g. enp3s5.
4. Name the interface after the interface's MAC address, e.g. enx78e7d1ea46da.
5. Name the interface using the legacy convention, e.g. eth0.

```
network interface enp3s
device address 03:05.0

$ lspci | fgrep Ethernet
03:05.0 Ethernet controller: Realtek Semiconductor Co., Ltd. RTL-8110SC/8169SC Gigabit
Ethernet (rev 10)
```

Red Hat Interface Configuration

- /etc/sysconfig/network (legacy)
- /etc/sysconfig/network-scripts/ifcfg-<interface-name>
- static configuration
- dynamic configuration via DHCP

```
# cat /etc/sysconfig/network-scripts/ifcfg-lo
DEVICE=lo
IPADDR=127.0.0.1
NETMASK=255.0.0.0
NETWORK=127.0.0.0
# If you're having problems with gated making 127.0.0.0/8 a martian,
# you can change this to something else (255.255.255.255, for example)
BROADCAST=127.255.255.255
ONBOOT=yes
NAME=loopback
```

```
# cat /etc/sysconfig/network-scripts/ifcfg-enp1s0
TYPE=Ethernet
PROXY_METHOD=none
BROWSER_ONLY=no
BOOTPROTO=dhcp
DEFROUTE=yes
IPV4_FAILURE_FATAL=no
IPV6INIT=yes
IPV6_AUTOCONF=yes
IPV6_DEFROUTE=yes
IPV6_FAILURE_FATAL=no
IPV6_ADDR_GEN_MODE=stable-privacy
NAME=enp1s0
UUID=a5606faa-358c-3f2d-a032-cd423a68f4c7
ONBOOT=yes
AUTOCONNECT_PRIORITY=-999
DEVICE=enp1s0
```

```
# cat /etc/sysconfig/network-scripts/ifcfg-MiFibra-13C3
ESSID=MiFibra-13C3
MODE=Managed
KEY_MGMT=WPA-PSK
SECURITYMODE=open
MAC_ADDRESS_RANDOMIZATION=default
TYPE=Wireless
PROXY_METHOD=none
BROWSER_ONLY=no
BOOTPROTO=dhcp
DEFROUTE=yes
IPV4_FAILURE_FATAL=no
IPV6INIT=yes
IPV6_AUTOCONF=yes
IPV6_DEFROUTE=yes
IPV6_FAILURE_FATAL=no
IPV6_ADDR_GEN_MODE=stable-privacy
NAME=MiFibra-13C3
UUID=02541f08-fdc8-4203-ad21-4a3aef3acd0b
DEVICE=wlp0s20f3
ONBOOT=yes
```

Debian Interface configuration

- /etc/network/interfaces
- /etc/network/interfaces.d

```
pue@debian:~$ cat /etc/network/interfaces
# This file describes the network interfaces available on your system
# and how to activate them. For more information, see interfaces(5).

source /etc/network/interfaces.d/*

# The loopback network interface
auto lo
iface lo inet loopback

root@debian:/home/pue# locate ens3
/var/lib/NetworkManager/dhclient-a8ae621c-26dd-4ff8-a18d-4bfc29f2ebd5-ens3.lease
/var/lib/NetworkManager/dhclient-ens3.conf

root@debian:/home/pue# cat /var/lib/NetworkManager/dhclient-ens3.conf
# Creado por NetworkManager
# Mezclado de /etc/dhcp/dhclient.conf
option rfc3442-classless-static-routes code 121 = array of unsigned integer 8;
#send dhcp-client-identifier 1:0:a0:24:ab:fb:9c;
#send dhcp-lease-time 3600;
#supersede domain-name "fugue.com home.vix.com";
#prepend domain-name-servers 127.0.0.1;
#require subnet-mask, domain-name-servers;
#timeout 60;
#retry 60;
#reboot 10;
#select-timeout 5;
#initial-interval 2;
#script "/sbin/dhclient-script";
#media "-link0 -link1 -link2", "link0 link1";
#reject 192.33.137.209;
send host-name "debian"; # added by NetworkManager

option rfc3442-classless-static-routes code 121 = array of unsigned integer 8;
option ms-classless-static-routes code 249 = array of unsigned integer 8;
option wpad code 252 = string;

request; # override dhclient defaults
also request subnet-mask;
```

```
also request broadcast-address;
also request time-offset;
also request routers;
also request domain-name;
also request domain-name-servers;
also request domain-search;
also request host-name;
also request dhcp6.name-servers;
also request dhcp6.domain-search;
also request dhcp6.fqdn;
also request dhcp6.sntp-servers;
also request netbios-name-servers;
also request netbios-scope;
also request interface-mtu;
also request rfc3442-classless-static-routes;
also request ntp-servers;
also request ms-classless-static-routes;
also request static-routes;
also request wpad;
also request root-path;
```

```
# cat /etc/networks
default         0.0.0.0
loopback        127.0.0.0
link-local      169.254.0.0
```

Example dynamic configuration:

```
auto lo
iface lo inet loopback

auto enp3s5
iface enp3s5 inet dhcp
```

Example static configuration

```
iface enp3s5 inet static
       address 192.168.1.2/24
       gateway 192.168.1.1
```

Network Tools: NetworkManager and iproute2

Network Manager

NetworkManager provides automatic detection and configuration of network interfaces on a Linux system. It works for both wired and wireless interfaces as well as having support for some modems and Virtual Private Network (VPN) connections.

NetworkManager uses the network management command line interface nmcli tool to manage network connections and display information about devices on a network. The nmcli command uses the following syntax:

```
nmcli [OPTIONS] OBJECT [COMMAND][ARGUMENTS...]
```

The OBJECT field can be one of the following:

    general

        Display information about or modify the status of NetworkManager.

    networking

        Display information about or modify the network managed by NetworkManager.

    connection

        Display information about or modify connections managed by NetworkManager.

    device

        Display information about or modify devices managed by NetworkManager.

    radio

        Display the status of, and enable or disable, the radio switches.

```
[root@mylaptop ~]# nmcli general
STATE       CONNECTIVITY  WIFI-HW  WIFI     WWAN-HW  WWAN
connected  full          enabled  enabled  enabled  enabled
```

```
root@debian:/home/pue# nmcli device
DEVICE    TYPE       STATE          CONNECTION
ens3      ethernet   conectado      Wired connection 1
docker0   bridge     sin gestión    --
lo        loopback   sin gestión    --

[root@localhost ~]# nmcli device
DEVICE              TYPE        STATE          CONNECTION
wlp0s20f3           wifi        connected      MOVISTAR_5AF0
docker0             bridge      connected      docker0
br-38fb360b0b9f     bridge      connected      br-38fb360b0b9f
virbr0              bridge      connected      virbr0
p2p-dev-wlp0s20f3   wifi-p2p    disconnected   --
enp1s0              ethernet    unavailable    --
vboxnet0            ethernet    unmanaged      --
lo                  loopback    unmanaged      --
virbr0-nic          tun         unmanaged      --

root@debian:/home/pue# nmcli device show ens3
GENERAL.DEVICE:                        ens3
GENERAL.TYPE:                          ethernet
GENERAL.HWADDR:                        52:54:00:B3:03:02
GENERAL.MTU:                           1500
GENERAL.STATE:                         100 (conectado)
GENERAL.CONNECTION:                    Wired connection 1
GENERAL.CON-PATH:
/org/freedesktop/NetworkManager/ActiveConnection/1
WIRED-PROPERTIES.CARRIER:              encendido
IP4.ADDRESS[1]:                        172.16.5.2/24
IP4.GATEWAY:                           172.16.5.254
IP4.ROUTE[1]:                          dst = 0.0.0.0/0, nh = 172.16.5.254, mt = 100
IP4.ROUTE[2]:                          dst = 172.16.5.0/24, nh = 0.0.0.0, mt = 100
IP4.DNS[1]:                            172.16.5.254
IP4.DOMAIN[1]:                         class.local
IP6.ADDRESS[1]:                        fe80::5054:ff:feb3:302/64
IP6.GATEWAY:                           --
IP6.ROUTE[1]:                          dst = fe80::/64, nh = ::, mt = 100
IP6.ROUTE[2]:                          dst = ff00::/8, nh = ::, mt = 256, table=255
```

```
[root@localhost ~]# nmcli -p connection show enp1s0
===============================================================================
                    Connection profile details (enp1s0)
```

```
================================================================================
connection.id:                       enp1s0
connection.uuid:                      a5606faa-358c-3f2d-a032-cd423a68f4c7
connection.stable-id:                 --
connection.type:                      802-3-ethernet
connection.interface-name:            enp1s0
connection.autoconnect:               yes
connection.autoconnect-priority:      -999
connection.autoconnect-retries:       -1 (default)
connection.multi-connect:             0 (default)
connection.auth-retries:              -1
connection.timestamp:                 1636205619
...


root@debian:/home/pue# nmcli -p connection show
========================================
  Perfiles de conexiones NetworkManager
========================================
NAME                 UUID                                     TYPE      DEVICE
--------------------------------------------------------------------------------
-----------------------------
Wired connection 1  a8ae621c-26dd-4ff8-a18d-4bfc29f2ebd5  ethernet  ens3
```

```
root@debian:/home/pue#  nmcli con add con-name eth1 ifname eth1 type ethernet \ip4
10.0.2.18/24 gw4 10.0.2.2
Conexión 'eth1' (aaaf6945-e063-43a4-aff7-f94a9a218384) agregada con éxito.

root@debian:/home/pue# nmcli -p connection show eth1
================================================================================
                Detalles de perfil de conexiones (eth1)
================================================================================
connection.id:                       eth1
connection.uuid:                      aaaf6945-e063-43a4-aff7-f94a9a218384
connection.stable-id:                 --
connection.type:                      802-3-ethernet
connection.interface-name:            eth1
connection.autoconnect:               sí
connection.autoconnect-priority:      0
connection.autoconnect-retries:       -1 (default)
connection.multi-connect:             0 (default)
connection.auth-retries:              -1
connection.timestamp:                 0
connection.read-only:                 no
```

Wireless interfaces

To configure a wireless interface, first determine the name by using the nmcli d command to
view interface devices.

```
$ nmcli radio wifi on

$ nmcli device wifi list

$ nmcli d wifi connect Chippewa_Guest password 1882
```

```
[root@localhost ~]# nmcli device wifi list
IN-USE  BSSID              SSID              MODE   CHAN  RATE        SIGNAL  BARS  SECURITY
        78:94:B4:C2:0F:81  vodafone0F80      Infra  5     130 Mbit/s  45      ▂▄__  WPA2
        78:94:B4:C2:0F:85  vodafone0F80_5G   Infra  48    540 Mbit/s  37      ▂▄__  WPA2
        78:29:ED:0A:09:84  MOVISTAR_0983     Infra  9     130 Mbit/s  35      ▂▄__  WPA2
        F4:69:42:6B:7D:BF  MOVISTAR_7DB0     Infra  1     130 Mbit/s  32      ▂▄__  WPA2
        78:81:02:68:79:51  vodafone7950      Infra  11    130 Mbit/s  30      ▂___  WPA2
        88:5D:FB:C6:C0:1B  MIWIFI_2G_4FrA    Infra  1     130 Mbit/s  29      ▂___  WPA1 WPA2
        78:29:ED:0A:09:91  MOVISTAR_PLUS_0983 Infra 40    540 Mbit/s  27      ▂___  WPA2
```

```
          7C:8F:DE:20:AB:81  sercommBB1824      Infra  1    195 Mbit/s  25     ▄___   WPA2
          8A:5D:FB:C6:C0:1C  MIWIFI_2G_4FrA     Infra  36   540 Mbit/s  24     ▄___   WPA1 WPA2
          88:5D:FB:C6:C0:1C  MIWIFI_5G_4FrA     Infra  36   540 Mbit/s  24     ▄___   WPA1 WPA2
          44:FE:3B:39:DC:BF  --                 Infra  100  540 Mbit/s  19     ▄___   WPA2
          7C:8F:DE:20:AB:85  sercommBB1824      Infra  64   540 Mbit/s  17     ▄___   WPA2
          60:8D:26:EC:7B:BB  Livebox6-7BBC      Infra  1    195 Mbit/s  15     ▄___   WPA2


$ nmcli device wifi connect timofon

$ nmcli device wifi connect timofon password MyPassword

$ nmcli device wifi connect timofon password MyPassword hidden yes

$ nmcli device wifi connect Hypnotoad password MyPassword ifname wlo1

[root@mylaptop ~]# nmcli connection show
NAME              UUID                                  TYPE       DEVICE
timofon            20925a66-11fe-42e5-800a-bc82d69b7bd7  wifi       wlp0s20f3
br-38fb360b0b9f   d3c0ec45-84cb-43bb-8cfe-4cd4a358aadb  bridge     br-38fb360b0b9f
docker0           5ebaa9e9-0d84-4826-ada4-87bf65a8a706  bridge     docker0
virbr0            6a3ad5cd-49ff-4aec-ae0d-f86499fc763a  bridge     virbr0
enp1s0            a5606faa-358c-3f2d-a032-cd423a68f4c7  ethernet   --
MiFibra-13C3      02541f08-fdc8-4203-ad21-4a3aef3acd0b  wifi       --

$ nmcli connection down timofon
$ nmcli connection up timofon
$ nmcli connection delete timofon


$ nmcli device disconnect wlo2
$ nmcli device connect wlo2

$ nmcli radio wifi off
$ nmcli radio wifi on
```

```
[root@mylaptop ~]# iwconfig wlp0s20f3
wlp0s20f3  IEEE 802.11   ESSID:"MOVI_AAAA"
          Mode:Managed  Frequency:2.437 GHz  Access Point: E2:41:36:0E:5A:F0
          Bit Rate=86.7 Mb/s   Tx-Power=22 dBm
          Retry short limit:7   RTS thr:off   Fragment thr:off
          Encryption key:off
          Power Management:on
          Link Quality=50/70  Signal level=-60 dBm
          Rx invalid nwid:0  Rx invalid crypt:0  Rx invalid frag:0
          Tx excessive retries:1  Invalid misc:29   Missed beacon:0
```

```
[root@mylaptop ~]# iwlist
Usage: iwlist [interface] scanning [essid NNN] [last]
              [interface] frequency
              [interface] channel
              [interface] bitrate
              [interface] rate
              [interface] encryption
              [interface] keys
              [interface] power
              [interface] txpower
              [interface] retry
              [interface] ap
              [interface] accesspoints
              [interface] peers
              [interface] event
              [interface] auth
              [interface] wpakeys
              [interface] genie
              [interface] modulation
```

iproute2 tools

Commands:
- ip link   Configure links
- ip address   Configure address
- ip route   Manage routing tables
- ip neighbors   Display and manage neighbors
- ip tunnel   Manage tunnels
- ip maddr   Manage multicast
- ip -s
- ss / netstat

< next chapter >

Systemd-networkd

The systemd-networkd daemon functions through configuration files, which reside in the /usr/lib/systemd/network/, /run/systemd/network, and /etc/systemd/network directories.

- systemd-networkd
- systemd-resolved
- resolvectl

Name resolution services on systems that use systemd are handled by systemd-resolved. This systemd service tells local applications where to find domain name information on a network. The systemd-resolved service can operate in four different modes, which are:
- Using a systemd DNS stub file located at /run/systemd/resolve/stub-resolv.conf.
- Preserving the legacy resolv.conf file we learned about earlier in this chapter.
- Automatic configuration with a network manager.
- Manual, or local DNS stub mode where alternate DNS servers are provided in the resolved.conf file.

The purpose of each configuration file depends on its suffix. File names ending in .netdev are used by systemd-networkd to create virtual network devices, such as bridge or tun devices. Files ending in .link set low-level configurations for the corresponding network interface. systemd-networkd detects and configures network devices automatically as they appear — as well as ignore devices already configured by other means — so there is little need to add these files in most situations.

The most important suffix is .network. Files using this suffix can be used to setup network addresses and routes.

Example Exercises

1. Which commands can be used to list the network adapters present in the system?
2. Which is the type of a network adapter whose interface name is wlo1?
3. Which entry in /etc/network/interfaces configures the interface eno1 to obtain its IP settings with DHCP?
4. IN Red Hat systems, which file configures the interface lo? and the interface eth0 ?
5. Configure nsswitch to do local name resolution before DNS resolution.
6. Which file contains the configuration of the resolver?
7. Show the hostname information.
8. Establish only the static hostname to myserver.
9. How do we associate the local address 127.0.0.1 to the local name myprettyhost?
10. What nmcli subcommand shows interface detailed information?
11. How can a user run the command nmcli to delete an unused connection named Hotel Internet?

12. Realitza els exercicis indicats a: [109.2 Persistent network configuration](#)
13. Realitza els exercicis del Question-Topics 109.2