# Mixology

## Manual Cold Brew

Frequency: Daily, at closing

#### **Materials Needed:**

- Cold Brew System Dishwasher Basket
- Sanitizer Solution
- Bar Towel

### 01 – Flush the system

- Ensure glass cans are empty and in place.
- Start the user interface.
- Select *Start* and the *Pump* screen will show.
- Select all 4 pumps the buttons will turn red.
- Select *Flush* to go to that screen, and then press *Flush*.
- When the 10-second system flush is complete, empty the glass cans.


### 02 - Clean the brewer

- Dump used coffee grounds into compost.
- Clean the cups, glasses, cans, drip tubes, drip trays and drip plates in the dishwasher using the cold brew system dishwasher basket.
- Wipe/dust all components.

### 03 – Replace the brewer pieces

• Put all the components back on the brewer.

Reference separate standard for Trailblazer Unit.



01 Flush the system





02 Clean the brewer



02 Dishwasher Basket



1

# Mixology

## Manual Cold Brew

Frequency: *Monthly* 

#### **Materials Needed:**

- Pump Cabinet Key
- Spare Filter (if needed)
- Paper Towels

Bar Towel

# 01 – Check the Pump Cabinet for leaks or water scaling

- Open the door cabinet with the key.
- Visually inspect the interior of the cabinet for signs of leaking or scale build-up. If either are present, contact the FCC for service.
- Close and lock the cabinet door.

### 02 - Clean the Pump Cabinet dust filter

- Use the blue tab to open the dust filter cover. Remove the filter.
- Rinse the filter clean with warm water in the 3-compartment sink.
- Blot the filter dry with clean paper towels. **NOTE**: If the filter does not come clean, replace it. Clean filters should be on hand in your spare parts.
- Place the filter back in the housing, and close the cover.

### 03 – Wipe the fins of the filter vent

• Use a clean, damp towel.



**01** Open the cabinet door, and check for leaks or water scaling



02 Open the dust filter cover



02 Rinse the filter



**03** Wipe the fins of the filter vent

