Jutge.org

The Virtual Learning Environment for Computer Programming

The one of the edition distance (II)

P48188_en

Concurso On-line 7 (OIE08) (2008)

At this stage, you surely already know that some problems are so classic that blah, blah, blah. Nothing new with this problem. Now, we ask you to compute the minimum cost to insert letters into or to modify letters from two words w_1 and w_2 to make them identical. Both words are made up of only letters chosen among the n smallest lowercase letters (for instance, for n = 4, the alphabet is $\{a, b, c, d\}$). For every letter (call it x), inserting an x in any place in any word has cost I_x . The cost to transform a letter x into a letter y is given by $\lceil (I_x + I_y)/4 \rceil$, i.e., a fourth part, ceiling, of the sum fo the insertion costs I_x and I_y .

Input

Input consists of several cases. Each case begins with $2 \le n \le 26$, followed by n strictly positive natural numbers I_a , I_b , I_c , Follow two words w_1 and w_2 made up of between 1 and 1000 lowercase letters chosen among the n smallest letters. Assume $1 \le I_x \le 1000$ for every letter x.

Output

For every case, print the minimum cost to make w_1 and w_2 identical.

Sample input

2 11 10 aaa aba 4 100 100 100 1 abcd bcda 3 1 10 100 abbcabccabbac bbcabacabbac 4 1 2 1 4 dcbbcbbddccdabdbdbdcbbc cddcab

Sample output

54 27 35

Problem information

Author: Omer Giménez Translator: Carlos Molina Generation: 2013-09-02 15:02:56

© *Jutge.org*, 2006–2013. http://www.jutge.org

Author : Omer Giménez