

# Support Edge Based Classifiers Review

Eduardo Henrique Basilio de Carvalho  
Departamento de Engenharia Eletrônica  
Universidade Federal de Minas Gerais  
Belo Horizonte, Brasil  
eduardohbc@ufmg.br

**Abstract**—This paper reviews the theoretical foundations of Support Edge-based classifiers, a family of graph-based machine learning algorithms leveraging Gabriel Graphs for decision boundaries. We evaluate their implementation in a modern C++20 framework, focusing on computational efficiency and scalability. Potential algorithmic improvements are explored, including structural optimizations and hardware-aware modifications. Additionally, we compare high-level synthesis (HLS) implementations for embedded platforms against traditional hardware description language (HDL) approaches, assessing their viability for edge computing applications. The study aims to bridge gaps in existing methodologies while providing reproducible code and evaluation pipelines.

**Index Terms**—Classification, Machine Learning, Nearest Neighbor, Gabriel Graph, Support Edge

## I. INTRODUCTION

Support Edge-based classifiers, such as CLAS and RCHIP-CLAS, utilize geometric representations like Gabriel Graphs to define large-margin decision boundaries [1]. Prior work by Souza et al. [2] and Arias-Garcia et al. [3], [4] has demonstrated their efficacy in embedded systems, yet challenges persist in scalability and hardware optimization. Existing implementations often rely on computationally expensive adjacency matrices and may overlook optimizations in the search for inter-class edges. This review addresses these limitations by proposing algorithmic refinements and evaluating modern hardware synthesis tools. By integrating software optimizations with high-level synthesis workflows, we aim to enhance the feasibility of these classifiers for real-time edge applications.

## II. THEORETICAL BACKGROUND

### III. POSSIBLE IMPROVEMENTS

Two key algorithmic improvements are proposed. First, replacing adjacency matrices with adjacency lists reduces memory complexity from  $O(n^2)$  to  $O(n + |E|)$ , where  $|E|$  is the number of edges in the Gabriel Graph. This is particularly advantageous for sparse datasets. Second, post-filtering steps can be optimized by computing edges exclusively between points of opposing classes, eliminating redundant intra-class calculations. This approach leverages class label metadata early in the pipeline, reducing computational overhead during graph construction.

## IV. METHODOLOGY

The implementation, available at <https://github.com/eduardo-ufmg/CLAS>, employs C++20 for classifier development. Synthetic datasets—generated via Python’s `sklearn`—are used to evaluate decision boundaries under varying geometric complexities. Python scripts automate performance benchmarking, including accuracy and latency measurements. For hardware evaluation, Vitis HLS synthesizes the classifiers for two platforms: the Alveo U55C (data center-grade FPGA) and Zedboard (embedded FPGA). The HLS workflows are compared against hand-optimized Verilog/VHDL implementations to assess trade-offs in resource utilization and throughput.

## V. RESULTS




Fig. 1. Good classification results on linearly separable data.




Fig. 2. Bad classification results on linearly separable data.




Fig. 3. Classification results on spiral dataset.

## REFERENCES

- [1] L. C. B. Torres, “Classificador por arestas de suporte (CLAS): métodos de aprendizado baseados em Grafos de Gabriel,” Manuscript, 2016.
- [2] A. C. Souza, C. Leite Castro, J. A. Garcia, L. C. B. Torres, L. J. Acevedo Jaimes and B. R. A. Jaimes, “Improving the Efficiency of Gabriel Graph-based Classifiers for Hardware-optimized Implementations,” 2019 XXII Symposium on Image, Signal Processing and Artificial Vision (STSIVA), Bucaramanga, Colombia, 2019.




Fig. 4. Classification results on moons dataset.




Fig. 5. Classification results on concentric circles dataset.

- [3] J. Arias-Garcia et al., "Enhancing Performance of Gabriel Graph-Based Classifiers by a Hardware Co-Processor for Embedded System Applications," in IEEE Transactions on Industrial Informatics, vol. 17, no. 2, Feb. 2021.
- [4] J. Arias-Garcia et al., "Improved Design for Hardware Implementation of Graph-Based Large Margin Classifiers for Embedded Edge Computing," in IEEE Transactions on Neural Networks and Learning Systems, vol. 35, no. 1, Jan. 2024.
- [5] L. C. B. Torres, C. L. Castro and A. P. Braga, "A parameterless mixture model for large margin classification," 2015 International Joint Conference on Neural Networks (IJCNN), Killarney, Ireland, 2015.
- [6] L. C. B. Torres, C. L. Castro, F. Coelho and A. P. Braga, "Large Margin Gaussian Mixture Classifier With a Gabriel Graph Geometric Representation of Data Set Structure," in IEEE Transactions on Neural Networks and Learning Systems, vol. 32, no. 3, March 2021.
- [7] L. C. B. Torres, C. L. Castro, F. Coelho, F. Sill Torres and A. P. Braga, "Distance-based large margin classifier suitable for integrated circuit implementation," Manuscript, 2015.




Fig. 6. Classification results on XOR dataset.