

The Web (HTML + CSS)

Interface Pessoa-Máquina - 25/26 - LEI / UM


Hugo Pacheco

hpacheco@di.uminho.pt

The Web: uma revolução?


- Internet, antes da Web
- Computadores interligados
 - 1. Conectar a servidor FTP
 - 2. Pesquisar ficheiros
 - 3. Download de recursos
 - 4. Abrir localmente com o programa certo
- Internet, depois da Web
- Abrir hiperligação no browser

```
phoenixnap@test-system:~$ ftp 192.168.100.9
Connected to 192.168.100.9.
220 (vsFTPd 3.0.3)
Name (192.168.100.9:phoenixnap): phoenixnap
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> 
```




The Web: uma revolução de usabilidade

- Computadores ligados são
 - servidores: fornecedores de conteúdos (hosting de páginas)
 - clientes: utilizadores (utilizando diversos dispositivos)
- Utilizadores só precisam de um tipo de software instalado
 - um browser web
- (O mesmo computador pode ser ambos)



The Web



The Web: usabilidade é sobrevivência

“If a website is difficult to use, people **leave**.

If the homepage fails to clearly state what a company offers and what users can do on the site, people **leave**.

If users get lost on a website, they **leave**.

If a website's information is hard to read or doesn't answer users' key questions, they **leave**.

Note a pattern here? There's no such thing as a **user reading a website manual** or otherwise spending much time **trying to figure out an interface**.

There are plenty of other websites available; **leaving is the first line of defense** when users encounter a difficulty.”

(Nielsen Norman Group)



The Web

- O que acontece quando abrimos um URL no browser?


1. Cliente envia um HTTP request

3. Servidor responde com um HTTP response

5. O browser interpreta e mostra o HTML



The Web: um bocado de História



The Web: uma tríade atual

Tipografia, cores,
layout, efeitos
visuais, animação




Hierarquia, navegação,
significado, conteúdo

Interação e automação;
linguagem general-
purpose que corre no
cliente

Exemplo: HTML + CSS + JS

HTML

Our Solar System



.

[Sol](#)



.

[Mercury](#)





.

[Venus](#)



HTML + CSS

Our Solar System



Saturn

Uranus

Neptune

Pluto and
Charon

Jupiter

Venus


Earth

Mars

Mercury

Sol


Our Solar System




Sol




Mercury



Venus



Earth




Mars



Jupiter



Saturn



Uranus




Neptune



Pluto and
Charon



Sol



Mercury

Images courtesy of:
Sol: ESA/NASA/SOHO; Mercury: NASA;
Mars: NASA/JPL/MSSS; Jupiter: NASA;
ESA/ESO Space Telescope European C

HTML + CSS + JS



Mercury

Actividade: “Despir” um website

1. Ir a um site, e.g., de um jornal
2. Abrir as Developer Tools do browser
3. Remover **CSS** e **JS**
 - tags `<style>`, `<script>` e `<link>`
4. Recarregar o site

PÚBLICO

- [Médio Oriente](#)
- [Guerra na Ucrânia](#)
- [Sociedade](#)
- [Mundo](#)
- [Enter](#)
- [Ípsilon](#)
- [Público Brasil](#)
- [Opinião](#)
- [Jogos](#)
- [Azul](#)



- [Oferecer assinatura](#)



- Pesquise no PÚBLICO



Segunda-feira, 29 Set 2025


[Edição impressa](#)

Temas em destaque



[Edição impressa](#)

Disponível todos os dias através do nosso e-reader



[Azul](#)

Crise climática, ambiente e sustentabilidade



[Autárquicas 2025](#)

Os nossos trabalhos sobre as próximas eleições



[Cinecartaz](#)

Estreias da semana, críticas e programação


The Web: tecnologias

- Idealmente, independência completa de conceitos
 - **HTML** (estrutura) + **CSS** (apresentação) + **JS** (comportamento)
- Na verdade, alguma fusão de conceitos / tecnologias
 - **HTML 3.2** com tags de formatação (****, ****, etc)
 - **CSS** influencia frequentemente a estrutura do **HTML**
 - Comum introduzir **<div>** apenas para efeitos de formatação
 - E.g., **grid-template** impõe utilização de tags (e.g. <https://grid.layoutit.com/>)
 - Em **JS** vale tudo (o que o browser deixa)... alterar o **HTML** e o **CSS** dinamicamente
 - ...

HTML

Elementos HTML

- HyperText Markup Language (HTML) é uma markup language (um conjunto de tags)
- Anatomia de uma tag / elemento HTML (dois modos)



- **Programação declarativa**
 - O quê? HTML descreve a estrutura e conteúdo de uma página
 - Como? Browser trata da renderização
- [HTML Living Standard](#) (25/09/2025)

Exemplo: uma página HTML

1. Visualizar em <https://codepen.io/pen>
2. Abrir Developer Tools do browser
3. O mesmo código?



```
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Hello world</title>
</head>
<body>
  <p>Hello <em>world</em> 🙌</p>
</body>
</html>
```

Atributos HTML

- Atributos fornecem metadados ou funcionalidade adicional
- Frequentemente utilizados como “âncoras” para **CSS** ou **JS** (e.g., **class**, **id**)
- No entanto, não determinam renderização!



```
<a href="https://google.com">world</a>
```



```
<input type="checkbox" checked>
```


```

```

Document Object Model (DOM)

- Documento HTML = árvore de elementos HTML
- DOM = representação que o browser faz do documento HTML em memória

```
<!DOCTYPE html>
<html>
<head>...</head>
<body>Hello <em>world</em> 🙌</body>
</html>
```



HTML → DOM

- DOM representa uma hierarquia / árvore de elementos HTML
 - Relações pai-filho entre elementos
- *HTML parsing* = converter documento HTML numa árvore DOM
 - Um processo crucial para interoperabilidade HTML+CSS+JS+browsers
- ! Demorou cerca de 25 anos a estabilizar!
- Hierarquia HTML ≠ Hierarquia DOM?

```
<table>
  <tr><td>One</td></tr>
</table>
```



table
tbody
tr
td
One

HTML Parsing

- 💡 Uma das vantagens de uma linguagem declarativa é precisamente que é muito mais fácil ser-se **liberal em relação a erros**
 - Browser **nunca mostra erros** (excepto em modo de debugging)
 - Página carrega sempre, no limite mostrada como blank page
- + Parser HTML tenta **corrigir erros**
 - Tags que abrem mas não fecham, tags esperadas, tags inexistentes, etc
- + Uma forma de suportar **backward compatibility**
 - Self-closing tags (`` = ``), etc

Exercício: erros na Web

- 💡 Diferentes mecanismos de tratamento de erros

- **HTML + CSS** são **linguagens declarativas**
 - **HTML** tenta corrigir erros
 - **CSS** ignora erros
- **JS** é uma **linguagem imperativa**
 - **JS** pára (o script) e produz um erro (na consola)

1. Abrir página no browser. Render? Developer Tools?
2. **HTML:** apagar ou renomear tags?
3. **CSS:** criar propriedades inexistentes? apagar um ;?
4. **JS:** apagar “? Não fechar (?) Dois scripts?

```
<style>
  h1 {
    color: slategray;
    color: yolo;
    font-style: red;
    font-weight: normal;
  }
</style>
<script>
  console.log("Hello");
</script>
<h1 yolo="1">
  Error handling in <strong>HTML,
  <em>CSS</em></strong>, JS</em>
</h1>
```

Tags HTML5

- **Root element**

- html

- **Document metadata**

- head
- title
- base
- link
- meta

- **Style**

- style

- **Sections**

- body
- article
- section
- nav
- aside
- h1, h2, h3, h4, h5, h6
- hgroup
- header
- footer
- address

- **Grouping content**

- p
- hr
- pre
- blockquote
- ol
- ul
- li
- dl

- dt
- dd
- figure
- figcaption
- main
- div

- **Text-level semantics**

- a
- em
- strong
- small
- s
- cite
- q
- dfn
- abbr
- ruby
- rt
- rp
- data
- time
- code
- var
- samp
- kbd
- sub
- sup
- i
- b
- u
- mark

- bdi
- bdo
- span
- br
- wbr

- **Edits**

- ins
- del

- **Embedded content**

- picture
- source
- img
- iframe
- embed
- object
- param
- video
- audio
- source
- track
- map
- area

- **Tabular data**

- table
- caption
- colgroup
- col
- tbody
- thead
- tfoot

- tr
- td
- th

- **Forms**

- form
- label
- input
- button
- select
- datalist
- optgroup
- option
- textarea
- keygen
- output
- progress
- meter
- fieldset
- legend

- **Interactive elements**

- details
- summary
- menu
- menuitem
- dialog

- **Scripting**

- script
- noscript
- template
- canvas

HTML: Listas

- Existem três tipos de listas em HTML (cf. LaTeX):
 - Não ordenadas (``): mostram os itens com marcadores ou outros símbolos
 - Ordenadas (``): mostram os itens com números ou letras
 - Descrições (`<dl>`): mostram os itens com termos e definições
- Cada item de uma lista é marcado com
 - uma tag `` (para listas ordenadas ou não ordenadas)
 - ou pares `<dt>` (título) e `<dd>` (definição)

HTML: Listas

```
<ul>
  <li>All games</li>
  <li>My games</li>
  <li>Add games</li>
</ul>

<ol>
  <li>All games</li>
  <li>My games</li>
  <li>Add games</li>
</ol>

<dl>
  <dt>HTML</dt>
  <dd>HiperText Markup Language</dd>
  <dt>CSS</dt>
  <dd>Cascade Style Sheets</dd>
  <dt>Javascript</dt>
  <dd>Uma linguagem de scripting para desenvolvimento web</dd>
</dl>
```

- All games
- My games
- Add games

1. All games
2. My games
3. Add games

HTML

HiperText Markup Language

CSS

Cascade Style Sheets

Javascript

Uma linguagem de scripting para desenvolvimento web

HTML: Tabelas

- Tabela HTML (<table>)
 - Elemento <tr> para cada linha da tabela
 - Elementos <th> (cabeçalho) ou <td> (dados) para cada célula
 - Atributos colspan e rowspan para fazer as células ocuparem várias colunas ou linhas
 - Elemento <caption> para legendas
 - Elementos <thead>, <tfoot> para cabeçalhos e rodapés
 - Elemento <tbody> para o corpo é obrigatório (ou inferido)

HTML: Tabelas

```
<table>
  <caption>Frutas e cores</caption>
  <thead>
    <tr>
      <th>Fruta</th> <th>Cor</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td>Morango</td><td>Vermelha</td>
    </tr>
    <tr>
      <td>Banana</td><td>Amarela</td>
    </tr>
    <tr>
      <td>Laranja</td><td>Laranja</td>
    </tr>
  </tbody>
</table>
```

Fruta	Cor
Morango	Vermelha
Banana	Amarela
Laranja	Laranja

HTML: Formulários

- Formulário HTML (<form>)
 - Elementos de tipos diferentes
 - <input>, <label>, <select>, <textarea>, ...
 - Cada elemento de input tem atributos
 - name (nome usado para referência)
 - value (valor por defeito)
 - type (define o seu comportamento e aparência)
- Atributos action e method indicam ações (para onde dados são enviados) e como, respectivamente

HTML: Formulários

```
<form action="/enviar.jsp" method="POST">
  <fieldset>
    <legend>Identificação</legend>
    <label for="nome">Nome:</label>
    <input type="text" id="nome" name="nome" required>
    <label for="email">Email:</label>
    <input type="email" id="email" name="email" required>
  </fieldset>
  <fieldset>
    <legend>Mensagem</legend>
    <label for="assunto">Assunto:</label>
    <select id="assunto" name="assunto">
      <option value="duvida">Dúvida</option>
      <option value="sugestao">Sugestão</option>
      <option value="reclamacao">Reclamação</option>
    </select>
    <label for="mensagem">Mensagem:</label>
    <textarea id="mensagem" name="mensagem" rows="3" cols="20"></textarea>
  </fieldset>
</form>
```

The screenshot shows a web page with a form containing two fieldsets. The first fieldset is labeled 'Identificação' and contains two input fields: 'Nome:' and 'Email:'. The second fieldset is labeled 'Mensagem' and contains a dropdown menu labeled 'Assunto:' with options 'Dúvida', 'Sugestão', and 'Reclamação', and a large text area labeled 'Mensagem:'.

```
<form method="get" action="https://www.google.com/search"
target="_blank">
  <input name="q" required />
  <button>Search Google</button>
</form>
```



HTML: Formulários

- Diferentes tipos de inputs

```
<input type="button">  
<input type="checkbox">  
<input type="color">  
<input type="date">  
<input type="datetime-local">  
<input type="email">  
<input type="file">  
<input type="hidden">  
<input type="image">  
<input type="month">  
<input type="number">  
<input type="password">  
<input type="radio">  
<input type="range">
```

The image shows a collection of HTML form elements arranged in a grid. From top-left to bottom-right, the elements are:

- A color picker (a small square with a color gradient).
- A date input field with a placeholder "dd/mm/yyyy" and a calendar icon.
- A date-time local input field with a placeholder "dd/mm/yyyy, --:--" and a calendar icon.
- A file input field with a placeholder "Choose file" and a "No file chosen" message, accompanied by a "Submit" button with a file icon.
- A date input field with a placeholder "-----" and a calendar icon.
- A range slider with a blue handle and a track.
- A hidden input field.
- A submit button labeled "Submit".
- A time input field with a placeholder "--:--" and a clock icon.
- A month input field with a placeholder "Week --, -----" and a calendar icon.

```
<input type="reset">  
<input type="search">  
<input type="submit">  
<input type="tel">
```

```
<input type="text">  
<input type="time">  
<input type="url">  
<input type="week">
```

HTML: Formulários

- Declarativo (HTML)

```
<form>
  <label for="user">Username:</label>
  <input type="text" name="user" />
  <input type="submit" value="Submit" />
</form>
```



- Imperativo (Java)

```
JFrame frame = new JFrame("Form Example");
JPanel panel = new JPanel();
JLabel label = new JLabel("Username:");
JTextField textField = new JTextField(10);
JButton button = new JButton("Submit");

button.addActionListener(e -> {
    String value = textField.getText();
    leNome(value);
});

panel.add(label);
panel.add(textField);
panel.add(button);

frame.add(panel);
frame.pack();
frame.setVisible(true);
```

💡 Imperativo inclui layout

💡 Podíamos ter repetido o exercício em JS
(ainda mais complexo)



Markup semântico

- ? **Puzzle:** cabeçalho vs texto normal

```
<h1>This is a top level heading</h1>
<span style="font-size: 2em; margin: 0.67em
0; font-weight: bold;">
  Is this a top level heading?
</span>
```

This is a top level heading

Is this a top level heading?


- 💡 Mesma representação visual, significado diferente

- ? Porque é que a semântica é relevante?

- Nem todos os “web surfers” vêem bem ⇒ screen readers lêem páginas para inviduais
- Nem todos os “web surfers” usam rato ⇒ navegação com o teclado depende da estrutura
- Compatibilidade ⇒ rendering pode mudar com browsers e versões

Navegação com o teclado

- HTML tem uma noção de elemento atualmente focado
 - Clickar em elementos com o rato altera foco
 - Tab/Space navegam pela página, alterando foco
- Nem todos os elementos são navegáveis
 - <https://allyjs.io/data-tables/focusable.html>
- Exemplos:
 - <input type="text" **autofocus**>
 - https://www.google.com/advanced_search



The image shows a screenshot of an 'Amazon Create account' form. The 'Your name' input field is highlighted with a red border, indicating it is the currently focused element. A large orange arrow points from the text 'autofocus' in the list above to this highlighted field. The form also includes fields for Email, Password, and Password again, along with a 'Create your Amazon account' button and a link to the Conditions of Use and Privacy Notice.

Create account

Your name

Email

Password

at least 6 characters

Password again



Create your Amazon account

By creating an account, you agree to Amazon's [Conditions of Use](#) and [Privacy Notice](#).

Already have an account? [Sign in](#) •

Navegação alternativa

- Nem todos os “web surfers” são humanos
 - Screen readers
 - Web crawlers
 - Web scrapers
- Nem todos os browsers têm interfaces gráficas



Hierarquia HTML ≠ Hierarquia Conteúdo?

- E.g., podemos construir sites inteiros só com tabelas
- 💡 Algo muito comum antes de **CSS** (**flex** ou **grid** layouts) ser tão poderoso
- + Posicionamento mais previsível
- Hierarquia flat
- Estrutura afetada por visualização

```
<form method="post" action="/login">
  <table>
    <tr>
      <td>Username:</td>
      <td><input type="text"></td>
    </tr>
    <tr>
      <td>Password:</td>
      <td><input type="password"></td>
    </tr>
  </table>
</form>
```

The diagram illustrates the visual representation of the HTML code. It shows a simple login interface with two text input fields. The first field is labeled "Username:" and the second is labeled "Password:", each with a corresponding empty input box.

Markup semântico

- 💡 Tags **HTML** têm significado (excepto `<div>` e ``)
- 💡 Utilização de tags para definir o seu conteúdo, não a sua visualização
- + Facilita manutenção do código
- + Facilita o acesso (e.g., utilizadores com deficiência, indexação por motores de busca), independentemente de **CSS** e **JS**
- + Facilita formatação com **CSS** e interação com **JS**
- + Facilita adaptação a diferentes media / dispositivos
- 💡 **Uma forma de usabilidade:** nem sempre trivial, mas esforço compensa

Exemplo: identificar markup?

The screenshot shows a user interface for managing a game collection. The page has a header with 'Title', 'App name', and 'User name' fields, and navigation links for 'All games', 'My games', and 'Add game'. Below this is a table listing two games: Game 1 (1992, Megadrive) and Game 2 (2017, PC). To the right is a 'Filter' sidebar with dropdowns for 'year' and 'Platform'. A large green smiley face icon is centered on the page. At the bottom are page navigation links (1, 2, 3) and a footer with 'Footer information ©'.

<header>

<main>

<nav>

<aside>

<footer>

Title

App name

User name

All games My games Add game

Games	Year	Platform
Game 1	1992	Megadrive
Game 2	2017	PC

Filter

year

Platform

1 2 3

Footer information ©

Exemplo: identificar markup?

Screenshot of an Amazon search results page for "4 Stars & Up : Get It by Tomorrow : \"css\"". The results are sorted by Featured.

The search results page shows several books related to CSS and web design. One book, "CSS: The Definitive Guide: Visual Presentation for the Web" by Eric A. Meyer and Estelle Weyl, is highlighted with a red border. This book is the first result in the list.

Other books listed include:

- "HTML and CSS: Design and Build Websites" by Jon Duckett
- "Web Design with HTML, CSS, JavaScript and jQuery Set" by Jon Duckett
- "Learning Web Design: A Beginner's Guide to HTML, CSS, JavaScript, and Web Graphics" by Jennifer Robbins
- "CSS Secrets: Better Solutions to Everyday Web Design Problems" by Lea Verou
- "CSS: The Missing Manual" by David Sawyer McFarland
- "Head First HTML and CSS" by Elisabeth Robson and Eric Freeman
- "CSS Pocket Reference: Visual Presentation for the Web" by Eric A. Meyer
- "Web Design Playground: HTML & CSS the Interactive Way" by Paul McFedries
- "HTML, CSS, and JavaScript All in One, Sams Teach Yourself (3rd Edition)" by Julie C. Meloni and Jennifer Kyrnin
- "HTML5 and CSS3 All-in-One For Dummies" by Andy Harris
- "HTML and CSS: Visual QuickStart Guide (8th Edition)" by Elizabeth Castro and Bruce Hyslop

On the left side of the page, there is a sidebar with various filtering options such as Prime, Delivery Day, Eligible for Free Shipping, Department (Books), Avg. Customer Review, Amazon Global Store, International Shipping, and Condition (New). There is also a promotional banner for the Microsoft Surface Pro 7.

Exemplo: identificar markup?

The screenshot shows an Amazon search results page for books related to CSS. The search query is "4 Stars & Up : Get It by Tomorrow : css". The results are sorted by Featured. A red circle highlights the first result, "CSS: The Definitive Guide (4th Edition)", which has a large red "div" drawn over its cover image. A yellow callout box points to the "div.s-expand-height.s-include-content-margin.s-border-bottom" element in the browser's developer tools. The developer tools also show the full HTML structure for the first result, including the product image, title, author, price, and availability information.

1-48 of 323 results for 4 Stars & Up : Get It by Tomorrow : css

Sort by: Featured

Amazon Prime

vprime

Delivery Day

< Clear Get it by Tomorrow

Eligible for Free Shipping

Free Shipping by Amazon

All customers get FREE Shipping on orders over \$25 shipped by Amazon

Department

Books

Avg. Customer Review

< Clear

★★★★★ & Up

★★★★☆ & Up

★★★☆☆ & Up

★★☆☆☆ & Up

Amazon Global Store

Amazon Global Store

International Shipping

International Shipping Eligible

Condition

Deals for Valentine's Day

HTML and CSS: Design and Build Websites by Jon Duckett \$17⁵⁸ \$29.99

Web Design with HTML, CSS, JavaScript and jQuery Set by Jon Duckett \$26⁹⁹ \$58.00

Learning Web Design: A Beginner's Guide to HTML, CSS, JavaScript, and Web Graphics by Jennifer Robbins \$46⁹⁹ \$59.99

CSS Secrets: Better Solutions to Everyday Web Design Problems by Lea Verou \$27²¹ \$44.99

CSS: The Missing Manual by David Sawyer McFarland \$9.99

Condition

Elements Network Debugger Resources Timelines Storage Canvas Audit Console

```
<div class="s-expand-height s-include-content-margin s-border-bottom"> = $0
  ::before
  <div class="a-section a-spacing-medium">
    <div class="a-section a-spacing-micro s-grid-status-badge-container"> </div>
    <span data-component-type="s-product-image" class="rush-component" data-component-id="9">
      <a class="a-link-normal" href="/CSS-Definitive-Guide-Visual-Presentation/dp/1449393195/ref=sr_1_1?ddk=4r6bZw05Ww6fy30TTA0XyA%2C%2C&keywords(css&qid=1580895723&refinements=p_72%3A2661618011%2Cp_90%3A8308921011&rnid=2470954011&r=8-1">
        <div class="a-section aok-relative s-image-square-aspect">
          
        </div>
      </a>
    </span>
  <div class="a-section a-spacing-none a-spacing-top-small">
    <h2 class="a-size-mini a-spacing-none a-color-base s-line-clamp-4">...</h2>
    <div class="a-row a-size-base a-color-secondary">...</div>
  </div>
<div class="a-section a-spacing-none a-spacing-top-micro">...</div>
```

Exemplo: article HTML element


- “represents a **self-contained composition** in a document, page, application, or site, which is intended to be independently distributable or reusable”

HTML	CSS	OUTPUT												
<pre>1 <article class="forecast"> 2 <h1>Weather forecast for Seattle</h1> 3 <article class="day-forecast"> 4 <h2>03 March 2018</h2> 5 <p>Rain.</p> 6 </article> 7 <article class="day-forecast"> 8 <h2>04 March 2018</h2> 9 <p>Periods of rain.</p> 10 </article> 11 <article class="day-forecast"> 12 <h2>05 March 2018</h2> 13 <p>Heavy rain.</p> 14 </article> 15 </article></pre>		 <p>Weather forecast for Seattle</p> <table><thead><tr><th>Date</th><th>Description</th><th>Icon</th></tr></thead><tbody><tr><td>03 March 2018</td><td>Rain.</td><td></td></tr><tr><td>04 March 2018</td><td>Periods of rain.</td><td></td></tr><tr><td>05 March 2018</td><td>Heavy rain.</td><td></td></tr></tbody></table>	Date	Description	Icon	03 March 2018	Rain.		04 March 2018	Periods of rain.		05 March 2018	Heavy rain.	
Date	Description	Icon												
03 March 2018	Rain.													
04 March 2018	Periods of rain.													
05 March 2018	Heavy rain.													


CSS

CSS

- Cascading Style Sheets (CSS) é uma styling language para HTML




- CSS3 deixou de ter versões (níveis W3C)
 - Cada módulo CSS3 evolui de forma independente



[https://www.w3.org/TR/
selectors-4/](https://www.w3.org/TR/selectors-4/)

Estilos CSS

- Estilos (styles) definem formatação dos elementos HTML
- Anatomia de uma CSS rule



- **Programação declarativa**
 - O quê? CSS descreve um conjunto de regras independentes
 - Como? Browser trata de aplicar as regras
- CSS Snapshot (18/09/2025)

Cascading Style Sheets

- Documento HTML pode ter várias **Style Sheets**

- Externamente num ficheiro .css

```
<link rel="stylesheet" type="text/css" href="mystyle.css">
```

- Internamente ao documento (definida no `<header>` ou `<head>`)

```
<style> td {font-size: 0.8em;} </style>
```

- Inline (para um elemento HTML)


```
<dt style="margin-bottom:20px;">...</dt>
```

Cascading Style Sheets

- A **Cascade** é o algoritmo que corre no browser e define quais estilos **CSS** (de diversas fontes potencialmente conflituantes) se aplicam a cada elemento **HTML**
- Heurística de prioridade com base em diferentes fatores:
 - Origem:
 1. User
 2. Author (inline > interno > externo)
 3. User Agent (style sheet por defeito do browser, pode variar)
 - Especificidade:

`p[class="primary"] > p > *`

Cascading Style Sheets



Exemplo (HTML)

```
<!DOCTYPE html>
<html>
  <head>
    <title>My first styled page</title>
    <!--link rel="stylesheet" href="mystyle.css"-->
  </head>
  <body>
    <nav>
      <ul class="navbar">
        <li><a href="index.html">Home page</a>
        <li><a href="musings.html">Musings</a>
        <li><a href="town.html">My town</a>
        <li><a href="links.html">Links</a>
      </ul>
    </nav>
    <main>
      <h1>My first styled page</h1>
      <p>Welcome to my styled page!</p>
      <p>It lacks images, but at least it has style. And it has links, even if they don't go anywhere...</p>
      <p>There should be more here, but I don't know what yet.</p>
    </main>
    <address>Made 5 April 2004 by myself.</address>
  </body>
</html>
```

- [Home page](#)
- [Musings](#)
- [My town](#)
- [Links](#)

My first styled page

Welcome to my styled page!

It lacks images, but at least it has style. And it has links, even if they don't go anywhere...

There should be more here, but I don't know what yet.

Made 5 April 2004 by myself.

Exemplo (HTML + CSS)

```
body {  
    font-family: Georgia, "Times New Roman", Times, serif;  
    color: purple;  
    background-color: #d8da3d }  
  
h1 {  
    font-family: Helvetica, Geneva, Arial,  
    ... SunSans-Regular, sans-serif }  
  
nav {  
    padding: 0;  
    margin: 0;  
    width: 10em }  
nav > ul a {  
    text-decoration: none }  
a:link {  
    color: blue }  
a:visited {  
    color: purple }  
address {  
    margin-top: 1em;  
    padding-top: 1em;  
    border-top: thin dotted }  
...  
  
body { transition: padding-left 1s linear 0.1s; }  
  
ul.navbar { transition: width 1s linear 0.1s; }
```

- Home page
- Musings
- My town
- Links

My first styled page

Welcome to my styled page!

It lacks images, but at least it has style. And it has links, even if they don't go anywhere...

There should be more here, but I don't know what yet.

Made 5 April 2004 by myself.

Exemplo (HTML + CSS)

```
@media (min-width: 400px) {  
  body { padding-left: 12em; }  
  nav {  
    position: absolute;  
    top: 2em;  
    left: 1em; }  
  nav > ul {  
    list-style-type: none; }  
  nav > ul > li {  
    background: white;  
    margin: 0.5em 0;  
    padding: 0.3em;  
    border-right: 1em solid black }  
}
```

My first styled page

Welcome to my styled page!

It lacks images, but at least it has style. And it has links, even if they don't go anywhere...

There should be more here, but I don't know what yet.

Made 5 April 2004 by myself.

CSS Zen Garden



A demonstration of what can be accomplished through CSS-based design. Select any style sheet from the list to load it into this page.

Download the example [HTML FILE](#) and [CSS FILE](#)

THE ROAD TO ENLIGHTENMENT

Littering a dark and dreary road lay the past relics of browser-specific tags, incompatible DOMs, broken CSS support, and abandoned browsers.

We must clear the mind of the past. Web enlightenment has been achieved thanks to the tireless efforts of folk like the [W3C](#), [WASP](#), and the major browser creators.

The CSS Zen Garden invites you to relax and meditate on the important lessons of the masters. Begin to see with clarity. Learn to use the time-honored techniques

MID CENTURY
MODERN
by Andrew Lohman

GARMENTS
by Dan Mall

STEEL
by Steffen Knoeller

APOTHECARY
by Trent Walton

CSS ZEN GARDEN

The Beauty of CSS Design

Select a
Design:

[Mid Century Modern](#) by
Andrew Lohman

[Garments](#) by Dan Mall

[Steel](#) by Steffen Knoeller

[Apothecary](#) by Trent
Walton

[Screen Filler](#) by Elliot Jay
Stocks

[Fountain Kiss](#) by Jeremy
Carlson

[A Robot Named Jimmy](#) by
meltmedia

[Verde Moderna](#) by Dave

A screenshot of the CSS Zen Garden homepage in grayscale. The overall layout is identical to the original version, featuring a large central title "The Beauty of CSS Design" and a sidebar with design options. The background image of the garden is now grayscale, and the text is also in grayscale. The "VIEW ALL DESIGNS" button is visible at the top right of the main content area.

CSS: Simple Selectors

- Definem o conjunto de elementos HTML aos quais uma regra se aplica
- `*` (qualquer elemento)
 - `.class` (com classe `class`)
`<p class="right">txt</p>`
`.right {...}`
- `element` (com tag `element`)
 - `#id` (com identificador `id`)
`<h1 id="chap1">txt</h1>`
`#chap1 {...}`

CSS: Simple Selectors (atributos)

- Selecionar elementos com base em atributos gerais
- `[attr]` (contém atributo `attr`)
- `[attr="value"]` (contém atributo `attr` com valor `value`)
- `[attr^="starts"]` (contém atributo `attr` com valor iniciado por `starts`)
- `[attr$="ends"]` (contém atributo `attr` com valor acabado em `ends`)
- `[attr*="anywhere"]` (contém atributo `attr` com substring `anywhere`)
- `[attr~=“anywhere”]` (contém atributo `attr` com palavra `anywhere`)

```
<div class="box highlight big">
```

```
[class~="highlight"] {...} ≡ .highlight {...}
```

CSS: Compound Selectors

- Concatenação de selectors \triangleq interseção de conjuntos

```
<div class="foo bar baz"></div>
```

```
.foo.bar {...}
```

```
≡ [class~="foo"] [class~="bar"] {...}
```

```
≡ .foo and .bar {...}
```

```
<p class="center">Texto</p>
```

```
p.center {...}
```

```


```

```
img[loading=lazy] {...}
```

CSS: Complex Selectors

- Múltiplos compound selectors separados por combinadores \triangleq hierarquia de elementos
- Descendente
 - Próximo parente

`footer a { ... }`



`h1 + h2 { ... }`

`<h1>...</h1>`
`<h2>...</h2>`

- Filho direto

`ol.tasks > li { ... }`



`h1 ~ h2 { ... }`

`<h1>...</h1>`
`<p>`
`<h2>...</h2>`

- Parente subsequente

CSS: Selector Lists

- Múltiplos complex selectors separados por vírgulas \triangleq união de conjuntos

```
ul.bar li, .foo {...}
```

```
<ul class="bar">  
  <li>Matches (li inside ul.bar)</li>  
  <li class="foo">Matches twice (li inside ul.bar, and also .foo)</li>  
</ul>
```

```
h1, h2 {...}
```

```
<div>  
  <h1>Matches (h1)</h1>  
  <h2>Matches (h2)</h2>  
</div>
```

CSS: Pseudo-classes

- Identificar elementos com base nas suas características / estado; inspirado em JS
- Dinâmicas (activity-based)
 - Mouse over element :hover
 - Mouse down on element :active
 - Currently focused :focus
 - Contains currently focused :focus-within
 - Checked radio or checkbox :checked
 - Visited URL :visited
 - Non-visited URL :link


CSS: Pseudo-classes

- Estruturais (DOM-based)
 - Primeiro filho de elemento :first-child
 - Último filho de elemento :last-child
 - Único filho de elemento :only-child
 - Filhos em posição ímpar :nth-child(odd)
 - Filhos cujo índice n está no intervalo $[0..-n+3]$:nth-child(-n + 3)
 - Elemento que tem um descendente com classe child :has(.child)
 - Negação :not(:hover)


CSS: Pseudo-elements

- Identificar partes de um elemento

- ```
li::marker {
 color:red;
}
```



- ```
input::placeholder {  
    color:slategrey;  
}
```




CSS: Propriedades

- Estilo
 - Cores
 - Fontes
 - Espaçamento
 - Transformações
 - Transições e animações
 - ...
- Layout: posicionar os elementos na página

CSS: Propriedades (Inherited)

- Algumas propriedades são herdadas (passadas implicitamente de pais para filhos)
- Outras não (definidas só para o elemento atual)




Herdadas Não herdadas



CSS: Propriedades (Layout)

- Todos os elementos são uma “box”
- Propriedades determinam como “boxes” são desenhadas e se relacionam com outras “boxes”
 - `width/height` do conteúdo
 - `property` ou `property-X`
 - `X = { top,bottom,left,right }`
 - Largura efetiva do elemento
 - `width + padding + border + margin`
 - `* {box-sizing: border-box; }`



CSS: Propriedades (Tamanhos)

- CSS suporta várias unidades de tamanho
 - Absolute (mesmo tamanho em qualquer contexto)
 - Exemplos: `px`, `cm`, `mm`, `in`, `pt`
 - Relative (dependem de outros fatores)
 - Font-relative (dependem do tamanho do texto)
 - Exemplos: `em`, `ch`, `rem`, `ex`
 - Viewport-relative (dependem da janela)
 - Exemplos: `vh`, `vw`, `vmin`, `vmax`
 - Property-specific (comportamento variável, nem sempre aceite)
 - Percentagens, e.g., `50%vh`
 - Keyword `auto`

CSS: Propriedades (display)

- `display: block;`
 - Laid out from top to bottom
 - Line break before and after
 - Box as wide as all available space
 - Box as tall as all contents (wrapped)
 - Text wrapping inside box
 - We can set `width`, `height`, `margin`
- `display: inline;`
 - Laid out from left to right
 - Inline with surrounding text
 - Box as wide as all contents
 - Box as tall as one line
 - Text wrapping by box fragmentation
 - `width`, `height`, `margin` have no effect.



CSS: Propriedades (display)


- Outras opções de display
 - `inline-block`
 - Comporta-se essencialmente como um `inline`, mas com wrapping de `block`
 - We can set `width`, `height`, `margin-top`, `margin-bottom`
 - `none`
 - Não é mostrado
 - `contents`
 - Apenas são mostrados os seus conteúdos

CSS: Propriedades (display)

- Por defeito (depende de User Agent Stylesheet)
 - `block`
 - `<div> <h1> <h2> <h3> <h4> <h5> <h6> <p> <body> <html>`
 - `inline`
 - `<a> <mark> <code> <cite> <abbr>`
 - `inline-block`
 - `<button> <input> <textarea> <select>`
 - Replaced elements (não controlados por CSS)
 - Flutuam como um `inline-block`, mas conteúdos não são afetados por CSS
 - ` <video> <audio> <iframe> <canvas> <option> <object> <embed>`

CSS: Propriedades (display: flex)



- Distribuir items proporcionalmente, cálculo de margens automáticas
 - `flex-direction: row;`
 - `flex-direction: column;`



- `align-items`: alinhamento ao longo do eixo principal
- `justify-content`: alinhamento ao longo do eixo perpendicular

CSS: Propriedades (display)


- flex
 - Uma dimensão
- grid
 - Duas dimensões




CSS: Propriedades (display: grid)

- Permite criar layouts em duas dimensões (linhas e colunas) com facilidade e precisão
- Tamanho de cada coluna / linha (`grid-template-columns`, `grid-template-rows`)
- Espaçamento entre colunas e linhas (`gap`)
- Permitir que itens ocupem mais do que uma célula (`grid-row: start / end`, `grid-column: start / end`)


```
.grid-container {  
    display: grid;  
    grid-template-columns: 150px 1fr;  
    grid-template-rows: 80px 1fr 50px;  
    gap: 10px; }  
  
.header {  
    grid-column: 1 / 3;  
    grid-row: 1 / 2; }  
  
.sidebar {  
    grid-column: 1 / 2;  
    grid-row: 2 / 3; }  
  
.content {  
    grid-column: 2 / 2;  
    grid-row: 2 / 3; }
```




Exemplo: CSS Layouts




A: Flow layout




B: Traditional Floats — broken




C: Traditional Floats — "fixed"




D: Column Layout (using Multicolumn)




E: Flexbox




F: CSS Grid — stretch in both dimensions




G: CSS Grid — align items start




H: CSS Grid — align items end




I: CSS Grid — align items center



J: CSS Grid — differently sized items



K: CSS Grid — differently sized items — dense



L: CSS Grid — explicitly placed items (for wide browsers only)

CSS: Variables

- DRY (Don't Repeat Yourself) Principle

“Every piece of knowledge must have a single, unambiguous, authoritative representation within a system”

(Andy Hunt and Dave Thomas, The Pragmatic Programmer)

- Em CSS, **evitar duplicação utilizando variáveis** (reparem na herança)

```
:root {  
  --primary-bg-color: #1e90ff;  
  
body {  
  background-color: var(--primary-bg-color);}
```

Responsive Web Design

The screenshot shows a desktop view of the website. At the top, there's a header with three navigation links: 'THE WEBLOGUE', 'BACK ISSUES', and 'ABOUT OUR PAPER'. Below the header is a large, stylized illustration of two men in 19th-century attire. The central part of the page features a quote: "Give me problems, give me work." Below the quote is a paragraph of text. Further down, there's a section titled 'victors & villains' with six small portraits of characters. At the bottom, there's a note about illustrations by Sidney Paget and words by Sir Arthur Conan Doyle.

THE WEBLOGUE

BACK ISSUES

ABOUT OUR PAPER

The Baker Street
INQUIRER

"Give me problems, give me work."

In the year 1878 I took my degree of Doctor of Medicine of the University of London, and proceeded to Netley to go through the course prescribed for surgeons in the army. Having completed my studies there, I was duly attached to the Fifth Northumberland Fusiliers as Assistant Surgeon. The regiment was stationed in India at the time, and before I could join it, the second Afghan war had broken out. On landing at Bombay, I learned that my corps had advanced through the passes, and was already deep in the enemy's country.

victors & villains

SHERLOCK HOLMES

DR JOHN HENRY WATSON

EDGAR MORIARTY

EDIE ADLER

JAMES WINTER

Illustrations by [Sidney Paget](#), words by [Sir Arthur Conan Doyle](#).
What remains is by [Ethan Hawke](#).

This screenshot shows a smaller version of the website's layout, likely for a mobile device or a smaller screen. It includes the same header, quote, and character portraits, but the text below the quote is much smaller and less detailed than in the desktop version.

THE WEBLOGUE

BACK ISSUES

ABOUT OUR PAPER

The Baker Street
INQUIRER

"Give me problems, give me work."

In the year 1878 I took my degree of Doctor of Medicine of the University of London, and proceeded to Netley to go through the course prescribed for surgeons in the army. Having completed my studies there, I was duly attached to the Fifth Northumberland Fusiliers as Assistant Surgeon. The regiment was stationed in India at the time, and before I could join it, the second Afghan war had broken out. On landing at Bombay, I learned that my corps had advanced through the passes, and was already deep in the enemy's country.

victors & villains

SHERLOCK HOLMES

DR JOHN HENRY WATSON

EDGAR MORIARTY

EDIE ADLER

JAMES WINTER

Illustrations by [Sidney Paget](#), words by [Sir Arthur Conan Doyle](#).
What remains is by [Ethan Hawke](#).

SHERLOCK HOLMES

DR JOHN HENRY WATSON

EDGAR MORIARTY


EDIE ADLER

JAMES WINTER

Responsive Web Design

- “Think beyond the desktop, and craft designs that respond to your users’ needs – no matter how large or small the display.”
- 💡 Por defeito:
 - Smartphones renderizam páginas num viewport virtual, e encolhem o resultado
 - “Mobile is a magnifying glass for your usability problems.”

(Josh Brewer)



Resilient Web Design

- “It was as though the web design community were participating in a shared consensual hallucination. Rather than acknowledge the flexible nature of the browser window, they chose to settle on one set width as the ideal... even if that meant changing the ideal every few years.”
- “Look at the tools we use for designing on the web. It used to be Photoshop and then it was Sketch. Now it’s Figma. Whatever it is, they’re very precise high-fidelity pixel-perfect tools. They’re very imperative. So we take imperative approach and then we try to translate it into a declarative language like CSS which is supposed to be about setting boundary conditions, leaving the browser to figure out the details.”


(Jeremy Keith)

- “Be the browser’s mentor, not its micromanager.”

(Andy Bell)

A More Declarative Web Design

- + Avoid absolute widths
- + Do not optimize for specific devices
- + Use relative units
- + Use fluid grids
- + Keep layouts simple
- + **Media queries** (uma forma de aplicar regras CSS com base nas características do browser e do dispositivo)
 - Páginas adaptam-se ao dispositivo para melhorar usabilidade e aparência em qualquer tamanho e orientação do ecrã



CSS: Media queries

- Media features
 - Exemplos: `width`, `height`, `resolution`, `color`, `color-index`, ...

```
@media (width <= 600px) {...}  
@media (600px < width <= 1024px) {...}  
@media (width > 1024px) {...}  
@media (max-width: 600px) {...}  
@media (min-width: 601px) and (max-width: 1024px) {...}  
@media (min-width: 1025px) {...}
```

CSS: Media queries

```
@media (min-width: 300px) {  
    body { background-color: deeppink; }  
  
    @media (min-height: 500px) {  
        body {  
            background-image:  
                linear-gradient(  
                    to right,  
                    gold,  
                    transparent  
                );  
        }  
    }  
}
```

O mesmo
que um
AND

CSS: Media queries

Colunas laterais de 10px, colunas do meio ocupam 3/4 e 1/4 do restante espaço.

```
@media screen and (width >= 601px) {  
  .grid-container {  
    display: grid;  
    grid-template-columns: 10% 60% 20% 10%;  
    grid-template-rows: auto;  
    grid-template-areas:  
      ". header header ."  
      ". nav     nav   ."  
      ". main    aside ."  
      ". footer  footer ."  
  }  
  main {  
    margin-right: var(--small-margin);  
  }  
}
```

Linhas com altura ajustada ao conteúdo.

```
@media screen and (width <= 600px) {  
  .grid-container {  
    display: grid;  
    grid-template-columns: 1fr;  
    grid-template-rows: auto;  
    grid-template-areas:  
      "header"  
      "nav"  
      "aside"  
      "main"  
      "footer";  
  }  
  main {  
    margin-right: 0px;  
  }  
  aside {  
    margin-bottom: var(--small-margin);  
  }  
}
```

Uma só coluna a ocupar todo o espaço disponível