DEPARTAMENTO DE ELETRÓNICA, TELECOMUNICAÇÕES E INFORMÁTICA

**MESTRADO EM ENGENHARIA DE COMPUTADORES E TELEMÁTICA**

ANO 2025/2026

# MODELAÇÃO E DESEMPENHO DE REDES E SERVIÇOS

PRACTICAL GUIDE

Task 1

Consider a multiple-choice test such that each question has n multiple answers and only one is correct. Assume that the student has studied a percentage p (with $0\% \leq p \leq 100\%$) of the test content. When a question addresses the content that the student has studied, he selects the right answer with 100% of probability. Otherwise, the student always selects randomly one of the n answers with a uniform distribution.

1.a. When $p = 60\%$ and $n = 4$, determine the probability of the student to select the right answer. <u>Answer: 70%</u>

1.b. When $p = 70\%$ and $n = 5$, determine the probability of the student to know the answer when he selects the right answer. <u>Answer: 92.1%</u>

1.c. Draw a plot (with the same look as the plot below) with the probability of the student to select the right answer as a function of the probability p (consider the number of multiple answers $n = 3, 4$ and 5). What do you conclude from these results? <u>Answer:</u>


1.d. Draw a plot (with the same look as the plot below) with the probability of the student to know the answer when he selects the right answer as a function of the probability p (consider $n = 3, 4$ and 5). What do you conclude from these results? <u>Answer:</u>

Task 2

Consider a wireless link between multiple stations for data communications with a bit error rate (*ber*) of p. Assume that transmission errors in the different bits of a data frame are statistically independent (i.e., the number of errors of a data packet is a binomial random variable).

2.a. Determine the probability of a data frame of 100 Bytes to be received without errors when $p = 10^{-2}$. Answer: 0.0322%

2.b. Determine the probability of a data frame of 1000 Bytes to be received with exactly one error when $p = 10^{-3}$. Answer: 0.2676%

2.c. Determine the probability of a data frame of 200 Bytes to be received with one or more errors when $p = 10^{-4}$. Answer: 14.7863%

2.d. Draw a plot using a logarithmic scale for the X-axis (use the MATLAB function `semilogx`) with the same look as the plot below with the probability of a data frame (of size 100 Bytes, 200 Bytes or 1000 Bytes) being received without errors as a function of the *ber* (from $p = 10^{-8}$ up to $p = 10^{-2}$). What do you conclude from these results? Answer:


2.e. Draw a plot using a logarithmic scale for the Y-axis (use the MATLAB function `semilogy`) with the same look as the plot below with the probability of a data frame being received without errors (for $p = 10^{-4}$, 10^{-3} and 10^{-2}) as a function of the packet size (all integer values from 64 Bytes up to 1518 Bytes). What do you conclude from these results? Answer:

Task 3

Consider a wireless link between multiple stations for data communications. The bit error rate (*ber*) introduced by the wireless link (due to the variation of the propagation and interference factors along with time) is approximately given by the following Markov chain:


where the state transition rates are in number of transitions per hour. Consider that the link is in an interference state when its *ber* is at least 10^{-3} and in a normal state, otherwise. Assume that all stations detect with a probability of 100% when the data frames sent by the other stations are received with errors. Determine:

3.a. the probability of the link being in each of the five states; <u>answer:</u>
$9.86×10^{-1}$ (10^{-6}), $1.31×10^{-2}$ (10^{-5}), $6.57×10^{-4}$ (10^{-4}), $6.57×10^{-5}$ (10^{-3}), $1.31×10^{-5}$ (10^{-2})

3.b. the average percentage of time the link is in each of the five states; <u>answer:</u>
$9.86×10^{-1}$ (10^{-6}), $1.31×10^{-2}$ (10^{-5}), $6.57×10^{-4}$ (10^{-4}), $6.57×10^{-5}$ (10^{-3}), $1.31×10^{-5}$ (10^{-2})

3.c. the average *ber* of the link; <u>answer: $1.38×10^{-6}$</u>

3.d. the average holding time (in minutes) of the link in each of the five states;
<u>answer: 7.5 min (10^{-6}), 0.10 min (10^{-5}), 0.59 min (10^{-4}), 2.86 min (10^{-3}), 12.0 min (10^{-2})</u>

3.e. the probability of the link being in the normal state and in interference state; <u>answer:</u>
0.999921 (normal), $7.89×10^{-5}$ (interference)

3.f. the average *ber* of the link when it is in the normal state and when it is in the interference state; <u>answer: $1.18×10^{-6}$ (normal), $2.50×10^{-3}$ (interference)</u>

3.g. considering a data frame of size *B* (in Bytes) sent by one source station to a destination station, draw a plot with the same look as the plot below of the probability of the packet being received by the destination station <u>with at least one error</u> as a function of the packet size (from 64 Bytes up to 1500 Bytes); analyze and justify the results; <u>answer:</u>

3.h. considering that a data frame of size B (in Bytes) sent by one source station is received <u>with at least one error</u> by the destination station, draw a plot with the same look as the plot below of the probability of the link being <u>in the normal state</u> as a function of the packet size (from 64 Bytes up to 1500 Bytes); analyze and justify the results; <u>answer:</u>

3.i. considering that a data frame of size B (in Bytes) sent by one source station is received <u>without errors</u> by the destination station, draw a plot with the same look as the plot below (use the MATLAB function `semilogy`) of the probability of the link being <u>in the interference state</u> as a function of the packet size (from 64 Bytes up to 1500 Bytes); analyze and justify the results; <u>answer:</u>

Task 4

Consider an ideal link (i.e., with a *ber* = 0) from one router to another router with a capacity of C Mbps (1 Mbps = 10^6 bps) for IP communications. The link has a propagation delay of 10 μs (1 μs = 10^{-6} seconds). There is a very large queue at the output port of the link. The IP packet flow supported by the link is characterized by:

(i) the packet arrivals are a Poisson process with rate λ pps (packets/second)
(ii) the size of each IP packet is between 64 and 1518 bytes (the size includes the overhead of the Layer 2 protocol) with the probabilities: 19% for 64 bytes, 23% for 110 bytes, 17% for 1518 bytes and an equal probability for all other values (i.e., from 65 to 109 and from 111 to 1517).

Consider that λ = 1000 pps and C = 10 Mbps. Determine:

4.a. the average packet size (in Bytes) and the average packet transmission time of the IP flow; answer: 620.02 Bytes, 4.96×10^{-4} seconds

4.b. the average throughput (in Mbps) of the IP flow; answer: 4.96 Mbps

4.c. the capacity of the link, in packets/second; answer: 2016.06 pps

4.d. the average packet queuing delay and average packet system delay of the IP flow (the system delay is the queuing delay + transmission time + propagation delay) using the *M/G*/1 queuing model; answer: queuing – 4.60×10^{-4} seconds, system – 9.66×10^{-4} seconds

4.e. draw a plot with the same look as the plot below with the average packet system delay as a function of the packet arrival rate λ (from λ = 100 pps up to λ = 2000 pps); analyze the results and take conclusions.