```
# --- What counts as a deal ------------------------------------------------
filters:
  min_discount: 20        # % off the "was" price
  min_profit: 20          # dollars after fees, tax and shipping
  min_roi: 20             # % return on what you pay
  min_sales_30d: 8        # sold at least this many in 30 days (liquidity)
  min_price: 40
  max_price: 400
  require_sku: true       # only match on exact style code (avoids wrong-shoe mat

# --- Marketplace costs: CHECK these against your current StockX seller level ---
costs:
  seller_fee_pct: 0.10    # approx. seller fee + payment processing
  seller_flat_fee: 0
  shipping: 14            # your cost to ship a sold pair
  sales_tax: 0.095        # tax you pay when buying (LA County is about 9.5%)

# --- Resale price source --------------------------------------------------
resale:
  type: api               # api = third-party provider with StockX data | csv = y
  url: "https://REPLACE-WITH-PROVIDER/v1/stockx/products?query={sku}"
  api_key_env: RESALE_API_KEY

# --- Stores to scan (add as many as you like) -----------------------------
stores:
  - name: "Shoe Palace"
    type: shopify
    base_url: "https://www.shoepalace.com"
    collection: sale          # if the sale page doesn't load, change this to: al
    reliability: 8
    shipping: 8.00            # PLACEHOLDER: check what they charge at checkout a
    auto_coupons: true        # reads codes from their homepage banner each scan
    coupons: []               # add known codes here, e.g. - {code: TWENTY, amoun
  # - name: "Awin Feed Store"
  #   type: feed
  #   feed_url: "https://productdata.awin.com/datafeed/download/apikey/YOURKEY/..
  #   columns: {title: product_name, url: aw_deep_link, price: search_price, was:
  #   reliability: 9

  # --- Big retailers via a scraping service (needs SCRAPER_API_KEY secret). Open
  # fetch_url is your service's API with {key} and {url} placeholders; the line b
  # - name: "Nike Outlet"
  #   type: scrape
  #   fetch_url: "https://app.scrapingbee.com/api/v1/?api_key={key}&render_js=tru
```

```
  #   pages: ["https://www.nike.com/w/sale"]
  #   reliability: 10
  #   shipping: 0
  # - {name: "JD Sports",   type: scrape, fetch_url: "https://app.scrapingbee.com
  # - {name: "Finish Line", type: scrape, fetch_url: "https://app.scrapingbee.com
  # - {name: "Champs",      type: scrape, fetch_url: "https://app.scrapingbee.com

alerts:
  ntfy_topic: ""          # or set NTFY_TOPIC secret; install the free ntfy app a

db_path: deals.sqlite
output: deals.json
```