



/ Manage Jenkins / Clouds / docker-agents / Configure



Status



Configure



Cloud Statistics



Delete Cloud

[Build Executor Status](#)



Cloud docker-agents Configuration

Name

docker-agents

Docker Cloud details



Edited

Docker Host URI

unix:///var/run/docker.sock

Server credentials

- none -



Add

Advanced



Test Connection



Enabled

Error Duration

Default = 300

☐ Expose DOCKER_HOST

Container Cap

100

Docker Agent templates   Edited

Docker Agent templates

List of Images to be launched as agents

Docker Agent templates

Labels

python-agent

☒ Enabled

Name

python-agent

Docker Image

localhost:5000/python-agent:latest

Registry Authentication

Container settings  Edited

Instance Capacity

3

Remote File System Root

Usage

Idle timeout



Connect method

Prerequisites:

- Docker image must have [Java](#) installed.
- Docker image CMD must either be empty or simply sit and wait forever, e.g. `/bin/bash`.

The Jenkins remote agent code will be copied into the container and then run using the Java that's installed in the container.

See docker container [jenkins/agent](#) and/or source [jenkinsci/docker-agent](#) as an example.

User

Java Executable

JVM Arguments

EntryPoint Cmd

Stop timeout



Remove volumes

Pull strategy

Pull timeout

Node Properties



Add Node Property



Add Docker Template

Save

Apply