



/ Manage Jenkins ▾ / System ▾



System

Configure global settings and paths.

General

Home directory

By default, Jenkins stores all of its data in this directory on the file system

/var/jenkins_home



System Message

This message will be displayed at the top of the Jenkins main page. This can be useful for posting notifications to your users

Plain text [Preview](#)



Built-In Node is now configured in [Nodes](#).

Computer Retention Check Interval

60



Quiet period

5



SCM checkout retry count

0



Default view

☐ Restrict project naming

Jenkins Location

Jenkins URL

http://dev.citeve.pt/jenkins/

System Admin e-mail address

emoreira@citeve.pt

Serve resource files from another domain

Resource Root URL

Without a resource root URL, resources will be served from the Jenkins URL with Content-Security-Policy set.

Global properties

- ☐ Disable deferred wipeout on this node
- ☐ Disk Space Monitoring Thresholds
- ☐ Environment variables
- ☐ Keep node during Configuration as Code reload
- ☐ Tool Locations

Metrics

Access keys

 Add new access key

Pipeline Speed / Durability

Default Speed / Durability Level

None: use pipeline default (Maximum survivability/durability but slowest)

Usage Statistics

- ☒ Help make Jenkins better by sending anonymous usage statistics and crash reports to the Jenkins project

Folder Health Metrics

List of default health metrics for Folders

+ Add

Bitbucket Endpoints

Bitbucket Cloud



☐ Enable cache

Webhook management

Native Cloud

- ☐ Manage hooks
- ☐ Enable hooks signature verification
- ☐ Skip certificate verification
- ☐ Enable cache

+ Add

HTTP Proxy Configuration

Setup 

Global Build Time Out

☐ Enable Global Time Out

Develocity Build Scans

☐ Detect Build Scan links in all build logs

☐ Enable enriched summary

Develocity integration

Develocity Access Key credential ID

 The access key must be in the **<server host name>=<access key>** format. For more details please refer to the [documentation](#).

- none -

 Add

Develocity short-lived access tokens expiry

☐ Enable auto-injection

Timestamper

System clock time format

Elapsed time format

☐ Enabled for all Pipeline builds

Fingerprints

☐ Disable Fingerprint Cleanup

Administrative monitors

Administrative monitors are warnings shown to Jenkins administrators about the state of the Jenkins instance. It is generally strongly recommended to keep all administrative monitors enabled, but if you are not interested in specific warnings, uncheck them here to permanently hide them.

Administrative monitors 

Global Build Discarders

Project Build Discarder

Build discarders configured for a job are only run after a build finishes. This option runs jobs' configured build discarders periodically, applying configuration changes even when no new builds are run. This option has no effect if there is no build discarder configured for a job.

 Add

Default notification URL

Notification URL

Default

GitHub

GitHub Servers

+ Add GitHub Server

Advanced



Edited

GitHub API usage

Github API usage rate limiting strategy

Normalize API requests

GitHub Enterprise Servers

+ Add

Prometheus

Path

prometheus

Default Namespace

default

☐ Enable authentication for prometheus end-point

Collecting metrics period in seconds

120



- ☒ Count duration of successful builds
- ☒ Count duration of unstable builds
- ☒ Count duration of failed builds
- ☒ Count duration of not-built builds
- ☒ Count duration of aborted builds
- ☒ Fetch the test results of builds
- ☐ Add build parameter label to metrics
- ☐ Add build status label to metrics
- ☐ Process disabled jobs

Job attribute name

jenkins_job

Build parameters that will be added as separate labels to metrics

- ☒ Collect disk usage
- ☒ Collect node status
- ☐ Collect metrics for each run per build [Important: read help before enabling this option]
- ☐ Collect code coverage
- ☐ Disable metrics

Global Trusted Pipeline Libraries

Sharable libraries available to any Pipeline jobs running on this system. These libraries will be trusted, meaning they run without "sandbox" restrictions and may use @Grab.

Library



Name

jenkins-pipeline-helper

Default version

main

☐

Load implicitly

☒

Allow default version to be overridden

☒

Include @Library changes in job recent changes

☐

Cache fetched versions on controller for quick retrieval

Retrieval method

Modern SCM

Loads a library from an SCM plugin using newer interfaces optimized for this purpose. The recommended option when available.

Source Code Management

Git

Project Repository

https://github.com/eduardoftmoreira-citeve/jenkins-pipeline-

Credentials

eduardoftmoreira-citeve/*****

Add

Behaviours

Discover branches



Add

☐ Fresh clone per build

Library Path (optional)

.

Library



Name

Default version

- ☐ Load implicitly
- ☒ Allow default version to be overridden
- ☒ Include @Library changes in job recent changes
- ☐ Cache fetched versions on controller for quick retrieval

Retrieval method

Modern SCM

Loads a library from an SCM plugin using newer interfaces optimized for this purpose. The recommended option when available.

Source Code Management

Git

Project Repository

Credentials

- none -

+ Add

Behaviours

Discover branches

×

+ Add

☐ Fresh clone per build

Library Path (optional)

+ Add

Global Untrusted Pipeline Libraries

Sharable libraries available to any Pipeline jobs running on this system. These libraries will be untrusted, meaning they run with "sandbox" restrictions and cannot use @Grab.

+ Add

Build-timeout Plugin > BuildStep Action

☐ Enable BuildStep Action

Git plugin

Global Config user.name Value

Global Config user.email Value

- ☐ Create new accounts based on author/committer's email
 - ☐ Use existing account with same email if found
 - ☐ Show the entire commit summary in changes
 - ☐ Hide credential usage in job output
 - ☐ Disable performance enhancements
 - ☐ Preserve second fetch during checkout
 - ☐ Add git tag action to jobs
-

Shell

Shell executable

Extended E-mail Notification

SMTP server

SMTP Port

Advanced

 Edited

Default user e-mail suffix

@citeve.pt

Advanced 

 Edited

Default Content Type

Plain Text (text/plain)

List ID

☐ Add 'Precedence: bulk' E-mail Header

Default Recipients

Reply To List

Emergency reroute

Allowed Domains

Excluded Recipients

Default Subject

\$PROJECT_NAME - Build # \$BUILD_NUMBER - \$BUILD_STATUS!

Maximum Attachment Size

-1



Default Attach Build Log

Do Not Attach Build Log

Default Content

\$PROJECT_NAME - Build # \$BUILD_NUMBER - \$BUILD_STATUS:

Check console output at \$BUILD_URL to view the results.

Default Pre-send Script

Default Post-send Script

Additional groovy classpath

+ Add

- ☐ Enable Throttling
- ☒ Enable Debug Mode
- ☐ Require Administrator for Template Testing
- ☐ Enable watching for jobs
- ☐ Allow sending to unregistered users

Default Triggers 

Content Token Reference

E-mail Notification

SMTP server

Default user e-mail suffix

Advanced 

 Edited

☐ Test configuration by sending test e-mail

Save

Apply