

Allen B. Downey

The Little Book of Semaphores

Version 2.2.1

<http://www.greenteapress.com/semaphores/LittleBookOfSemaphores.pdf>

3.7.1 Reusable barrier non-solution (3.7.1a.rebarrier_nonsol.pml)

```
$ cat -n 3.7.1a.rebarrier_nonsol.pml | expand
```

```
1  /* The Little Book of Semaphores (2.2.1)
2    by A. Downey
3
4    Chapter 3. Basic synchronization patterns
5
6    3.7 Reusable barrier
7    3.7.1 Reusable barrier non-solution
8
9    vk, 2017
10 */
11
12 #define THREADS 3    /* value for threads number */
13 #define N        3    /* value for barrier limit */
14
15 #define wait(sem)    atomic { sem > 0; sem-- }
16 #define signal(sem) sem++
17
18 byte count=0, mutex=1, turnstile=0    /* turnstile is locked */
19
```

...

3.7.1 Reusable barrier non-solution (3.7.1a.rebarrier_nonsol.pml)

...

```
20 proctype Th(byte i) {
21     byte temp
22
23     rendezvous:
24     do
25         :: wait(mutex)
26             temp=count
27             count=temp+1
28             signal(mutex)
29         if
30             :: count == N ->
31                 signal(turnstile)
32             :: else
33         fi
34         wait(turnstile)
35         printf("Th(%d): count = %d\n",i,count)
36         signal(turnstile)

```

...

3.7.1 Reusable barrier non-solution (3.7.1a.rebarrier_nonsol.pml)

```
...
37  critical:
38      wait(mutex)
39      temp=count
40      count=temp-1
41      signal(mutex)
42      if
43      :: count == 0 ->
44          wait(turnstile)
45      :: else
46      fi
47      break    /* one only iteration */
48  od
49  }
50
...
```

3.7.1 Reusable barrier non-solution (3.7.1a.rebarrier_nonsol.pml)

```
$ spin 3.7.1a.rebarrier_nonsol.pml | expand
    Th(3): count = 3
    Th(2): count = 3
    Th(1): count = 3
    turnstile = 0
4 processes created

$ spin 3.7.1a.rebarrier_nonsol.pml | expand
    Th(1): count = 3
    Th(3): count = 3
    Th(2): count = 2
    turnstile = 0
4 processes created

$ spin 3.7.1a.rebarrier_nonsol.pml | expand
    Th(3): count = 3
    Th(2): count = 3
    Th(1): count = 1
    turnstile = 0
4 processes created
```

3.7.1 Reusable barrier non-solution (3.7.1b.rebarrier_nonsol.pml)

```
...
51  init {
52      byte i
53
54      atomic {
55          for (i: 1 .. THREADS) {
56              run Th(i)
57          }
58      }
59      _nr_pr == 1 ->
60          assert(turnstile == 0)
61          printf("turnstile = %d\n",turnstile)
62  }
```

3.7.1 Reusable barrier non-solution (3.7.1b.rebarrier_nonsol.pml)

```
$ spin 3.7.1b.rebarrier_nonsol.pml | expand
```

```
    Th(3): count = 3
    Th(2): count = 2
    Th(1): count = 2
    turnstile = 0
4 processes created
```

```
$ spin 3.7.1b.rebarrier_nonsol.pml | expand
```

```
    Th(2): count = 3
    Th(3): count = 3
    Th(1): count = 3
spin: 3.7.1b.rebarrier_nonsol.pml:60, Error: assertion violated
spin: text of failed assertion: assert((turnstile==0))
#processes: 1
    count = 0
    mutex = 1
    turnstile = 1
76:   proc 0 (:init::1) 3.7.1b.rebarrier_nonsol.pml:60 (state 12)
4 processes created
```

3.7.1 Reusable barrier non-solution (3.7.1c.rebarrier_nonsol.pml)

```
...
51  init {
52      byte i
53
54      atomic {
55          for (i: 1 .. THREADS) {
56              run Th(i)
57          }
58      }
59      _nr_pr == 1 ->
60          assert(turnstile < 3)
61          printf("turnstile = %d\n",turnstile)
62  }
```

3.7.1 Reusable barrier non-solution (3.7.1c.rebarrier_nonsol.pml)

```
$ spin 3.7.1c.rebarrier_nonsol.pml | expand
pan:1: invalid end state (at depth 55)
pan: wrote 3.7.1c.rebarrier_nonsol.pml.trail
```

(Spin Version 6.4.6 -- 2 December 2016)
Warning: Search not completed
+ Partial Order Reduction

Full statespace search for:

never claim	- (none specified)
assertion violations	+
cycle checks	- (disabled by -DSAFETY)
invalid end states	+

State-vector 48 byte, depth reached 61, **errors: 1**
66 states, stored
5 states, matched
71 transitions (= stored+matched)
12 atomic steps


hash conflicts: 0 (resolved)

...

3.7.1 Reusable barrier non-solution (3.7.1c.rebarrier_nonsol.pml)

```
$ spin -t -p -g -l 3.7.1c.rebarrier_nonsol.pml | expand
...
Starting Th with pid 1 ...
Starting Th with pid 2 ...
Starting Th with pid 3 ...
28:   proc 1 (Th:1) 3.7.1c.rebarrier_nonsol.pml:30 (state 7) [((count==3))]
29:   proc 1 (Th:1) 3.7.1c.rebarrier_nonsol.pml:31 (state 8) [turnstile = (turnstile+1)]
      turnstile = 1
...
38:   proc 3 terminates
...
      Th(2): count = 2
...
      Th(1): count = 1
...
54:   proc 2 terminates

55:   proc 1 (Th:1) 3.7.1c.rebarrier_nonsol.pml:41 (state 22)      [mutex = (mutex+1)]
      mutex = 1
56:   proc 1 (Th:1) 3.7.1c.rebarrier_nonsol.pml:43 (state 23)      [((count==0))]
spin: trail ends after 56 steps
#processes: 2
      count = 0
      mutex = 1
      turnstile = 0
56:   proc 1 (Th:1) 3.7.1c.rebarrier_nonsol.pml:44 (state 26)
56:   proc 0 (:init::1) 3.7.1c.rebarrier_nonsol.pml:59 (state 11)
4 processes created
...
```



3.7.1 Reusable barrier non-solution (3.7.1c.rebarrier_nonsol.pml)

```
$ spin -run -E 3.7.1c.rebarrier_nonsol.pml | expand
```

```
(Spin Version 6.4.6 -- 2 December 2016)
+ Partial Order Reduction
```

```
Full statespace search for:
```

never claim	- (none specified)
assertion violations	+
cycle checks	- (disabled by -DSAFETY)
invalid end states	- (disabled by -E flag)

```
State-vector 48 byte, depth reached 63, errors: 0
```

```
16071 states, stored
```

```
20784 states, matched
```

```
36855 transitions (= stored+matched)
```

```
12 atomic steps
```

```
hash conflicts:      7 (resolved)
```

```
...
```

3.7.3 Reusable barrier non-solution (3.7.3a.rebarrier_nonsol.pml)

```
$ cat -n 3.7.3a.rebarrier_nonsol.pml | expand
```

```
1  /* The Little Book of Semaphores (2.2.1)
2     by A. Downey
3
4     Chapter 3. Basic synchronization patterns
5
6     3.7 Reusable barrier
7     3.7.3 Reusable barrier non-solution #2
8
9     vk, 2017
10 */
11
12 #define THREADS 3    /* value for threads number */
13 #define N        3    /* value for barrier limit */
14
15 #define wait(sem)    atomic { sem > 0; sem-- }
16 #define signal(sem) sem++
17
18 byte count=0, mutex=1, turnstile=0    /* turnstile is locked */
19
```

...

3.7.3 Reusable barrier non-solution (3.7.3a.rebarrier_nonsol.pml)

```
...
20 proctype Th(byte i) {
21     byte temp
22
23     rendezvous:
24     do
25         :: wait(mutex)
26             temp=count
27             count=temp+1
28     if
29         :: count == N ->    /* may be true for one thread only */
30             signal(turnstile)
31         :: else
32     fi
33     signal(mutex)
34
35     wait(turnstile)
36     signal(turnstile)
37     printf("Th(%d): count = %d, turnstile = %d\n",
38           i, count, turnstile)

```

...

3.7.3 Reusable barrier non-solution (3.7.3a.rebarrier_nonsol.pml)

```
...
38  critical:
39      wait(mutex)
40      temp=count
41      count=temp-1
42      if
43      :: count == 0 ->    /* may be true for one threads only */
44          wait(turnstile) /* leave turnstile locked */
45      :: else
46      fi
47      signal(mutex)
48      break    /* one only iteration */
49  od
50  }
51
...
```

3.7.3 Reusable barrier non-solution (3.7.3a.rebarrier_nonsol.pml)

```
...
52  init {
53      byte i
54
55      atomic {
56          for (i: 1 .. THREADS) {
57              run Th(i)
58          }
59      }
60      _nr_pr == 1 ->
61          assert(turnstile == 0)
62          printf("turnstile = %d\n",turnstile)
63  }
```


3.7.3 Reusable barrier non-solution (3.7.3a.rebarrier_nonsol.pml)

```
$ spin -run 3.7.3a.rebarrier_nonsol.pml | expand
```

```
(Spin Version 6.4.6 -- 2 December 2016)
+ Partial Order Reduction
```

```
Full statespace search for:
```

```
never claim          - (none specified)
assertion violations +
cycle checks         - (disabled by -DSAFETY)
invalid end states  +
```

```
State-vector 48 byte, depth reached 61, errors: 0
```

```
...
```

3.7.3 Reusable barrier non-solution (3.7.3a.rebarrier_nonsol.pml)

```
$ spin 3.7.3a.rebarrier_nonsol.pml | expand
```

```
    Th(2): count = 3, turnstile = 1
```

```
    Th(1): count = 3, turnstile = 1
```

```
        Th(3): count = 2, turnstile = 1
```

```
    turnstile = 0
```

```
4 processes created
```

```
$ spin 3.7.3a.rebarrier_nonsol.pml | expand
```

```
        Th(3): count = 3, turnstile = 1
```

```
    Th(1): count = 3, turnstile = 0
```

```
        Th(2): count = 3, turnstile = 1
```

```
    turnstile = 0
```

```
4 processes created
```

```
$ spin 3.7.3a.rebarrier_nonsol.pml | expand
```

```
        Th(3): count = 3, turnstile = 0
```

```
    Th(2): count = 3, turnstile = 0
```

```
        Th(1): count = 1, turnstile = 0
```

```
    turnstile = 0
```

```
4 processes created
```

3.7.3 Reusable barrier non-solution (3.7.3b.rebarrier_nonsol.pml)

```
$ cat -n 3.7.3b.rebarrier_nonsol.pml | expand
```

```
1  /* The Little Book of Semaphores (2.2.1)
2     by A. Downey
3
4     Chapter 3. Basic synchronization patterns
5
6     3.7 Reusable barrier
7     3.7.3 Reusable barrier non-solution #2
8
9     vk, 2017
10 */
11
12 #define THREADS 3    /* value for threads number */
13 #define N        3    /* value for barrier limit */
14
15 #define wait(sem)    atomic { sem > 0; sem-- }
16 #define signal(sem) sem++
17
18 byte count=0, mutex=1, turnstile=0    /* turnstile is locked */
19 byte loop[THREADS+1]=1
20 bool sameLoop=true
```

...

3.7.3 Reusable barrier non-solution (3.7.3b.rebarrier_nonsol.pml)

```
...
22 proctype Th(byte i) {
23     byte temp, j
24
25     rendezvous:
26     do
27         :: wait(mutex)
28             temp=count
29             count=temp+1
30     if
31         :: count == N ->    /* may be true for one thread only */
32             signal(turnstile)
33         :: else
34     fi
35     signal(mutex)
36
37     wait(turnstile)
38     signal(turnstile)
39     printf("Th(%d): loop %d\n",i,loop[i])
40
41 ...
```

3.7.3 Reusable barrier non-solution (3.7.3b.rebarrier_nonsol.pml)

```
...
41 critical:
42     atomic {
43         for (j: 1 .. N-1) {
44             sameloop = sameloop && (loop[j] == loop[j+1])
45         }
46         assert(sameloop)
47     }
48
49     wait(mutex)
50     temp=count
51     count=temp-1
52     if
53     :: count == 0 ->    /* may be true for one threads only */
54         wait(turnstile) /* leave turnstile locked */
55     :: else
56     fi
57     signal(mutex)
58
...
```

3.7.3 Reusable barrier non-solution (3.7.3b.rebarrier_nonsol.pml)

```
...
59     if
60     :: loop[i] == 2 ->
61         break
62     :: else ->
63         loop[i]++
64     fi
65 od
66 }
67
68 init {
69     byte i
70
71     atomic {
72         for (i: 1 .. THREADS) {
73             run Th(i)
74         }
75     }
76     _nr_pr == 1 ->
77         assert(turnstile == 0)
78         printf("turnstile = %d\n",turnstile)
79 }
```

3.7.3 Reusable barrier non-solution (3.7.3b.rebarrier_nonsol.pml)

```
$ spin 3.7.3b.rebarrier_nonsol.pml | expand
    Th(1): loop 1
        Th(2): loop 1
            Th(3): loop 1
                Th(1): loop 2
spin: 3.7.3b.rebarrier_nonsol.pml:46, Error: assertion violated
spin: text of failed assertion: assert(sameloop)
#processes: 4
    count = 1
    mutex = 0
    turnstile = 1
    loop[0] = 1
    loop[1] = 2
    loop[2] = 2
    loop[3] = 1
    sameloop = 0
128:    proc  3 (Th:1) 3.7.3b.rebarrier_nonsol.pml:52 (state 38)
128:    proc  2 (Th:1) 3.7.3b.rebarrier_nonsol.pml:26 (state 47)
128:    proc  1 (Th:1) 3.7.3b.rebarrier_nonsol.pml:46 (state 26)
128:    proc  0 (:init::1) 3.7.3b.rebarrier_nonsol.pml:76 (state 11)
4 processes created
```

3.7.5 Reusable barrier solution (3.7.5.rebarrier.pml)

```
$ cat -n 3.7.5.rebarrier.pml | expand
 1  /* The Little Book of Semaphores (2.2.1)
 2     by A. Downey
 3
 4     Chapter 3. Basic synchronization patterns
 5
 6     3.7 Reusable barrier
 7     3.7.5 Reusable barrier solution
 8
 9     vk, 2017
10 */
11
12 #define THREADS 3    /* value for threads number */
13 #define N      3    /* value for barrier limit */
14
15 #define wait(sem)    atomic { sem > 0; sem-- }
16 #define signal(sem) sem++
17
18 byte count=0, mutex=1, turnstile=0, turnstile2=1
19 byte loop[THREADS+1]=1
20 bool sameloop=true
21
...
```

3.7.5 Reusable barrier solution (3.7.5.rebarrier.pml)

```
...
22 proctype Th(byte i) {
23     byte temp, j
24
25     rendezvous:
26     do
27         :: wait(mutex)
28             temp=count
29             count=temp+1
30         if
31             :: count == N ->
32                 wait(turnstile2)    /* lock the second */
33                 signal(turnstile)    /* unlock the first */
34             :: else
35             fi
36         signal(mutex)
37
38         wait(turnstile)              /* first turnstile */
39         signal(turnstile)
40         printf("Th(%d): loop %d\n",i,loop[i])
41
...

```

3.7.5 Reusable barrier solution (3.7.5.rebarrier.pml)

```
...
42 critical:
43     atomic {
44         for (j: 1 .. N-1) {
45             sameloop = sameloop && (loop[j] == loop[j+1])
46         }
47         assert(sameloop)
48     }
49
50     wait(mutex)
51     temp=count
52     count=temp-1
53     if
54         :: count == 0 ->
55             wait(turnstile)    /* lock the first */
56             signal(turnstile2) /* unlock the second */
57         :: else
58         fi
59     signal(mutex)
60
61     wait(turnstile2)           /* second turnstile */
62     signal(turnstile2)
...

```

3.7.5 Reusable barrier solution (3.7.5.rebarrier.pml)

```
...
63         if
64         :: loop[i] == 3 ->
65             break
66         :: else ->
67             loop[i]++
68         fi
69     od
70 }
71
72 init {
73     byte i
74
75     atomic {
76         for (i: 1 .. THREADS) {
77             run Th(i)
78         }
79     }
80     _nr_pr == 1 ->
81         assert(turnstile == 0)
82         assert(turnstile2 == 1)
83 }
```

3.7.5 Reusable barrier solution (3.7.5.rebarrier.pml)

```
$ spin 3.7.5.rebarrier.pml | expand
```

```
Th(1): loop 1
    Th(3): loop 1
    Th(2): loop 1
    Th(2): loop 2
    Th(3): loop 2
Th(1): loop 2
    Th(2): loop 3
Th(1): loop 3
    Th(3): loop 3
```

4 processes created

```
$ spin -run 3.7.5.rebarrier.pml | expand
```

(Spin Version 6.4.6 -- 2 December 2016)

+ Partial Order Reduction

Full statespace search for:

never claim	- (none specified)
assertion violations	+
cycle checks	- (disabled by -DSAFETY)
invalid end states	+

State-vector 48 byte, depth reached 236, **errors: 0**

...

3.7.6 Preloaded turnstile (3.7.6.rebarrier_preloaded.pml)

```
$ cat -n 3.7.6.rebarrier_preloaded.pml | expand
 1  /* The Little Book of Semaphores (2.2.1)
 2      by A. Downey
 3
 4      Chapter 3. Basic synchronization patterns
 5
 6      3.7 Reusable barrier
 7      3.7.6 Preloaded turnstile
 8
 9      vk, 2017
10  */
11
12  #define THREADS 3      /* value for threads number */
13  #define N        3      /* value for barrier limit */
14
15  #define wait(sem)      atomic { sem > 0; sem-- }
16  #define signal(sem)    sem++
17  #define signalN(sem,NN) for (j: 1 .. NN) { sem++ } /* no atomic */
18
19  byte count=0, mutex=1, turnstile=0, turnstile2=0
20  byte loop[THREADS+1]=1
21  bool sameLoop=true
...

```

3.7.6 Preloaded turnstile (3.7.6.rebarrier_preloaded.pml)

```
...
22
23  proctype Th(byte i) {
24      byte temp, j
25
26      rendezvous:
27          do
28              :: wait(mutex)
29                  temp=count
30                  count=temp+1
31              if
32                  :: count == N ->
33                      signalN(turnstile,N) /* unlock the first */
34                  :: else
35              fi
36              signal(mutex)
37
38              wait(turnstile) /* first turnstile */
39              printf("Th(%d): loop %d\n",i,loop[i])
40
...

```

3.7.6 Preloaded turnstile (3.7.6.rebarrier_preloaded.pml)

```
...
41  critical:
42      atomic {
43          for (j: 1 .. N-1) {
44              sameloop = sameloop && (loop[j] == loop[j+1])
45          }
46          assert(sameloop)
47      }
48
49      wait(mutex)
50      temp=count
51      count=temp-1
52      if
53      :: count == 0 ->
54          signalN(turnstile2,N) /* unlock the second */
55      :: else
56      fi
57      signal(mutex)
58
59      wait(turnstile2)          /* second turnstile */
...
```

3.7.6 Preloaded turnstile (3.7.6.rebarrier_preloaded.pml)

```
...
60      if
61      :: loop[i] == 3 ->
62          break
63      :: else ->
64          loop[i]++
65      fi
66  od
67 }
68
69 init {
70     byte i
71
72     atomic {
73         for (i: 1 .. THREADS) {
74             run Th(i)
75         }
76     }
77     _nr_pr == 1 ->
78         assert(turnstile == 0)
79         assert(turnstile2 == 0)
80 }
```


3.7.6 Preloaded turnstile (3.7.6.rebarrier_preloaded.pml)

```
$ spin -run 3.7.6.rebarrier_preloaded.pml | expand
```

```
(Spin Version 6.4.6 -- 2 December 2016)
+ Partial Order Reduction
```

Full statespace search for:

```
never claim           - (none specified)
assertion violations   +
cycle checks          - (disabled by -DSAFETY)
invalid end states     +
```

State-vector 48 byte, depth reached 272, **errors: 0**

```
$ spin 3.7.6.rebarrier_preloaded.pml | expand
```

```
Th(2): loop 1
Th(1): loop 1
Th(3): loop 1
Th(1): loop 2
Th(3): loop 2
Th(2): loop 2
Th(3): loop 3
Th(1): loop 3
Th(2): loop 3
```

4 processes created

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
$ cat -n 3.7.7.barrier_object.pml | expand
```

```
1  /* The Little Book of Semaphores (2.2.1)
2    by A. Downey
3
4    Chapter 3. Basic synchronization patterns
5
6    3.7 Reusable barrier
7    3.7.7 Barrier objects
8
9    vk, 2017
10 */
11
12 #include "Semaphore.h"
13 #include "Barrier.h"
14
15 #define THREADS 3    /* value for threads number */
16 #define N       3    /* value for barrier limit */
17
18 Semaphore mutex=1
19 Barrier   barrier
20
21 byte loop[THREADS+1]=1
22 unsigned group : 31 = 0
23
```

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
...
24 proctype Th(byte i) {
25     do
26         ::
27             printf("Th(%d): loop %d\n",i,loop[i])
28     rendezvous:
29         bar_wait(barrier)
30     critical:
31         group=group*10+loop[i]
32         assert(group==1 || group==11 || group==111 ||
33             group==1112 || group==11122 || group==111222 ||
34             group==1112223 || group==11122233 || group==111222333)
35         printf("Th(%d): loop %d passed with %d\n",i,loop[i],group)
36
37         if
38             :: loop[i] == 3 ->
39                 break
40             :: else ->
41                 loop[i]++
42         fi
43     od
44 }
45
...
```

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
...
46 init {
47     byte i
48
49     bar_init(barrier,N)
50
51     atomic {
52         for (i: 1 .. THREADS) {
53             run Th(i)
54         }
55     }
56     _nr_pr == 1 ->
57         assert(barrier._turnstile == 0)
58         assert(barrier._turnstile2 == 0)
59 }
```

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
$ cat -n Semaphore.h | expand
```

```
1
2  #define Semaphore    byte
3
4  #define wait(sem)      atomic { sem > 0; sem-- }
5  #define signal(sem)    sem++
6  #define signalN(sem,NN) for (_i: 1 .. NN) { sem++ } /* no atomic */
7
8  byte _i=0
9
```

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
$ cat -n Barrier.h | expand
```

```
1
2  typedef Barrier {
3      byte      _n
4      byte      _count
5      Semaphore _mutex
6      Semaphore _turnstile
7      Semaphore _turnstile2
8  }
9
10 inline bar_init(bar,n) {
11     bar._n      = n
12     bar._count   = 0
13     bar._mutex   = 1
14     bar._turnstile = 0
15     bar._turnstile2 = 0
16 }
17
```

...

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
...
18 inline bar_phase1(bar) {
19     wait(bar._mutex)
20     bar._count++    /* atomic here */
21     if
22     :: bar._count == bar._n ->
23         signalN(bar._turnstile,bar._n)
24     :: else
25     fi
26     signal(bar._mutex)
27     wait(bar._turnstile)
28 }
29
...
```

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
...
30 inline bar_phase2(bar) {
31     wait(bar._mutex)
32     bar._count--    /* atomic here */
33     if
34     :: bar._count == 0 ->
35         signalN(bar._turnstile2,bar._n)
36     :: else
37     fi
38     signal(bar._mutex)
39     wait(bar._turnstile2)
40 }
41
42 inline bar_wait(bar) {
43     bar_phase1(bar)
44     bar_phase2(bar)
45 }
46
```

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
$ spin -T 3.7.7.barrier_object.pml | expand
```

```
Th(1): loop 1
Th(2): loop 1
Th(3): loop 1
Th(2): loop 1 passed with 1
Th(1): loop 1 passed with 11
Th(2): loop 2
Th(3): loop 1 passed with 111
Th(1): loop 2
Th(3): loop 2
Th(1): loop 2 passed with 11122
Th(2): loop 2 passed with 11122
Th(2): loop 3
Th(3): loop 2 passed with 111222
Th(1): loop 3
Th(3): loop 3
Th(2): loop 3 passed with 1112223
Th(1): loop 3 passed with 11122233
Th(3): loop 3 passed with 111222333
4 processes created
```

3.7.7 Barrier objects (3.7.7.barrier_object.pml)

```
$ spin -run 3.7.7.barrier_object.pml | expand
```

```
(Spin Version 6.4.6 -- 2 December 2016)
+ Partial Order Reduction
```

```
Full statespace search for:
```

```
never claim          - (none specified)
assertion violations +
cycle checks         - (disabled by -DSAFETY)
invalid end states  +
```

```
State-vector 52 byte, depth reached 232, errors: 0
```

```
...
```

3.8.4 Exclusive queue (3.8.4a.exclusive_queue.pml)

```
$ cat -n 3.8.4a.exclusive_queue.pml | expand
```

```
1  /* The Little Book of Semaphores (2.2.1)
2     by A. Downey
3
4     Chapter 3. Basic synchronization patterns
5
6     3.8 Queue
7     3.8.4 Exclusive queue solution
8
9     vk, 2017
10 */
11
12 #include "Semaphore.h"
13
14 #define N 6
15
16 Semaphore mutex=1, leaderQueue=0, followerQueue=0, rendezvous=0
17 byte      leaders=0, followers=0
18
```

...

3.8.4 Exclusive queue (3.8.4a.exclusive_queue.pml)

...

```
19 proctype Leader(byte i) {
20     wait(mutex)
21     if
22     :: followers > 0 ->
23         followers--
24         signal(followerQueue)
25     :: else ->
26         leaders++
27         signal(mutex)
28         wait(leaderQueue)
29     fi
30
31     dance:
32         printf("leader %d: to dance\n",i)
33         wait(rendezvous)
34         printf("leader %d: dancing\n",i)
35         signal(mutex)
36 }
37
```

...

3.8.4 Exclusive queue (3.8.4a.exclusive_queue.pml)

```
...
38  proctype Follower(byte i) {
39      wait(mutex)
40      if
41      :: leaders > 0 ->
42          leaders--
43          signal(leaderQueue)
44      :: else ->
45          followers++
46          signal(mutex)
47          wait(followerQueue)
48      fi
49
50  dance:
51      atomic {
52          signal(rendezvous)
53          printf("follower %d: dancing\n",i)
54      }
55  }
56
...
```

3.8.4 Exclusive queue (3.8.4a.exclusive_queue.pml)

```
...
57  init {
58      byte i
59
60      atomic {
61          for (i: 1 .. N) {
62              if
63              :: i % 2 -> run Leader(i)
64              :: else -> run Follower(i)
65              fi
66          }
67      }
68  }
```

3.8.4 Exclusive queue (3.8.4a.exclusive_queue.pml)

```
$ spin -T 3.8.4a.exclusive_queue.pml | expand
follower 2: dancing
leader 1: to dance
leader 1: dancing
follower 6: dancing
leader 3: to dance
leader 3: dancing
follower 4: dancing
leader 5: to dance
leader 5: dancing
7 processes created
```

```
$ spin -T 3.8.4a.exclusive_queue.pml | expand
follower 2: dancing
leader 5: to dance
leader 5: dancing
leader 3: to dance
follower 6: dancing
leader 3: dancing
leader 1: to dance
follower 4: dancing
leader 1: dancing
7 processes created
```

3.8.4 Exclusive queue (3.8.4b.exclusive_queue.pml)

```
...
19 proctype Leader(byte i) {
20     wait(mutex)
21     if
22     :: followers > 0 ->
23         followers--
24         assert(followerQueue == 0)
25         signal(followerQueue)
26     :: else ->
27         leaders++
28         signal(mutex)
29         wait(leaderQueue)
30     fi
31
32     dance:
33         printf("leader %d: to dance\n",i)
34         wait(rendezvous)
35         printf("leader %d: dancing\n",i)
36         signal(mutex)
37 }
38
...
```


3.8.4 Exclusive queue (3.8.4b.exclusive_queue.pml)

```
...
39  proctype Follower(byte i) {
40      wait(mutex)
41      if
42      :: leaders > 0 ->
43          leaders--
44          assert(leaderQueue == 0)
45          signal(leaderQueue)
46      :: else ->
47          followers++
48          signal(mutex)
49          wait(followerQueue)
50      fi
51
52  dance:
53      atomic {
54          signal(rendezvous)
55          printf("follower %d: dancing\n",i)
56      }
57  }
58
...
```

3.8.4 Exclusive queue (3.8.4b.exclusive_queue.pml)

```
$ spin -run 3.8.4b.exclusive_queue.pml | expand
```

```
(Spin Version 6.4.6 -- 2 December 2016)
+ Partial Order Reduction
```

Full statespace search for:

never claim	- (none specified)
assertion violations	+
cycle checks	- (disabled by -DSAFETY)
invalid end states	+

State-vector 68 byte, depth reached 77, **errors: 0**

```
...
```

3.8.4 Exclusive queue (3.8.4c.exclusive_queue.pml)

```
$ cat -n 3.8.4c.exclusive_queue.pml | expand
```

```
1  /* The Little Book of Semaphores (2.2.1)
2     by A. Downey
3
4     Chapter 3. Basic synchronization patterns
5
6     3.8 Queue
7     3.8.4 Exclusive queue solution
8
9     vk, 2017
10 */
11
12 #include "Semaphore.h"
13
14 #define N 5
15
16 Semaphore mutex=1, leaderQueue=0, followerQueue=0, rendezvous=0
17 byte      leaders=0, followers=0
18
...
```

3.8.4 Exclusive queue (3.8.4c.exclusive_queue.pml)

```
$ spin -run 3.8.4c.exclusive_queue.pml | expand
```

```
pan:1: invalid end state (at depth 59)
pan: wrote 3.8.4c.exclusive_queue.pml.trail
```

(Spin Version 6.4.6 -- 2 December 2016)

Warning: Search not completed
+ Partial Order Reduction

Full statespace search for:

never claim	- (none specified)
assertion violations	+
cycle checks	- (disabled by -DSAFETY)
invalid end states	+

State-vector 60 byte, depth reached 60, **errors: 1**

...

3.8.4 Exclusive queue (3.8.4c.exclusive_queue.pml)

```
$ spin -run -E 3.8.4c.exclusive_queue.pml | expand
```

```
(Spin Version 6.4.6 -- 2 December 2016)
+ Partial Order Reduction
```

```
Full statespace search for:
```

```
never claim          - (none specified)
assertion violations  +
cycle checks          - (disabled by -DSAFETY)
invalid end states    - (disabled by -E flag)
```

```
State-vector 60 byte, depth reached 60, errors: 0
```

```
...
```

3.8.4 Exclusive queue (3.8.4d.exclusive_queue.pml)

```
$ cat -n 3.8.4d.exclusive_queue.pml | expand
```

```
1  /* The Little Book of Semaphores (2.2.1)
2    by A. Downey
3
4    Chapter 3. Basic synchronization patterns
5
6    3.8 Queue
7    3.8.4 Exclusive queue solution
8
9    vk, 2017
10 */
11
12 #include "Semaphore.h"
13
14 #define N 6
15
16 Semaphore mutex=1, leaderQueue=0, followerQueue=0, rendezvous=0
17 byte      leaders=0, followers=0
18
```

```
...
```

3.8.4 Exclusive queue (3.8.4d.exclusive_queue.pml)

```
...
59  init {
60      byte i
61
62      atomic {
63          for (i: 0 .. N) {
64              if
65                  :: i % 2 -> run Leader(i)
66                  :: else -> run Follower(i)
67              fi
68          }
69      }
70  }
```

3.8.4 Exclusive queue (3.8.4d.exclusive_queue.pml)

```
$ spin -run 3.8.4d.exclusive_queue.pml | expand
pan:1: invalid end state (at depth 83)
pan: wrote 3.8.4d.exclusive_queue.pml.trail
```

(Spin Version 6.4.6 -- 2 December 2016)

Warning: Search not completed
+ Partial Order Reduction

Full statespace search for:

never claim	- (none specified)
assertion violations	+
cycle checks	- (disabled by -DSAFETY)
invalid end states	+

State-vector 76 byte, depth reached 84, **errors: 1**

...

3.8.4 Exclusive queue (3.8.4d.exclusive_queue.pml)

```
$ spin -run -E 3.8.4d.exclusive_queue.pml | expand
```

```
(Spin Version 6.4.6 -- 2 December 2016)
+ Partial Order Reduction
```

```
Full statespace search for:
```

never claim	- (none specified)
assertion violations	+
cycle checks	- (disabled by -DSAFETY)
invalid end states	- (disabled by -E flag)

```
State-vector 76 byte, depth reached 84, errors: 0
```

```
...
```