



VIZM.EX15228 Fittings, Rubber Gasketed

[Page Bottom](#)

Fittings, Rubber Gasketed

[See General Information for Fittings, Rubber Gasketed](#)
SHANDONG LEDE MACHINERY CO LTD

EX15228

No 3998

West Waihuan N Rd

Weicheng District

Weifang, Shandong 261057 CHINA

Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT1	Cut, Rolled	40	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"	300
XGQT1	Cut, Rolled	GB/T3091	2-1/2" (76.1 mm), 5" (139.7 mm)	300
XGQT1	Cut, Rolled	GB/T3092	6" (165 mm)	300
XGQT1-M1	Cut	40	4", 6", 8"	500
XGQT1-M1	Cut	GB/T8163	5"	500
GKS	Rolled	10	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10"	300
GKS	Cut, Rolled	40	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"	300
GKS	Rolled	GB/T3091	3 OD (76.1 mm), 5-1/2 OD (139.7 mm), 6-1/2 OD (165.1 mm)	300
GKS	Rolled	Fire-Flo Schedule 7	1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	300
1512	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5	500
1512	Rolled	10	6, 8	450
1512	Rolled	10	10	400
1512	Cut, Rolled	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5	500
1512	Cut, Rolled	40	6, 8	450
1512	Cut, Rolled	40	10, 12	400
1512	Cut, Rolled	GB/T3091	3 OD (76.1 mm), 5-1/2 OD (139.7 mm)	500
1512	Cut, Rolled	GB/T3091	6-1/2 OD (165.1 mm)	450

Fast-connected coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT4	Rolled	Fire-Flo Schedule 7	1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	300
XGQT4	Rolled	10	1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"	300

Flange Adapter

				Rated Pressure
--	--	--	--	----------------

Model	Groove Type	Pipe	Size (in.)	(psig)
XGQT09	Cut, Rolled	40	2", 2-1/2", 3", 4", 5", 6", 8"	175
XGQT09	Cut, Rolled	GB/T3091	2-1/2" (76.1 mm), 5" (139.7 mm)	175
XGQT09	Cut, Rolled	GB/T3092	6" (165 mm)	175
L991	Cut, Rolled	40	2", 2-1/2", 3", 4", 5", 6", 8"	250

Flexible coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT1	Rolled	Fire-Flo Schedule 7	1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	300
XGQT1	Rolled	10	1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"	300
XGQT2	Cut, Rolled	40	1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"	300
XGQT2	Cut, Rolled	GB/T3091	2-1/2" (76.1 mm), 5" (139.7 mm)	300
XGQT2	Cut, Rolled	GB/T3092	6" (165 mm)	300
XGQT2	Rolled	Fire-Flo Schedule 7	1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	300
XGQT2	Rolled	10	1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	300
1212	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2, 4, 5	500
1212	Rolled	10	6	450
1212	Cut, Rolled	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2, 4, 5	500
1212	Cut, Rolled	40	6, 8	450
1212	Cut, Rolled	40	10, 12	400
1212	Cut, Rolled	GB/T3091	3 OD (76.1 mm), 5-1/2 OD (139.7 mm)	500
1212	Cut, Rolled	GB/T3091	6-1/2 OD (165.1 mm)	450

Reducing Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT3	Cut, Rolled	40	2" x 1-1/2", 2-1/2" x 2", 3" x 2", 3" x 2-1/2", 4" x 2", 4" x 2-1/2", 4" x 3", 6" x 2-1/2", 6" x 3", 6" x 4", 8" x 6"	300
XGQT3	Cut, Rolled	40 x GB/T3091	3" x 76.1 mm	300
XGQT3	Cut, Rolled	40 x GB/T3091	4" x 76.1 mm	300
XGQT3	Cut, Rolled	GB/T3091 x 40	76.1 mm x 2"	300
XGQT3	Rolled	10	1-1/2 x 1-1/4; 2-1/2 x 1, 1-1/4, 1-1/2; 3 x 1, 1-1/4, 1-1/2; 5 x 4; 6 x 5, 6-1/2 OD (165.1 mm)	300
XGQT3	Cut, Rolled	40	1-1/2 x 1-1/4; 2-1/2 x 1, 1-1/4, 1-1/2; 3 x 1, 1-1/4, 1-1/2; 5 x 4; 6 x 5, 6-1/2 OD (165.1 mm)	300
XGQT3	Cut, Rolled	GB/T3091	3 OD (76.1 mm) x 1-1/2, 2-1/2; 6-1/2 OD (165.1 mm) x 3	300

Side outlet

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
-------	-------------	------	------------	-----------------------

XGQT04	Threaded	40	2" x 1/2", 3/4", 1", 1-1/4", 1-1/2"	300
XGQT04	Threaded	40	2-1/2" x 1/2", 3/4", 1", 1-1/4", 1-1/2"	300
XGQT04	Threaded	40	3" x 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"	300
XGQT04	Threaded	40	4" x 1", 1-1/4", 1-1/2", 2", 2-1/2"	300
XGQT04	Threaded	40	5" x 1", 1-1/4", 1-1/2", 2", 2-1/2"	300
XGQT04	Threaded	40	6" x 1", 1-1/4", 1-1/2", 2", 2-1/2"	300
XGQT04	Threaded	40	8" x 1", 1-1/4", 1-1/2", 2", 2-1/2"	300
XGQT04	Threaded	GB/T3091	76.1 mm x 1/2", 3/4", 1", 1-1/4", 1-1/2"	300
XGQT04	Threaded	GB/T3091	139.7 mm x 1", 1-1/4", 1-1/2", 2", 2-1/2"	300
XGQT04	Threaded	GB/T3092	165 mm x 1", 1-1/4", 1-1/2", 2", 2-1/2"	300
XGQT04G	Grooved	40	2" x 1-1/4", 1-1/2"	300
XGQT04G	Grooved	10, 40	2-1/2" x 1-1/4", 1-1/2"	300
XGQT04G	Grooved	40	3" x 1-1/4", 1-1/2", 2"	300
XGQT04G	Grooved	40	4" x 1-1/4", 1-1/2", 2", 2-1/2", 76.1 mm	300
XGQT04G	Grooved	40	5" x 1-1/2", 2"	300
XGQT04G	Grooved	10, 40	6" x 1-1/4", 1-1/2", 2-1/2"	300
XGQT04G	Grooved	40	6" x 2", 76.1 mm	300
XGQT04G	Grooved	10, 40	6" x 3", 4"	175
XGQT04G	Grooved	10, 40	8" x 2-1/2", 76.1 mm, 3"	300
XGQT04G	Grooved	GB/T3091	76.1 mm x 1-1/4", 1-1/2"	300
XGQT04G	Grooved	GB/T3091	139.7 mm x 1-1/2", 2"	300
XGQT04G	Grooved	GB/T3092	165 mm x 2", 76.1 mm	300
041	Threaded	40	1-1/4" x 1/2", 3/4", 1"	300
041	Threaded	40	1-1/2" x 1/2", 3/4", 1"	300
041	Threaded	40	2" x 1/2", 3/4", 1"	300
041	Threaded	40	2-1/2" x 1/2", 3/4", 1"	300
L922	Threaded	10	1-1/4" x 1/2", 3/4", 1"	300
L922	Threaded	10	1-1/2" x 1/2", 3/4", 1"	300
L922	Threaded	10	2" x 1/2", 3/4", 1"	300
L922	Threaded	10	2-1/2" x 1/2", 3/4", 1"	300
L922	Threaded	GB/T3091	76.1 mm x 1/2", 3/4", 1"	300

Models XGQT04, 041 and L922 in the 1/2, 3/4, and 1 in. nominal outlet size is intended for direct connection to sprinklers.

Models XGQT04, 041, XGQT42 and L922 in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

10 refers to Schedule 10 steel pipe in accordance with NFPA 13.

40 refers to Schedule 40 steel pipe in accordance with NFPA 13.

GB/T3091 refers to steel pipe manufactured in accordance with GB/T3091.

GB/T3092 refers to steel pipe manufactured in accordance with GB/T3092.

GB/T8163 refers to steel pipe manufactured in accordance with GB/T8163.

Fire-Flo Schedule 7 refers to Youngstown Tube Schedule 7 pipes.

Trademark and/or Tradename: "PREM",

LEDE

[Last Updated](#) on 2016-08-23[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".