



HHXX.EX6624

Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

Page Bottom

Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

See General Information for Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

JINAN MEIDE CASTING CO LTD

EX6624

3 NANMEN RD

PINGYIN

JINAN, SHANDONG 250400 CHINA

Ductile Iron Fittings (ANSI/ASME B16.3)

Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.3

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
90R	Reducing 90° Elbow	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2 3x3/4	500
120	45° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500
130	Tee	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
130R	Reducing Tee	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3/4x1/2x1/2, 3/4x1/2x3/4, 2-1/2x2-1/2x3/4, 2-1/2x2-1/2x1, 2-1/2x2-1/2x1-1/4, 2-1/2x2-1/2x1-1/2, 2-1/2x2-1/2x2, 2-1/2x2-1/2x3	500
241	Hex Bushing	1, 1-1/4, 1-1/2, 2, 1-1/4x3/4	500
220	Straight Coupling w/stop	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500
240	Reducing	1/2, 3/4, 1, 1-1/4,	500
	Coupling w/hex	1-1/4x1, 1-1/2x1, 1-1/2x1-1/4, 2x1-1/4, 2x1-1/2	
180	Cross	1, 1-1/4, 1-1/2, 2 3/4	500
180R	Reducing Cross	1-1/4, 1-1/2, 2	500
300	Cap	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500
291	Square Head Plug	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
342	Union	1, 1-1/4, 1-1/2, 2	500

CAST IRON FITTINGS

Cast Iron Fittings (ANSI/ASME B16.4)

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
90R	Reducing 90° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3/4x1/2, 3x2	300
120	45° Elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
130	Tee	1, 1-1/4, 1-1/2, 2, 2-1/2 3, 4	300
130R	Reducing Tee	1, 1-1/4, 1-1/2, 2, 2-1/2, 1x1x1-1/2, 2x1/2x2, 2x1x1-1/2, 2-1/2x1/2x2-1/2, 2-1/2x2x1/2, 2-1/2x2x3/4, 2-1/2x2x1, 2-1/2x2x1-1/4, 2-1/2x2x1-1/2, 2-1/2x2x2, 2-1/2x2x2-1/2, 3x3x1-1/4, 3x3x1-1/2, 3x3x2	300
180	Cross	1, 1-1/4, 1-1/2, 2	300
180R	Reducing Cross	1-1/4x1, 1-1/2x1, 2x1	300
240	Reducing Coupling w/hex	1, 2, 1-1/4x1, 2x3/4	300
291	Cored Plugs	3/4, 1, 1-1/4, 1-1/2, 2	300
291S	Solid Plugs	1/2	300

Malleable Iron Fittings (ANSI/ASME B16.3, ANSI/ASME B16.14)

Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.3

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
90	90° Elbow	2-1/2, 3, 3-1/2, 4, 5, 6	300
90R	90° Reducing Elbow	1/2x1/4, 3/8; 3/4x1/4, 3/8, 1/2; 1x3/8, 1/2, 3/4; 1-1/4x1/2, 3/4, 1; 1-1/2x3/4, 1, 1-1/4; 2x3/4, 1, 1-1/4, 1-1/2	500
90R	90° Reducing Elbow	2-1/2x1-1/2, 2; 3x2, 2-1/2; 4x3	300
92	90° Street Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
92	90° Street Elbow	2-1/2, 3, 4, 6	300
120	45° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
120	45° Elbow	2-1/2, 3, 4, 5, 6	300
121	45° Street Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
121	45° Street Elbow	2-1/2, 3, 4	300
130	Tee	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
130	Tee	2-1/2, 3, 3-1/2, 4, 5, 6	300
130R	Reducing Tee	3/8x3/8x1/2, 1/2x1/4x1/2, 1/2x3/8x1/2, 1/2x1/2x1/4, 1/2x1/2x3/8, 1/2x1/2x3/4, 1/2x1/2x1, 3/4x1/2x1/2, 3/4x1/2x3/4, 3/4x3/4x1/4, 3/4x3/4x3/8, 3/4x3/4x1/2, 3/4x3/4x1, 1x1/2x1/2, 1x1/2x3/4, 1x1/2x1, 1x3/4x1/2, 1x3/4x3/4, 1x3/4x1, 1x1x1/4, 1x1x3/8, 1x1x1/2, 1x1x3/4, 1x1x1-1/4, 1x1x1-1/2, 1x1x2, 1-1/4x1/2x1, 1-1/4x1/2x1-1/4, 1-1/4x3/4x3/4, 1-1/4x3/4x1, 1-1/4x3/4x1-1/4, 1-1/4x1x1/2, 1-1/4x1x3/4, 1-1/4x1x1, 1-1/4x1x1-1/4, 1-1/4x1-1/4x3/8, 1-1/4x1-1/4x1/2, 1-1/4x1-1/4x3/4, 1-1/4x1-1/4x1, 1-1/4x1-1/4x1-1/2, 1-1/4x1-1/4x2, 1-1/2x1/2x1-1/2, 1-1/2x3/4x1-1/2, 1-1/2x1x1, 1-1/2x1x1-1/4, 1-1/2x1x1-1/2, 1-1/2x1-1/4x1/2, 1-1/2x1-1/4x3/4, 1-1/2x1-1/4x1, 1-1/2x1-1/4x1-1/4, 1-1/2x1-1/4x1-1/2, 1-1/2x1-1/2x1/2, 1-1/2x1-1/2x3/4, 1-	500

		1/2x1-1/2x1, 1-1/2x1-1/2x1-1/4, 1-1/2x1-1/2x2, 2x1/2x2, 2x3/4x2, 2x1x1-1/2, 2x1x2, 2x1-1/4x1-1/4, 2x1-1/4x1-1/2, 2x1-1/4x2, 2x1-1/2x1, 2x1-1/2x1-1/4, 2x1-1/2x1-1/2, 2x1-1/2x2, 2x2x1/2, 2x2x3/4, 2x2x1, 2x2x1-1/4, 2x2x1-1/2	
130R	Reducing Tee	2x2x2-1/2, 2-1/2x1-1/2x2, 2-1/2x1-1/2x2-1/2, 2-1/2x2x2, 2-1/2x2x2-1/2, 2-1/2x2-1/2x3/4, 2-1/2x2-1/2x1, 2-1/2x2-1/2x1-1/4, 2-1/2x2-1/2x1-1/2, 2-1/2x2-1/2x2, 3x2x2, 3x2x3, 3x3x3/4, 3x3x1, 3x3x1-1/4, 3x3x1-1/2, 3x3x2, 3x3x2-1/2, 4x4x1-1/2, 4x4x2, 4x4x2-1/2, 4x4x3	300
134	Street Tee	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
165	45° Y-Branches	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
165	45° Y-Branches	2-1/2, 3, 4	300
180	Cross	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
180	Cross	2-1/2, 3, 3-1/2, 4	300
180R	Reducing Cross	3/4x1/2, 1x1/2, 1x3/4, 1-1/4x3/4, 1-1/4x1, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2	500
180R	Reducing Cross	2-1/2x2, 3x2	300
220	Coupling	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
220	Coupling	2-1/2, 3, 4	300
240	Reducing Coupling	1/2x1/8, 1/2x1/4, 1/2x3/8, 3/4x1/4, 3/4x3/8, 3/4x1/2, 1x1/4, 1x3/8, 1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x1/2, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2	500
240	Reducing Coupling	2-1/2x1-1/2, 2-1/2x2, 3x1-1/2, 3x2, 3x2-1/2, 4x2, 4x3	300
300	Cap	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
300	Cap	2-1/2, 3, 3-1/2, 4, 5, 6	300

Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.14

Model	Configuration	Size, in.	Rated Pressure, psig
241	Bushing	1/2x1/8, 1/2x1/4, 1/2x3/8, 3/4x1/8, 3/4x1/4, 3/4x3/8, 3/4x1/2, 1x1/8, 1x1/4, 1x3/8, 1x1/2, 1x3/4, 1-1/4x1/4, 1-1/4x3/8, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/4, 1-1/2x3/8, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x1/4, 2x3/8, 2x1/2, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2, 2-1/2x1/2, 2-1/2x3/4, 2-1/2x1, 2-1/2x1-1/4, 2-1/2x1-1/2, 2-1/2x2, 3x1/2, 3x3/4, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 3x2-1/2, 3-1/2x2-1/2, 3-1/2x3, 4x1-1/4, 4x1-1/2, 4x3, 4x3-1/2, 5x4, 6x5	300
291	Cored Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2	300
291S	Solid Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2	300
291-4	Slotted Head Plugs	4, 5, 6	300
291N	Countersunk Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300

Last Updated on 2008-03-10

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2009 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

