



NB-988

Conventional Rate of Rise
Heat Detector

NB-989

Conventional Fixed
Temperature Heat Detector



988,989 Series detectors are manufactured in accordance with CE/ISO 9001 standards, and can be calibrated to EN-54

NB 988/989 Series Heat detectors are manufactured in accordance with CE/ISO 9001 standards, and can be calibrated to EN-54

The Range Includes :

NB-988 Rate of Rise heat detector

NB-989 Fixed Temperature Heat detector

Product Features:

- . Detection of intense fires with fast response under rapid temperature-rise situation
- . Mechanical moving parts provide stability, durability and reliability
- . Self-restoring bimetal elements allow continual use
- . Plastic: Shining PC, high temperature endurable and fireproof polymeric material
- . Alarm indicator: LED, continuously emitting red light
- . Easy installation and maintenance
- . Sleek low-profile housing design
- . Two-year limited warranty

Specification:

- . Operating Voltage: 10~30 VDC
- . Alarm Current: 100mA
- . Switching temperature: 70°C for HD-989 model
- . Standby Current: 0 Ah
- . Operating temperature range: -10°C to 50°C
- . Humidity: 0% to 95% RH, no condensation or icing

Sensitivity (NB-988 model):

- . Detector will be activated within 30 seconds when it is normal to airflow at temperature 30°C higher than room temperature with speed of 85cm/sec
- . Detector will be activated within 4.5 minutes when it faces a horizontal airflow heated with a rise rate of 15°C/min from room temperature