

Introducción a Haskell

Anabel Ovide
Ignacio Ballesteros
Luis Eduardo Bueso
Santiago Cervantes

https://github.com/edububa/haskell_course

17 de mayo de 2017



Índice

Introducción

Instalación

Introducción Histórica

¿Qué es Haskell?

Primeros Pasos

GHCi

Primeras funciones

Listas

Tuplas

Tipos y Typeclasses

Sintaxis en funciones

Pattern matching

Guards

where

let

Case Expressions

Recursión



Introducción

Instalación

- ▶ Con gestores de paquetes

- ▶ Debian/Ubuntu

```
sudo apt-get update  
sudo apt-get install ghc
```

- ▶ Arch

```
sudo pacman -S ghc
```

- ▶ macOS

```
brew install ghc
```

- ▶ Desde la web

<https://www.haskell.org/platform/mac.html>

<https://www.haskell.org/platform/windows.html>

<https://www.haskell.org/downloads/linux>

Introducción

Introducción Histórica



Introducción

¿Qué es Haskell?



Primeros pasos

GHCi

- Así abrimos el intérprete de Haskell

```
\$ ghci
GHCi, version 8.0.2: http://www.haskell.org/ghc/
:? for help
Prelude>
```

- Podemos escribir expresiones aritméticas y lógicas:

```
Prelude> 2 + 2
4
Prelude> True && False
False
```

Primeros pasos

GHCi

- Podemos llamar a funciones

```
Prelude> 2 + 2
4
Prelude> True && False
False
```

- Errores

```
Prelude> 2 + "hola"

<interactive>:6:1: error:
• No instance for (Num [Char]) arising from a use
  of '+'
• In the expression: 2 + "hola"
In an equation for 'it': it = 2 + "hola"
```

Primeros pasos

GHCi

► Expresiones útiles:

```
Prelude> :t 5
```

```
5 :: Num t => t
```

```
Prelude> :t 2
```

```
2 :: Num t => t
```

```
Prelude> :t "hola"
```

```
"hola" :: [Char]
```

```
Prelude> :l introduccion.hs
```

```
[1 of 1] Compiling Main
```

```
( introduccion.hs, interpreted )
```

```
Ok, modules loaded: Main.
```

```
*Main>
```


Primeros pasos

Primeras funciones

Ejemplos:

```
doubleMe x = x + x
```

```
doubleUs x y = doubleMe x + doubleMe y
```

```
doubleSmallNumber x = (if x > 100 then x else x*2) + 1
```

Primeros pasos

Listas

Creando listas en un fichero .hs:

```
list = [1,2,3,4,5]  
list' = [1..5]
```

Ejemplos de listas en el GHCi

```
Prelude> let list = [1,2,3,4,5]  
Prelude> let list1 = [1..5]  
Prelude> list == list1  
list == list1  
True  
Prelude>
```

Primeros pasos

Listas

Las listas pueden concatenarse con el operador ++ y construirse con el operador :

```
Prelude> [1..9] ++ [10..19]
[1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19]
Prelude> "hello " ++ "world!"
"hello world!"
Prelude> 1:[2..5]
1:[2..5]
[1,2,3,4,5]
Prelude> 'h':"ello"
"hello"
Prelude> 1:[]
[1]
```

Primeros pasos

Listas

Las operaciones básicas en las listas son:

► head:

```
Prelude> head [1..10]  
1
```

► tail:

```
Prelude> tail [1..10]  
[2,3,4,5,6,7,8,9,10]
```

► last:

```
Prelude> last [1..10]  
10
```

Primeros pasos

Listas

► init:

```
Prelude> init [1..10]  
[1,2,3,4,5,6,7,8,9]
```

► length:

```
Prelude> length [1..10]  
10
```

► reverse:

```
Prelude> reverse [1..10]  
[10,9,8,7,6,5,4,3,2,1]
```

► take:

```
Prelude> take 4 [1..10]  
[1,2,3,4]
```

Primeros pasos

Tuplas



Tipos y *Typeclasses*



Sintaxis en funciones

Pattern matching

```
sayMe :: (Integral a) => a -> String
sayMe 1 = "One!"
sayMe 2 = "Two!"
sayMe 3 = "Three!"
sayMe 4 = "Four!"
sayMe 5 = "Five!"
sayMe x = "Not between 1 and 5"
```

```
Prelude> :l introduccion.hs
[1 of 1] Compiling Main
( introduccion.hs, interpreted )
Ok, modules loaded: Main.
*Main> sayMe 5
"Five!"
```


Sintaxis en funciones

Guards

```
compare :: (Ord a) => a -> a -> Ordering
a `compare` b
  | a > b      = GT
  | a == b     = EQ
  | otherwise = LT
```

```
Prelude> :l introduccion.hs
[1 of 1] Compiling Main
( introduccion.hs, interpreted )
Ok, modules loaded: Main.
*Main> 1 `myCompare` 2
LT
*Main> 1 `myCompare` 0.5
GT
```

Sintaxis en funciones

where

```
initials :: String -> String -> String
initials firstname lastname = [f] ++ ". " ++ [l] ++ ". "
    where (f:_) = firstname
          (l:_) = lastname
```

Sintaxis en funciones

let

```
cylinder :: (RealFloat a) => a -> a -> a
cylinder r h =
    let sideArea = 2 * pi * r * h
        topArea = pi * r ^2
    in  sideArea + 2 * topArea
```

Sintaxis en funciones

Case Expressions

```
describeList :: [a] -> String
describeList xs = "The list is " ++
  case xs of [] -> "empty."
             [x] -> "a singleton list."
             xs -> "a longer list."
```

Recursión



Aclaraciones

Todo es mentira.

