COMPTIA SECURITY+ SY0-701 | DOMAIN 5 · SECURITY PROGRAM MANAGEMENT AND OVERSIGHT (20%)

Security+ 5.2 · Business Impact Analysis

Mestre CyberSec · **Lesson 5.2 — Business Impact Analysis** (2:55) · Assistir Vídeo no YouTube ↗ · Treino Interativo: edusouzamarques.github.io/cybersec

> **Executive Lesson Summary:** BIA: impacto de negócio se o processo crítico PARAR. MTR/MTTR (tempo de resposta); MTTU (mean time to use); MTBF (mean time between failure). Alimenta RTO/RPO.

💡 Key Exam Highlights & Critical Concepts

- BIA: quanto o negócio PERDE por hora/dia se processo critico para
- MTTR: tempo de resposta/reparo; MTBF: confiabilidade

🎯 Exam Tips & Typical CompTIA Scenarios

- 'evaluates impact of losing critical process'=BIA

🧯 Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 5.2 — Business Impact Analysis)

Why is this advanced coverage required for SY0-701?: Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Business Impact Analysis (BIA)

A formal process that evaluates the potential business impact of losing a critical process, system, or service, and determines requirements that feed RTO and RPO.

⚠ ***Exam Trap:*** *Gatilho: 'evaluates impact of losing critical process' = BIA. Não é o plano de recuperação; é a análise que define o que precisa ser recuperado e com que prioridade.*

• Recovery Time Objective (RTO)

The maximum acceptable time that a critical process can be unavailable before unacceptable business impact occurs; it is the target time to restore service.

⚠ ***Exam Trap:*** *Se a questão pergunta 'quanto tempo pode ficar parado?', é RTO. RTO é objetivo; MTTR é o tempo médio real de reparo.*

• Recovery Point Objective (RPO)

The maximum acceptable amount of data loss measured in time from the last valid backup or recovery point.

⚠ ***Exam Trap:*** *Se a questão fala 'quanto dado posso perder?' ou 'backup deve ser de quantas horas atrás?', é RPO.*

• Mean Time to Repair (MTTR)

The average time required to repair or restore a failed component or system after a failure occurs.

⚠ ***Exam Trap:*** *Confiabilidade operacional: tempo médio de resposta/reparo. Não confundir com RTO (objetivo de recuperação) nem com MTBF (tempo entre falhas).*

• Mean Time Between Failures (MTBF)

The average time between failures of a repairable system or component; a higher MTBF indicates greater reliability.

⚠ ***Exam Trap:*** *Gatilho: 'reliability' ou 'tempo entre falhas' = MTBF. Aplicável a itens reparáveis; não é o mesmo que MTTF.*

• Mean Time to Failure (MTTF)

The expected average time until a non-repairable component or system fails; used as a reliability metric for asset lifespan.

⚠ ***Exam Trap:*** *MTTF é para itens não reparáveis; MTBF é para itens reparáveis. Se a questão mencionar vida útil esperada de um disco/componente, pense MTTF.*

• **Maximum Tolerable Downtime (MTD)**
The maximum total time a business process can be unavailable before the organization suffers unacceptable or unrecoverable impact.

⚠️ ***Exam Trap:*** *RTO deve ser menor ou igual ao MTD. Se a questão descreve o limite absoluto antes de dano inaceitável, é MTD.*

• **Mean Time to Use (MTTU)**
A secondary BIA/BC metric for the average time required before a restored or recovered resource can actually be used productively by the business process.

⚠️ ***Exam Trap:*** *Não é o acrônimo mais cobrado; o foco CompTIA é BIA, RTO/RPO, MTTR/MTBF/MTTF. Se aparecer, diferencie 'restaurado' de 'utilizável pelo negócio'.*

✅ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A hospital's admissions team completes a BIA for its patient registration process. Executives state that registration can be unavailable for no more than four hours before patient safety and revenue are seriously affected. Which metric have the executives defined?

A) Recovery point objective (RPO)

B) Maximum tolerable downtime (MTD)

C) Mean time to repair (MTTR)

D) Mean time between failures (MTBF)

QUESTION 2 · EXAM SCENARIO

An online retailer's BIA states that the order-processing system must be back online within three hours after a disruption, and no more than ten minutes of transaction data can be lost. Which pair of metrics matches these requirements?

A) RPO of three hours and RTO of ten minutes

B) MTBF of three hours and MTTR of ten minutes

C) RTO of three hours and RPO of ten minutes

D) MTD of three hours and MTTF of ten minutes

QUESTION 3 · EXAM SCENARIO

A security analyst reviews six months of logs for a database server. The server failed four times, with an average of 45 days between failures, and each repair took about 3 hours. Which value should be reported as the average time between failures?

A) 3 hours

B) 45 days

C) 4 failures

D) 48 days

QUESTION 4 · EXAM SCENARIO

A company uses network switches that are replaced rather than repaired when they fail. Historical data show that a switch operates for about five years before failing. Which metric best describes this five-year average?

A) Mean time between failures (MTBF)

B) Mean time to repair (MTTR)

C) Mean time to failure (MTTF)

D) Recovery point objective (RPO)

QUESTION 5 · EXAM SCENARIO

During BIA for a payroll system, the team documents that payroll must be restored within 24 hours and that up to 4 hours of payroll data can be lost. Which metrics should be used to express these two requirements?

A) RTO of 24 hours and RPO of 4 hours

B) MTBF of 24 hours and MTTR of 4 hours

C) MTD of 24 hours and MTTF of 4 hours

D) RPO of 24 hours and RTO of 4 hours

QUESTION 6 · EXAM SCENARIO

After a ransomware incident, a file server is technically restored in two hours, but permissions and search indexes are rebuilt over the next 90 minutes before staff can use the shared drive. Which metric captures the additional time until the restored service is actually usable by the business?

A) Recovery point objective (RPO)

B) Mean time between failures (MTBF)

C) Mean time to failure (MTTF)

D) Mean time to use (MTTU)

QUESTION 7 · EXAM SCENARIO

A BIA shows that a payment processing application has a maximum tolerable downtime of eight hours. The disaster recovery plan states that the application will be restored within twelve hours. What is the most significant risk in this plan?

A) The data loss target is longer than the backup schedule.

B) The recovery target is later than the business can tolerate.

C) The hardware failure rate is higher than the repair time.

D) The restoration point is earlier than the recovery point.

QUESTION 8 · EXAM SCENARIO

A claims processing system has an RPO of 15 minutes, but its database is backed up only once each night. Which action best aligns the backup strategy with the BIA requirement?

A) Reduce the MTTR by adding spare servers.

B) Increase the MTBF by replacing older disks.

C) Increase backup frequency so no more than 15 minutes of data can be lost.

D) Lengthen the RTO to 24 hours to match the backup schedule.

QUESTION 9 · EXAM SCENARIO

A BIA for an e-commerce company finds that order fulfillment stops when the external payment gateway is unavailable, even though the company's own servers remain online. What should the BIA document about the payment gateway?

A) It is outside the scope of the BIA because it is managed by a third party.

B) It affects only the RPO and not the RTO.

C) It can be ignored because the internal servers have high MTBF.

D) It is a dependency of a critical business process, and its outage impact must be included in recovery planning.

QUESTION 10 · EXAM SCENARIO

A data center tracks power supplies that are swapped out when they fail. A supply typically operates for 18 months before failure, and replacement takes 30 minutes. Which mapping of metrics is correct?

A) MTBF is 30 minutes, and MTTF is 18 months.

B) MTTF is 18 months, and MTTR is 30 minutes.

C) MTTR is 18 months, and MTBF is 30 minutes.

D) RTO is 18 months, and RPO is 30 minutes.

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option B — Maximum tolerable downtime (MTD)

MTD is the maximum time a critical business process can be unavailable before unacceptable impact occurs. RTO is the target time to restore service and should be less than or equal to MTD; RPO defines tolerable data loss; MTBF measures reliability between failures.

Question 2: Option C — RTO of three hours and RPO of ten minutes

RTO is the maximum acceptable time to restore service after disruption, so three hours is the RTO. RPO is the maximum acceptable data loss, so ten minutes is the RPO. The other options invert the concepts or use reliability/repair metrics that do not express recovery requirements.

Question 3: Option B — 45 days

MTBF is the average time between failures of a repairable system, calculated from operating time divided by the number of failures. Here, 45 days is the MTBF. Three hours is MTTR; four is the failure count; 48 days incorrectly adds repair time to the interval.

Question 4: Option C — Mean time to failure (MTTF)

MTTF is used for non-repairable assets and represents the average time until failure. MTBF applies to repairable systems; MTTR is repair time; RPO is tolerable data loss, not equipment lifespan.

Question 5: Option A — RTO of 24 hours and RPO of 4 hours

RTO is the target time to restore service, so 24 hours is the RTO. RPO is the maximum tolerable data loss, so 4 hours is the RPO. MTBF, MTTR, and MTTF measure reliability and repair, not the recovery requirements defined by the BIA.

Question 6: Option D — Mean time to use (MTTU)

MTTU represents the average time until a recovered resource is actually usable by the business, beyond technical repair. MTBF measures reliability between failures; MTTF measures time until failure for a non-repairable asset; RPO concerns data loss.

Question 7: Option B — The recovery target is later than the business can tolerate.

The RTO of 12 hours exceeds the MTD of 8 hours, so planned recovery would occur after the business can tolerate the outage. The RTO should be less than or equal to the MTD. The other options confuse RPO, MTBF/MTTR, or invert recovery terms.

Question 8: Option C — Increase backup frequency so no more than 15 minutes of data can be lost.

RPO defines the maximum tolerable data loss. Nightly backups cannot meet a 15-minute RPO, so backup frequency must increase or replication must be used. MTTR and MTBF affect availability/reliability; changing the RTO does not correct data loss.

Question 9: Option D — It is a dependency of a critical business process, and its outage impact must be included in recovery planning.

The BIA must map dependencies of critical processes, including third-party services. If the payment gateway outage stops order fulfillment, its impact must be analyzed and included in recovery planning. It is not out of scope, does not affect only RPO, and cannot be ignored because of internal MTBF.

Question 10: Option B — MTTF is 18 months, and MTTR is 30 minutes.

Because the power supplies are not repaired but replaced, the average time until failure is MTTF: 18 months. The replacement time is MTTR: 30 minutes. MTBF applies to repairable systems; RTO/RPO are business recovery targets, not hardware reliability metrics.