COMPTIA SECURITY+ SY0-701 | DOMAIN 2 · THREATS, VULNERABILITIES, AND MITIGATIONS (22%)

Security+ 2.4 · Indicators of Compromise

Mestre CyberSec · **Lesson 2.4 — Indicators of Compromise** (10:59) · Assistir Vídeo no YouTube ↗ · Treino Interativo: edusouzamarques.github.io/cybersec

> **Executive Lesson Summary:** IOC: sinal de comprometimento — account lockout em série (spraying); impossible travel (login NY/Bangalore em 10 min); resource consumption anormal (CPU/exit de rede); hora atípica; baseline deviation. IOC = IP malicioso, hash, domínio. Defesa: EDR/SIEM correlacionando, threat fe

💡 Key Exam Highlights & Critical Concepts

- IOC = IP malicioso, hash de malware, domínio de C2 — pista técnica
- Impossible travel = login geograficamente impossível na JANELA de tempo
- Account lockout em série = brute force/spraying em curso

🎯 Exam Tips & Typical CompTIA Scenarios

- 'login from two distant locations within minutes' = impossible travel (IOC)
- 'IP address known to be malicious' = IOC

🚨 Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 2.4 — Indicators of Compromise)

Why is this advanced coverage required for SY0-701?: Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Indicator of Compromise (IOC)

A forensic artifact — such as a known-malicious IP address, malware file hash, or command-and-control domain — that signals a system or network has already been compromised. It is evidence of a realized breach.

⚠️ ***Exam Trap:*** *Se a questão apresenta evidência concreta ('known malicious IP', 'file hash of known malware', 'traffic to a C2 domain'), a resposta é IOC. Não confunda com IOA (sinal comportamental durante o ataque) nem com vulnerability (fraqueza ANTES do comprometimento).*

• Impossible Travel

An authentication anomaly where the same account successfully logs in from two geographically distant locations within a time window that makes physical travel impossible — typically indicating stolen credentials.

⚠️ ***Exam Trap:*** *Gatilho clássico: 'login from New York, then Bangalore 10 minutes later' = impossible travel (um IOC). Não escolha brute force (muitas senhas em UMA conta) nem password spraying (muitos lockouts em muitas contas).*

• Password Spraying

An attack that tries a small set of common passwords against many accounts, frequently producing a wave of simultaneous account lockouts — an observable IOC that the spraying is in progress.

⚠️ ***Exam Trap:*** *'Numerous account lockouts across many users in a short window' = password spraying (IOC). Distinção de prova: credential stuffing usa pares usuário/senha vazados; brute force foca em UMA conta com muitas senhas.*

• Command and Control (C2)

The attacker-controlled infrastructure (servers, domains, channels) used to send instructions to compromised systems and extract data from them.

⚠️ ***Exam Trap:*** *'Traffic to a known C2 domain' ou beaconing periódico nos logs = IOC de host comprometido. O domínio/IP de C2 é o indicador técnico; beaconing é o comportamento correlacionado por EDR/SIEM.*

• Baseline Deviation

A deviation from the documented normal operating behavior of a system or network — such as abnormal CPU consumption, unusual network egress, or authentications at atypical times — flagging a potential indicator of compromise.

⚠️ ***Exam Trap:*** *'Resource consumption abnormally high' ou 'logons at atypical hours' devem ser comparados à baseline estabelecida. Não confunda com SLA (desempenho contratual) nem MTBF/MTTR (confiabilidade e manutenção).*

• Endpoint Detection and Response (EDR)

A solution that continuously monitors endpoints to detect, investigate, and respond to threats by correlating behavioral indicators, IOCs, and host-level resource anomalies.

⚠️ ***Exam Trap:*** *'Detect, alert and respond on the endpoint (isolate host, kill process)' = EDR. Não confunda com XDR (agrega fontes múltiplas, não só endpoint) nem firewall/IPS (controle de rede, não análise comportamental do host).*

• Security Information and Event Management (SIEM)

A platform that aggregates and correlates logs and alerts from across the enterprise — authentication systems, firewalls, endpoints — to reveal patterns such as impossible travel or serial account lockouts.

⚠️ ***Exam Trap:*** *'Centralized log aggregation and correlation from many sources, triggering alerts' = SIEM. Distinções de prova: SIEM correlaciona e alerta; SOAR automatiza a resposta (playbooks); syslog apenas coleta/transporta logs.*

• Threat Feed

A continuously updated source of threat intelligence — known-bad IPs, domains, and file hashes — that security tools subscribe to so they can automatically flag matching indicators of compromise.

⚠️ ***Exam Trap:*** *'Automatically block/detect traffic to addresses from a dynamic list of known-bad IPs' = threat feed / threat intelligence. Distinção: o feed fornece IOCs 'known bad'; a sandbox analisa o comportamento de amostras em ambiente isolado; a CASB governa aplicações em nuvem.*

✅ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A security analyst at a logistics company reviews VPN authentication logs and finds that a regional sales director's account successfully authenticated from the New York headquarters at 09:00 local time, then opened a new valid session from Bangalore 12 minutes later. Both sessions used the correct password, and no MFA challenge was recorded for either login. What is the most likely conclusion?

A) A clock synchronization mismatch between the New York and Bangalore authentication servers is skewing the logged timestamps

B) The account's credentials have been compromised and are being used by an unauthorized party

C) A password spraying campaign is underway against the sales department's user accounts

D) The VPN concentrator is misrouting the director's session traffic through an Asian exit node

QUESTION 2 · EXAM SCENARIO

Overnight, the service desk receives dozens of tickets: hundreds of user accounts across finance, HR, and engineering are locked out. Domain controller logs show exactly one or two failed logon attempts per username, cycling through a very long list of usernames every 30 minutes. No single account accumulated repeated failures. Which attack does this pattern indicate?

A) A brute-force attack cycling through every possible password combination against a single privileged account

B) Credential stuffing replaying known username and password pairs from a public breach dump

C) Password spraying, testing a small set of common passwords across a large number of accounts

D) Pass-the-hash lateral movement replaying captured NTLM hashes of domain administrators

QUESTION 3 · EXAM SCENARIO

After containing a ransomware outbreak, the incident response lead must document indicators of compromise to share with partner organizations through the industry ISAC. Which set of items qualifies as IOCs that other defenders can search for in their own environments?

A) The CVE identifier, CVSS base score, and vector string of the vulnerability that was exploited

B) The total downtime hours, asset replacement costs, and incident response labor billed

C) The MITRE ATT&CK tactic names the adversary used and the threat actor's inferred motivation

D) The ransomware dropper's SHA-256 file hash, the command-and-control domain it contacted, and the source IP address of the initial access host

QUESTION 4 · EXAM SCENARIO

A security team subscribes to a commercial threat intelligence feed. The feed publishes an IOC package containing 40 file hashes, 12 domains, and 30 IP addresses tied to an active malware campaign targeting their sector. What is the best next step to determine whether the organization has been affected?

A) Ingest the indicators into the SIEM and EDR and search current and historical telemetry for matches

B) Reimage every endpoint that has ever communicated with any external IP address

C) Block the entire autonomous systems that contain the listed IP addresses

D) Wait for the vendor's next quarterly report, which lists the affected industries, before taking action

QUESTION 5 · EXAM SCENARIO

A database server's documented baseline is roughly 20% CPU and 2 GB of network egress per day. For the past 72 hours the server has held at 95% CPU, an unfamiliar process runs late each night, and 40 GB per day now flows to a single external IP address that has never appeared in the NetFlow records. What should the analyst do first?

A) Restart the database service and file a change request for additional CPU capacity on the host

B) Raise the performance alerting thresholds for that host so the repeated alerts stop

C) Treat the server as a suspected compromise and investigate the unknown process and external connection using EDR telemetry before the activity spreads

D) Assume a legitimate backup job rescheduled itself and ask the DBA team to confirm by email

QUESTION 6 · EXAM SCENARIO

The EDR agent on a finance department workstation raises a high-severity alert: WINWORD.EXE spawned powershell.exe carrying a base64-encoded command, which then attempted to write a registry Run key for persistence and to connect to an external host. What is the most appropriate immediate response?

A) Mark the alert as a false positive because macros from the finance workflow routinely launch PowerShell

B) Use the EDR's network containment feature to isolate the workstation and begin triage using the alert telemetry

C) Email all company staff instructing them to run a full antivirus scan on their own machines

D) Delete the alert and lower the EDR's sensitivity so that routine documents stop generating tickets

QUESTION 7 · EXAM SCENARIO

Within a single hour, a contractor's account generates four events: one failed VPN logon, one antivirus detection that was automatically quarantined, one USB mass-storage device connection, and one outbound connection to a third-party file-sharing site. Each event alone fell below every individual alerting threshold, and nothing was noticed until the SIEM correlated all four against the user's behavioral baseline. What capability does this demonstrate?

A) Correlating individually low-severity events from multiple data sources to reveal a compromise pattern no single tool would have flagged

B) Automatically patching the vulnerability the attacker exploited to gain entry

C) Encrypting the logs at rest so that the attacker cannot erase their tracks

D) Deduplicating repetitive log entries to reduce the overall log storage volume

QUESTION 8 · EXAM SCENARIO

Firewall logs show that an accounting department workstation makes an outbound HTTPS request every 45 seconds, around the clock and through weekends, to a domain that was registered nine days ago. The workstation's established baseline shows bursty web browsing only during business hours. What does this consistent, periodic egress most likely indicate?

A) A scheduled Microsoft Defender signature download that an administrator configured at that cadence

B) An employee replaying a long series of recorded training webinars on loop

C) The workstation's NTP client synchronizing with an external time source

D) Command-and-control beaconing from a compromised host to attacker infrastructure

QUESTION 9 · EXAM SCENARIO

At 03:14 on a Sunday, the SIEM flags that a human resources user account authenticated to the payroll server and exported a large file. The account owner normally works Monday through Friday from 08:00 to 17:00, and the HR team never accesses payroll outside business hours. What should the analyst conclude about this event?

A) A time-zone normalization artifact caused by the SIEM incorrectly converting UTC timestamps

B) A denial-of-service attack against the payroll application's database

C) An atypical-hours behavioral deviation indicating the account may be compromised, warranting urgent investigation

D) A false positive triggered by a scheduled maintenance window that can be dismissed without review

QUESTION 10 · EXAM SCENARIO

NetFlow analysis reveals that a shipping-department workstation uploaded 40 GB of data over the weekend to a consumer cloud storage service the organization has never used. The same host averages under 1 GB per week and normally communicates only with the internal print backend, and the egress occurred at a steady rate from 01:00 to 05:00 both nights. How should the analyst interpret this?

A) The vendor's patch management agent is uploading diagnostic bundles to its support cloud

B) Probable data exfiltration; the host is likely compromised and staging data out, so it should be investigated and contained

C) A misconfigured print spooler is flushing its rendering cache to an external endpoint

D) A failed operating system feature update is retrying uploads to Microsoft's delivery optimization servers

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option B — The account's credentials have been compromised and are being used by an unauthorized party

Twelve minutes is nowhere near enough time to travel from New York to Bangalore; successful authentications from geographically distant locations within a short window is the classic impossible travel indicator and a strong signal that the credentials were stolen and are actively in use. A clock skew would not change the source geography of the sessions, password spraying produces mass failed logons and account lockouts rather than valid logins on one person's account, and VPN misrouting affects where traffic egresses, not where a correct password was entered.

Question 2: Option C — Password spraying, testing a small set of common passwords across a large number of accounts

In password spraying, the attacker tries a handful of likely passwords against thousands of accounts while limiting failed attempts on each account to avoid triggering lockouts; one or two failures per account, many accounts affected in sequence, and periodic repetition match that behavior exactly. Brute force would concentrate thousands of failures on a single account, credential stuffing uses real leaked password pairs and typically produces successful logons, and pass-the-hash authenticates directly with captured hashes without generating failed-password lockouts.

Question 3: Option D — The ransomware dropper's SHA-256 file hash, the command-and-control domain it contacted, and the source IP address of the initial access host

IOCs are concrete, machine-matchable technical artifacts such as file hashes, malicious domains and URLs, IP addresses, file names, and registry keys that other organizations can match against their own logs and endpoints to detect the same campaign. CVE and CVSS details describe the vulnerability, cost figures describe business impact, and ATT&CK tactics describe adversary behavior, but none of those can be directly searched for or blocked in operational telemetry.

Question 4: Option A — Ingest the indicators into the SIEM and EDR and search current and historical telemetry for matches

Threat feeds deliver value only when operationalized: load the IOCs into the SIEM and EDR, run retrospective and ongoing searches for hash, domain, and IP matches, and create targeted detection rules or blocks with human review to limit false positives. Blocking whole autonomous systems would cut off large amounts of legitimate traffic and services, wholesale reimaging is impractical and destroys forensic evidence, and waiting for a quarterly report defeats the purpose of a near-real-time feed.

Question 5: Option C — Treat the server as a suspected compromise and investigate the unknown process and external connection using EDR telemetry before the activity spreads

A sharp baseline deviation combined with abnormal resource consumption (sustained 95% CPU) and unexpected egress to a never-before-seen external IP is a strong combination of indicators of compromise, so the first action is to investigate with EDR telemetry and isolate the host if confirmation is found, preventing exfiltration or lateral movement. Capacity tuning cannot explain a new nightly process and an unknown external peer, silencing thresholds hides genuine incidents, and assuming benign backup drift without verification is unsafe.

Question 6: Option B — Use the EDR's network containment feature to isolate the workstation and begin triage using the alert telemetry

The parent-child chain of an Office application spawning obfuscated PowerShell, followed by registry persistence attempts and an outbound connection, is a hallmark of malicious document delivery and justifies immediate network isolation through the EDR, which interrupts command-and-control and lateral movement while preserving evidence for triage. Dismissing a high-severity behavioral chain as routine, blast-emailing all users, or suppressing alerts all leave a potentially compromised host online and uncontained.

Question 7: Option A — Correlating individually low-severity events from multiple data sources to reveal a compromise pattern no single tool would have flagged

The core detection value of a SIEM is aggregation and correlation of events from many sources, such as VPN, antivirus, endpoint, and firewall, compared against behavioral baselines; low-and-slow attacks are invisible event by event but become evident when the events are stitched together into a single timeline. A SIEM does not patch systems, its primary function is not at-rest encryption of logs, and deduplication is a storage optimization rather than a detection capability.

Question 8: Option D — Command-and-control beaconing from a compromised host to attacker infrastructure

Fixed-interval callbacks, in this case every 45 seconds, running 24/7 to a recently registered domain is the textbook pattern of C2 beaconing and one of the most reliable network indicators of an implant awaiting instructions on a

compromised host. Defender updates originate from known Microsoft infrastructure rather than a nine-day-old domain, video streaming produces variable traffic patterns instead of exact periodicity, and NTP uses UDP/123 rather than HTTPS and does not loop continuously at short fixed intervals.

Question 9: Option C — An atypical-hours behavioral deviation indicating the account may be compromised, warranting urgent investigation

Activity inconsistent with the documented work schedule is the off-hours / atypical-hours indicator of compromise, and when paired with an export of sensitive payroll data it strongly suggests a stolen or misused account, so the analyst should urgently investigate, for example by disabling the account and reviewing the session's source IP. Dismissing the event without review risks missing a real breach, a denial-of-service attack does not involve successful authentication and file export, and a timestamp conversion issue would alter the recorded hour, not create the login session itself.

Question 10: Option B — Probable data exfiltration; the host is likely compromised and staging data out, so it should be investigated and contained

Sustained, large egress, 40 GB to an unsanctioned external service, at 40 times the host's normal weekly volume and occurring off-hours, is a classic data exfiltration indicator of compromise; the correct response is to treat the host as compromised, investigate with EDR telemetry, isolate it, and review what data was sent. Updates and diagnostics target known vendor endpoints and are overwhelmingly inbound for a client workstation, print spoolers do not upload rendering caches to external services, and assuming vendor misconfiguration without validating the destination domain and IP would dangerously delay containment.