COMPTIA SECURITY+ SY0-701 | DOMAIN 2 · THREATS, VULNERABILITIES, AND MITIGATIONS (22%)

Security+ 2.5 · Mitigation Techniques

Mestre CyberSec · **Lesson 2.5 — Mitigation Techniques** (6:51) · Assistir Vídeo no YouTube ↗ · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Técnicas de mitigação em CAMADAS: patching (a base mais esquecida); encryption (proteção do dado); monitoring/EDR (observar + responder); least privilege (menor acesso); backup (recovery); training (treinar o humano); compensating control (quando o ideal não dá).

💡 Key Exam Highlights & Critical Concepts

- Patching: a defesa básica mais esquecida (a maioria dos breach era patch conhecida)
- Least privilege: cada pessoa só o mínimo
- Defesa em camadas: nunca 1 solução — empilha

🎯 Exam Tips & Typical CompTIA Scenarios

- 'reduces impact but doesn't eliminate vulnerability' = compensating control

🚨 Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 2.5 — Mitigation Techniques)

Why is this advanced coverage required for SY0-701?: Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Patching (N/A)

The process of updating software, firmware, and OSes to fix known vulnerabilities; it is a foundational vulnerability mitigation and should be prioritized by risk and exposure.

⚠️ ***Exam Trap:*** *Se a questão mencionar 'known vulnerability explorada' ou 'breach por falta de atualização', a resposta provável é patching/patch management. Lembre: patch corrige a vulnerabilidade; compensating control apenas reduz o risco.*

• Encryption (N/A)

The conversion of data into unreadable ciphertext to protect confidentiality at rest and in transit; it reduces impact if data is intercepted or stolen.

⚠️ ***Exam Trap:*** *Criptografia protege confidencialidade/integridade, não disponibilidade nem impede malware. Se a questão fala de 'dados roubados mas inúteis', escolha encryption. Key management é o ponto crítico.*

• Endpoint Detection and Response (EDR)

A security solution that continuously monitors endpoint activity, detects suspicious behavior, and enables response actions such as isolation or remediation.

⚠️ ***Exam Trap:*** *EDR = monitorar + detectar + responder no endpoint; não é só antivírus. Se a questão pedir 'correlacionar logs de várias fontes', pense SIEM; se for 'isolar host infectado', pense EDR.*

• Least Privilege (PoLP)

The principle that users, applications, and systems receive only the minimum access rights necessary to perform their legitimate tasks.

⚠️ ***Exam Trap:*** *Least privilege reduz superfície de ataque e blast radius. Distinga de 'need to know' (acesso à informação) e de 'separation of duties' (dividir funções críticas).*

• Backup (N/A)

A copy of data and configurations used to restore availability and integrity after loss, corruption, or ransomware; backups must be tested and protected.

⚠️ ***Exam Trap:*** *Se a questão pedir 'recuperar após ransomware' ou 'restaurar dados', escolha backup. Lembre da regra 3-2-1 e de backups offline/imutáveis para não serem criptografados.*

• Security Awareness Training (SAT)

An administrative control that educates users to recognize and avoid threats such as phishing, social engineering, and unsafe data handling.

⚠️ ***Exam Trap:*** *Humanos são o elo mais fraco; se a questão mencionar phishing, engenharia social ou erro do usuário, treinamento/conscientização é a mitigação. Não é controle técnico.*

• Compensating Control (N/A)

An alternative safeguard used when the primary or ideal control cannot be implemented; it reduces risk/impact but does not eliminate the underlying vulnerability.

⚠️ ***Exam Trap:*** *Gatilho clássico: 'reduces impact but doesn't eliminate the vulnerability' = compensating control. Não confunda com controle corretivo (corrige o problema) nem preventivo (impede).*

• Defense in Depth (DiD)

A layered security strategy that combines multiple controls so that if one fails, others still protect the asset; no single mitigation is sufficient.

⚠️ ***Exam Trap:*** *Se a questão sugerir 'layered mitigation', 'multiple controls' ou 'never rely on one solution', escolha defense in depth. É o conceito guarda-chuva da lição.*

✅ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A mid-sized accounting firm experienced a ransomware outbreak that encrypted files on every workstation and two file servers. Forensic analysis revealed the attackers exploited a critical vulnerability in the firm's internet-facing VPN concentrator that had a patch released by the vendor four months earlier. Which mitigation technique, if performed consistently, would most likely have prevented the initial intrusion?

A) Implementing a disciplined vulnerability management and patch management program with monthly review cycles

B) Deploying network-based intrusion prevention system signatures for all known malware

C) Mandating security awareness training focused on recognizing phishing emails

D) Enforcing least privilege access controls on all domain user accounts

QUESTION 2 · EXAM SCENARIO

A regional hospital stores protected health information (PHI) on laptops used by traveling physicians. After a laptop is stolen from a physician's car, the security team must ensure that the PHI on the device cannot be read by the thief even if the disk is extracted and mounted on another computer. Which mitigation technique directly addresses this confidentiality requirement?

A) Implementing full-disk encryption (FDE) using AES-256 on all endpoint devices

B) Enforcing least privilege access through role-based access control on the laptop

C) Configuring endpoint detection and response agents to quarantine unknown processes

D) Deploying mobile device management to remotely wipe the stolen laptop

QUESTION 3 · EXAM SCENARIO

A manufacturing company's legacy Windows 7 controllers on the production floor cannot be replaced for at least 18 months due to operational constraints. The security team must protect these systems even though they no longer receive vendor security updates. Which mitigation technique is most appropriate in this situation?

A) Implementing a compensating control such as network segmentation and an IPS in front of the legacy systems

B) Disabling all user accounts on the legacy controllers until replacement occurs

C) Installing the latest endpoint protection agent even though it is unsupported on Windows 7

D) Migrating all data from the legacy controllers to a cloud-based SaaS platform immediately

QUESTION 4 · EXAM SCENARIO

An attacker compromised a domain administrator account through a credential-stuffing attack and was then able to access every system and database in the organization, including systems unrelated to the administrator's job function. Which mitigation principle, if properly implemented, would have limited the scope of access the compromised account could reach?

A) Enforcing the Principle of Least Privilege with role-based access and just-in-time administrative elevation

B) Deploying full-disk encryption on all file servers housing sensitive data

C) Implementing an automatic enterprise-wide patch deployment system

D) Configuring geofencing rules on the administrator's account to restrict logins

QUESTION 5 · EXAM SCENARIO

A ransomware attack encrypted a company's primary file shares and, critically, also encrypted the connected backup mount because the backup volume was mapped as a network drive and visible to the compromised hosts. The company lost access to 30 days of operational data. Which mitigation technique must be redesigned to prevent recurrence of this specific failure?

A) Implementing the 3-2-1 backup rule with immutable, air-gapped or offline copies that are not continuously mounted

B) Deploying additional endpoint antivirus signatures specific to ransomware families

C) Migrating all file shares to a cloud-based SaaS document management system

D) Training end users to identify phishing emails that deliver the ransomware payload

QUESTION 6 · EXAM SCENARIO

A retail company's phishing simulation results show that 28% of employees still click on embedded links in simulated phishing emails, even after the company deployed advanced email gateway filtering that catches 99.5% of malicious messages. The CISO wants a mitigation that addresses the residual human risk. Which technique most directly addresses this risk?

A) Implementing a continuous security awareness training program with simulated phishing campaigns and just-in-time coaching

B) Blocking all external email at the mail gateway to eliminate phishing vectors

C) Purchasing an extended detection and response (XDR) platform for endpoint telemetry

D) Requiring all employees to use hardware security keys for multi-factor authentication

QUESTION 7 · EXAM SCENARIO

The security operations center (SOC) of a software company detects a suspicious process on a developer workstation that is loading unsigned PowerShell scripts from memory, evading the legacy antivirus. The malware communicates with an external C2 server. Which mitigation technology is specifically designed to detect and respond to this kind of fileless, behavior-based attack?

A) Endpoint Detection and Response (EDR) with behavioral analytics and process telemetry

B) Full-disk encryption enforced via BitLocker with TPM binding

C) A vulnerability scanner running weekly authenticated scans against workstations

D) A network firewall with stateful packet inspection rules

QUESTION 8 · EXAM SCENARIO

An organization wants to apply multiple layers of mitigation so that if one control fails, additional controls continue to protect the asset. The architect designs overlapping controls: network firewalls, EDR on endpoints, application allowlisting, encrypted backups, least-privilege access, and security training. Which security principle is being applied?

A) Defense in Depth (DiD) with layered, overlapping controls

B) Single point of failure elimination through redundancy

C) Zero Trust with continuous verification

D) Principle of least functionality applied to systems

QUESTION 9 · EXAM SCENARIO

A new SaaS application used by the marketing department stores customer credit card data in its database. The vendor does not yet offer field-level encryption for that data column. The security team must choose a mitigation to reduce the risk of exposure if the SaaS database is breached. Which technique directly addresses the confidentiality of the data itself, independent of the vendor's controls?

A) Implementing application-layer encryption of the card data before it is transmitted and stored, using keys the organization controls

B) Increasing the frequency of vendor security assessment questionnaires

C) Mandating that the vendor rotate database passwords every 30 days

D) Requiring the marketing staff to use a VPN when accessing the SaaS application

QUESTION 10 · EXAM SCENARIO

Following a Business Email Compromise (BEC) incident, an audit reveals that the organization's only protective controls were a basic spam filter and a firewall. There was no EDR, no MFA, no backup verification, no formal patch cadence, and no awareness training. The CISO wants to implement a comprehensive mitigation strategy that addresses people, process, and technology layers. Which combination best represents a layered mitigation roadmap aligned to defense in depth?

A) Deploy MFA on all email accounts, enforce least privilege with role-based mailboxes, enable EDR on endpoints, implement immutable offline backups, run a continuous security awareness program, and establish a monthly patch management cycle

B) Purchase a next-generation firewall, switch to a different spam filter vendor, and increase password complexity requirements

C) Hire a managed security service provider to monitor logs, replace the firewall, and require annual security training

D) Disable external email forwarding, mandate 16-character passwords, and replace antivirus with a free alternative

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option A — Implementing a disciplined vulnerability management and patch management program with monthly review cycles

Correct: Patching is the foundational mitigation technique. The attack exploited a known, four-month-old flaw for which a vendor patch already existed. A consistent patch management program ensures vulnerabilities are remediated promptly before attackers exploit them. Option B addresses exploitation but is reactive to known signatures, not the vulnerability itself. Option C addresses phishing, not VPN exploitation. Option D limits damage but does not prevent the initial compromise. Patching remains the most cost-effective, highest-ROI mitigation in defense-in-depth strategy.

Question 2: Option A — Implementing full-disk encryption (FDE) using AES-256 on all endpoint devices

Correct: Full-disk encryption (FDE) protects data at rest. Even if the physical disk is removed and mounted elsewhere, the data remains unreadable without the encryption key. This is the only option that protects the actual data from physical theft or disk extraction. Option B limits what users can access but does not protect the disk contents. Option C addresses malware behavior, not physical theft. Option D requires network connectivity to execute and assumes the laptop is online; it does not protect data already exfiltrated or the disk if the wipe fails or never occurs.

Question 3: Option A — Implementing a compensating control such as network segmentation and an IPS in front of the legacy systems

Correct: When the ideal mitigation (replacement/patching) is not feasible due to business or technical constraints, a compensating control is the proper approach. Network segmentation isolates the legacy systems, and an IPS provides additional detection/prevention for exploits targeting them. This is the textbook definition of a compensating control per CompTIA Security+. Option B would halt production. Option C may cause instability on unsupported systems and is not a true control. Option D is unrealistic given the 18-month operational constraint and is not a security control but a business decision.

Question 4: Option A — Enforcing the Principle of Least Privilege with role-based access and just-in-time administrative elevation

Correct: Least privilege (PoLP) ensures each account only has the permissions necessary to perform its job. A domain admin should not have unfettered access to every database; instead, tiered administration and JIT elevation scope privileges tightly. This is a foundational mitigation per CompTIA Security+. Option B protects data at rest but does not control access scope. Option C addresses vulnerabilities, not authorization. Option D reduces risk but does not address the core issue of excessive permissions.

Question 5: Option A — Implementing the 3-2-1 backup rule with immutable, air-gapped or offline copies that are not continuously mounted

Correct: The backup strategy failed because backups were online and accessible to ransomware. The 3-2-1 rule (3 copies, 2 media types, 1 offsite/offline) combined with immutable or air-gapped backups ensures recovery is possible even when primary systems and online backups are destroyed. Option B addresses detection, not recovery. Option C may help but is not a backup mitigation and ignores the architectural flaw. Option D is important but does not address the failure of the backup design itself.

Question 6: Option A — Implementing a continuous security awareness training program with simulated phishing campaigns and just-in-time coaching

Correct: Security awareness training with simulated phishing and just-in-time coaching targets the human factor directly. When technical controls miss 0.5% of malicious emails, the user becomes the last line of defense. Training reduces click-through rates over time. Option B would cripple business operations. Option C addresses endpoint detection, not the human decision to click. Option D protects authentication but does not stop a user from clicking a malicious link that leads to credential harvesting on a fake portal.

Question 7: Option A — Endpoint Detection and Response (EDR) with behavioral analytics and process telemetry

Correct: EDR solutions monitor endpoint process behavior, script execution (PowerShell, WMI, etc.), network connections, and memory activity, using behavioral analytics and threat intelligence to detect fileless attacks that signature-based AV misses. They also enable rapid response (isolate host, kill process). Option B protects data at rest but does not detect attacks. Option C finds vulnerabilities, not active intrusions. Option D filters traffic but cannot detect in-memory attacks using allowed protocols/ports.

Question 8: Option A — Defense in Depth (DiD) with layered, overlapping controls

Correct: Defense in Depth is the principle of layering multiple, overlapping controls so that the failure of any single control does not result in compromise. The described scenario lists firewalls, EDR, allowlisting, encrypted backups, least

privilege, and training — clearly a layered approach. Option B is an availability concept (HA). Option C is a specific architectural model that assumes no implicit trust and requires continuous verification — distinct from DiD. Option D is a related but narrower principle about disabling unnecessary services/functions.

Question 9: Option A — Implementing application-layer encryption of the card data before it is transmitted and stored, using keys the organization controls

Correct: Application-layer encryption (sometimes called client-side or envelope encryption) ensures data is encrypted before it ever reaches the vendor's database, using keys the organization retains. Even if the vendor is breached, the ciphertext is meaningless without the organization's keys. This is a classic encryption mitigation. Option B is governance, not data protection. Option C addresses credential management, not data confidentiality. Option D protects the network session but not the stored data.

Question 10: Option A — Deploy MFA on all email accounts, enforce least privilege with role-based mailboxes, enable EDR on endpoints, implement immutable offline backups, run a continuous security awareness program, and establish a monthly patch management cycle

Correct: This answer covers all mitigation layers: MFA + least privilege (access controls), immutable backups (recovery), EDR (detection/response), awareness training (people), and patch management (vulnerability). This is true defense in depth. Option B addresses only network and authentication layers superficially. Option C improves monitoring but lacks prevention and recovery depth. Option D is a narrow set of weak controls that does not address detection, response, recovery, or training.