

Security+ 1.4 · Certificates

Mestre CyberSec · Lesson 1.4 — Certificates (14:38) · [Assistir Vídeo no YouTube](#) ↗ · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Certificado digital: arquivo assinado pela CA (Certificate Authority) que liga domínio a chave pública. Self-signed = tu mesmo assina (confiança própria, não deve ir pro público). CSR = Certificate Signing Request (tu manda a chave pública + identidade pra CA assinar). CRL (lista

💡 Key Exam Highlights & Critical Concepts

- CA assina o certificado — cadeia de confiança root CA → intermediária → leaf
- CSR = requisição de assinatura: contém a chave pública + identidade
- CRL/OCSP/stapling = como o browser checa se certificado foi revogado

🎯 Exam Tips & Typical CompTIA Scenarios

- 'contains public key and identity, signed by CA' = certificate
- 'revocation checking method with online query' = OCSP

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Digital Certificate (N/A)

A digital file signed by a Certificate Authority (CA) that binds a public key to an identity (domain, organization, or user), enabling trusted encryption and authentication.

⚠ **Exam Trap:** Gatilho de prova: 'signed by a CA and contains a public key + identity' = certificate. Não confunda com CRL ou CSR.

• Certificate Authority (CA)

A trusted third-party entity that issues, signs, and manages digital certificates, forming the root of the chain of trust used in PKI.

⚠ **Exam Trap:** Gatilho de prova: 'trusted third party that signs certificates' = CA. Lembre da hierarquia: Root CA → Intermediate CA → Leaf certificate.

• Certificate Signing Request (CSR)

A message sent to a CA containing the applicant's public key and identity information (e.g., domain name, organization), which the CA uses to generate a signed certificate.

⚠ **Exam Trap:** Gatilho de prova: 'contains public key and identity, sent to CA for signing' = CSR. Não confundir com o certificado final em si.

• Self-Signed Certificate (N/A)

A certificate where the same entity signs its own public key, providing no third-party trust. Used internally or for testing but should not be exposed publicly.

⚠ **Exam Trap:** Gatilho de prova: 'signed by itself / no chain of trust' = self-signed. Examinadores adoram perguntar por que NÃO deve ser usado em produção pública.

• Certificate Revocation List (CRL)

A published list of certificates that have been revoked by the issuing CA before their expiration date, used to check certificate validity.

⚠ **Exam Trap:** Gatilho de prova: 'list of revoked certificates published by CA' = CRL. Diferencia do OCSP: CRL é download estático; OCSP faz query em tempo real.

• Online Certificate Status Protocol (OCSP)

An online query protocol that allows clients to check in real-time whether a digital certificate has been revoked, providing immediate validation.

⚠ **Exam Trap:** Gatilho de prova: 'revocation checking method with online query' = OCSP. Examinadores costumam comparar com CRL e OCSP stapling.

• OCSP Stapling

A performance optimization where the web server periodically retrieves and 'staples' a time-stamped OCSP response to its TLS handshake, eliminating the need for clients to query the CA directly.

⚠ **Exam Trap:** Gatilho de prova: 'server provides OCSP response to client during handshake' = OCSP stapling. Melhora privacidade e desempenho — saiba diferenciá-lo do OCSP tradicional.

• Chain of Trust (N/A)

The hierarchical trust model in PKI where a Root CA trusts Intermediate CAs, which in turn trust end-entity (leaf) certificates through digital signatures.

⚠ **Exam Trap:** Gatilho de prova: 'Root → Intermediate → Leaf hierarchy' = chain of trust. Conheça a ordem: validação sempre começa no certificado folha e sobe até a Root confiável.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A hospital runs an internal patient portal at `https://portal.hospital.local`. The security team wants to encrypt traffic and avoid browser warnings for employees, but the domain is not resolvable from the Internet. Which certificate deployment approach best fits this requirement?

- A) Install a self-signed server certificate and distribute its trust to managed employee workstations.
- B) Purchase a public CA-issued certificate for a public domain and use it for the `.local` host.
- C) Use an OCSP stapling response as the server certificate to establish trust.
- D) Submit a CRL to the internal DNS server and enable HTTPS.

QUESTION 2 · EXAM SCENARIO

A web administrator has generated a key pair on a public e-commerce server. To obtain a publicly trusted TLS certificate, the administrator must send the server's public key and identity details to a certificate authority. Which artifact should be generated and submitted?

- A) A Certificate Revocation List (CRL)
- B) A Certificate Signing Request (CSR)
- C) An Online Certificate Status Protocol (OCSP) response
- D) A root certificate from the server's trust store

QUESTION 3 · EXAM SCENARIO

A security analyst learns that a stolen laptop contained a private key for an internal web service. The analyst asks the PKI team to publish the certificate serial number so clients can reject it before its expiration date. Which PKI component is designed to provide this list of revoked certificates?

- A) Certificate Signing Request (CSR)
- B) OCSP Stapling
- C) Certificate Revocation List (CRL)
- D) Subject Alternative Name (SAN)

QUESTION 4 · EXAM SCENARIO

To reduce the latency and privacy impact of clients contacting the CA directly for revocation checks, a load balancer administrator configures the TLS server to include a recent, signed revocation status response with the certificate during the handshake. Which mechanism is being used?

- A) OCSP Stapling
- B) CRL distribution point
- C) Self-signed certificate chaining
- D) Certificate Signing Request (CSR)

QUESTION 5 · EXAM SCENARIO

Users report a browser error when connecting to a company web application: the server certificate is valid, but the browser cannot build a path to a trusted root. The server is configured to send only its leaf certificate. Which additional certificate should the administrator install on the server to correct this issue?

- A) The root CA certificate
- B) An intermediate CA certificate
- C) A CRL from the issuing CA
- D) A new CSR signed by the leaf certificate

QUESTION 6 · EXAM SCENARIO

A network team needs to check whether a remote VPN gateway's certificate has been revoked in near real time, without downloading a large, periodically updated list. Which protocol should the team use?

- A) Certificate Signing Request (CSR)
- B) Online Certificate Status Protocol (OCSP)
- C) Certificate Revocation List (CRL)
- D) Root certificate repository of the CA

QUESTION 7 · EXAM SCENARIO

A developer generates a certificate for a temporary lab API. The certificate's issuer and subject fields are identical, and it is trusted only on the developer's machine after manual import. Which type of certificate was created?

- A) Domain Validation (DV) certificate
- B) Extended Validation (EV) certificate
- C) Self-signed certificate
- D) Wildcard certificate

QUESTION 8 · EXAM SCENARIO

During a TLS inspection review, an auditor asks why the browser trusts a website's certificate. The certificate contains the website's public key and identity information, and it is digitally signed by a trusted third party. What is the primary security purpose of this digital certificate?

- A) To bind a public key to an identity and enable trust through a certificate authority's signature
- B) To encrypt the server's private key before storage
- C) To list all certificates that have been revoked by the organization
- D) To request a new key pair from the client's browser

QUESTION 9 · EXAM SCENARIO

An administrator needs to replace an expiring web server certificate. After creating a new private key on the server, the administrator prepares a file containing the public key, common name, and organizational details. What should be sent to the certificate authority to request the replacement certificate?

- A) A Certificate Revocation List (CRL)
- B) An OCSP Stapling response
- C) A Certificate Signing Request (CSR)
- D) A self-signed root certificate

QUESTION 10 · EXAM SCENARIO

A company deploys an internal PKI for device certificates. Employees' laptops currently do not trust certificates issued by the internal issuing CA, so TLS connections to internal services fail. What should be added to the laptops' trusted root certificate store?

- A)** The internal root CA certificate
- B)** A CRL from the internal root CA
- C)** The leaf certificate of each internal server
- D)** An OCSP responder URL

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option A — Install a self-signed server certificate and distribute its trust to managed employee workstations.

A self-signed certificate is appropriate for internal services that are not publicly accessible, as long as its trust is distributed to managed clients through group policy or a trusted store. Public CAs normally cannot validate internal domains such as .local. OCSP and CRLs are revocation-checking mechanisms, not server certificates.

Question 2: Option B — A Certificate Signing Request (CSR)

A CSR contains the public key and identity information of the requester and is sent to the CA for signing. The CA uses the CSR to issue the certificate. CRL and OCSP deal with revocation status, and a root certificate does not request issuance.

Question 3: Option C — Certificate Revocation List (CRL)

The CRL is a signed list published by the CA that contains serial numbers of revoked certificates. Clients can download it to check whether a certificate has been revoked. CSR is an issuance request, OCSP Stapling provides on-demand revocation status, and SAN specifies additional names in a certificate.

Question 4: Option A — OCSP Stapling

In OCSP Stapling, the server obtains a signed OCSP response from the CA and staples it to the certificate presentation during the TLS handshake. This avoids direct client-to-CA queries and improves performance and privacy. A CRL distribution point indicates where to download a CRL; a CSR is an issuance request.

Question 5: Option B — An intermediate CA certificate

The chain of trust normally requires the server to send the leaf certificate and the necessary intermediate certificates. The root certificate should already be in the client's trusted store; sending it from the server does not resolve the missing intermediate. CRLs and CSRs do not complete the chain.

Question 6: Option B — Online Certificate Status Protocol (OCSP)

OCSP allows a client to query the status of a specific certificate directly or through an OCSP responder, returning a near-real-time response without downloading the entire CRL. A CRL is a periodic list; a CSR requests issuance; a root repository stores trust anchors.

Question 7: Option C — Self-signed certificate

A self-signed certificate has identical issuer and subject fields because it is not signed by an external CA; it is signed by its own corresponding private key. It is not trusted by default and must be manually imported. DV, EV, and wildcard are categories/types of certificates issued by CAs.

Question 8: Option A — To bind a public key to an identity and enable trust through a certificate authority's signature

A digital certificate binds a public key to an identity, such as a domain or organization, and is signed by a CA. The CA's signature allows clients to trust the public key if they trust the CA. It does not encrypt the private key, list revocations, or request keys.

Question 9: Option C — A Certificate Signing Request (CSR)

The CSR is the artifact sent to the CA containing the public key and the requester's identity information. The CA validates and signs this request to issue the certificate. CRL and OCSP are used for revocation status; a self-signed root certificate does not request issuance.

Question 10: Option A — The internal root CA certificate

For clients to trust the chain, the trust anchor must be the internal root CA certificate installed in the trusted root store. The client can then validate intermediate and leaf certificates issued by that root. CRLs, individual leaf certificates, and OCSP URLs do not establish the PKI trust anchor.