

Security+ 2.3 · Buffer Overflows

Mestre CyberSec · Lesson 2.3 — Buffer Overflows (3:37) · [Assistir Vídeo no YouTube](#) ↗ · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Escreve MAIS dado do que o buffer aguenta = sobrescreve memória adjacente (pode ser shellcode). Defesa: bounds checking, DEP/ASLR, secure coding, compilar com proteção.

💡 Key Exam Highlights & Critical Concepts

- Buffer overflow: escreve além do tamanho do buffer
- DEP: barra execução na heap/stack; ASLR: randomiza endereços

🎯 Exam Tips & Typical CompTIA Scenarios

- 'application writes beyond allocated memory' = buffer overflow
- 'randomizes memory addresses' = ASLR

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 2.3 — Buffer Overflows)

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Buffer Overflow (N/A)

A vulnerability where an application writes data beyond the allocated memory boundary of a buffer, potentially overwriting adjacent memory and adjacent data such as the EIP (instruction pointer).

 **Exam Trap:** Exam trigger: 'application writes beyond allocated memory' or 'writes more data than the buffer can hold' = Buffer Overflow. Also watch for 'overflows the stack'.

• Stack Overflow (N/A)

A type of buffer overflow targeting the call stack memory region, typically overwriting the return address to redirect execution to attacker-supplied shellcode.

 **Exam Trap:** Exam tip: Stack is associated with function calls, local variables, and return addresses — the classic target for control-flow hijacking attacks.

• Heap Overflow (N/A)

A buffer overflow occurring in the heap memory region (dynamic memory), which can corrupt program data structures and lead to arbitrary code execution.

 **Exam Trap:** Exam tip: Heap is used for dynamic allocation — distinguish from stack overflow when the scenario mentions dynamically allocated memory or malloc/new.

• Shellcode (N/A)

Malicious machine code payload injected by an attacker, typically delivered via a buffer overflow, designed to spawn a shell or execute arbitrary commands on the target.

 **Exam Trap:** Exam tip: When the scenario mentions injected code, payloads, or attacker-supplied code following memory corruption = think Shellcode as the attack payload.

• Data Execution Prevention (DEP)

A security feature that marks memory regions (such as the heap and stack) as non-executable, preventing code from running in those areas to mitigate buffer overflow exploitation.

 **Exam Trap:** Exam trigger: 'prevents execution in the heap/stack' or 'blocks execution on data regions' = DEP. Don't confuse DEP (memory protection) with DLP (Data Loss Prevention).

• Address Space Layout Randomization (ASLR)

A security technique that randomizes the memory addresses used by system and application processes, making it significantly harder for attackers to predict and exploit buffer overflows.

 **Exam Trap:** Exam trigger: 'randomizes memory addresses' = ASLR. Pairs with DEP as a defense-in-depth strategy against memory-based attacks.

• Bounds Checking (N/A)

A secure coding practice that validates input length against the buffer's allocated size before writing, preventing buffer overflow conditions at the source-code level.

 **Exam Trap:** Exam tip: Bounds checking is the primary preventive control in 'secure coding' answers — choose it when asked how developers mitigate buffer overflows at the source.

• Compiler Protections / Stack Canaries (N/A)

Built-in compiler defenses (e.g., /GS flag, stack canaries, safe functions like strncpy) that detect or prevent buffer overflows by adding integrity checks to compiled code.

 **Exam Trap:** Exam tip: When the question asks about compiling with protection, enabling compiler flags, or using safe string functions, the answer relates to compiler protections, not ASLR or DEP.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

During a secure code review of a C application, a developer finds that user-supplied input from a network socket is copied into a 256-byte stack array using `strcpy` without checking the source length. The application later crashes on long input. The team wants to remove the vulnerability at its source. Which remediation is MOST appropriate?

- A) Enable Data Execution Prevention on all servers hosting the application.
- B) Replace the copy operation with a bounded function and reject or truncate input that exceeds the destination size.
- C) Deploy an intrusion prevention system signature to block long input strings.
- D) Run the application with least privilege to limit impact if exploitation occurs.

QUESTION 2 · EXAM SCENARIO

A penetration tester sends a crafted payload to a vulnerable service. The payload overwrites a return address on the stack and redirects execution to a small set of processor instructions that starts a command shell. Which term BEST describes the payload's role?

- A) Logic bomb
- B) Shellcode
- C) Rootkit
- D) Keylogger

QUESTION 3 · EXAM SCENARIO

A legacy internal service is vulnerable to a stack buffer overflow. During testing, the exploit places malicious instructions on the stack and redirects execution there, but the instructions do not run and the process terminates with an access violation. The OS is configured with a protection that marks stack memory as non-executable. Which protection is MOST likely responsible?

- A) Address Space Layout Randomization
- B) Stack canary
- C) Data Execution Prevention
- D) Input validation

QUESTION 4 · EXAM SCENARIO

A security analyst reviews an application crash log that shows stack smashing detected immediately after a malformed request. The application was compiled with a security option that places a random value before the saved return address and checks it before returning from a function. Which protection is being described?

- A) Address Space Layout Randomization
- B) Data Execution Prevention
- C) Bounds checking
- D) Stack canary

QUESTION 5 · EXAM SCENARIO

An attacker exploits a vulnerability in a server process that allocates memory dynamically for user profiles. The overflow corrupts adjacent heap metadata and later causes an overwrite of a function pointer. Which type of overflow is MOST likely?

- A) Stack overflow
- B) Integer overflow
- C) Heap overflow
- D) Format string vulnerability

QUESTION 6 · EXAM SCENARIO

A company wants to make buffer overflow exploits less reliable by ensuring that the exact memory addresses of the stack, heap, and libraries change each time a process starts. Which security control should be enabled?

- A) Data Execution Prevention
- B) Address Space Layout Randomization
- C) Stack canaries
- D) Input length validation

QUESTION 7 · EXAM SCENARIO

During an incident, a web server process is found to have executed a command shell after receiving a crafted HTTP header. Reverse engineering shows the attacker overwrote the saved return address in a function's stack frame. Which vulnerability was exploited?

- A) Stack buffer overflow
- B) Heap buffer overflow
- C) Cross-site scripting
- D) SQL injection

QUESTION 8 · EXAM SCENARIO

A development team is updating a C++ application that processes barcode data into fixed-size arrays. The security architect recommends a technique that checks the size of data before it is written and prevents writing past the end of the array. Which technique is being recommended?

- A) Address Space Layout Randomization
- B) Data Execution Prevention
- C) Bounds checking
- D) Code obfuscation

QUESTION 9 · EXAM SCENARIO

A security engineer is hardening a Linux application compiled from C source. The goal is to detect cases where a function writes beyond a local stack buffer and corrupts the saved return address before the function returns. Which compiler hardening feature is MOST directly designed for this?

- A) Position-independent executable
- B) Stack protector / stack canary
- C) Non-executable stack
- D) Address Space Layout Randomization

QUESTION 10 · EXAM SCENARIO

A legacy C application uses `gets()` to read user input into a fixed-size buffer. A security consultant says this function is dangerous because it cannot limit how many characters are read. Which change BEST addresses the buffer overflow risk?

- A) Compile the application with Address Space Layout Randomization.
- B) Replace `gets()` with a function that enforces a maximum input length and validates the result.
- C) Enable Data Execution Prevention on the host.
- D) Run the application as a low-privileged service account.

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option B — Replace the copy operation with a bounded function and reject or truncate input that exceeds the destination size.

The root cause is an unbounded copy into a fixed-size stack buffer. Bounds checking and safe bounded copy functions, or validating and truncating input before copying, remove the flaw by ensuring data cannot exceed the destination. DEP, IPS signatures, and least privilege may reduce impact or exploitability but do not fix the vulnerable code.

Question 2: Option B — Shellcode

Shellcode is the small machine-code payload an attacker injects and executes after gaining control of the instruction pointer. A logic bomb is triggered code, a rootkit hides access, and a keylogger records keystrokes; none is the injected code that starts a shell in this scenario.

Question 3: Option C — Data Execution Prevention

DEP and NX mark memory regions such as the stack and heap as non-executable. If shellcode is placed there, the CPU refuses to execute it, often causing an access violation. ASLR randomizes addresses, stack canaries detect stack corruption, and input validation prevents malformed input but does not make stack memory non-executable.

Question 4: Option D — Stack canary

A stack canary is a random value placed between local buffers and the saved return address. Before a function returns, the canary is checked; if a buffer overflow overwrites it, the program detects tampering and terminates, producing messages such as stack smashing detected. ASLR randomizes addresses, DEP prevents execution, and bounds checking prevents the write.

Question 5: Option C — Heap overflow

Heap overflows occur in dynamically allocated memory, the heap. Corrupting heap metadata or adjacent objects to influence a later function pointer is characteristic of heap exploitation. Stack overflows target stack frames; integer overflows and format string bugs are different vulnerability classes.

Question 6: Option B — Address Space Layout Randomization

ASLR randomizes the base addresses of the stack, heap, and libraries each time a process starts, making it harder for an attacker to predict where shellcode or return addresses are located. DEP prevents code execution from writable memory, stack canaries detect stack corruption, and input validation prevents malicious input from being accepted.

Question 7: Option A — Stack buffer overflow

Overwriting a saved return address in a function's stack frame is the classic stack buffer overflow. Heap overflows corrupt dynamically allocated memory, XSS affects browsers, and SQL injection manipulates database queries; none matches the described memory corruption.

Question 8: Option C — Bounds checking

Bounds checking verifies that data being written fits within the allocated array or buffer before the write occurs, preventing out-of-bounds writes. ASLR and DEP are runtime exploit mitigations, and code obfuscation does not enforce memory safety.

Question 9: Option B — Stack protector / stack canary

Stack protector and stack canary insert a known value on the stack and verify it before returning from a function, helping detect corruption of the saved return address. PIE helps with ASLR, non-executable stack is a DEP or NX feature, and ASLR randomizes address locations; none directly checks for stack overwrite before return.

Question 10: Option B — Replace gets() with a function that enforces a maximum input length and validates the result.

The root cause is use of gets(), which cannot limit input length and may write past the buffer. Replacing it with a bounded input function and validating the length addresses the vulnerability. ASLR, DEP, and least privilege are mitigations that may reduce exploitability or impact but do not remove the dangerous unbounded read.

