

Security+ 3.2 · Network Appliances

Mestre CyberSec · Lesson 3.2 — Network Appliances (11:56) · [Assistir Vídeo no YouTube ↗](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Appliances: jump server (única entrada pra admin); proxy (intermedia HTTP — cache/filter/auth); load balancer (distribui); sensors (IDS/IPS); collectors (junta logs pra SIEM).

💡 Key Exam Highlights & Critical Concepts

- Jump box: única porta de ADMINISTRACAO — reduz surface
- Proxy: cache + filter + auth no tráfego HTTP
- Load balancer: distribui e dá redundância

🎯 Exam Tips & Typical CompTIA Scenarios

- 'single entry point for administrators' = jump server

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 3.2 — Network Appliances)

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Jump Server (Jump Box) (N/A)

A hardened, isolated server that acts as the single administrative entry point for managing critical systems; administrators connect to it first, then access other devices.

 **Exam Trap:** Palavra-chave: 'single entry point for administrators' = jump server. Não confunda com proxy ou VPN; o foco é acesso administrativo controlado e auditado.

• Proxy Server (N/A)

An intermediary appliance that handles client requests, often for HTTP/HTTPS, providing caching, content filtering, authentication, and logging.

 **Exam Trap:** Se a questão mencionar cache, filtro de URL/conteúdo e autenticação no tráfego web, pense em proxy. Forward proxy = atende clientes internos; reverse proxy = protege servidores internos.

• Forward Proxy (N/A)

A proxy that sits between internal users and external networks, forwarding outbound client requests to the Internet and enforcing policies.

 **Exam Trap:** Exam trigger: internal users accessing external sites through a proxy. It hides client IPs and filters outbound traffic. Not the same as reverse proxy.

• Reverse Proxy (N/A)

A proxy placed in front of internal servers to accept external client requests, providing load balancing, caching, TLS termination, and protection.

 **Exam Trap:** Exam trigger: external clients accessing internal web servers; reverse proxy hides servers and can offload TLS/SSL. Contrast with forward proxy.

• Load Balancer (LB)

A network appliance that distributes incoming traffic across multiple servers to improve performance, availability, and redundancy.

 **Exam Trap:** Se a questão citar distribuição de tráfego, failover, health checks ou alta disponibilidade, escolha load balancer. Pode ser L4 (TCP/UDP) ou L7 (HTTP).

• Sensors (IDS/IPS)

Network sensors monitor traffic for malicious activity; IDS detects and alerts, while IPS can actively block or prevent intrusions.

 **Exam Trap:** Gatilho: 'detecta e alerta' = IDS; 'detecta e bloqueia' = IPS. Sensor é o componente que coleta/monitora o tráfego para o IDS/IPS.

• Collector (N/A)

A log collector aggregates and forwards log data from many sources to a central system, often a SIEM, for correlation and analysis.

 **Exam Trap:** Exam trigger: 'aggregates logs' or 'feeds SIEM' = collector. It does not analyze by itself; it centralizes/forwards logs.

• Security Information and Event Management (SIEM)

A centralized platform that collects, correlates, and analyzes security logs and events from multiple sources to support detection and response.

⚠ Exam Trap: Se a questão falar em correlação de logs, dashboards, alertas centralizados e retenção para investigação, pense em SIEM. Collectors alimentam o SIEM.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A systems administrator needs to provide secure remote administrative access to a hardened management network that hosts network devices, hypervisors, and storage controllers. The security team requires that no direct inbound administrative connections be permitted to these critical assets from outside the network. Which network appliance should be deployed as the single, controlled entry point for administrative sessions into this isolated management zone?

- A) A jump server placed in a screened subnet that brokers all administrative sessions to the management network
- B) A reverse proxy configured to terminate TLS for inbound administrator HTTPS traffic to management endpoints
- C) An inline IPS sensor performing deep packet inspection on management VLAN traffic
- D) A load balancer using round-robin distribution across the management controllers

QUESTION 2 · EXAM SCENARIO

A mid-sized company wants to reduce bandwidth costs and enforce acceptable-use policies for outbound web traffic from 800 employees. The security team also needs to block known malicious domains and prevent users from uploading sensitive documents to unauthorized cloud storage services. Which appliance best satisfies all three requirements by sitting between the users and the Internet?

- A) A forward proxy that inspects outbound HTTP/HTTPS requests, enforces content filtering, and caches frequently accessed objects
- B) A reverse proxy deployed in front of the internal file servers to cache downloads
- C) A jump server used as the default gateway for all employee workstations
- D) A network-based IDS sensor placed at the Internet edge in passive monitor mode

QUESTION 3 · EXAM SCENARIO

An e-commerce company is hosting a public-facing checkout application on multiple internal web servers behind a single public IP address. The security engineer wants to terminate TLS at a perimeter appliance, hide the internal server topology from attackers, and inspect inbound requests for malicious payloads before they reach the application servers. Which appliance should be deployed in the DMZ?

- A) A reverse proxy that terminates inbound HTTPS, performs request inspection, and forwards cleansed traffic to the appropriate backend web server
- B) A forward proxy configured as the default gateway on each web server
- C) A jump server that brokers all customer HTTPS sessions to the database tier
- D) A passive IDS sensor that mirrors traffic from the DMZ switch SPAN port

QUESTION 4 · EXAM SCENARIO

A streaming service is experiencing slow response times during primetime hours. The application team has deployed six identical application servers in the data center, but a single health check reveals one server is returning HTTP 503 errors. The network architect wants to automatically remove the failing server from the pool, distribute new client connections evenly across the healthy servers, and provide SSL offloading. Which appliance meets these requirements?

- A) A load balancer performing health checks, distributing traffic via round-robin or least-connections, and offloading TLS decryption to optimize backend performance
- B) A reverse proxy with a static DNS A record pointing to the first available server
- C) A jump server configured with SSH tunnels to each application node
- D) An inline IPS sensor blocking malformed HTTP responses from the backend

QUESTION 5 · EXAM SCENARIO

A security operations team needs a network device that monitors east-west traffic between virtual machines inside the data center, copies packets for analysis, and raises alerts when signatures of known attack patterns are matched. The device must NOT modify or block traffic because the team only wants visibility for tuning detection rules. Which deployment best fits this requirement?

- A) A passive IDS sensor connected to a SPAN/mirror port that analyzes copies of traffic and generates alerts on signature matches
- B) An inline IPS sensor placed in series with the VM traffic flow that drops matching packets
- C) A reverse proxy terminating all VM-to-VM HTTP connections
- D) A load balancer distributing traffic across the hypervisor virtual switches

QUESTION 6 · EXAM SCENARIO

After several successful SQL injection attacks evaded signature-based detection, the security team wants an inline device in front of the public web servers that can inspect HTTP request bodies, drop malicious requests in real time, and update its signatures automatically from the vendor's threat feed. Which appliance should the team deploy?

- A) An inline IPS sensor placed in the network path that performs deep packet inspection and actively blocks malicious traffic
- B) A passive IDS connected to a SPAN port that only logs suspicious payloads
- C) A reverse proxy configured to serve static content from the cache
- D) A jump server that brokers all database connections from the application tier

QUESTION 7 · EXAM SCENARIO

A multinational organization has firewalls, switches, servers, and endpoint agents generating millions of log entries per day across different formats and time zones. The SOC wants a single point of collection that normalizes timestamps and formats, enriches events, and forwards them to a long-term analytical platform for correlation. Which appliance best fulfills this role?

- A) A log collector that receives events from diverse sources, normalizes them into a common schema, enriches the data, and forwards it to the SIEM
- B) An inline IPS sensor that drops suspicious traffic and writes alerts to local storage
- C) A jump server that brokers all administrative sessions and writes them to a text file
- D) A reverse proxy that records every HTTP request in its access log

QUESTION 8 · EXAM SCENARIO

A SOC analyst wants to query a centralized platform that combines firewall logs, Windows event logs, IDS alerts, web proxy logs, and authentication events in a single pane of glass. The platform should support correlation rules that combine events from these different sources to detect multi-stage attacks such as phishing leading to lateral movement. Which solution best satisfies this requirement?

- A)** A SIEM that ingests normalized events from multiple collectors, correlates them across sources, and provides dashboards and alerting
- B)** A standalone jump server that aggregates text logs into a single directory
- C)** An inline IPS sensor that consolidates signatures from multiple vendors
- D)** A reverse proxy that combines access logs from frontend and backend web servers

QUESTION 9 · EXAM SCENARIO

A small financial firm has 12 servers, several switches, and two firewalls spread across one data center and one branch office. The CISO wants a simple, secure way for administrators to perform routine maintenance on all devices without exposing SSH or RDP directly to the Internet. The solution must also produce a single audit log of who did what and when across all administrative actions. Which design best meets these goals?

- A)** Deploy a hardened jump server in the management VLAN, require all admins to authenticate to it first, and forward its session logs to the SIEM
- B)** Open TCP port 22 on the perimeter firewall with a strong password policy for direct SSH access
- C)** Replace the firewalls with a single IDS sensor in passive monitoring mode
- D)** Use a public reverse proxy with no authentication to expose the management interfaces

QUESTION 10 · EXAM SCENARIO

An enterprise architect is designing the perimeter of a new data center and must decide where to place several appliances. Internal clients will browse the Internet, public users will reach a cluster of web servers, the SOC needs visibility into malicious traffic patterns, and admins must reach all internal devices securely. Which placement correctly matches each appliance to its role?

- A)** Forward proxy for outbound client traffic, reverse proxy in the DMZ for inbound web traffic, IDS/IPS sensor at the perimeter for detection/prevention, and jump server for administrative access
- B)** Reverse proxy for outbound browsing, forward proxy for inbound web traffic, jump server for traffic inspection, and IDS sensor for admin access
- C)** Jump server in the DMZ serving public traffic, forward proxy for admin sessions, IDS sensor terminating TLS, and reverse proxy as the default gateway
- D)** IDS sensor caching outbound web content, forward proxy inspecting inbound HTTPS, jump server blocking SQL injection, and reverse proxy providing admin access

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option A — A jump server placed in a screened subnet that brokers all administrative sessions to the management network

A jump server (jump box) is the standard CompTIA answer for providing a single, audited, controlled entry point into a hardened administrative or management zone. It brokers RDP/SSH sessions, reduces the attack surface by eliminating direct inbound admin access, and produces a centralized audit trail. A reverse proxy fronts web services, not generic admin protocols; an IPS inspects traffic but does not broker sessions; a load balancer distributes application traffic, not administrative sessions.

Question 2: Option A — A forward proxy that inspects outbound HTTP/HTTPS requests, enforces content filtering, and caches frequently accessed objects

A forward proxy is designed to sit on behalf of internal clients making outbound requests to the Internet. It caches content to reduce bandwidth, enforces acceptable-use and DLP policies, and can block malicious destinations. A reverse proxy serves inbound traffic to internal servers; a jump server is for administrative access; an IDS in passive mode observes traffic but does not enforce outbound filtering.

Question 3: Option A — A reverse proxy that terminates inbound HTTPS, performs request inspection, and forwards cleansed traffic to the appropriate backend web server

A reverse proxy sits in front of internal servers to represent them to external clients. It terminates TLS, hides internal addressing/topology, can perform WAF-like inspection of inbound requests, and forwards traffic to the correct backend. A forward proxy represents internal clients to the outside, not the reverse. A jump server brokers admin sessions, not customer traffic. A passive IDS only observes and would not terminate TLS or forward traffic.

Question 4: Option A — A load balancer performing health checks, distributing traffic via round-robin or least-connections, and offloading TLS decryption to optimize backend performance

A load balancer (hardware or software) is the canonical solution for distributing traffic across multiple servers, performing active health checks to remove failed nodes, and offloading TLS to reduce CPU load on backends. A reverse proxy alone typically targets one server. A jump server is for administrative access. An IPS blocks attacks but does not distribute or load-balance traffic.

Question 5: Option A — A passive IDS sensor connected to a SPAN/mirror port that analyzes copies of traffic and generates alerts on signature matches

An IDS (Intrusion Detection System) sensor is a passive monitoring appliance that receives copies of traffic (typically via a SPAN port or TAP) and alerts on suspicious patterns without altering the traffic. The question explicitly forbids modification, which rules out an inline IPS. A reverse proxy and load balancer are not detection devices.

Question 6: Option A — An inline IPS sensor placed in the network path that performs deep packet inspection and actively blocks malicious traffic

An IPS (Intrusion Prevention System) is the inline counterpart to an IDS. It actively blocks malicious traffic based on signatures, anomalies, or behavioral rules. The requirement for inline placement and real-time blocking clearly maps to an IPS. A passive IDS only alerts, a reverse proxy in this context wouldn't enforce signature-based blocking, and a jump server is unrelated.

Question 7: Option A — A log collector that receives events from diverse sources, normalizes them into a common schema, enriches the data, and forwards it to the SIEM

A collector (or log collector/forwarder) is specifically designed to ingest logs from many heterogeneous sources, normalize the data into a consistent format, and forward the normalized events to a SIEM for correlation and analysis. The other options either produce logs incidentally or are not designed for centralized multi-source log collection.

Question 8: Option A — A SIEM that ingests normalized events from multiple collectors, correlates them across sources, and provides dashboards and alerting

A SIEM (Security Information and Event Management) is the platform built for centralized log aggregation, normalization, correlation across diverse log sources, and alerting on complex multi-stage attack patterns. The other options describe appliances that produce logs or block traffic but are not correlation engines across heterogeneous sources.

Question 9: Option A — Deploy a hardened jump server in the management VLAN, require all admins to authenticate to it first, and forward its session logs to the SIEM

A jump server is the textbook solution for consolidating administrative access, eliminating direct inbound admin services from the Internet, and producing centralized audit logs of administrative activity. The other options either weaken security (open SSH, no authentication) or fail to provide admin brokering (IDS, reverse proxy).

Question 10: Option A — Forward proxy for outbound client traffic, reverse proxy in the DMZ for inbound web traffic, IDS/IPS sensor at the perimeter for detection/prevention, and jump server for administrative access

Each appliance has a defined role in a properly designed perimeter: forward proxy = outbound client traffic to Internet, reverse proxy = inbound web traffic in DMZ, IDS/IPS sensor = perimeter inspection/detection/prevention, jump server = administrative access. The other options swap roles incorrectly, demonstrating that the answer requires understanding each appliance's purpose.