

Security+ 4.1 · Application Security

Mestre CyberSec · Lesson 4.1 — Application Security (8:26) · [Assistir Vídeo no YouTube ↗](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: AppSec: input validation (NUNCA confie no input — sanitize tudo); secure cookie (HttpOnly, Secure, SameSite); code signing (assinatura do executável); sandboxing; SAST (static code analysis).

💡 Key Exam Highlights & Critical Concepts

- Input validation: base de TUDO — sanitize/escape/whitelist
- HttpOnly cookie: JS não lê — mitiga stealing (XSS)

🎯 Exam Tips & Typical CompTIA Scenarios

- 'JavaScript cannot access= this cookie'=HttpOnly

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 4.1 — Application Security)

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Input Validation (N/A)

Process of verifying and sanitizing all external or user-supplied data before processing to prevent injection, XSS, and malformed input. It is the foundation of secure application coding.

⚠ **Exam Trap:** *CompTIA: validação de entrada é a base de TUDO; use whitelist/allowlist, sanitize e escape. Não confie em nenhum input.*

• HttpOnly Cookie

Cookie attribute that prevents client-side JavaScript from accessing the cookie via document.cookie, reducing session theft via XSS.

⚠ **Exam Trap:** *Gatilho clássico: 'JavaScript cannot access this cookie' = HttpOnly. Não substitui Secure nem SameSite.*

• Secure Cookie Attribute

Cookie attribute that ensures the cookie is only transmitted over HTTPS/TLS-encrypted connections, protecting it from interception in cleartext.

⚠ **Exam Trap:** *CompTIA: Secure = somente HTTPS. Se a questão fala de confidencialidade no transporte do cookie, é Secure, não HttpOnly.*

• SameSite Cookie Attribute

Cookie attribute that controls whether cookies are sent with cross-site requests, helping mitigate CSRF and cross-site tracking.

⚠ **Exam Trap:** *Gatilho: proteção contra CSRF/cross-site request = SameSite. Valores comuns: Strict, Lax, None (None exige Secure).*

• Code Signing (N/A)

Use of a digital signature on executables, scripts, or applications to verify publisher authenticity and integrity, ensuring code has not been altered.

⚠ **Exam Trap:** *CompTIA: assinatura do executável = code signing. Distingue de hashing simples: fornece autenticidade e integridade via certificado do desenvolvedor.*

• Sandboxing (N/A)

Isolation technique that runs code or applications in a restricted environment to limit access to system resources and prevent damage from malicious or untrusted code.

⚠ **Exam Trap:** *Gatilho: executar código não confiável com baixo impacto = sandbox. Não é antivírus; é contenção/isolamento.*

• Static Application Security Testing (SAST)

Testing method that analyzes source code, bytecode, or binaries without executing the application to find security flaws early in the SDLC.

⚠ **Exam Trap:** *CompTIA: SAST = analisa código sem executar (white-box). Não confunda com DAST, que testa a aplicação em execução (black-box).*

• Cross-Site Scripting (XSS)

Web vulnerability where an attacker injects malicious scripts into trusted sites viewed by other users, often stealing cookies or session tokens.

⚠ **Exam Trap:** *Gatilho: script malicioso executado no navegador da vítima = XSS. Mitigações: input validation, output encoding, HttpOnly cookies, CSP.*

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A web application displays a user's search term in the results page by inserting it directly into the HTML response. Security testing shows that an attacker can submit a search term containing JavaScript that executes in a victim's browser. Which control should be implemented to address this vulnerability at its source?

- A) Add the HttpOnly attribute to the session cookie.
- B) Perform context-aware output encoding and server-side input validation.
- C) Configure the session cookie with SameSite=Strict.
- D) Require code signing for the application binaries.

QUESTION 2 · EXAM SCENARIO

An online retailer's session cookie is accessible through JavaScript, and the cookie is transmitted even when users connect over unencrypted HTTP. A penetration tester warns that a single cross-site scripting flaw or network sniffing could lead to session hijacking. Which set of cookie attributes should the developer apply to the session cookie?

- A) HttpOnly, Secure, SameSite=Strict
- B) Domain, Path, Expires
- C) SameSite=None, Secure=false
- D) Max-Age, Priority=High

QUESTION 3 · EXAM SCENARIO

A banking application uses a session cookie that is automatically sent on all requests from any website. A security analyst demonstrates that a malicious site can submit a hidden form to the bank and trigger an authenticated funds transfer. Which cookie attribute change best mitigates this cross-site request forgery risk?

- A) Add the Secure attribute.
- B) Add the HttpOnly attribute.
- C) Set SameSite=Strict on the session cookie.
- D) Increase the cookie's Max-Age value.

QUESTION 4 · EXAM SCENARIO

A software vendor distributes a Windows desktop client through its public website. Users have begun receiving warnings that the publisher cannot be verified, and attackers may distribute a modified installer. Which control should the vendor implement to let users verify the software's origin and integrity?

- A) Run SAST against the desktop client source code.
- B) Deploy the client in a sandboxed container.
- C) Add HttpOnly and SameSite flags to the web session cookie.
- D) Sign the executable and installer with a trusted code-signing certificate.

QUESTION 5 · EXAM SCENARIO

A malware analyst needs to open suspicious email attachments and observe their behavior without risking the corporate workstation or letting the sample contact command-and-control servers. Which approach is most appropriate?

- A) Code-sign the attachments before opening them.
- B) Execute the attachments in an isolated sandbox with restricted network access.
- C) Run a SAST scan on the email attachments.
- D) Set the email client's cookies to HttpOnly.

QUESTION 6 · EXAM SCENARIO

A development team wants to identify insecure coding patterns, such as hard-coded credentials and unsanitized database queries, before the application is compiled and deployed. Which application security activity should be integrated into the CI/CD pipeline?

- A) Static application security testing (SAST)
- B) Dynamic application security testing (DAST)
- C) Code signing
- D) Sandboxing

QUESTION 7 · EXAM SCENARIO

A web application allows users to upload profile pictures. A penetration tester successfully uploads a file named `avatar.php` containing server-side code and then accesses it through a URL. Which control should be implemented to prevent this file upload vulnerability?

- A) Add the Secure attribute to the session cookie.
- B) Sign the web application's executable files.
- C) Validate file type and extension, and store uploaded files outside the web root with randomized names.
- D) Set the session cookie to SameSite=Lax.

QUESTION 8 · EXAM SCENARIO

During a security review, a developer confirms that a session cookie is marked Secure and SameSite=Lax, but a cross-site scripting flaw still allows an attacker to read the cookie value from `document.cookie`. Which cookie attribute should be added to prevent JavaScript access to the session cookie?

- A) Secure
- B) SameSite=Strict
- C) Domain
- D) HttpOnly

QUESTION 9 · EXAM SCENARIO

An organization wants to ensure that only approved, unmodified internal applications can run on employee endpoints. Endpoint security should verify that each application carries a valid digital signature from the software publisher before allowing execution. Which application security control does this describe?

- A) Code signing verification with application allowlisting
- B) Input validation
- C) Static application security testing (SAST)
- D) Sandboxing

QUESTION 10 · EXAM SCENARIO

A security engineer is reviewing source code for a new payment service. The engineer wants to find potential injection flaws and unsafe API usage without executing the application or attacking a running environment. Which technique should be used?

- A) Dynamic application security testing (DAST)
- B) Static application security testing (SAST)
- C) Sandboxing
- D) Secure cookie configuration

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option B — Perform context-aware output encoding and server-side input validation.

The vulnerability is cross-site scripting caused by unencoded user input. Context-aware output encoding prevents the browser from treating user data as executable script, and server-side input validation reduces malicious input. HttpOnly, SameSite, and code signing protect other areas, such as cookie theft or binary integrity, but they do not fix the root cause of reflected XSS.

Question 2: Option A — HttpOnly, Secure, SameSite=Strict

HttpOnly prevents JavaScript from reading the cookie, Secure ensures it is sent only over HTTPS, and SameSite=Strict limits cross-site sending. Domain, Path, Expires, Max-Age, and Priority do not provide the same confidentiality and anti-CSRF protections.

Question 3: Option C — Set SameSite=Strict on the session cookie.

SameSite=Strict prevents the browser from sending the session cookie on cross-site requests, which blocks the demonstrated CSRF attack. Secure protects cookie confidentiality in transit, HttpOnly blocks JavaScript access, and Max-Age affects persistence, but none of those directly stop cross-site form submissions.

Question 4: Option D — Sign the executable and installer with a trusted code-signing certificate.

Code signing uses a digital signature to prove the publisher's identity and confirm that the binary has not been altered. SAST finds source-code flaws, sandboxing limits runtime impact, and cookie flags protect web sessions, but none of those let users verify installer origin and integrity.

Question 5: Option B — Execute the attachments in an isolated sandbox with restricted network access.

Sandboxing runs untrusted code in an isolated environment and can restrict network access, allowing safe behavioral observation. Code signing verifies trusted software but does not make malware safe, SAST analyzes source code, and HttpOnly is a web cookie control.

Question 6: Option A — Static application security testing (SAST)

SAST examines source code or binaries without executing the application, making it suitable for finding hard-coded secrets and unsafe query patterns early in CI/CD. DAST tests a running application, code signing verifies integrity, and sandboxing isolates execution.

Question 7: Option C — Validate file type and extension, and store uploaded files outside the web root with randomized names.

The application must validate uploads and prevent user-controlled executable files from being served. Restricting type and extension, storing files outside the web root, and randomizing names reduce the chance of code execution. Cookie attributes and code signing do not address unsafe file upload handling.

Question 8: Option D — HttpOnly

HttpOnly prevents client-side scripts from accessing the cookie through document.cookie, reducing session theft via XSS. Secure protects transmission, SameSite limits cross-site requests, and Domain scopes where the cookie is sent, but none block JavaScript access.

Question 9: Option A — Code signing verification with application allowlisting

Code signing verification checks the publisher's digital signature and integrity, and allowlisting can permit only signed, approved applications to execute. Input validation, SAST, and sandboxing are valuable controls but do not enforce publisher authenticity at endpoint execution time.

Question 10: Option B — Static application security testing (SAST)

SAST analyzes source code, bytecode, or binaries without running the application, so it can identify injection flaws and unsafe API use early. DAST tests a running application, sandboxing isolates execution, and secure cookie settings address session security rather than source-code flaws.

