

Security+ 4.5 · Email Security

Mestre CyberSec · Lesson 4.5 — Email Security (7:05) · [Assistir Vídeo no YouTube ↗](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: SPF (lista de IP autorizado), DKIM (assinatura da mensagem), DMARC (política: o que fazer se falhar — reject/quarantine + notifica o dono). Gateway security antispam/antivirus. Encryption: S/MIME, PGP. Sem DMARC qualquer um impersona o domínio.

💡 Key Exam Highlights & Critical Concepts

- SPF: lista os IP autorizado; DKIM: assina o corpo
- DMARC: a política — reject/quarantine quando falha; protege contra spoof

🎯 Exam Tips & Typical CompTIA Scenarios

- 'email spoofing prevented by which combination of protocols'=SPF+DKIM+DMARC

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

- **Sender Policy Framework (SPF)**

DNS TXT record that lists the IP addresses and hosts authorized to send email for a domain, helping receiving servers verify the envelope sender.

⚠ **Exam Trap:** Se a questão mencionar lista de IPs autorizados, é SPF. SPF valida o envelope/remetente, não o corpo nem o cabeçalho visível da mensagem.

- **DomainKeys Identified Mail (DKIM)**

Uses a digital signature added to email headers or body; the receiving server validates it using a public key in DNS to confirm message integrity and domain ownership.

⚠ **Exam Trap:** Se mencionar assinatura criptográfica da mensagem, é DKIM. Não autoriza IPs; verifica integridade e autenticidade do domínio assinante.

- **Domain-based Message Authentication, Reporting, and Conformance (DMARC)**

DNS policy that tells receiving servers how to handle email failing SPF/DKIM alignment and requests reports; policies include none, quarantine, or reject.

⚠ **Exam Trap:** Gatilho de prova: combinação que previne spoofing = SPF + DKIM + DMARC. DMARC fornece a política (reject/quarantine) e notifica o dono do domínio.

- **Email Spoofing (N/A)**

Forging the sender address of an email so it appears to come from a trusted domain or person. Without DMARC, attackers can impersonate a domain.

⚠ **Exam Trap:** Spoofing é facilitado pela falta de DMARC; SPF/DKIM sozinhos não definem o que fazer se falharem. DMARC protege contra impersonação do domínio.

- **Secure Email Gateway (SEG)**

Appliance or cloud service that filters inbound and outbound email for spam, phishing, malware, and policy violations before delivery.

⚠ **Exam Trap:** Gateway security antispam/antivírus é SEG; atua antes da caixa de correio. Não confundir com criptografia ponta a ponta.

- **Secure/Multipurpose Internet Mail Extensions (S/MIME)**

Standard for public key encryption and digital signatures of email, commonly using X.509 certificates for confidentiality and authentication.

⚠ **Exam Trap:** Se a questão falar de certificados digitais/X.509 em e-mail corporativo, é S/MIME. Fornece confidencialidade, integridade e autenticação.

- **Pretty Good Privacy (PGP)**

Encryption standard or tool using a web of trust for email confidentiality, integrity, and authentication; often implemented as OpenPGP.

⚠ **Exam Trap:** PGP é associado a web of trust, não a X.509/PKI corporativa. S/MIME usa certificados centralizados; PGP usa confiança descentralizada.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A security analyst notices that external attackers are sending emails with a visible From address of `ceo@contoso.com`. The company has a valid SPF record for `contoso.com` with `-all`. Investigation shows the messages are passing SPF because attackers use a different envelope sender domain, while the visible From header is `contoso.com`. Which email authentication control should be implemented to require that the visible From domain aligns with an authenticated domain and allows a policy to reject unaligned mail?

- A) S/MIME
- B) DKIM
- C) DMARC
- D) PGP

QUESTION 2 · EXAM SCENARIO

A receiving mail server examines a message header containing a cryptographic signature and a selector. It retrieves the public key from a DNS TXT record to verify that the message content was not altered and that the signing domain authorized the message. Which technology is being used?

- A) SPF
- B) DKIM
- C) DMARC
- D) S/MIME

QUESTION 3 · EXAM SCENARIO

An organization publishes a DMARC record with `p=none` and receives aggregate reports. After analyzing the reports, the CISO wants receivers to block messages that fail both SPF and DKIM alignment for the company's domain, rather than only monitoring them. Which DMARC policy should be set?

- A) `p=none`
- B) `p=quarantine`
- C) `v=spf1 -all`
- D) `p=reject`

QUESTION 4 · EXAM SCENARIO

A security team wants to receive regular XML reports from major mailbox providers summarizing how many messages using its domain passed or failed SPF, DKIM, and DMARC, along with source IP addresses. Which DMARC DNS record tag should the team configure?

- A) `rua`
- B) `ruf`
- C) `adkim`
- D) `p`

QUESTION 5 · EXAM SCENARIO

A company uses Microsoft Outlook and an internal public key infrastructure. Employees must digitally sign and encrypt email so that recipients can verify sender identity and only intended recipients can read message contents. The company wants native Outlook integration and certificate-based trust. Which standard should be deployed?

- A) PGP
- B) S/MIME
- C) DKIM
- D) SPF

QUESTION 6 · EXAM SCENARIO

A decentralized open-source project needs to exchange encrypted and signed email without relying on a corporate certificate authority. Team members prefer a web-of-trust model and already use standalone key management tools. Which email security standard best fits this requirement?

- A) S/MIME
- B) DKIM
- C) PGP
- D) SPF

QUESTION 7 · EXAM SCENARIO

A company wants to inspect inbound and outbound email before it reaches the mail server. The solution must block spam and malware, detect phishing URLs, and apply data loss prevention policies to attachments. Which technology should be deployed?

- A) Secure email gateway
- B) SPF record
- C) DMARC record
- D) S/MIME certificate

QUESTION 8 · EXAM SCENARIO

An administrator has configured SPF for example.com as `v=spf1 include:_spf.google.com -all`. A new business application sends email as `alerts@example.com` through a third-party SMTP relay that is not included in the SPF record. Recipients are rejecting the alerts because SPF fails. What is the most appropriate fix?

- A) Add a DKIM signature to the alerts
- B) Add the relay's authorized sending IPs or an include mechanism to the SPF record
- C) Change DMARC to `p=none`
- D) Replace SPF with S/MIME

QUESTION 9 · EXAM SCENARIO

An organization has valid SPF and DKIM records for its domain but has not published a DMARC record. An attacker sends phishing messages with the organization's domain in the visible From header. Which statement best describes the primary security gap?

- A) SPF will automatically reject all spoofed visible From messages
- B) DKIM will encrypt the message to prevent spoofing
- C) Without DMARC, receivers lack a domain policy requiring aligned authentication and rejection/quarantine
- D) S/MIME will verify the message if the recipient has a certificate

QUESTION 10 · EXAM SCENARIO

A company sends marketing email through a third-party platform. The messages have a visible From address of news@company.com. SPF passes for the platform's envelope domain, but DMARC fails because the SPF-authenticated domain does not align with company.com. The platform supports custom DKIM signing. Which action is the best way to make DMARC pass while preserving the visible From domain?

- A) Change DMARC policy to p=none
- B) Remove the SPF record
- C) Configure DKIM signing with d=company.com
- D) Enable S/MIME for all recipients

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option C — DMARC

SPF checks the envelope MAIL FROM/Return-Path domain, so it can pass for the attacker's domain even if the visible From header is spoofed. DMARC uses SPF and/or DKIM with identifier alignment against the visible From domain and allows policies such as p=reject or p=quarantine. S/MIME and PGP sign or encrypt messages but do not enforce domain-based anti-spoofing policy.

Question 2: Option B — DKIM

DKIM publishes a public key in DNS and signs message headers/body, allowing the receiver to validate integrity and the signing domain. SPF authorizes sending IPs for the envelope domain. DMARC defines policy and alignment. S/MIME uses user-level certificates, not DNS TXT selector-based signatures.

Question 3: Option D — p=reject

p=none only monitors, p=quarantine sends suspicious mail to spam/quarantine, and p=reject blocks it. v=spf1 -all affects only SPF and does not define the DMARC policy for SPF/DKIM alignment failures.

Question 4: Option A — rua

The rua tag specifies URIs for aggregate reports. ruf is used for forensic/failure reports. adkim defines DKIM alignment mode. p defines the DMARC policy.

Question 5: Option B — S/MIME

S/MIME uses X.509 certificates, integrates with Outlook, and provides message signing and encryption. PGP uses a web-of-trust model and separate tools, with less native enterprise integration. DKIM and SPF are domain authentication mechanisms, not end-to-end message encryption.

Question 6: Option C — PGP

PGP uses public/private key pairs and a web-of-trust model, independent of a central CA. S/MIME relies on certificate authorities. DKIM and SPF perform domain authentication, not end-to-end encryption.

Question 7: Option A — Secure email gateway

A secure email gateway filters email, provides anti-spam, antivirus, data loss prevention, and URL filtering. SPF and DMARC records perform domain authentication. S/MIME certificates are used for message signing and encryption.

Question 8: Option B — Add the relay's authorized sending IPs or an include mechanism to the SPF record

SPF must list all authorized senders for the domain. DKIM may help DMARC but does not correct SPF failure. p=none only monitors; S/MIME does not replace SPF.

Question 9: Option C — Without DMARC, receivers lack a domain policy requiring aligned authentication and rejection/quarantine

SPF and DKIM alone can pass for other domains or lack alignment. DMARC enforces alignment with the visible From domain and provides a policy for rejection or quarantine. SPF does not automatically reject all visible-From spoofing, DKIM does not encrypt, and S/MIME does not replace DMARC.

Question 10: Option C — Configure DKIM signing with d=company.com

A DKIM signature with d=company.com aligns with the visible From domain and can make DMARC pass even if SPF aligns to the vendor. p=none only monitors, removing SPF worsens authentication, and S/MIME is unrelated to DMARC alignment.