

Security+ 4.5 · Firewalls

Mestre CyberSec · Lesson 4.5 — Firewalls (11:31) · [Assistir Vídeo no YouTube ↗](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: NGFW: aplicação-aware (vê o tráfego por app); user-aware; threat intel integrado; SSL inspection. UTM = tudo em 1 (pequena empresa). Screened subnet (DMZ) = zona entre internet e interno. Firewall rules: allow/deny/port/protocol/IP.

💡 Key Exam Highlights & Critical Concepts

- NGFW = stateful + app + user + threat intelligence
- Screened subnet (DMZ): zona entre a internet e a rede interna

🎯 Exam Tips & Typical CompTIA Scenarios

- 'firewall that inspects traffic at the application layer'=NGFW/WAF

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Next-Generation Firewall (NGFW)

A firewall that adds application awareness, user awareness, integrated threat intelligence, and SSL/TLS inspection beyond traditional stateful filtering.

⚠ **Exam Trap:** Gatilho: 'inspeciona tráfego na camada de aplicação' ou 'identifica aplicativos/usuários' = NGFW. Distinção: WAF é focado em HTTP/HTTPS e ataques web.

• Unified Threat Management (UTM)

An all-in-one security appliance that combines firewall, IDS/IPS, antivirus, VPN, content filtering, and other controls, often for small or medium businesses.

⚠ **Exam Trap:** Gatilho: 'tudo em um' para pequena empresa = UTM. Distinção: NGFW é mais focado em app/user/threat intelligence, não necessariamente um pacote UTM completo.

• Screened Subnet (DMZ)

A network zone between the Internet and the internal network that hosts public-facing services, isolating them from the internal LAN.

⚠ **Exam Trap:** Gatilho: 'zona entre a Internet e a rede interna' ou 'DMZ' = screened subnet. Distinção: não é a LAN interna; é uma área intermediária controlada.

• Stateful Firewall (N/A)

A firewall that tracks active connections using a state table and allows return traffic for established sessions.

⚠ **Exam Trap:** Gatilho: 'lembra do estado da conexão' = stateful. Distinção: não confunda com stateless, que analisa cada pacote isoladamente.

• Stateless Firewall (N/A)

A firewall that filters each packet independently using static rules or ACLs without tracking connection state.

⚠ **Exam Trap:** Gatilho: 'filtragem de pacotes sem estado' ou 'ACL simples' = stateless. Distinção: mais rápido, porém menos seguro que stateful.

• Web Application Firewall (WAF)

A firewall that inspects HTTP/HTTPS traffic to protect web applications from Layer 7 attacks such as SQL injection and XSS.

⚠ **Exam Trap:** Gatilho: ataques a aplicações web / HTTP/HTTPS = WAF. Distinção: se o enunciado fala de camada de aplicação genérica/app-aware, pode ser NGFW.

• SSL/TLS Inspection

The process where a firewall decrypts, inspects, and re-encrypts SSL/TLS traffic to detect threats hidden in encrypted sessions.

⚠ **Exam Trap:** Gatilho: 'inspeção de tráfego criptografado' é recurso do NGFW. Distinção: exige certificado de CA interna e pode gerar preocupações de privacidade.

• Firewall Rules (ACL)

Ordered allow/deny statements that specify source/destination IP, port, protocol, and action, evaluated top-down by the firewall.

⚠ **Exam Trap:** Gatilho: a primeira regra correspondente vence; há regra implícita deny all no final. Distinção: ordem incorreta causa bloqueio ou permissão indevida.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A retail company wants to enforce a policy that only the sales group may use a specific cloud CRM, even though employees also access many other HTTPS sites on TCP 443. The security team must identify traffic by application and by user identity rather than by IP address and port alone. Which type of firewall should they deploy?

- A) Stateless packet-filtering firewall
- B) Web application firewall
- C) Next-generation firewall
- D) Stateful firewall with port-based ACLs

QUESTION 2 · EXAM SCENARIO

A small dental office has one internet connection and a limited IT budget. It needs a single appliance that provides firewall filtering, antivirus scanning, intrusion prevention, and web content filtering. Which solution best fits these requirements?

- A) Next-generation firewall limited to application awareness
- B) Unified threat management appliance
- C) Web application firewall
- D) Screened subnet with a stateful firewall

QUESTION 3 · EXAM SCENARIO

A company hosts an internet-facing web server. Security requirements state that internet users must reach it on TCP 443, but if the server is compromised it must not be able to initiate direct connections to the internal database network. Where should the web server be placed?

- A) On the internal user VLAN
- B) In a screened subnet
- C) In the management VLAN
- D) On the same subnet as the database server

QUESTION 4 · EXAM SCENARIO

Administrators want to allow internal users to initiate HTTPS sessions to internet websites and have the firewall automatically permit the return traffic. They also want the firewall to track active connections and make decisions based on session state. Which firewall behavior should they implement?

- A) Stateless packet filtering
- B) Stateful inspection
- C) Web application filtering
- D) Network address translation only

QUESTION 5 · EXAM SCENARIO

A legacy router ACL permits inbound TCP port 80 to an internal web server. Users can reach the server, but the server's responses are dropped unless an outbound rule is also added. Which firewall type is described?

- A) Stateful inspection firewall
- B) Stateless packet-filtering firewall
- C) Next-generation firewall
- D) Web application firewall

QUESTION 6 · EXAM SCENARIO

An e-commerce site is receiving SQL injection and cross-site scripting attempts in HTTP requests. The security team wants to block these application-layer attacks before they reach the web server. Which control is best suited for this task?

- A) Stateful firewall rule
- B) Web application firewall
- C) SSL/TLS inspection policy
- D) Screened subnet

QUESTION 7 · EXAM SCENARIO

A company's perimeter firewall cannot detect malware inside outbound HTTPS traffic because the payload is encrypted. Security wants the firewall to decrypt, inspect, and then re-encrypt the traffic before it reaches the destination. Which feature should be enabled?

- A) DNSSEC validation
- B) Network address translation
- C) SSL/TLS inspection
- D) Stateless packet filtering

QUESTION 8 · EXAM SCENARIO

A firewall administrator must permit only the accounting subnet 10.20.30.0/24 to reach the payroll server 10.20.40.10 over TCP 443. Which ACL entry follows the principle of least privilege?

- A) permit tcp any any eq 443
- B) permit ip 10.20.30.0 0.0.0.255 any
- C) permit tcp 10.20.30.0 0.0.0.255 host 10.20.40.10 eq 443
- D) deny tcp any any eq 443

QUESTION 9 · EXAM SCENARIO

A firewall has a rule permitting 10.0.0.50 to reach a database on TCP 1521, but the rule was placed after a rule that denies the entire 10.0.0.0/24 subnet. The database administrator reports that the connection is still blocked. What should the administrator do first?

- A) Move the specific permit rule above the subnet deny rule
- B) Change the specific permit rule to permit any any
- C) Disable the subnet deny rule permanently
- D) Add a second deny rule below the permit rule

QUESTION 10 · EXAM SCENARIO

The security team wants the perimeter firewall to automatically block IP addresses and domains from a commercial threat feed without manually editing ACLs every day. Which NGFW capability should be configured?

- A) Threat intelligence feed integration
- B) SSL/TLS inspection
- C) Application-aware policy
- D) User identity awareness

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option C — Next-generation firewall

A next-generation firewall (NGFW) can identify applications regardless of port and can enforce rules based on user or group identity. A stateless or stateful port-based firewall cannot reliably distinguish the CRM from other HTTPS traffic, and a WAF protects web applications rather than enforcing user/application access policy across the network.

Question 2: Option B — Unified threat management appliance

A unified threat management (UTM) appliance combines multiple security functions, such as firewall, antivirus, IPS, and content filtering, in one device, which is appropriate for a small organization with limited budget and staff. NGFW may include some features, but a UTM is specifically positioned as an all-in-one solution; WAF protects web apps, and a screened subnet is an architecture, not an all-in-one security appliance.

Question 3: Option B — In a screened subnet

A screened subnet, often called a DMZ, is a buffer zone between the internet and the internal network. Public-facing servers are placed there, and firewall rules can allow inbound 443 while restricting outbound access from the DMZ to internal systems. Internal VLANs, management VLANs, and the database subnet improperly expose internal resources if the web server is compromised.

Question 4: Option B — Stateful inspection

Stateful inspection maintains a state table of active connections. When an internal user initiates an outbound HTTPS session, the firewall can automatically allow the corresponding return packets without a separate inbound rule. Stateless filtering evaluates each packet independently and would require explicit return rules; WAF and NAT alone do not provide connection-state tracking.

Question 5: Option B — Stateless packet-filtering firewall

A stateless packet-filtering firewall evaluates each packet against static rules and does not track sessions, so return traffic must be explicitly permitted by another ACL entry. Stateful and next-generation firewalls track connections and can allow return traffic automatically; a WAF focuses on HTTP application attacks, not basic packet return behavior.

Question 6: Option B — Web application firewall

A web application firewall (WAF) inspects HTTP/HTTPS requests and can detect and block application-layer attacks such as SQL injection and XSS. A stateful firewall generally enforces network-layer connections, SSL/TLS inspection decrypts traffic for inspection but is not the attack-blocking logic itself, and a screened subnet is a network segmentation design.

Question 7: Option C — SSL/TLS inspection

SSL/TLS inspection allows the firewall to act as a trusted intermediary, decrypting outbound HTTPS traffic, inspecting it for malware or policy violations, and re-encrypting it before forwarding. DNSSEC validates DNS responses, NAT translates addresses, and stateless filtering cannot inspect encrypted application payloads.

Question 8: Option C — permit tcp 10.20.30.0 0.0.0.255 host 10.20.40.10 eq 443

The rule should specify the source subnet, destination host, protocol, and destination port so that only the required traffic is allowed. Permit any any eq 443 allows too much, permit IP from the subnet to any allows all protocols and destinations, and a deny rule alone would not satisfy the requirement.

Question 9: Option A — Move the specific permit rule above the subnet deny rule

Firewall ACLs are typically processed top-down and stop at the first match. If a broad deny for 10.0.0.0/24 appears before the specific permit for 10.0.0.50, the deny wins. The correct fix is to move the specific permit above the broad deny while preserving least privilege. Making the permit any any or disabling the deny rule would create excessive access, and adding another deny rule would not help.

Question 10: Option A — Threat intelligence feed integration

Threat intelligence integration allows an NGFW to consume dynamic feeds of malicious IPs, domains, and URLs and enforce blocks automatically. SSL/TLS inspection decrypts traffic, application-aware policy controls apps, and user identity awareness maps users to policies; none of these alone automatically consumes malicious IP/domain feeds.