

Security+ 4.6 · Password Security

Mestre CyberSec · Lesson 4.6 — Password Security (6:22) · [Assistir Vídeo no YouTube](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Password: COMPRIMENTO > complexidade (14+ é melhor); password manager (gera forte, guarda cifrado); passwordless (FIDO2/YubiKey, biometria, Magic link) = o futuro; NIST: sem troca forçada (incentiva fraca).

💡 Key Exam Highlights & Critical Concepts

- Comprimento > complexidade (14 chars simples > 8 complexos)
- FIDO2/YubiKey = passwordless: a chave física que não pode ser phishing

🎯 Exam Tips & Typical CompTIA Scenarios

- 'length over complexity'=NIST 800-63B guidance

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 4.6 — Password Security)

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• NIST Special Publication 800-63B (NIST 800-63B)

Digital identity guidelines from NIST that recommend prioritizing password length over complexity and discourage forced periodic password rotation, as these practices often lead to weaker, predictable passwords.

 **Exam Trap:** *Se a pergunta mostrar uma política exigindo troca de senha a cada 30/90 dias ou regras de complexidade extremas (caracteres especiais múltiplos), está em CONFLITO com o NIST 800-63B — escolha a alternativa alinhada ao NIST.*

• Password Manager (N/A)

An application that generates, stores, and auto-fills strong, unique, random passwords in an encrypted vault, allowing users to remember only one master password while using complex credentials everywhere.

 **Exam Trap:** *Cenário de prova: 'usuários reutilizam senhas fracas em múltiplos sites' = solução correta é implementar um password manager corporativo, NÃO impor regras de complexidade mais rígidas.*

• FIDO2

An open authentication standard from the FIDO Alliance combining WebAuthn (browser API) and CTAP2 (authenticator protocol) that enables passwordless, phishing-resistant logins using public-key cryptography.

 **Exam Trap:** *Distinguir FIDO2 de MFA comum: FIDO2 é inerentemente resistente a phishing porque a origem (origin) do site é validada criptograficamente — MFA por SMS ou OTP pode ser interceptado via phishing AiTM.*

• YubiKey (Y/A)

A physical hardware security key (USB/NFC) manufactured by Yubico that implements FIDO2/WebAuthn protocols to provide phishing-resistant, passwordless authentication through cryptographic challenge-response.

 **Exam Trap:** *Quando a questão mencionar 'hardware token resistente a phishing' ou a melhor forma de MFA para executivos/admins, pense em YubiKey/FIDO2 — é superior a OTP por SMS, TOTP em app ou push notification.*

• Biometric Authentication (N/A)

Authentication based on unique physical or behavioral characteristics (fingerprint, facial recognition, iris, voice) — a primary passwordless method, but with trade-offs like false acceptance/rejection rates and inability to be 'reset'.

 **Exam Trap:** *Cuidado com a pegadinha clássica: 'Você não pode reresetar uma credencial biométrica se ela for comprometida' — diferentemente de uma senha, um dedo vazado não pode ser trocado.*

• Magic Link (N/A)

A passwordless authentication method where the server emails a single-use, time-limited, signed URL/token to the user; clicking the link authenticates the session — relies entirely on email account security.

 **Exam Trap:** *Magic link NÃO é MFA; é 'something you have' (acesso ao e-mail). Se a conta de e-mail for comprometida, o atacante recebe todos os magic links — diferente de FIDO2 que é resistente a phishing.*

• Account Lockout (N/A)

A brute-force mitigation that disables an account after a threshold of consecutive failed authentication attempts within a defined time window, typically unlocking automatically after a cooldown period.

 **Exam Trap:** *Distinguir de password spraying (que usa poucas senhas em muitas contas — lockout por conta NÃO ajuda). Para password spraying, a defesa correta é rate limiting por IP e bloqueio por IP, não por conta.*

• Dictionary Attack (N/A)

A password attack that iterates through a precompiled list of common words, leaked passwords, and predictable variations (password123, Summer2024!) — defeated by avoiding real words and using random passphrases.

⚠ Exam Trap: Se a questão perguntar POR QUE senhas longas são melhores que complexas curtas: a entropia vem do comprimento. 'HorseBatteryStapleCorrect' tem mais bits de entropia que 'P@ssw0rd!' mesmo sendo 'simples'.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A company's current password policy requires 8-character passwords with three character classes and forces a change every 60 days. Following NIST SP 800-63B, which policy change should the security team recommend?

- A) Require a minimum of 14 characters, remove periodic expiration unless compromise is suspected, and screen new passwords against breached lists.
- B) Keep 60-day expiration but increase the minimum to 10 characters and require four character classes.
- C) Require users to change passwords after every 10 logins to limit credential reuse.
- D) Replace the password policy with mandatory security questions for all account recovery.

QUESTION 2 · EXAM SCENARIO

Employees at a mid-sized firm reuse passwords across cloud services because they must remember many credentials. Management wants to reduce password reuse without increasing helpdesk calls. Which control is most appropriate?

- A) Deploy an enterprise password manager that generates unique passwords and stores them in an encrypted vault.
- B) Enforce a 30-day password expiration policy across all cloud services.
- C) Require users to store passwords in a shared, access-controlled spreadsheet.
- D) Disable multifactor authentication for cloud services to simplify access.

QUESTION 3 · EXAM SCENARIO

A financial services company wants to protect executives from credential phishing. The CISO requests a phishing-resistant authentication method for high-risk users. Which solution best meets this requirement?

- A) SMS-based one-time passcodes.
- B) FIDO2/WebAuthn security keys such as YubiKeys.
- C) Email-based magic links with 24-hour validity.
- D) Time-based one-time passwords stored in a mobile authenticator app.

QUESTION 4 · EXAM SCENARIO

A healthcare provider wants clinicians to authenticate to workstations without typing passwords, while ensuring credentials cannot be shared. Which combination best supports this goal?

- A) Username/password plus TOTP authenticator app.
- B) Shared department YubiKey kept at the nursing station.
- C) FIDO2 authenticator using platform biometrics with WebAuthn.
- D) Magic links sent to a shared clinical email account.

QUESTION 5 · EXAM SCENARIO

The VPN logs show many failed login attempts using common words and variations from a password list. The current policy locks accounts for 30 minutes after five failures. Which additional control best mitigates this dictionary attack while following NIST guidance?

- A) Rate-limit authentication attempts and check passwords against breached and common password lists.
- B) Reduce the lockout threshold to two attempts and require monthly password changes.
- C) Disable account lockout so attackers cannot cause denial of service.
- D) Require passwords to include at least one uppercase letter and one symbol at 8 characters.

QUESTION 6 · EXAM SCENARIO

A software team proposes magic links for customer login to reduce password use. A security architect must approve the design. Which implementation is most appropriate?

- A) Reusable magic link valid for 24 hours to improve user convenience.
- B) Single-use magic link with a short expiration, delivered over TLS, and tied to the requesting session.
- C) Magic link token stored in browser local storage permanently for seamless login.
- D) Magic link sent over HTTP to avoid TLS overhead on the authentication endpoint.

QUESTION 7 · EXAM SCENARIO

An organization enables Windows Hello for Business so users can sign in with a PIN or fingerprint on managed laptops. Which standard provides the underlying phishing-resistant authentication mechanism?

- A) SAML 2.0
- B) OAuth 2.0 implicit grant
- C) LDAP simple bind
- D) FIDO2/WebAuthn

QUESTION 8 · EXAM SCENARIO

A company deploys an enterprise password manager. The vault database is encrypted, but administrators are concerned about an attacker who compromises an endpoint and obtains the encrypted vault. Which control best reduces the risk of vault compromise?

- A) Require a strong master passphrase and enforce MFA for vault unlock.
- B) Configure the vault to use a shared master password for all users to simplify administration.
- C) Store the master password alongside the vault on the endpoint for recovery.
- D) Disable automatic vault locking so users do not need to reauthenticate.

QUESTION 9 · EXAM SCENARIO

During a security review, a manager suggests requiring complex 8-character passwords that expire every 90 days to improve password security. Which recommendation better aligns with current NIST guidance and reduces password-related risk?

- A)** Maintain 8-character complexity rules and add more special character requirements.
- B)** Increase minimum length to at least 14 characters, remove forced periodic expiration, and block commonly breached passwords.
- C)** Require users to rotate passwords every 30 days but allow simpler passwords.
- D)** Store passwords using reversible encryption so they can be audited and recovered.

QUESTION 10 · EXAM SCENARIO

A company wants to move internal applications toward passwordless authentication. Which deployment approach is most appropriate for a large enterprise?

- A)** Pilot FIDO2 security keys or platform biometrics with key applications, register a backup authenticator, then expand and remove passwords as supported.
- B)** Immediately remove all passwords from every application and rely only on email magic links.
- C)** Issue one shared YubiKey per department to reduce hardware costs.
- D)** Use SMS one-time codes as the sole passwordless method for all administrators.

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option A — Require a minimum of 14 characters, remove periodic expiration unless compromise is suspected, and screen new passwords against breached lists.

NIST SP 800-63B emphasizes password length over complex composition, recommends screening against breached/common password lists, and advises against forced periodic expiration because it often leads to weaker, predictable passwords. The other options either keep ineffective rotation/complexity rules or weaken recovery security.

Question 2: Option A — Deploy an enterprise password manager that generates unique passwords and stores them in an encrypted vault.

An enterprise password manager generates strong unique passwords per site, stores them encrypted, and reduces the burden of memorization, which directly lowers reuse. Expiration encourages predictable changes, spreadsheets are not a secure vault, and disabling MFA weakens security.

Question 3: Option B — FIDO2/WebAuthn security keys such as YubiKeys.

FIDO2/WebAuthn security keys use origin-bound public-key cryptography, making them resistant to real-time phishing and credential relay attacks. SMS, TOTP, and email magic links can be phished, relayed, or forwarded.

Question 4: Option C — FIDO2 authenticator using platform biometrics with WebAuthn.

FIDO2 with WebAuthn and platform biometrics provides passwordless, phishing-resistant authentication tied to a user and device. A shared security key or shared email account breaks individual accountability and can be abused.

Question 5: Option A — Rate-limit authentication attempts and check passwords against breached and common password lists.

NIST guidance favors rate limiting, monitoring, and screening passwords against breached/common lists to reduce online guessing success. Aggressive lockout thresholds can create DoS, disabling lockout removes protection, and minimal complexity at 8 characters is weak.

Question 6: Option B — Single-use magic link with a short expiration, delivered over TLS, and tied to the requesting session.

Magic links should be short-lived, single-use, transmitted securely, and bound to the session or device to prevent replay and token theft. Reusable, long-lived, permanently stored, or non-TLS link transmission increases account takeover risk.

Question 7: Option D — FIDO2/WebAuthn

Windows Hello for Business uses FIDO2/WebAuthn concepts and asymmetric key pairs bound to the device and user, providing phishing-resistant passwordless authentication. SAML, OAuth implicit, and LDAP simple bind do not provide the same phishing-resistant device-bound credential model.

Question 8: Option A — Require a strong master passphrase and enforce MFA for vault unlock.

A password manager vault depends on protecting the master secret and unlock process. A strong master passphrase plus MFA makes offline cracking and unauthorized vault unlock much harder. Shared master passwords, storing the master password with the vault, and disabling auto-lock all undermine vault security.

Question 9: Option B — Increase minimum length to at least 14 characters, remove forced periodic expiration, and block commonly breached passwords.

NIST SP 800-63B prioritizes length, breached-password screening, and avoiding forced periodic rotation. Longer passwords/passphrases provide more entropy than short complex strings, and blocking breached passwords prevents known compromised credentials. Reversible encryption and frequent rotation are insecure practices.

Question 10: Option A — Pilot FIDO2 security keys or platform biometrics with key applications, register a backup authenticator, then expand and remove passwords as supported.

A phased passwordless rollout with FIDO2/WebAuthn or platform biometrics allows testing, backup enrollment, and fallback while maintaining usability and security. Immediate removal, shared authenticators, or SMS-only for administrators creates availability, accountability, and phishing risks.

