

Security+ 1.4 · Blockchain Technology

Mestre CyberSec · Lesson 1.4 — Blockchain Technology (2:22) · [Assistir Vídeo no YouTube](#) ↗ · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Blockchain: ledger público distribuído; cada bloco contém hash do anterior — cadeia tamper-evident. Public (Bitcoin — open) vs Private blockchain (permissão controlada). Smart contracts = código executando em cima do ledger.

💡 Key Exam Highlights & Critical Concepts

- Cada bloco contém o hash do ANTERIOR — mudou um, quebrou a cadeia
- Public (Bitcoin — open) vs Private (permissão restricta)

🎯 Exam Tips & Typical CompTIA Scenarios

- 'tamper-evident distributed ledger' = blockchain
- 'each block contains a hash of the previous' = prova de encadeamento

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 1.4 — Blockchain Technology)

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Blockchain (N/A)

A distributed, tamper-evident ledger where data is stored in blocks, each containing the cryptographic hash of the previous block, forming an unbroken chain.

 **Exam Trap:** *CompTIA describes blockchain as a 'tamper-evident distributed ledger' — if a single block is altered, every subsequent block's hash becomes invalid, breaking the chain instantly.*

• Distributed Ledger (DLT)

A decentralized database replicated across multiple participants/nodes, where no single party controls the records and all copies are synchronized via consensus.

 **Exam Trap:** *Recognize 'distributed ledger' as the parent category of blockchain — exam questions may use either term to test the same concept of decentralized, synchronized records.*

• Cryptographic Hash (N/A)

A one-way function (e.g., SHA-256) that produces a fixed-size output from input data; any modification to the input produces a completely different hash value.

 **Exam Trap:** *Each block contains the hash of the PREVIOUS block — this is the linking mechanism that makes blockchain tamper-evident. The exam may ask what makes a blockchain 'immutable'.*

• Public Blockchain (N/A)

An open, permissionless blockchain (e.g., Bitcoin) where anyone can read, submit transactions, and participate in consensus without requiring authorization.

 **Exam Trap:** *Public = open to everyone, no central control, fully transparent. Bitcoin is the canonical exam example — distinguish from private/permissioned chains.*

• Private Blockchain (Permissioned) (N/A)

A restricted blockchain where participation, reading, and validation require explicit permission from a central authority controlling access.

 **Exam Trap:** *Watch the trap: 'private' does NOT mean more secure from a cryptographic standpoint — it means access-controlled. Enterprise/consortium chains use this model.*

• Smart Contract (N/A)

Self-executing code stored on a blockchain that automatically enforces contract terms when predefined conditions are met, without intermediaries.

 **Exam Trap:** *Smart contracts RUN ON TOP of the ledger — they are application logic, not the ledger itself. Exam may test this distinction: blockchain = data layer; smart contract = execution layer.*

• Tamper-Evident (N/A)

A property of blockchain where any modification to a block's data invalidates its hash and breaks the chain of subsequent blocks, making alterations immediately detectable.

 **Exam Trap:** *Memorize the phrase 'tamper-evident' — CompTIA uses it verbatim in exam questions to describe blockchain. It is NOT the same as 'tamper-proof'; changes are detectable, not impossible.*

• Block (N/A)

A data structure in the blockchain that bundles transactions together along with its own timestamp, nonce, and the hash of the preceding block.

⚠ Exam Trap: Every block = (transaction data + previous block's hash + metadata). Change the previous hash and you chain reaction breaks the entire chain from that point forward.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A group of banks wants to share transaction records among known partners. Each partner must be identified, and only approved institutions may validate new entries. They do not want anonymous participants or public mining. Which blockchain deployment model best fits these requirements?

- A) Public permissionless blockchain
- B) Private permissioned blockchain
- C) Centralized database with digital signatures
- D) Smart contract-only architecture without a ledger

QUESTION 2 · EXAM SCENARIO

A healthcare company wants to use a public blockchain to prove that consent forms have not been modified. The forms contain patient names, diagnoses, and treatment details. What should the security architect recommend to protect sensitive data?

- A) Store only cryptographic hashes or pointers on-chain and keep the documents off-chain
- B) Encrypt the private key and place the full patient record in each block
- C) Use shorter block intervals so records are less visible
- D) Rely on the public blockchain's immutability to keep patient data confidential

QUESTION 3 · EXAM SCENARIO

An auditor asks how a blockchain ledger can detect if an attacker changes a transaction in an earlier block. Which blockchain property provides this detection?

- A) Each block contains the cryptographic hash of the previous block
- B) Each block stores all users' private keys
- C) The consensus algorithm deletes duplicate transactions
- D) Smart contracts automatically encrypt every block with TLS

QUESTION 4 · EXAM SCENARIO

A financial technology team is ready to deploy a smart contract that transfers funds based on customer data. The contract code is complex and will be immutable after deployment. Which action best reduces the risk of a logic flaw causing financial loss?

- A) Perform an independent code audit and test the contract on a test network before deployment
- B) Enable multifactor authentication for the developers' email accounts
- C) Rotate the organization's TLS certificates before deployment
- D) Store the smart contract source code in a public repository without review

QUESTION 5 · EXAM SCENARIO

A hospital consortium operates a blockchain where multiple hospitals submit and validate records. The consortium wants only approved hospitals to participate, and it must be able to revoke a hospital's access if its credentials are compromised. Which control should be implemented?

- A) Permissioned membership with identity verification and revocation capabilities
- B) Proof-of-work mining rewards for all participants
- C) Anonymous wallet addresses for each hospital
- D) A smart contract that publishes all patient records to the public chain

QUESTION 6 · EXAM SCENARIO

A smart contract releases payment when an Internet-of-Things sensor reports that a shipment has arrived. Security analysts worry that a compromised sensor could falsely trigger payment. What should be implemented to improve trust in the sensor data before the contract executes?

- A) Validate data through multiple trusted oracles and require corroborating sources
- B) Increase the block size so sensor data is stored faster
- C) Move the smart contract to a public blockchain with anonymous miners
- D) Disable smart contract event logging to reduce data exposure

QUESTION 7 · EXAM SCENARIO

A pharmaceutical distributor wants to use blockchain to track drugs from manufacturer to pharmacy. Management claims this will prove every drug is authentic and eliminate counterfeits. Which statement best describes the security limitation?

- A) Blockchain can provide tamper-evident provenance, but it cannot verify that the physical item entered the chain is authentic
- B) Blockchain automatically scans each package and validates its chemical composition
- C) Blockchain prevents all insider fraud because blocks cannot be altered by any participant
- D) Blockchain encrypts the physical supply chain so counterfeit drugs become unusable

QUESTION 8 · EXAM SCENARIO

After an attacker altered database audit logs to hide unauthorized access, a CISO wants a tamper-evident logging mechanism. Which approach best applies blockchain concepts to protect log integrity?

- A) Write log hashes to an append-only distributed ledger shared by multiple independent parties
- B) Store logs on a single server protected by RAID 6
- C) Encrypt the log server's disk with a single symmetric key
- D) Configure the SIEM to deduplicate repeated log entries

QUESTION 9 · EXAM SCENARIO

An employee loses the private key to a cryptocurrency wallet that holds company funds. The company asks the blockchain network administrator to reset the key and restore access. Which characteristic of public blockchain explains why this is usually not possible?

- A)** Control of assets depends on possession of the private key, and there is no central administrator to reset it
- B)** Public blockchains store private keys in every full node for recovery
- C)** Smart contracts can always reverse transactions after a key loss
- D)** Consensus algorithms automatically reassign lost keys to the organization

QUESTION 10 · EXAM SCENARIO

A consortium of manufacturers needs a shared ledger for warranty claims. Each manufacturer must write records, no single manufacturer is trusted to host the master database, and all participants must see the same validated history. Which solution best meets these requirements?

- A)** A permissioned blockchain with agreed governance and consensus among consortium members
- B)** A public permissionless blockchain with anonymous miners
- C)** A spreadsheet shared through email with manual version control
- D)** A single manufacturer's database with read-only accounts for others

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option B — Private permissioned blockchain

A private permissioned blockchain restricts participation and validation to approved entities, matching the need for known banks and controlled validation without anonymous public miners. A public permissionless blockchain allows anonymous or unknown participants to validate, while a centralized database and a smart-contract-only design do not provide the same shared distributed ledger model.

Question 2: Option A — Store only cryptographic hashes or pointers on-chain and keep the documents off-chain

Public blockchains are transparent and replicated, so sensitive data should not be placed on-chain. A hash or pointer can prove integrity while the actual document remains in a controlled off-chain system. Immutability prevents tampering but does not provide confidentiality.

Question 3: Option A — Each block contains the cryptographic hash of the previous block

Blocks are linked by including the hash of the previous block. If an earlier transaction is altered, its hash changes, which breaks the chain and makes the tampering evident to validating nodes. Private keys are not stored in blocks, and TLS/smart contracts are not the mechanism for chain integrity.

Question 4: Option A — Perform an independent code audit and test the contract on a test network before deployment

Smart contracts execute automatically and may be difficult to change after deployment, so independent review and testnet simulation are key controls to find logic flaws. MFA, certificate rotation, and public posting do not validate contract logic or prevent financial loss.

Question 5: Option A — Permissioned membership with identity verification and revocation capabilities

A permissioned blockchain uses identity and membership controls so only approved organizations can submit or validate transactions, and access can be revoked. Proof-of-work and anonymous addresses do not enforce approved membership, and publishing patient records violates confidentiality.

Question 6: Option A — Validate data through multiple trusted oracles and require corroborating sources

Smart contracts act on the data they receive. If the data source is compromised, the contract may execute incorrectly. Using multiple trusted oracles and corroborating sources helps validate input. Block size, public mining, and disabling logs do not verify sensor truth.

Question 7: Option A — Blockchain can provide tamper-evident provenance, but it cannot verify that the physical item entered the chain is authentic

A blockchain can record and protect the provenance trail, but it depends on accurate data at the point of entry. It cannot independently verify physical authenticity. It also does not scan packages, eliminate insider fraud, or encrypt physical goods.

Question 8: Option A — Write log hashes to an append-only distributed ledger shared by multiple independent parties

An append-only distributed ledger with hash chaining makes it difficult for one party to alter historical logs without detection, because the hash chain and replicated copies expose changes. RAID, disk encryption, and deduplication do not provide tamper-evident, independently verifiable integrity.

Question 9: Option A — Control of assets depends on possession of the private key, and there is no central administrator to reset it

On a public blockchain, ownership and control are exercised through private keys, and no central authority can reset credentials or reverse transactions. Full nodes do not store private keys for recovery, smart contracts generally cannot reverse confirmed transactions, and consensus does not reassign keys.

Question 10: Option A — A permissioned blockchain with agreed governance and consensus among consortium members

A permissioned blockchain allows a known consortium to share a replicated ledger, control write/validate permissions, and use agreed consensus and governance without relying on one trusted central host. A public anonymous chain may be inappropriate for private business data, while email spreadsheets and a single manufacturer's database lack distributed trust and tamper-evident validation.