

Security+ 2.3 · Hardware Vulnerabilities

Mestre CyberSec · Lesson 2.3 — Hardware Vulnerabilities (6:27) · [Assistir Vídeo no YouTube ↗](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Firmware (BIOS/UEFI: a interface hardware-SO) — comprometido é quase invisível. EOL (End of Life) = sem patch, desativar ou segmentar. Legacy device: máquina antiga com vulnerabilidade explorable. Defesa: patch firmware, replace/segmenta EOL, air gap pro crítico.

💡 Key Exam Highlights & Critical Concepts

- Firmware comprometido sobrevive reinstalação do SO
- EOL = sem suporte do fabricante; segmentar/replace

🎯 Exam Tips & Typical CompTIA Scenarios

- 'device cannot receive updates anymore' = EOL risk
- 'compromise persists after OS reinstall' = firmware compromise

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 2.3 — Hardware Vulnerabilities)

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Firmware (N/A)

Software embedded in hardware that controls low-level device operation and boot processes; compromise can persist across OS reinstalls.

 **Exam Trap:** *Se um comprometimento persistir após reinstalar o SO, suspeite de firmware comprometido.*

• BIOS (Basic Input/Output System)

Legacy firmware interface that initializes hardware during boot; outdated versions may have exploitable vulnerabilities.

 **Exam Trap:** *BIOS legado sem atualizações é risco de firmware; verifique suporte do fabricante.*

• UEFI (Unified Extensible Firmware Interface)

Modern firmware interface replacing BIOS; supports Secure Boot and firmware updates, but compromise can bypass OS security.

 **Exam Trap:** *UEFI comprometido pode burlar o Secure Boot e persistir mesmo após reinstalar o SO.*

• End of Life (EOL)

Product stage where the vendor no longer provides patches or security updates, leaving known vulnerabilities unpatched.

 **Exam Trap:** *'device cannot receive updates anymore' indica risco EOL; substitua ou segmente.*

• Legacy Device (N/A)

Older hardware or software no longer supported or updated; often runs insecure protocols and cannot be patched.

 **Exam Trap:** *Dispositivo legado é vulnerabilidade explorável; isole, segmente ou substitua.*

• Air Gap (N/A)

Physical network isolation that separates critical systems from untrusted networks to protect unpatched or EOL devices.

 **Exam Trap:** *Sistemas críticos EOL/sem patch podem exigir air gap ou segmentação rigorosa.*

• Firmware Patch/Update (N/A)

Vendor-provided fix for firmware vulnerabilities; should be applied regularly to BIOS/UEFI and embedded device firmware.

 **Exam Trap:** *Defesa contra vulnerabilidade de firmware é aplicar patch; se não houver, substitua ou segmente.*

• Hardware Vulnerability (N/A)

Weakness in a physical device, firmware, or embedded software that can be exploited, including EOL, legacy, and firmware compromise.

 **Exam Trap:** *Vulnerabilidades de hardware geralmente não são corrigidas apenas por atualizações do SO.*

Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A forensic team finds that a laptop reimaged with a clean OS still connects to an external command-and-control server before any user logs in. The disk was wiped and the OS was reinstalled. Which hardware-level compromise should be suspected?

- A) UEFI/BIOS firmware implant
- B) Malicious browser extension synchronized from a cloud profile
- C) Compromised TPM endorsement key
- D) Failing hard drive with remapped sectors

QUESTION 2 · EXAM SCENARIO

A branch office uses a router whose vendor declared it end-of-life two years ago. A recent scan shows a remotely exploitable management vulnerability, but no firmware update exists. The router must remain in service for six months due to budget constraints. Which compensating control is most appropriate?

- A) Change the default administrator password and continue normal internet exposure.
- B) Enable the router's built-in IDS/IPS signatures and monitor logs.
- C) Encrypt the router's configuration backups and store them offline.
- D) Disable remote management from the internet and place the router on an isolated management VLAN with strict ACLs.

QUESTION 3 · EXAM SCENARIO

A manufacturing plant runs a legacy Windows XP workstation to configure a computer-controlled milling machine. The vendor will not support upgrading the OS, and the machine cannot be patched. Which strategy best reduces risk while maintaining operation?

- A) Deploy next-generation antivirus and enable automatic updates.
- B) Join the workstation to the corporate domain for centralized patching.
- C) Isolate the workstation with strict segmentation or an air gap and allow only required industrial protocols.
- D) Replace the workstation with a modern laptop but keep the same network access.

QUESTION 4 · EXAM SCENARIO

An administrator must update UEFI firmware on 200 production servers to fix a privilege escalation flaw. The vendor provides a download and a detached signature. Which practice best ensures the update is authentic and has not been modified?

- A) Install the update from a mirrored third-party site if the vendor download is slow.
- B) Disable Secure Boot before applying the update to avoid signature errors.
- C) Run the update during business hours so rollback is easier.
- D) Verify the firmware image's digital signature against the vendor's trusted public key before installation.

QUESTION 5 · EXAM SCENARIO

An attacker with brief physical access to a kiosk PC replaces the legitimate bootloader with a malicious one. The OS disk is encrypted, but the PC still starts the malicious bootloader. Which UEFI feature is designed to prevent this?

- A) TPM password
- B) Secure Boot
- C) Self-encrypting drive (SED)
- D) UEFI network stack

QUESTION 6 · EXAM SCENARIO

A company suspects employees can bypass endpoint controls by rebooting laptops and booting from Linux USB drives. Which firmware-level control most directly mitigates this risk?

- A) Enable full-disk encryption on the internal drive.
- B) Install endpoint detection and response software in the OS.
- C) Enable a screen lock timeout.
- D) Set a UEFI/BIOS administrator password and disable booting from external media.

QUESTION 7 · EXAM SCENARIO

A vulnerability scanner reports that a network switch model is no longer supported by its manufacturer, and no new firmware security fixes will be issued. The device is still functional but outdated. How should this device be classified?

- A) Zero-day vulnerability
- B) End-of-life (EOL) device
- C) Supply chain compromise
- D) Misconfigured firewall

QUESTION 8 · EXAM SCENARIO

A hospital's MRI workstation runs an unsupported OS and cannot be patched because the vendor forbids modifications. The workstation must communicate only with the MRI scanner and one image archive server. Which control best limits exploitability from the corporate network?

- A) Install antivirus and enable automatic updates on the workstation.
- B) Connect it to the corporate network but use a strong password.
- C) Place it on an isolated VLAN with firewall rules allowing only required traffic to the scanner and archive server.
- D) Replace the MRI workstation with a personal tablet for viewing images.

QUESTION 9 · EXAM SCENARIO

A security analyst learns that an attacker exploited an old UEFI firmware version on a server. The attacker then downgraded the firmware to the vulnerable version after a reboot. Which control best prevents unauthorized firmware downgrades?

- A) Enable full-disk encryption with a TPM.
- B) Enable firmware rollback protection and signed firmware updates in UEFI settings.
- C) Disable unused USB ports.
- D) Implement a host-based intrusion prevention system.

QUESTION 10 · EXAM SCENARIO

A company has an end-of-life VPN concentrator that terminates remote access for employees. The vendor no longer provides firmware patches, and a critical vulnerability was announced. The device cannot be replaced for 90 days. Which action best addresses the vulnerability during the 90-day window?

- A)** Continue normal operation and rely on employee laptop antivirus.
- B)** Install a software firewall on the VPN concentrator.
- C)** Move the concentrator to the DMZ and enable default logging.
- D)** Restrict VPN access to essential users, monitor for exploitation, and accelerate replacement.

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option A — UEFI/BIOS firmware implant

A UEFI/BIOS firmware implant can persist across OS reinstalls and disk wipes because firmware executes before the operating system. Browser extensions would not survive a clean OS install, a TPM endorsement key does not cause outbound C2 traffic, and bad sectors do not explain pre-login network connections. The correct response includes reflashing or updating firmware from a trusted source and verifying signatures.

Question 2: Option D — Disable remote management from the internet and place the router on an isolated management VLAN with strict ACLs.

For an end-of-life device with an unpatchable remote management vulnerability, the best compensating control is to reduce exposure by disabling internet-facing management and isolating the device behind strict access controls. Changing a password alone is insufficient, built-in signatures may be outdated or unsupported, and encrypting backups does not protect the live vulnerable service.

Question 3: Option C — Isolate the workstation with strict segmentation or an air gap and allow only required industrial protocols.

Because the legacy system cannot be patched or upgraded, isolating it from general corporate and internet traffic is the strongest practical control. This limits lateral movement and exploit exposure while preserving required industrial communication. Antivirus and centralized patching may not be supported or effective on the legacy OS, and replacing the workstation while preserving broad network access does not address the legacy network risk.

Question 4: Option D — Verify the firmware image's digital signature against the vendor's trusted public key before installation.

Firmware updates must be verified against a trusted vendor signature to prevent installation of tampered or malicious firmware. Third-party mirrors are risky, disabling Secure Boot weakens boot integrity and is usually unnecessary for a properly signed update, and business-hours timing affects availability, not authenticity.

Question 5: Option B — Secure Boot

Secure Boot validates the digital signatures of bootloaders and early boot components, blocking unauthorized bootloaders from running. A TPM password may protect keys but does not by itself validate a bootloader, an SED encrypts data but does not prevent bootloader replacement, and the UEFI network stack enables network boot functions rather than boot integrity.

Question 6: Option D — Set a UEFI/BIOS administrator password and disable booting from external media.

Disabling external boot options and protecting firmware settings with an administrator password directly prevents users from booting an unauthorized OS from USB. Full-disk encryption protects data at rest but does not stop another OS from booting, EDR runs only after the OS starts, and screen lock timeout is unrelated to boot control.

Question 7: Option B — End-of-life (EOL) device

An end-of-life device is one for which the vendor no longer provides support, including firmware security updates. This makes known vulnerabilities effectively unpatchable. A zero-day is an unknown exploited vulnerability, supply chain compromise involves a trusted supplier or component being compromised, and firewall misconfiguration is a configuration issue rather than a device lifecycle status.

Question 8: Option C — Place it on an isolated VLAN with firewall rules allowing only required traffic to the scanner and archive server.

Network isolation with strict firewall rules limits the legacy workstation to only required communications, reducing exposure to corporate network threats. Antivirus and automatic updates may not be supported or permitted, a strong password does not compensate for an unpatchable system, and a personal tablet is not an appropriate or compatible medical device control.

Question 9: Option B — Enable firmware rollback protection and signed firmware updates in UEFI settings.

Firmware rollback protection prevents installation of older, known-vulnerable firmware versions, while signed firmware updates ensure only vendor-authorized images can be installed. Full-disk encryption protects data at rest, disabling USB ports only reduces one physical vector, and HIPS operates at the OS level and cannot reliably block firmware downgrades.

Question 10: Option D — Restrict VPN access to essential users, monitor for exploitation, and accelerate replacement.

Because the end-of-life VPN concentrator cannot be patched, the best interim action is to reduce exposure and impact while replacing it as quickly as possible. Limiting access, increasing monitoring, and expediting replacement are practical compensating controls. Relying on endpoint antivirus, installing unsupported software, or only moving the device and enabling default logging does not sufficiently address the unpatchable critical vulnerability.