

Security+ 2.3 · Misconfiguration

Mestre CyberSec · Lesson 2.3 — Misconfiguration (7:09) · [Assistir Vídeo no YouTube](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Configurar errado é a falha mais comum de TODAS: senha default, porta aberta que não devia, permissão de bucket, debug mode em produção, TLS fraco, IAM permissivo. Defesa: baseline secure (CIS benchmark), CSPM automation, revisão de config antes de deploy.

💡 Key Exam Highlights & Critical Concepts

- Senha default / porta aberta / permissão generosa = as failures nº1
- Defesa: baseline + automatização (CIS benchmarks, CSPM)

🎯 Exam Tips & Typical CompTIA Scenarios

- 'most common vulnerability is human configuration error' = misconfiguration

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 2.3 — Misconfiguration)

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Misconfiguration (N/A)

A security weakness caused by improper or insecure system, application, cloud, or network settings, often due to human error or default configurations. CompTIA emphasizes it as the most common vulnerability category.

 **Exam Trap:** Se a questão citar 'erro humano', 'padrão inseguro', 'senha default' ou 'configuração deixada como veio', marque *misconfiguration*. Não confunda com vulnerabilidade de software (bug) ou zero-day.

• Default Credentials (N/A)

Preconfigured usernames and passwords provided by a vendor or device that have not been changed. They are a classic misconfiguration allowing trivial unauthorized access.

 **Exam Trap:** Palavras como 'admin/admin', 'root/toor', 'senha de fábrica' ou 'nunca alterada' indicam *default credentials*. A correção é trocar antes da implantação e usar gerenciamento de senhas.

• Open Ports and Services (N/A)

Network ports or services left listening and reachable when not required, expanding the attack surface. Misconfigured firewalls or unintended services often expose them.

 **Exam Trap:** Se a questão mencionar 'porta 3389 exposta', 'serviço desnecessário' ou 'firewall permissivo', pense em *open ports/services*. A defesa é fechar portas, desabilitar serviços e revisar regras.

• Open Permissions (IAM)

Access control settings that grant broader access than necessary, such as public cloud storage buckets or overly permissive identity and access management roles. This violates least privilege.

 **Exam Trap:** Palavras como 'bucket público', 'S3 exposto', 'role com *', 'permissão generosa' indicam *open permissions*. A correção é aplicar *least privilege* e revisar ACLs/políticas.

• Debug Mode / Verbose Errors (N/A)

A development setting left enabled in production that reveals stack traces, configuration details, or sensitive data to users. It can expose credentials, paths, and internal logic.

 **Exam Trap:** Se a questão citar 'mensagens de erro detalhadas', 'stack trace' ou 'debug ativo em produção', marque *debug mode/verbose errors*. A defesa é desabilitar debug e usar mensagens genéricas.

• Weak TLS / Unsecure Protocols

Use of deprecated protocols, weak cipher suites, or improper TLS configurations that allow interception or downgrade attacks. Examples include SSLv3, TLS 1.0, and weak ciphers.

 **Exam Trap:** Se a questão mencionar 'SSL', 'TLS 1.0', 'cifra fraca' ou 'protocolo legado', é *configuração criptográfica insegura*. A defesa é desabilitar versões antigas e usar TLS 1.2/1.3 com cifras fortes.

• Secure Baseline (CIS)

A documented set of minimum secure configuration settings applied to systems, often based on CIS Benchmarks. It provides a repeatable standard to prevent misconfigurations.

 **Exam Trap:** Se a questão pedir a melhor defesa contra *misconfiguration*, procure 'secure baseline' ou 'CIS Benchmarks'. Não é apenas uma política; é configuração técnica verificável.

• Cloud Security Posture Management (CSPM)

Automated tools that continuously assess cloud configurations against baselines and compliance standards to detect and remediate misconfigurations. It helps identify public buckets, open ports, and permissive IAM.

⚠ Exam Trap: Se a questão citar 'nuvem', 'configuração contínua', 'automação de conformidade' ou 'detectar bucket público', a resposta provável é CSPM. Diferente de CASB, que foca acesso a SaaS, e de CWPP, que protege workloads.

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A security analyst scans an internal subnet and finds a network management appliance that exposes a web login page. The appliance is reachable from the entire user VLAN, and its administrator account still uses the credentials printed in the vendor's installation guide. Which misconfiguration is most directly responsible for the unauthorized access risk?

- A) Weak TLS cipher suites
- B) Verbose debug errors
- C) Default credentials
- D) Overly permissive IAM role

QUESTION 2 · EXAM SCENARIO

A company deploys a new e-commerce server. A cloud security review shows that the MySQL service on TCP 3306 is reachable from 0.0.0.0/0 because the security group allows all inbound traffic. Which misconfiguration should be corrected first?

- A) Default credentials
- B) Open ports and services
- C) Debug mode enabled
- D) Permissive IAM policy

QUESTION 3 · EXAM SCENARIO

A cloud engineer creates an object storage bucket for financial reports. A penetration tester later downloads the reports without authentication and reports that the bucket policy grants s3:GetObject to everyone. Which misconfiguration category does this represent?

- A) Weak TLS protocols
- B) Unpatched operating system
- C) Enabled debug mode
- D) Open permissions

QUESTION 4 · EXAM SCENARIO

Users of an internal application report that when they submit invalid input, the web page returns a full stack trace including database connection strings and internal file paths. Which configuration issue should the security team address?

- A) Default administrative credentials
- B) Open database port to the internet
- C) Debug mode or verbose error reporting enabled
- D) Weak TLS cipher suites

QUESTION 5 · EXAM SCENARIO

A legacy web service is configured to accept TLS 1.0 and RC4 because the vendor has not updated the application. An auditor flags this as a finding. Which remediation best addresses the misconfiguration?

- A) Enable verbose logging for all TLS handshakes
- B) Disable weak protocols and cipher suites, then require TLS 1.2 or higher
- C) Rotate the service account password every 90 days
- D) Move the service to a public subnet with a WAF

QUESTION 6 · EXAM SCENARIO

A company is standardizing new Linux server builds. Administrators currently install a generic image, leave several unnecessary services enabled, and use inconsistent password settings. Management wants a repeatable, industry-recognized hardening checklist before deployment. Which approach should be used?

- A) Enable a web application firewall in monitoring mode
- B) Configure a SIEM correlation rule for failed logins
- C) Deploy endpoint detection and response to all servers
- D) Apply a secure baseline such as CIS Benchmarks

QUESTION 7 · EXAM SCENARIO

A multinational enterprise has hundreds of cloud accounts across two providers. The security team needs continuous, automated visibility into publicly exposed storage, unrestricted security groups, and unencrypted volumes, with alerts when new resources violate policy. Which solution best fits this requirement?

- A) Host-based intrusion prevention system
- B) Cloud Security Posture Management (CSPM)
- C) Web application firewall
- D) File integrity monitoring

QUESTION 8 · EXAM SCENARIO

A DevOps team uses Terraform to provision AWS infrastructure. Security wants to catch public S3 buckets and overly open security groups before the infrastructure is created, without waiting for a post-deployment scan. What should be integrated into the CI/CD pipeline?

- A) Runtime cloud workload protection
- B) Security information and event management
- C) Endpoint detection and response
- D) Infrastructure as Code (IaC) security scanning with policy checks

QUESTION 9 · EXAM SCENARIO

A serverless function runs in a cloud account. Its execution role allows Action: "*" on Resource: "*" because a developer used a quick-start template and never changed it. Which misconfiguration should be remediated?

- A) Weak TLS version
- B) Default application credentials
- C) Overly permissive IAM permissions
- D) Public object storage bucket

QUESTION 10 · EXAM SCENARIO

A cloud VM runs an in-memory data store on TCP 6379. The security group allows inbound traffic from any IP, and the service has no authentication enabled. Attackers connect and write unauthorized entries. Which misconfiguration is the primary cause?

- A) Verbose debug messages
- B) Open service port with no authentication
- C) Default operating system account
- D) Weak cipher suite in the web server

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option C — Default credentials

The risk is caused by unchanged vendor-supplied administrator credentials. Default credentials are a common misconfiguration because attackers can look up documented usernames and passwords. The other issues may be risks, but they are not the direct cause described here.

Question 2: Option B — Open ports and services

The database service is exposed to the internet through an overly broad security group rule, which is an open ports/services misconfiguration. The immediate fix is to restrict the rule to required sources and remove unnecessary exposure. Default credentials, debug mode, and IAM policies are separate misconfiguration categories.

Question 3: Option D — Open permissions

The bucket policy allows unauthenticated public read access, which is an open permissions misconfiguration. Cloud storage permissions should follow least privilege and be reviewed continuously. Weak TLS, patching, and debug mode are different issues.

Question 4: Option C — Debug mode or verbose error reporting enabled

Detailed stack traces and connection strings in responses indicate debug mode or verbose error reporting is enabled in production. This leaks sensitive implementation details to attackers. The fix is to disable debug output and return generic error messages.

Question 5: Option B — Disable weak protocols and cipher suites, then require TLS 1.2 or higher

TLS 1.0 and RC4 are deprecated and weak. The correct remediation is to disable them and enforce modern TLS versions and strong cipher suites. Logging, password rotation, and WAF placement do not fix weak TLS configuration.

Question 6: Option D — Apply a secure baseline such as CIS Benchmarks

A secure baseline like CIS Benchmarks provides a repeatable, industry-recognized set of hardening settings for operating systems and services. It addresses unnecessary services, password policy, and other configuration items before deployment. WAF, SIEM, and EDR are valuable but do not replace secure baseline configuration.

Question 7: Option B — Cloud Security Posture Management (CSPM)

CSPM tools continuously assess cloud configurations against policies and benchmarks, detecting issues such as public storage, open security groups, and missing encryption. HIPS, WAF, and FIM address different layers and do not provide broad multi-cloud configuration posture management.

Question 8: Option D — Infrastructure as Code (IaC) security scanning with policy checks

IaC scanning analyzes templates such as Terraform before deployment and can fail the pipeline when resources violate security policies. This shifts misconfiguration detection left, before resources are created. Runtime, SIEM, and EDR are not pre-deployment IaC controls.

Question 9: Option C — Overly permissive IAM permissions

The role grants full administrative permissions to the function, violating least privilege. Overly permissive IAM policies are a common cloud misconfiguration. The fix is to scope actions and resources to only what the function requires. Weak TLS, default credentials, and public buckets are distinct issues.

Question 10: Option B — Open service port with no authentication

The data store is exposed to the internet on an open port and lacks authentication, which is an open ports/services misconfiguration. The fix is to restrict network access and enable authentication. Debug messages, default OS accounts, and web server ciphers are not the primary cause described.