

# Security+ 4.5 · Operating System Security

Mestre CyberSec · Lesson 4.5 — Operating System Security (3:22) · [Assistir Vídeo no YouTube ↗](#) · Treino Interativo: [edusouzamarques.github.io/cybersec](https://edusouzamarques.github.io/cybersec)

**Executive Lesson Summary:** AD (Active Directory: contas/group/GPO do Windows); Group Policy (deploy de política em massa); SELinux (MAC no Linux — cada processo só o que precisa); patch baseline; disable contas orfãs.

## 💡 Key Exam Highlights & Critical Concepts

- Active Directory: o diretório corporativo Windows
- SELinux: MAC no Linux (mais rigoroso que root)

## 🎯 Exam Tips & Typical CompTIA Scenarios

- 'centralized identity management in Windows'=Active Directory

## Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 4.5 — Operating System Security)

**Why is this advanced coverage required for SY0-701?** Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

### • Active Directory (AD)

Microsoft's centralized directory service that manages users, groups, computers, and resources in a Windows domain environment through a hierarchical database.

 **Exam Trap:** If the question mentions 'centralized identity management in Windows' or 'single sign-on for corporate resources' — the answer is Active Directory. Do NOT confuse with LDAP, which is only the protocol AD uses.

### • Group Policy Object (GPO)

A collection of security and configuration settings that can be applied en masse to users and computers within an Active Directory domain.

 **Exam Trap:** Exam trigger: 'deploy password policies or restrictions to many machines in a Windows domain' = GPO. GPO works ONLY with AD — without AD, there is no GPO.

### • Security-Enhanced Linux (SELinux)

A Linux kernel security module that implements Mandatory Access Control (MAC), restricting every process to only the minimum permissions it requires.

 **Exam Trap:** Exam trigger: 'MAC on Linux' or 'process-level least privilege beyond root' = SELinux. Do NOT confuse with AppArmor (also Linux MAC, but different framework — Debian/Ubuntu default).

### • Mandatory Access Control (MAC)

An access control model where the operating system enforces permissions based on labels and security policies — the user cannot change permissions, even as root.

 **Exam Trap:** MAC vs DAC: in DAC the owner decides; in MAC the OS/admin policy decides. SELinux = MAC, NTFS permissions = DAC. Exam always tests this distinction.

### • Patch Baseline (N/A)

A documented set of approved updates and configuration standards that defines the minimum security posture all systems must meet before going into production.

 **Exam Trap:** Exam trigger: 'minimum configuration standard for new systems' or 'reference point for vulnerability scanning' = patch baseline. Often paired with CIS/NIST benchmarks on the exam.

### • Orphaned Account (N/A)

An unused user account that remains active after the employee has left the organization, creating a security risk if compromised by attackers.

 **Exam Trap:** Exam answer is ALWAYS 'disable or remove'. Never leave orphaned accounts active. Triggers: 'former employee', 'unused account', 'access review' — best practice is disable first, then delete.

### • Discretionary Access Control (DAC)

An access control model where the resource owner decides who has permissions — standard model used in Linux/Windows basic file permissions and NTFS.

 **Exam Trap:** Trigger: 'owner controls permissions' = DAC. NTFS permissions and chmod are DAC. If the question mentions 'the system enforces permissions regardless of owner' — that's MAC.

### • Lightweight Directory Access Protocol (LDAP)

A protocol used to query and manage directory services, such as Active Directory, for centralized authentication and resource lookups.

**⚠ Exam Trap:** LDAP is the protocol; Active Directory is the directory service that USES LDAP. Secure version = LDAPS (port 636). Do not answer 'AD' when the question specifically asks about the protocol.

## ✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

### QUESTION 1 · EXAM SCENARIO

During a quarterly access review at a hospital, the security team discovers 14 Active Directory user accounts belonging to contractors whose contracts ended more than 90 days ago. The accounts are still enabled and remain members of privileged groups. Management wants to reduce identity-related risk immediately. Which action should the security team take FIRST?

- A) Reset the account passwords and require multifactor authentication at next sign-in.
- B) Disable the accounts, remove their privileged group memberships, and preserve them for audit retention according to policy.
- C) Convert the accounts to shared service accounts for the department's administrative tasks.
- D) Move the accounts to a new OU and apply a GPO that hides them from the address list.

### QUESTION 2 · EXAM SCENARIO

A company with 1,200 Windows workstations must enforce a 10-minute inactivity screen lock and a 12-character password requirement for all domain users. Administrators want the settings applied consistently and automatically, including to new computers. Which solution BEST meets the requirement?

- A) Configure the Local Security Policy on each workstation during imaging only.
- B) Deploy a logon script that changes the registry on each user's first logon.
- C) Enable SELinux enforcing mode on the domain controllers.
- D) Create and link a Group Policy Object to the domain or appropriate OUs.

### QUESTION 3 · EXAM SCENARIO

A Linux web server hosts several public sites. After a vulnerability in the web service is disclosed, the security team wants to limit the damage if the service is exploited, so that the httpd process can access only its web content and required network ports, even if an attacker gains code execution. Which security control BEST addresses this requirement?

- A) Configure SELinux in enforcing mode with a targeted policy and correct file contexts/booleans.
- B) Set the web content directory permissions to 777 so the process does not fail.
- C) Implement discretionary access control by making the web service account the owner of all files.
- D) Use iptables to allow only inbound TCP 80 and 443 to the server.

#### QUESTION 4 · EXAM SCENARIO

An organization has 300 Windows servers. Patching is inconsistent: some servers install updates automatically, others are months behind, and administrators manually approve updates differently per team. Auditors require a standardized list of approved patches and a repeatable deployment process. Which action BEST establishes a patch baseline?

- A) Enable automatic updates on every server and let each administrator reboot when convenient.
- B) Create a GPO that disables Windows Update on all servers to prevent unapproved patches.
- C) Define an approved patch baseline in a central management platform and deploy it to server groups on a schedule.
- D) Run a weekly script that downloads all available updates and installs them without testing.

#### QUESTION 5 · EXAM SCENARIO

A finance department uses a shared folder on a Windows file server. Currently, each finance employee is added individually to the folder ACL, and when someone changes roles, permissions are often left behind. The security team wants to simplify administration and enforce least privilege based on job role. What should they do?

- A) Create an AD security group for finance, assign folder permissions to the group, and manage user membership.
- B) Create an AD distribution group for finance and assign folder permissions to the group.
- C) Place all finance users in the Domain Admins group and then remove their individual ACL entries.
- D) Configure a GPO that maps the shared folder for all authenticated users.

#### QUESTION 6 · EXAM SCENARIO

A custom HR application needs to authenticate employees against the company's Active Directory. Security policy prohibits storing employee passwords in the application database and requires centralized account disablement to take effect immediately. Which integration approach BEST meets these requirements?

- A) Create local application accounts and synchronize passwords nightly from Active Directory.
- B) Store password hashes from Active Directory in a flat file accessible to the application.
- C) Require users to sign in with a shared application account managed by the HR team.
- D) Configure the application to authenticate users through LDAP(S) queries/binds to Active Directory.

#### QUESTION 7 · EXAM SCENARIO

A company wants to block USB mass storage devices on computers used by the finance department but allow USB keyboards and mice. The finance computers are in a dedicated OU, and the company uses Windows domain-joined systems. Which method is MOST efficient and enforceable?

- A) Physically glue all USB ports on finance computers.
- B) Create a GPO linked to the finance OU that disables removable storage access.
- C) Apply a local security policy on each finance computer and ask users not to plug in drives.
- D) Configure SELinux booleans on the finance workstations to deny USB storage.

#### QUESTION 8 · EXAM SCENARIO

On a Linux server, developers own files in a shared project directory. Security discovers that a developer can change permissions on a sensitive file and grant read access to other users, even though the file contains regulated data. The security team wants the operating system to enforce access rules that file owners cannot override. Which control BEST provides this?

- A) Standard UNIX discretionary access control permissions.
- B) Access control lists that grant the developer ownership.
- C) A SELinux mandatory access control policy.
- D) A sudoers rule allowing developers to manage file permissions.

#### QUESTION 9 · EXAM SCENARIO

An audit of a Linux application server finds a local service account named appsvc. The application it supported was decommissioned six months ago, but the account still has a valid password, an SSH authorized key, and a Bash shell. Which action should the administrator take to reduce risk?

- A) Change the password and store it in the team's password vault for future use.
- B) Add the account to the sudoers file so future administrators can troubleshoot it.
- C) Change the account's UID and leave its files unchanged.
- D) Lock the account, remove its SSH keys, set the shell to nologin, and delete it if no dependency exists.

#### QUESTION 10 · EXAM SCENARIO

A critical manufacturing server runs a vendor-certified application. The vendor has not certified the latest security update, but the organization's patch baseline requires it. The server cannot be taken offline for testing this quarter. What should the security team do?

- A) Document a time-limited exception, apply compensating controls, and track the server in a separate patch group until vendor certification.
- B) Remove the server from all patching and monitoring because it cannot be updated.
- C) Apply the update immediately without testing and accept any application outage.
- D) Disable the server's firewall so the vendor can remotely apply an unapproved patch.

## ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

### **Question 1: Option B — Disable the accounts, remove their privileged group memberships, and preserve them for audit retention according to policy.**

Correct: Orphaned accounts are a major risk because they remain enabled and privileged after the user should no longer have access. The first action is to disable them and remove privileged group memberships while preserving them only as required for audit retention. Resetting passwords leaves the accounts enabled; converting them to shared service accounts creates accountability problems; hiding them from the address list does not remove access.

### **Question 2: Option D — Create and link a Group Policy Object to the domain or appropriate OUs.**

Correct: Group Policy Objects centrally deploy and enforce Windows security settings across domain-joined systems and can apply to new computers placed in the linked domain or OU. Local Security Policy affects only the local machine and may not cover new systems reliably; logon scripts are less reliable and are not true security policy; SELinux is a Linux mandatory access control mechanism, not a Windows AD policy tool.

### **Question 3: Option A — Configure SELinux in enforcing mode with a targeted policy and correct file contexts/booleans.**

Correct: SELinux is a Linux mandatory access control system that confines processes such as httpd to declared types/domains and limits what they can access even after compromise. Setting permissions to 777 increases risk; making the service account owner is still discretionary access control and too broad; iptables filters network traffic but does not confine a compromised process's file and process access.

### **Question 4: Option C — Define an approved patch baseline in a central management platform and deploy it to server groups on a schedule.**

Correct: A patch baseline is a documented set of approved patches and configuration used by central management to deploy updates consistently. Automatic updates per server cause inconsistency; disabling Windows Update prevents security fixes; installing all updates without testing violates change control and can disrupt services.

### **Question 5: Option A — Create an AD security group for finance, assign folder permissions to the group, and manage user membership.**

Correct: AD security groups are designed for permission assignment and simplify role-based access control. Distribution groups are for email and cannot be used for security permissions; Domain Admins grants excessive privilege; mapping the folder for all authenticated users grants overly broad access.

### **Question 6: Option D — Configure the application to authenticate users through LDAP(S) queries/binds to Active Directory.**

Correct: LDAP(S) allows the application to query and bind to Active Directory for authentication without storing employee passwords. Nightly password synchronization delays centralized disablement and stores credentials; storing password hashes is insecure; a shared application account breaks accountability and does not enforce immediate centralized disablement per user.

### **Question 7: Option B — Create a GPO linked to the finance OU that disables removable storage access.**

Correct: A GPO linked to the finance OU centrally enforces device restrictions for all current and future computers in that OU. Physically gluing ports is impractical and affects all USB devices; local policy is not centrally enforced; SELinux is a Linux control, not a Windows domain workstation policy mechanism.

### **Question 8: Option C — A SELinux mandatory access control policy.**

Correct: SELinux mandatory access control enforces policy independently of file ownership and DAC, so even an owner cannot override SELinux denials. Standard UNIX permissions and ACLs are discretionary access controls; a sudoers rule increases the developer's ability to change permissions.

### **Question 9: Option D — Lock the account, remove its SSH keys, set the shell to nologin, and delete it if no dependency exists.**

Correct: This is an orphaned local account with active credentials. Best practice is to remove access by locking it, removing SSH keys, setting a non-interactive shell, and deleting it if no dependency exists. Keeping the password, adding sudo privileges, or changing the UID leaves access paths and violates least privilege.

**Question 10: Option A — Document a time-limited exception, apply compensating controls, and track the server in a separate patch group until vendor certification.**

Correct: When a patch baseline cannot be applied, formal exception management with compensating controls and tracking is appropriate until the vendor certifies the update. Removing patching and monitoring increases risk; applying an untested update may disrupt critical manufacturing; disabling the firewall is unsafe.