

Security+ 4.6 · Multifactor Authentication

Mestre CyberSec · Lesson 4.6 — Multifactor Authentication (4:29) · [Assistir Vídeo no YouTube](#) · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: MFA: 2+-fatores de CATEGORIA DIFERENTE: sabe (senha/PIN); tem (token, celular, FIDO2); é (biometria); sei (location). Senha+PIN não conta (mesma categoria).

💡 Key Exam Highlights & Critical Concepts

- MFA: fatores de TIPO DIFERENTE — saber/ter/ser
- Senha + PIN = MESMA categoria ('sabe') — NÃO é MFA
- TOTP: código de 6 dígitos que muda a cada 30s

🎯 Exam Tips & Typical CompTIA Scenarios

- 'combines something you know with something you have'=proper MFA

Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 4.6 — Multifactor Authentication)

Why is this advanced coverage required for SY0-701? Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Multifactor Authentication (MFA)

Authentication requiring two or more factors from DIFFERENT categories (something you know, have, are, or somewhere you are). Provides significantly stronger identity verification than single-factor authentication.

 **Exam Trap:** *SENHA + PIN = mesma categoria ('sabe') → NÃO é MFA (pegadinha clássica). Se a questão diz 'combines something you know with something you have', isso É MFA verdadeiro.*

• Something You Know

Authentication factor based on memorized information: password, PIN, security question answers, or a passphrase.

 **Exam Trap:** *Password E PIN pertencem ao MESMO fator — usar os dois juntos é single-factor e a prova adora esse trap. Este fator é o mais vulnerável a shoulder surfing, sniffing e social engineering.*

• Something You Have

Authentication factor based on physical or digital possession: smart card, hardware token, TOTP app on a mobile phone, or FIDO2 security key.

 **Exam Trap:** *Senhas + qualquer 'have' (token, celular, smart card) = MFA correto. Um código TOTP recebido no celular conta como 'tem'. Combina com 'know' nas perguntas de cenário.*

• Something You Are

Biometric factor based on unique physical characteristics: fingerprint, facial recognition, iris scan, retina scan, or voice print.

 **Exam Trap:** *Biometria ('are') NÃO é 'have'. Digital + senha = MFA válido. Biometria não pode ser trocada se comprometida e levanta questões de privacidade e volume de dados.*

• Somewhere You Are

Location-based authentication factor using geolocation/GPS or IP address to grant or deny access based on the user's physical location.

 **Exam Trap:** *Questão citando restrição de acesso por país/região/IP → fator 'somewhere you are'. É uma categoria válida para MFA quando combinada com outro fator de categoria diferente.*

• Something You Do

Behavior-based factor analyzing personal patterns: typing cadence, swipe/screen unlock pattern, gait, or mouse movement.

 **Exam Trap:** *Padrão de digitação = 'algo que você faz' (comportamento), diferente de 'algo que você é' (biometria estática) e de 'algo que você sabe' (conteúdo da senha). Distinção fina cobrada na prova.*

• Time-based One-Time Password (TOTP)

One-time password generated by an app or hardware token from a shared secret plus the current time; produces a 6-digit code that changes every 30 seconds.

 **Exam Trap:** *'Código de 6 dígitos que expira a cada 30 s' = TOTP. Diferença-chave: HOTP é baseado em contador (válido até ser usado), TOTP é baseado em tempo (expira). TOTP conta como fator 'have'.*

• Hardware Security Key (FIDO2)

Physical authenticator (USB/NFC/Bluetooth) using FIDO2/WebAuthn standards and public-key cryptography to provide phishing-resistant 'something you have' authentication.

 **Exam Trap:** *FIDO2 = fator 'have'. Usa challenge-response assíncrono (não envia segredo/código, por isso resiste a phishing). A prova pode contrapor chave FIDO2 a OTP por SMS ou códigos TOTP.*

✓ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A software company rolls out a new policy that requires employees to enter their standard password followed by a six-digit PIN before the source code repository opens. The IT director announces at the all-hands meeting that the repository now satisfies the compliance mandate for multifactor authentication. A security analyst who reviews the login flow disagrees and plans to file a finding. What is the most technically accurate justification for the analyst's position?

- A) The six-digit PIN is too short to be recognized as a valid second factor by compliance frameworks
- B) The password and the PIN belong to the same factor category, so the login remains single-factor authentication
- C) Prompting for two secrets in the same browser session prevents the second factor from being validated by a separate server
- D) Compliance mandates require at least one biometric input before a login can be counted as multifactor

QUESTION 2 · EXAM SCENARIO

An online banking platform asks customers to enter their password and then a six-digit code that refreshes every 30 seconds inside a mobile authenticator application. During onboarding training, a new fraud analyst asks which authentication factor category that rotating code represents. What should the instructor answer?

- A) Something you have, because the code is generated by a device in the customer's possession
- B) Something you know, because the customer has to read the digits and type them manually
- C) Something you are, because the code is uniquely bound to the account holder's identity
- D) Somewhere you are, because the code only validates from registered geographic regions

QUESTION 3 · EXAM SCENARIO

Attackers ran an adversary-in-the-middle phishing campaign that captured employees' passwords and relayed their one-time codes in real time, completely defeating the current SMS-based second factor. The CISO wants a phishing-resistant method for all privileged accounts and has budget approved for hardware. Which solution best meets the requirement?

- A) Increase SMS one-time codes from six to eight digits to frustrate automated interception
- B) Deliver the one-time codes through an encrypted messaging application instead of SMS
- C) Send tap-to-approve push notifications to employees' registered smartphones
- D) Issue FIDO2 hardware security keys that cryptographically verify the legitimate service's origin before releasing a credential

QUESTION 4 · EXAM SCENARIO

A hospital's IT team configures the electronic health record portal so that clinicians can sign in only from the hospital's internal networks and its registered VPN address ranges. Attempts from hotels, airports, or unfamiliar foreign IP addresses are denied even when the username, password, and authenticator-app code are all supplied correctly. Which authentication factor category is the hospital enforcing with this rule?

- A) Something you have
- B) Something you do
- C) Somewhere you are
- D) Something you are

QUESTION 5 · EXAM SCENARIO

Visitors at a co-location data center must tap a chip-enabled smart badge on the entrance reader and then place a finger on a biometric scanner inside the mantrap before the inner door releases. Which combination of factor categories does this two-stage entry procedure enforce?

- A) Something you know and something you have
- B) Something you have and something you are
- C) Something you are and somewhere you are
- D) Something you do and something you know

QUESTION 6 · EXAM SCENARIO

An e-commerce company is hardening its administrative console and must select a login flow that qualifies as genuine multifactor authentication. Which implementation satisfies that requirement?

- A) A long passphrase immediately followed by a four-digit account PIN
- B) A password plus two personal verification questions pulled from the user's HR profile
- C) A numeric PIN combined with the answer to a memorable security question
- D) A password combined with a live scan of the administrator's iris

QUESTION 7 · EXAM SCENARIO

A fraud-prevention team at a brokerage firm deploys continuous session monitoring that builds a baseline of each trader's typing cadence and mouse-movement dynamics; when a live session deviates significantly from that baseline, the system forces step-up verification. Which authentication factor category does this behavioral profiling represent?

- A) Something you do
- B) Something you are
- C) Something you have
- D) Somewhere you are

QUESTION 8 · EXAM SCENARIO

Attackers executed SIM swap fraud against several employees and intercepted the SMS one-time codes used for remote VPN logins, even though every affected user had entered the correct password and code pair. Leadership wants to keep two-step verification but eliminate the dependency on the mobile carrier. Which change best accomplishes this?

- A) Keep SMS delivery but extend the codes from six digits to eight digits
- B) Redirect one-time codes to employees' corporate email addresses as the delivery channel
- C) Replace SMS codes with TOTP codes generated by an authenticator application installed on each employee's smartphone
- D) Reduce the SMS code expiration window from ten minutes down to sixty seconds

QUESTION 9 · EXAM SCENARIO

Users of a cloud productivity suite habitually approve push-notification MFA prompts without reading them because several arrive during the workday. Attackers holding harvested passwords exploited this habit at 2 a.m., flooding one user with approval requests until an accidental tap granted access. The security team wants a feature that compels users to actively verify which attempt they are authorizing. Which modification best fits this goal?

- A)** Extend the push-prompt expiration window from two minutes to five minutes
- B)** Enable number matching, requiring the user to type the numeric code displayed on the login screen into the approving device
- C)** Fall back to SMS-delivered approval links whenever the app notification goes unanswered
- D)** Allow users to register their laptop as a trusted device so push prompts are skipped on familiar sign-ins

QUESTION 10 · EXAM SCENARIO

An airport plans to replace staff checkpoint badge readers with a facial recognition turnstile. The security director asks the vendor which accuracy metric expresses the likelihood that the screening will wrongly admit a person who is not an authorized employee. Which metric should be reported?

- A)** False rejection rate, because it measures how often a genuine employee is denied
- B)** Crossover error rate, because it indicates the sensitivity point where both error types balance
- C)** False acceptance rate, because it measures how often an unauthorized individual is incorrectly granted access
- D)** Enrollment time, because it reflects how quickly staff faces are registered in the system

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option B — The password and the PIN belong to the same factor category, so the login remains single-factor authentication

True multifactor authentication requires credentials from at least two DIFFERENT factor categories: something you know, something you have, something you are, somewhere you are, or something you do. Both a password and a PIN fall into 'something you know,' so although the user supplies two separate secrets, the login is still single-factor and the compliance mandate is not met. To remediate the finding, the company should add a genuinely different category, such as a TOTP app, a hardware security key, or a biometric reader.

Question 2: Option A — Something you have, because the code is generated by a device in the customer's possession

Even though the user types the value, a time-based one-time password (TOTP) is produced by an authenticator app or hardware token that the user possesses, so CompTIA classifies it as 'something you have.' The category is determined by how the credential is generated and bound — possession of the seeded device — not by the physical act of typing it. That is why pairing a password (know) with a TOTP code (have) achieves true multifactor authentication.

Question 3: Option D — Issue FIDO2 hardware security keys that cryptographically verify the legitimate service's origin before releasing a credential

FIDO2 security keys are phishing-resistant because the private key never leaves the device and the signature is bound to the genuine origin (domain) registered at enrollment; a proxy phishing site presents a different origin, so the key refuses to authenticate and an adversary-in-the-middle relay obtains nothing usable. Longer codes or an encrypted delivery channel still transmit a replayable secret through the attacker's proxy, and tap-to-approve push notifications remain exposed to real-time relay and fatigue attacks.

Question 4: Option C — Somewhere you are

Restricting access based on network location, IP address, or geofencing implements the 'somewhere you are' factor. The clinician already presents a knowledge factor (password) and a possession factor (TOTP app), but the policy adds an independent category — a valid geographic or network context — which raises the overall authentication strength beyond the two submitted credentials.

Question 5: Option B — Something you have and something you are

The smart badge is a possession credential ('something you have'), and the fingerprint scan captures a physiological trait ('something you are'). Because the two checks draw from different categories, the mantrap enforces genuine multifactor authentication — a lost badge alone cannot open the door, and a stolen fingerprint template alone cannot either.

Question 6: Option D — A password combined with a live scan of the administrator's iris

Only the password with the iris scan combines two distinct categories: something you know and something you are. Passphrases, PINs, and security-question answers are all knowledge-based secrets, so the other three options — however many prompts they stack — remain single-factor and would fail an MFA compliance review.

Question 7: Option A — Something you do

Typing rhythm, mouse dynamics, and gait are behavioral characteristics, which map to the 'something you do' factor. It is distinct from 'something you are,' which relies on physiological attributes such as fingerprints, irises, or facial geometry. The system is authenticating how the user acts, not a body part, a possession, or a location.

Question 8: Option C — Replace SMS codes with TOTP codes generated by an authenticator application installed on each employee's smartphone

TOTP codes are computed locally by the authenticator app from a shared seed and never travel over the carrier network, so a SIM swap gives the attacker nothing to intercept. Extending the code length or shortening the expiry only tunes the same vulnerable SMS channel, and email delivery merely swaps one interceptable, reset-prone channel for another while keeping MFA intact.

Question 9: Option B — Enable number matching, requiring the user to type the numeric code displayed on the login screen into the approving device

Number matching forces the user to enter the value displayed on the legitimate login screen; a request lacking that code cannot be completed, which defeats blind taps and blunts MFA-fatigue (push bombing) attacks. A longer expiration only gives attackers more time, SMS approval links reintroduce interception and SIM-swap risk, and skipping prompts on trusted devices removes the second factor entirely for those sessions.

Question 10: Option C — False acceptance rate, because it measures how often an unauthorized individual is incorrectly granted access

The false acceptance rate (FAR) quantifies how frequently the biometric system accepts an impostor — exactly the risk of wrongly admitting an unauthorized person. The false rejection rate (FRR) measures the opposite problem of denying legitimate users, the crossover error rate (CER) is the sensitivity point where FAR and FRR intersect and is used to compare systems rather than describe impostor risk, and enrollment time is an operational speed metric unrelated to admission errors.