COMPTIA SECURITY+ SY0-701 | DOMAIN 4 · SECURITY OPERATIONS (28%)

Security+ 4.5 · Endpoint Security

Mestre CyberSec · **Lesson 4.5 — Endpoint Security** (9:25) · Assistir Vídeo no YouTube ↗ · Treino Interativo: edusouzamarques.github.io/cybersec

> **Executive Lesson Summary:** Endpoint: EDR (behavior + isolate + revert — evolution do antivírus); posture assessment (checa o dispositivo antes de dar acesso — MDM, AV, patch); remediation; NAC (802.1X + postura).

💡 Key Exam Highlights & Critical Concepts

- EDR: vê o comportamento e RESPONDE (isola o host)
- Posture assessment: o 'exame de saúde' antes de conectar à rede

🎯 Exam Tips & Typical CompTIA Scenarios

- 'detects malicious behavior on endpoint and can isolate'=EDR

🧯 Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 4.5 — Endpoint Security)

Why is this advanced coverage required for SY0-701?: Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• Endpoint Detection and Response (EDR)

An advanced endpoint security solution that continuously monitors endpoint behavior, detects malicious activity through behavioral analysis, and can automatically isolate compromised hosts and revert them to a clean state. It represents the evolution of traditional antivirus into a proactive, behavior-based security tool.

⚠ ***Exam Trap:*** *Trigger phrase: 'detects malicious behavior on endpoint and can isolate the host' = EDR (NOT antivirus). EDR is the modern evolution that responds; legacy AV only detects known signatures.*

• Posture Assessment (N/A)

A health check performed on an endpoint before granting network access, verifying that the device meets security requirements such as having updated antivirus, current patches, and MDM enrollment. It is a core component of Network Access Control (NAC) implementations.

⚠ ***Exam Trap:*** *Trigger phrase: 'health check before connecting to the network' = Posture Assessment. Often paired with NAC; the endpoint must pass posture checks or be sent to remediation.*

• Network Access Control (NAC)

A security framework that restricts network access based on a device's identity, authentication, and security posture, commonly using 802.1X for port-based authentication. Non-compliant devices are denied, quarantined, or sent to a remediation network.

⚠ ***Exam Trap:*** *Trigger phrase: '802.1X + posture assessment' = NAC. NAC = port-based access control + health checks; answers are about controlling WHO can connect and WHAT state they must be in.*

• IEEE 802.1X

A port-based network access control standard that authenticates devices connecting to a LAN or WLAN before allowing full network access, using a supplicant (client), authenticator (switch/AP), and authentication server (typically RADIUS). It is the protocol backbone of NAC implementations.

⚠ ***Exam Trap:*** *Trigger phrase: 'port-based network authentication' = 802.1X. Remember the trio: Supplicant + Authenticator + Authentication Server (RADIUS). Used by NAC to enforce access control.*

• Mobile Device Management (MDM)

A centralized management solution used to enforce security policies on mobile endpoints (smartphones, tablets, laptops), including device encryption, remote wipe, app control, and ensuring OS patching compliance for posture assessment.

⚠️ ***Exam Trap:*** *Trigger phrase: 'managing and enforcing policy on mobile devices / BYOD' = MDM. MDM = device-side enforcement; MAM (Mobile Application Management) = app-side only.*

• Remediation (N/A)

The process of correcting security deficiencies on a non-compliant endpoint, such as installing missing patches, updating antivirus signatures, or enabling a host-based firewall, before granting full network access. Often implemented via a quarantined VLAN.

⚠️ ***Exam Trap:*** *Trigger phrase: 'fix the endpoint to meet policy before allowing access' = Remediation. A non-compliant device gets sent to a remediation network/VLAN, NOT denied entirely (unless no fix is possible).*

• Quarantine Network (Quarantined VLAN) (N/A)

An isolated, restricted network segment where non-compliant or suspicious endpoints are placed to undergo remediation or forensic analysis, with limited access only to update servers and security resources. Used by NAC and EDR response actions.

⚠️ ***Exam Trap:*** *Trigger phrase: 'isolated network for non-compliant or infected devices' = Quarantine Network. EDR isolates hosts here, and NAC sends posture-failed devices here for remediation.*

• Host Isolation (N/A)

An EDR response action that disconnects a compromised endpoint from the network (or restricts it to a quarantine VLAN) to prevent lateral movement and further spread of malware while preserving the device for forensic investigation.

⚠️ ***Exam Trap:*** *Trigger phrase: 'EDR response that disconnects a compromised endpoint' = Host Isolation. This is the key differentiator: AV detects, EDR detects AND responds (isolates/reverts).*

✅ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

A security analyst receives an EDR alert indicating that a word processor process on a workstation has spawned a command shell that is downloading an encoded payload from an unknown external IP address. The user is actively working on the machine, and the analyst wants to stop the attack from spreading to other hosts while preserving volatile evidence and keeping the ability to communicate with the endpoint through the EDR console. Which action should the analyst take?

A) Isolate the host from the network using the EDR console while maintaining the management channel

B) Disable the user's Active Directory account immediately

C) Reimage the workstation to remove the malicious code

D) Block the external IP address at the perimeter firewall

QUESTION 2 · EXAM SCENARIO

A company deploys IEEE 802.1X on all wired switch ports with a RADIUS server. An employee's laptop authenticates successfully using a valid certificate, but the posture assessment reports that the antivirus signatures are 45 days out of date and the operating system is missing critical patches. Corporate policy requires compliant devices before granting full network access. What should the NAC solution do?

A) Reject the authentication request and permanently block the device's MAC address

B) Move the device into a quarantined VLAN that permits access only to patch and antivirus update servers

C) Grant full network access and log the posture violation for later review

D) Revoke the device's certificate and require re-enrollment

QUESTION 3 · EXAM SCENARIO

Ransomware begins encrypting files on several workstations and a file server. The EDR console shows that the malicious process is still running and has just started encrypting files on a shared network drive. Administrators must stop the encryption immediately and restore the affected files without paying a ransom. Which action should they take?

A) Block the malicious file's hash and update antivirus signatures on all hosts

B) Terminate the EDR alert and restore the file server from the most recent backup

C) Use the EDR to isolate the affected hosts and then apply the rollback feature to restore files modified by the malicious process

D) Enable full-disk encryption on the affected workstations

QUESTION 4 · EXAM SCENARIO

An organization uses an MDM solution to manage corporate smartphones and tablets. Before a device is allowed to access corporate email, the MDM performs a posture assessment. A device attempting to enroll reports that full-device encryption is disabled and the OS version is three major releases behind. Which action should the MDM take?

A) Wipe the device and require the user to enroll it again

B) Allow email access but restrict the user to read-only mail

C) Issue a new client certificate and allow access

D) Deny access to corporate email and push a compliance policy requiring encryption and an OS update

QUESTION 5 · EXAM SCENARIO

A manufacturing plant uses 300 unmanaged IoT sensors that cannot run endpoint agents. A sensor is found communicating with a known malicious IP address. The security team wants to contain the device while the vendor investigates, but the sensor must still be able to reach the vendor's internal update server. Which control best achieves this?

A) Deploy an EDR agent to the sensor and use host isolation

B) Assign the sensor's switch port to a quarantined VLAN with an ACL that allows traffic only to the internal update server

C) Block the malicious IP address on the perimeter firewall

D) Change the sensor's DNS server to the internal resolver

QUESTION 6 · EXAM SCENARIO

A network engineer is deploying 802.1X on the corporate campus. The design includes client software on each laptop, the access switches, and a RADIUS server. During testing, the engineer needs to confirm which component forwards the authentication credentials to the RADIUS server and controls the port state. Which component performs this role?

A) The client software acting as the supplicant

B) The RADIUS server acting as the authentication server

C) The access switch acting as the authenticator

D) The certificate authority acting as the registration authority

QUESTION 7 · EXAM SCENARIO

A remote contractor connects to the corporate VPN. The NAC solution performs a host posture check and finds that the endpoint's operating system firewall is disabled. Company policy requires non-compliant devices to be remediated before they can reach internal resources. Which action should the NAC take?

A) Redirect the endpoint to a remediation portal that provides the required configuration or tooling and then re-assess compliance

B) Terminate the VPN session and permanently block the contractor's account

C) Allow full access but enable session recording for the contractor

D) Automatically disable the corporate firewall rules for that session

QUESTION 8 · EXAM SCENARIO

A user receives a document that exploits a vulnerability in an office application, and the malicious code runs entirely in memory without writing a file to disk. The traditional antivirus product does not generate an alert because the payload has no known signature. Which technology is most likely to detect this activity?

A) A signature-based antivirus scanner after its definition files are updated

B) EDR, by correlating anomalous process behavior such as an office application spawning a scripting engine

C) A host firewall, by blocking inbound traffic on port 445

D) Full-disk encryption, by validating the boot chain

QUESTION 9 · EXAM SCENARIO

An EDR alert on a marketing workstation is confirmed as a trojan. The analyst isolates the host. The incident response lead wants to determine root cause, remove the malware, and ensure the host can be trusted before it returns to the network. Which sequence of actions best meets these goals?

A) Collect forensic artifacts while the host is isolated, then reimage the endpoint, restore user data, and return it to the network

B) Run an antivirus scan, delete the detected file, and reconnect the host immediately

C) Reconnect the host and monitor it with EDR for 24 hours before deciding

D) Move the host to a different VLAN and reset the user's password

QUESTION 10 · EXAM SCENARIO

An organization allows employees to use personal smartphones for corporate email through an MDM. The security policy requires that devices be enrolled, have a screen lock, and not be rooted or jailbroken. An employee enrolls a device that reports it is jailbroken. The MDM posture check fails. Which action should the organization take?

A) Allow access because the employee signed the acceptable use policy

B) Grant access to calendar and contacts only

C) Send the device to the EDR console for host isolation

D) Deny access to corporate email until the device is restored to a supported, non-jailbroken state

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option A — Isolate the host from the network using the EDR console while maintaining the management channel

Host isolation is an EDR containment action that cuts the endpoint off from the network while keeping the EDR management channel intact. This stops lateral movement and command-and-control traffic, preserves volatile memory and running processes for forensic analysis, and lets the analyst continue collecting telemetry and issuing commands. Disabling an AD account does not stop the already-running malicious process. Reimaging destroys evidence and is a remediation step, not containment. Blocking a single external IP is easily bypassed by domain generation algorithms or new infrastructure and does not contain the host.

Question 2: Option B — Move the device into a quarantined VLAN that permits access only to patch and antivirus update servers

The device has proven its identity but not its health. In a NAC deployment with posture assessment, the standard response to an authenticated-but-non-compliant device is to place it in a quarantined VLAN, a restricted network segment that only permits access to remediation resources such as patch servers and antivirus update servers. Once the device satisfies the posture policy, it is re-evaluated and can be moved to the production VLAN. Rejecting authentication or revoking the certificate would punish a valid user, granting full access violates policy, and permanently blocking the MAC address is unnecessarily disruptive.

Question 3: Option C — Use the EDR to isolate the affected hosts and then apply the rollback feature to restore files modified by the malicious process

Isolation stops the ransomware from spreading to other hosts and prevents further network encryption, while the EDR's rollback/revert capability restores files modified by the malicious process to their pre-encryption state. Together they contain and recover quickly. Hash blocking is reactive and does not help files already encrypted, restoring from backup may lose data and takes much longer, terminating the alert does nothing to stop the process, and full-disk encryption neither restores encrypted files nor stops the attack.

Question 4: Option D — Deny access to corporate email and push a compliance policy requiring encryption and an OS update

A compliance (posture) policy in the MDM should block access to corporate resources until the device meets the organization's baseline requirements, such as device encryption and a supported OS version. The MDM can push the required configuration or direct the user to remediate. Allowing read-only email or issuing a new certificate still grants corporate data access to a non-compliant device. A full wipe is disproportionate for an enrollment-time posture failure and destroys user data without first attempting remediation.

Question 5: Option B — Assign the sensor's switch port to a quarantined VLAN with an ACL that allows traffic only to the internal update server

A quarantined VLAN with ACLs is the appropriate control for devices that cannot run an endpoint agent. The switch can dynamically assign the port to a restricted VLAN where traffic is limited, for example only to the vendor's internal update server, isolating the compromised sensor from the rest of the network. EDR host isolation requires an agent on the device. Blocking a single malicious IP at the perimeter does not contain the device or prevent it from reaching other internal hosts. Changing the DNS server does not restrict network access.

Question 6: Option C — The access switch acting as the authenticator

In 802.1X, the roles are: the supplicant (client software on the endpoint), the authenticator (the switch or wireless AP that controls the port and relays EAP messages to the authentication server), and the authentication server (typically RADIUS, which validates credentials and returns the authorization decision). The switch is the authenticator; it does not validate credentials itself but forwards them to RADIUS and enforces the resulting port state.

Question 7: Option A — Redirect the endpoint to a remediation portal that provides the required configuration or tooling and then re-assess compliance

Posture assessment is meant to enforce compliance, not to permanently punish the user. The correct approach is to keep the device in a restricted (quarantine) state where it can reach a remediation portal, guide the user to enable the required control such as the host firewall, and re-assess. Only after the device is compliant should full access be granted. Permanently blocking the account is excessive, and allowing access with monitoring or disabling corporate firewall rules defeats the purpose of the control.

Question 8: Option B — EDR, by correlating anomalous process behavior such as an office application spawning a scripting engine

EDR uses behavioral analytics and process lineage tracking, so it can flag an office application spawning a scripting engine, PowerShell, or a command shell that then performs network or file operations, even when nothing is written to disk and no signature matches. Signature-based AV cannot detect previously unknown, fileless payloads. A host firewall rule on port 445 and full-disk encryption address different threats and would not detect in-memory code execution.

Question 9: Option A — Collect forensic artifacts while the host is isolated, then reimage the endpoint, restore user data, and return it to the network

Best practice after detecting malware is to contain, then preserve evidence before altering the system, then remediate. Because a trojan may have created persistence, modified system files, or left backdoors that a simple antivirus deletion can miss, the most reliable remediation for a confirmed infection is to reimage the endpoint and restore user data. Deleting one file and reconnecting immediately risks reinfection and does not establish trust. Monitoring a known-compromised host on the production network is not acceptable.

Question 10: Option D — Deny access to corporate email until the device is restored to a supported, non-jailbroken state

A jailbroken or rooted device bypasses the operating system's security controls, so it cannot be trusted to store corporate email data even with an MDM profile installed. The MDM's posture assessment should deny access to corporate resources until the device is returned to a supported, non-jailbroken state. An acceptable use policy or partial access such as calendar and contacts still exposes corporate data to an untrusted device. EDR host isolation does not apply because the device is not a managed endpoint on the corporate network.