COMPTIA SECURITY+ SY0-701 | DOMAIN 4 · SECURITY OPERATIONS (28%)

Security+ 4.5 · Web Filtering

Mestre CyberSec · **Lesson 4.5 — Web Filtering** (10:00) · Assistir Vídeo no YouTube ↗ · Treino Interativo: edusouzamarques.github.io/cybersec

Executive Lesson Summary: Web filtering: URL scanning por categoria; content filter; proxy HTTP (intermédia); DNS blocklist (bloqueia na resolução); reputation; bot detection.

💡 Key Exam Highlights & Critical Concepts

- DNS blocklist: bloqueia ANTES do browser abrir o site
- Web proxy: intermédia o HTTP/S e pode inspecionar

🎯 Exam Tips & Typical CompTIA Scenarios

- 'blocks domains at the DNS level'=DNS filtering

🚨 Beyond the Video: Official Exam Concepts, Protocols & Traps (Section 4.5 — Web Filtering)

Why is this advanced coverage required for SY0-701?: Video lectures provide foundational concepts, but CompTIA tests practical engineering judgment and requires deep familiarity with the following protocols, acronyms, and operational nuances in this domain:

• URL Filtering (URL Categorization)

A web filtering technique that classifies websites into categories (e.g., gambling, malware, social media) and blocks or allows access based on policy rules.

⚠️ ***Exam Trap:*** *If the question mentions blocking websites 'by category' (e.g., adult content, gambling), think URL filtering — it relies on an updated URL categorization database.*

• Content Filter (N/A)

Inspects the actual content of web pages (keywords, signatures, scripts) rather than just the URL, blocking pages containing prohibited material or malicious payloads.

⚠️ ***Exam Trap:*** *Distinguish from URL filtering: URL filter blocks by address/category; content filter blocks by what is *inside* the page (DLP-style keyword matching, malware signatures).*

• Web Proxy (Forward Proxy) (HTTP Proxy)

An intermediary server that retrieves web content on behalf of internal clients, enabling caching, logging, and inspection of HTTP/HTTPS traffic.

⚠️ ***Exam Trap:*** *Forward proxy = client-side intermediary (outbound traffic); reverse proxy = server-side (inbound). Know both — they appear as distinct answers.*

• DNS Blocklist (DNS Sinkhole / DNS Filtering) (DNSBL)

Blocks access to malicious or unwanted domains by preventing their resolution at the DNS layer, so the browser never reaches the site.

⚠️ ***Exam Trap:*** *Phrasing 'blocks domains at the DNS level' or 'prevents name resolution' = DNS filtering. Key distinction: it blocks *before* the HTTP connection even starts.*

• Reputation-Based Filtering (N/A)

Blocks or allows traffic based on the historical reputation score of a domain, IP, URL, or file — typically maintained by threat intelligence feeds.

⚠️ ***Exam Trap:*** *If a question mentions a 'score' or 'threat intelligence feed' being used to decide whether to block a site, the answer is reputation-based filtering — not URL categorization.*

• Bot Detection / Bot Filtering (N/A)

Identifies and blocks automated traffic (bots, scrapers, credential-stuffing tools) using behavioral analysis, CAPTCHA, or fingerprinting.

⚠️ ***Exam Trap:*** *When the scenario describes unusual request patterns, high-volume automated access, or scraping attempts — the control is bot detection, not standard URL filtering.*

- **SSL/TLS Inspection (HTTPS Interception) (SSL Inspection)**

Decrypts, inspects, and re-encrypts HTTPS traffic at a proxy so that encrypted web filtering and DLP can analyze the payload.

⚠️ ***Exam Trap:*** *If a question asks how a web proxy 'sees inside HTTPS traffic' — answer is SSL/TLS inspection (MITM proxy). Requires the proxy CA to be trusted by clients.*

✅ Authentic Practice Questions (10 Real Exam Scenarios)

Scenario-based exam questions. Complete explanations and distractor analysis are provided in the answer key below.

QUESTION 1 · EXAM SCENARIO

At a logistics company, employees are spending work hours on gambling and dating websites. The IT manager wants an automated solution that blocks entire classes of websites, such as gaming, gambling and adult content, without security staff having to manually list every offending domain. Which web filtering technique best fulfils this requirement?

A) Configuring a content filter that scans page text for gambling-related keywords

B) Enforcing URL categorization so that all domains falling in the gambling and dating categories are blocked

C) Creating individual host firewall allow/deny rules for each website as it is discovered

D) Enabling DNSSEC validation to prevent redirection to unauthorized domains

QUESTION 2 · EXAM SCENARIO

A security analyst at a manufacturing firm is responding to a phishing campaign that uses newly observed malicious domains. The CISO wants these domains blocked for every internal client at the earliest possible stage, before any device even attempts to establish a connection to the malicious web server. Which implementation achieves this goal?

A) A DNS blocklist that returns a sinkhole address for every listed malicious domain

B) A forward proxy that must be individually configured in each client application

C) Categorization rules deployed as browser extensions on each endpoint

D) A firewall policy that permits outbound TCP 443 to all destinations while logging the sessions

QUESTION 3 · EXAM SCENARIO

The compliance department of an insurance company requires that all web traffic generated by employees passes through a single controlled point where requests can be logged, corporate policy enforced, responses cached, and returned content scanned for malware before it reaches the clients. The solution must operate as an intermediary on behalf of internal clients accessing the internet. Which technology satisfies these requirements?

A) A reverse proxy that publishes internal web applications to external partners

B) A DNS blocklist that redirects queries for prohibited domains to a blackhole server

C) A forward proxy deployed as the intermediary for all outbound client web sessions

D) A stateful firewall performing NAT for all outbound connections from the LAN

QUESTION 4 · EXAM SCENARIO

A software development company permits general web browsing, but the security team is concerned about employees downloading malicious executables hosted on legitimate-looking or newly created websites, and about web pages that expose confidential internal financial data. The protection must inspect what is actually delivered, such as file types and page contents, regardless of the website's domain name. Which web filtering approach addresses this concern?

A) Reputation-based filtering that score-ranks domains according to their age and history

B) Content filtering that inspects the file types and contents of the returned web objects

C) URL categorization that blocks entire shopping and file-sharing categories

D) A DNS sinkhole that returns an invalid address for domains without an assigned category

QUESTION 5 · EXAM SCENARIO

After deploying a web filter at the network edge, the security team of a law firm discovers a major enforcement gap: since almost all websites now use HTTPS, the filter can only observe the destination domain name during the handshake and cannot see the full URL, page contents, or files returned inside the encrypted sessions. Management wants complete visibility and policy enforcement over encrypted web traffic without disabling HTTPS. Which capability should be implemented?

A) Forcing browsers back to plain HTTP by removing web server certificates

B) Adding every HTTPS site currently in use to a DNS sinkhole list

C) Blocking outbound TCP port 443 for the entire organization

D) SSL/TLS inspection that decrypts sessions using a trusted certificate installed on clients and re-encrypts them

QUESTION 6 · EXAM SCENARIO

A pharmaceutical company's web filter relies on manually curated lists and static categories, but attackers keep registering brand-new domains days or even hours before using them in phishing and malware-distribution campaigns, domains too new to appear in any category. The CISO wants the filter to automatically distrust domains based on factors such as registration age, historical activity, and threat intelligence indicators. Which feature provides this behavior?

A) Reputation-based filtering that assigns risk scores to domains sourced from threat intelligence

B) Content filtering that searches returned pages for generic phishing keywords

C) Bot detection that challenges clients with CAPTCHA tests before serving content

D) DNSSEC validation that rejects domains with unsigned DNS records

QUESTION 7 · EXAM SCENARIO

The web servers of an online retailer are under heavy automated abuse: scraping bots harvest the entire product catalogue within hours, and credential-stuffing scripts log in with thousands of stolen username/password pairs while imitating real browsers. The security architect needs a control deployed at the web layer that can differentiate automated clients from legitimate human shoppers and block or challenge the automated ones. Which solution applies?

A) Enabling URL categorization rules that exclude domains known to distribute scraping tools

B) Configuring the DNS blocklist so that the attacker workstations cannot resolve the retail site

C) Bot detection that analyzes client behavior and issues CAPTCHA or JavaScript challenges

D) Deploying a reverse proxy that caches static product pages for faster delivery

QUESTION 8 · EXAM SCENARIO

A university deployed DNS-based web filtering, blocking categories by intercepting all queries sent to its internal resolvers. During an audit, the networking team discovers that students still reach prohibited gambling sites by typing the sites' IP addresses directly into the browser, or by using bookmarks that bypass name resolution entirely. Which additional control most effectively closes this gap?

A) A content filter that scans page text only after pages have fully loaded

B) A forward proxy with URL/IP filtering that evaluates destinations even when no DNS query occurs

C) Removing the local hosts file from every managed endpoint

D) Increasing the DNS cache TTL on the internal resolvers to retain more entries

QUESTION 9 · EXAM SCENARIO

Following the rollout of DNS-based web filtering, the SOC of a financial services firm notices that some managed browsers never receive block pages: investigations show those browsers are configured to use DNS-over-HTTPS toward public resolvers, encrypting their name lookups so they completely bypass the internal DNS servers and their blocklists. Which mitigation directly addresses this bypass while keeping the DNS filtering policy intact?

A) Increasing the TTL values of the internal DNS zone records

B) Enabling DNSSEC signing on all internal zones

C) Publishing the internal resolver addresses only through DHCP instead of static configuration

D) Blocking the known public DNS-over-HTTPS endpoints so that clients fall back to the internal resolvers

QUESTION 10 · EXAM SCENARIO

Six weeks after enabling SSL/TLS inspection on the corporate web filter, the service desk is flooded with reports that a government benefits portal and several banking and healthcare applications fail with certificate warnings or refuse to connect. Analysis shows those applications perform certificate pinning and reject the certificates re-signed by the inspection proxy. The organization does not want to abandon inspection for the rest of its traffic. What is the most appropriate remediation?

A) Disabling SSL/TLS inspection for the whole organization and relying only on category filtering

B) Asking each bank and government portal to whitelist the organization's inspection certificate

C) Configuring bypass/exception rules on the filter that exempt destinations incompatible with interception

D) Installing the inspection proxy's root certificate directly inside each affected application

ANSWER KEY & COMPREHENSIVE DISTRACTOR EXPLANATIONS

Question 1: Option B — Enforcing URL categorization so that all domains falling in the gambling and dating categories are blocked

URL categorization groups millions of domains into predefined categories (gambling, adult content, social media, file sharing, etc.) that are maintained and continuously updated by the filtering vendor. Blocking entire categories automatically covers every domain placed in that category, including newly added ones, with no manual site-by-site work. A keyword-based content filter is unreliable, misses non-text content, and requires fetching the page first; per-site firewall rules do not scale and only act after a site is discovered; DNSSEC merely validates the integrity/authenticity of DNS responses and enforces no browsing policy at all.

Question 2: Option A — A DNS blocklist that returns a sinkhole address for every listed malicious domain

DNS blocklist filtering acts during name resolution: when a client queries a listed malicious domain, the internal resolver returns a sinkhole address (for example 127.0.0.1 or a dedicated blackhole server) instead of the real IP. Because the connection is never established, the threat is stopped at the earliest stage of the flow and protection is applied automatically to every device using the internal resolvers. A forward proxy only sees traffic routed to it and typically requires per-application configuration; browser extensions depend on the endpoint and are easy to bypass; a policy that permits all outbound HTTPS simply logs the connections while still allowing the phishing infrastructure to be reached.

Question 3: Option C — A forward proxy deployed as the intermediary for all outbound client web sessions

A forward proxy sits between internal clients and the internet: it receives requests on behalf of the clients, applies URL and content policies, logs activity, caches responses, and can scan returned content before delivering it. This intermediary role for outbound user traffic is exactly what compliance demands. A reverse proxy fills the opposite role, being placed in front of internal servers to handle inbound internet traffic; a DNS blocklist only stops resolution of prohibited names and offers no inspection or logging of general traffic; NAT on a stateful firewall changes addresses but does not mediate or inspect application-layer web requests.

Question 4: Option B — Content filtering that inspects the file types and contents of the returned web objects

Content filtering examines the data actually delivered within a web session, including page text, scripts, and file types such as executable downloads, and can block based on that content regardless of which domain serves it. This catches malicious files hosted on benign or brand-new sites that category or reputation data may not yet cover, and can also detect patterns of confidential data in the page contents. Reputation filtering only evaluates the domain's risk score; URL categorization decides by the class the site belongs to, not by what it serves; sinkholing uncategorized domains would either block large swaths of the legitimate internet or fail to inspect content on already-allowed sites.

Question 5: Option D — SSL/TLS inspection that decrypts sessions using a trusted certificate installed on clients and re-encrypts them

SSL/TLS inspection lets the proxy or filter terminate the client's TLS session, decrypt it using certificates issued by a trusted root/intermediate CA that the organization installs on its endpoints, inspect the plaintext URL and content, apply policy, and then re-encrypt the traffic toward the real destination. This restores visibility into full URLs and delivered content while encryption between the inspection device and the site is preserved. Downgrading to HTTP is insecure, unrealistic and breaks modern sites; sinkholing all HTTPS sites would merely block them without providing visibility; blocking port 443 outright eliminates modern web usage altogether.

Question 6: Option A — Reputation-based filtering that assigns risk scores to domains sourced from threat intelligence

Reputation-based filtering consumes continuously updated intelligence about a domain, including its registration age, historical behavior, WHOIS characteristics, and appearances in threat intelligence feeds, to compute a risk score. The filter can then automatically block or strongly warn on low-reputation domains, including freshly registered ones that no category lists yet. Keyword searches for phishing text are error-prone and require loading the page first; CAPTCHA challenges separate humans from bots but say nothing about the trustworthiness of the domain being visited; DNSSEC validates DNS data integrity and authenticity, and a perfectly signed phishing domain remains malicious.

Question 7: Option C — Bot detection that analyzes client behavior and issues CAPTCHA or JavaScript challenges

Bot detection/filtering inspects client characteristics and behavior, including user agents, headless-browser signatures, missing human interaction patterns, and request rates and sequences, to separate bots from real users, then responds with challenges such as CAPTCHA or JavaScript tests and blocks clients that fail. This is precisely the web-layer control requested to distinguish automated clients from humans. URL categorization classifies third-party websites, not the clients visiting the retailer; a DNS blocklist prevents resolution of malicious domain names and does not act on attacking

source IPs; a caching reverse proxy improves performance and softens the scraping load, but neither identifies nor blocks the automated clients.

Question 8: Option B — A forward proxy with URL/IP filtering that evaluates destinations even when no DNS query occurs

DNS filtering can only influence names that are actually resolved through the internal DNS servers. Connections made directly by IP address never trigger a DNS lookup, so the blocklist is never consulted. A forward proxy that all outbound web traffic is forced through can enforce URL and IP-based policy on the connection itself, checking the destination address and Host header, which closes the direct-IP bypass that DNS-only filtering cannot cover. A post-load content scan still lets the connection succeed and requires rendering risky content; the hosts file is unrelated to literal IP browsing; a longer cache TTL only extends entry retention and does not address the bypass.

Question 9: Option D — Blocking the known public DNS-over-HTTPS endpoints so that clients fall back to the internal resolvers

DoH wraps DNS queries inside HTTPS sessions toward external providers, so the internal servers are never queried and their blocklists no longer apply. The well-known public DoH services, identified by their resolver domain names and addresses, can themselves be blocked by the web filter or firewall, and most DNS filtering products include these endpoints in their blocklists by default. With external DoH blocked, browsers in automatic fallback mode resume using the system resolver, and the internal filtering policy is restored. Changing TTLs only affects cache duration; DNSSEC does not prevent encrypted lookups to external providers; distributing resolver addresses via DHCP does not stop users or browsers from configuring external DoH themselves.

Question 10: Option C — Configuring bypass/exception rules on the filter that exempt destinations incompatible with interception

Certificate-pinned applications refuse any certificate other than the exact one their pin expects, including certificates re-signed by an inspection appliance, and the organization has no authority over the pins embedded in external banks' or government portals' software. The accepted practice is to maintain an inspection exclusion or bypass list for destinations that break under interception, such as pinned applications and, for policy and privacy reasons, categories like banking and healthcare, while inspection continues everywhere else. Disabling inspection organization-wide removes visibility and policy enforcement from all traffic; external operators will not embed a customer organization's certificate in their pinning; adding the CA root inside an application changes nothing, because pinning validates the presented certificate against the pin baked into the application, and the re-signed certificate still fails that comparison.