

IDATT2503 - Cryptography Assignment 2

Edvard Berdal Eek

October 2025

Task 1 - AES a little history

1. Describe how the processes of establishing the two standards differ.

Data Encryption Standard (DES) was the standard for encryption before AES. The process of establishing DES was largely closed. It was developed by IBM (based on Lucifer) and modified with input from the NSA before being adopted as a U.S. standard in 1977. In contrast, AES was chosen through an open, international competition organized by NIST from 1997–2000, where cryptographers worldwide submitted and analyzed algorithms publicly.

2. What is the name of the algorithm that is known as AES and who developed this algorithm? Why was it by many a surprise that it was this that was chosen to be the new standard?

The algorithm selected as AES is called **Rijndael**, developed by Joan Daemen and Vincent Rijmen from Belgium. Its selection surprised many because it was a non-U.S. submission from two relatively unknown academics, chosen over candidates from major companies and institutions.

Task 2

- a) For each cipher above, encrypt both x1 and x2, using the key K1 and compare the results, with regards to diffusion.

```
Ciphertexts (for verification):
OTP_K1_x1: 0023456789ABCDEF0123456789ABCDEF
OTP_K1_x2: 0323456789ABCDEF0123456789ABCDEF
OTP_K2_x1: 1023456789ABCDEF0123456789ABCDEF
Affine_K1_x1: F023456789ABCDEF0123456789ABCDEF
Affine_K1_x2: DF23456789ABCDEF0123456789ABCDEF
Affine_K2_x1: 0023456789ABCDEF0123456789ABCDEF
```

Figure 1: Enter Caption

A XOR

```
def xor_bytes(a: bytes, b: bytes) -> bytes:
    return bytes(x ^ y for x, y in zip(a, b))
```

B Affine Cipher

```
def affine_encrypt(key: bytes, plaintext: bytes) -> bytes:
    a = int.from_bytes(key, "big")
    b = a
    x = int.from_bytes(plaintext, "big")
    y = (a * x + b) % (1 << 128)
    return y.to_bytes(16, "big")
```

Result below:

```
Ciphertexts (for verification):
OTP_K1_x1: 0023456789ABCDEF0123456789ABCDEF
OTP_K1_x2: 0323456789ABCDEF0123456789ABCDEF
OTP_K2_x1: 1023456789ABCDEF0123456789ABCDEF
Affine_K1_x1: F023456789ABCDEF0123456789ABCDEF
Affine_K1_x2: DF23456789ABCDEF0123456789ABCDEF
Affine_K2_x1: 0023456789ABCDEF0123456789ABCDEF
```

Figure 2: Enter Caption

C One round of AES

Number of Rounds: 1
Chaining:
Key
01234567 89abcdef 01234567 89abcdef
Expanded Key
Input
01000000 00000000 00000000 00000000
Encoding Rounds
Round 1
Encoded
01fcf41f 4c13eaaa 96747c97 c49b6222

Figure 3: AES one round with x_1 and K_1

Number of Rounds: 1
Chaining:
Key
01234567 89abcdef 01234567 89abcdef
Expanded Key
Input
02000000 00000000 00000000 00000000
Encoding Rounds
Round 1
Encoded
19fcf41f 4c13eaaa 96747c97 c49b6222

Figure 4: AES one round with x_2 and K_1

D Full AES

Number of Rounds: 10
Chaining:
Key
01234567 89abcdef 12345678 9abcde0f
Expanded Key
Input
01000000 00000000 00000000 00000000
Encoding Rounds
Encoded
6b86f1a9 35db65e7 3e29b6d7 4dfe9d33

Figure 5: AES with 10 rounds on x_1 with K_1

Number of Rounds: 10
Chaining:
Key
01234567 89abcdef 12345678 9abcde0f
Expanded Key
Input
02000000 00000000 00000000 00000000
Encoding Rounds
Encoded
29b542fd 4719deea cdc6b45c a2eee764

Figure 6: AES with 10 rounds on x_2 with K_1

```

Part (a): diffusion when plaintext changes (x1 vs x2, same key K1)
OTP: 1/16 bytes, 2/128 bits changed
Affine: 1/16 bytes, 5/128 bits changed
AES1: 1/16 bytes, 2/128 bits changed
AESfull: 16/16 bytes, 66/128 bits changed

```

Figure 7: Byte and bits comparison part a)

b) For each cipher, encrypt x_1 using K_1 and K_2 , and compare the results. How many bits change?

- A XOR
- B Affine Cipher

```

Ciphertexts (for verification):
OTP_K1_x1: 0023456789ABCDEF0123456789ABCDEF
OTP_K1_x2: 0323456789ABCDEF0123456789ABCDEF
OTP_K2_x1: 1023456789ABCDEF0123456789ABCDEF
Affine_K1_x1: F023456789ABCDEF0123456789ABCDEF
Affine_K1_x2: DF23456789ABCDEF0123456789ABCDEF
Affine_K2_x1: 0023456789ABCDEF0123456789ABCDEF

```

Figure 8: Enter Caption

C One round of AES

AES one round with x_1 and K_1 is the same as in precious task.

Number of Rounds: 1
Chaining:
Key
11234567 89abcdef 12345678 9abcde0f
Expanded Key
Input
01000000 00000000 00000000 00000000
Encoding Rounds
Round 1
Encoded
bf5c82a9 5b8de3b5 27c4c697 cc3bcbfb

Figure 9: AES one round with x_1 and K_2

D Full AES

AES with 10 rounds on $x1$ with $K1$ is the same as in previous task

Number of Rounds: 10
Chaining:
Key
11234567 89abcdef 12345678 9abcde0f
Expanded Key
Input
01000000 00000000 00000000 00000000
Encoding Rounds
Encoded
ed9d8fd0 fd632de9 3fd5197e d1c37fea

Figure 10: AES with 10 rounds on $x1$ with $K2$

```
Part (b): diffusion when key changes (K1 vs K2, same plaintext x1)
OTP: 1/16 bytes, 1/128 bits changed
Affine: 1/16 bytes, 4/128 bits changed
AES1: 15/16 bytes, 58/128 bits changed
AESfull: 16/16 bytes, 65/128 bits changed
```

Figure 11: Byte and bits comparison part b)

Task 3

Do the challenges on <https://www.cryptohack.org/challenges/aes/>, up to "Bringing it all together". Write down the captured flags, and submit the code (its in Python)

a) Keyed Permutation

crypto{bijection}

b) Resisting Bruteforce

crypto{biclique}

c) Structure of AES

crypto{inmatrix}

d) Round Keys

crypto{r0undk3y}

e) Confusion Through Substitution

crypto{l1n34rly}

f) Diffusion through Permutation

crypto{d1ffUs3R}

g) Bringing It All Together

crypto{MYAES128}

Task 4

In a standard Feistel cipher, decryption is equivalent to encryption with the round keys applied in reverse order. In this cipher, the round keys are mirrored:

$$(k_1, k_2, \dots, k_8, k_8, \dots, k_2, k_1),$$

which means that *encryption itself performs the same operations as decryption*.

Attack using a single oracle query:

1. Send the encrypted ciphertext c to the encryption oracle.
2. The oracle computes and returns the message m

$$\text{Encrypt}(c, k_1, \dots, k_{16}) = m,$$

because the mirrored keys cause the encryption process to effectively reverse the original encryption steps.

With a single query to the encryption oracle, an attacker can recover the plaintext m corresponding to any ciphertext c . This demonstrates that the cipher is vulnerable to a chosen-plaintext attack, as encryption and decryption are effectively identical due to the mirrored key schedule.