

Introduction to EBNF

What a Grammar Is

A grammar is a formal description of the structure of a language.

- Defines what strings are valid in the language
- Does not execute code or compute values
- Answers: “What does a well-formed program look like?”

Examples: - Arithmetic expressions - A subset of JavaScript - Configuration file format - Command language

The Idea Behind BNF and EBNF

BNF (Backus-Naur Form) was created to describe programming languages.

EBNF is a small extension that adds conveniences: - Repetition - Optional parts - Grouping

EBNF is not one standard; many dialects exist.

Basic Notation

An EBNF rule has the form:

```
name ::= definition
```

- `name` is a nonterminal (a grammatical category)
- `definition` is built from nonterminals and terminals

Example:

```
number ::= digit { digit }  
digit  ::= "0" | "1" | "2" | ... | "9"
```

A number is a digit followed by zero or more digits.

Core Operators

- `|` — choice (alternation)
- `{ }` — repetition (zero or more)

- [] — optional (zero or one)
- () — grouping

Example:

```
sign    ::= "+" | "-"
integer ::= [ sign ] digit { digit }
```

Valid: 7, -3, +42

Invalid: --3, +

Describing Expressions

A simple arithmetic grammar:

```
expression ::= term { ("+" | "-") term }
term        ::= factor { ("*" | "/" ) factor }
factor      ::= number | "(" expression ")"
number      ::= digit { digit }
digit       ::= "0" | "1" | ... | "9"
```

This encodes precedence: * and / bind tighter than + and -.

Valid: 3+4, 2*(5+1), 10/2-3

Invalid: +3, 3+, 2*(4+

Tokens vs Grammar

In practice, grammars operate on tokens, not characters.

Instead of:

```
number ::= digit { digit }
```

We assume:

```
number      ::= <NUMBER>
identifier  ::= <IDENTIFIER>
```

<NUMBER> and <IDENTIFIER> are produced by a tokenizer.

This keeps grammar focused on structure, not spelling.

Statements and Blocks

A tiny statement language:

```
program ::= { statement }
statement ::= assignment ";"
           | "if" "(" expression ")" block
           | "while" "(" expression ")" block
assignment ::= identifier "=" expression
block ::= "{" { statement } "}"
```

Valid program:

```
x = 3;
while (x) {
    x = x - 1;
}
```

What Grammars Do Not Do

A grammar does not:

- Check types
- Evaluate expressions
- Enforce variable declaration rules
- Decide whether a variable exists

Grammar allows:

```
x = y + 3;
```

Even if y is undefined.

Grammar answers only: - Is this structurally valid?

Ambiguity

A grammar is ambiguous if a string can be parsed in more than one way.

Classic example:

```
expression ::= expression "+" expression | number
```

The string $1 + 2 + 3$ can be grouped as: - $(1 + 2) + 3$ - $1 + (2 + 3)$

Solution: Introduce structure (term, factor, etc.).

Why EBNF Matters

EBNF is the bridge between: - Informal language descriptions - Working parsers

It lets us: - Be precise - Communicate structure - Reason about edge cases - Generate or implement parsers