



EXTENSIBLE PROVISIONING PROTOCOL EXTENSION MAPPING: <WHOIS INFO>

Version 1.0

COPYRIGHT NOTIFICATION

Copyright © 2005-2011, VeriSign, Inc. All rights reserved.

VERISIGN PROPRIETARY INFORMATION

This document is the property of VeriSign, Inc. Information contained herein may include trade secrets and confidential information belonging to VeriSign Inc.. Unauthorized disclosure without the express written consent of VeriSign, Inc. is prohibited. It may be used by recipient only for the purpose for which it was transmitted and will be returned upon request or when no longer needed by recipient. It may not be copied or communicated without the prior written consent of VeriSign, Inc.

DISCLAIMER AND LIMITATION OF LIABILITY

VeriSign, Inc. has made efforts to ensure the accuracy and completeness of the information in this document. However, VeriSign, Inc. makes no warranties of any kind (whether express, implied or statutory) with respect to the information contained herein.

VeriSign, Inc. assumes no liability to any party for any loss or damage (whether direct or indirect) caused by any errors, omissions or statements of any kind contained in this document. Further, VeriSign, Inc. assumes no liability arising from the application or use of the product or service described herein and specifically disclaims any representation that the products or services described do not infringe upon any existing or future intellectual property rights. Nothing herein grants the reader any license to make, use, or sell equipment or products constructed in accordance with this document. Finally, all rights and privileges related to any intellectual property right described in this document are vested in the patent, trademark, or service mark owner, and no other person may exercise such rights without express permission, authority, or license secured from the patent, trademark, or service mark owner.

VeriSign Inc. reserves the right to make changes to any information herein without further notice.

NOTICE AND CAUTION

Concerning U.S. Patent or Trademark Rights

The inclusion in this document, the associated on-line file, or the associated software of any information covered by any patent, trademark, or service mark rights will not constitute nor imply a grant of, or authority to exercise, any right or privilege protected by such patent, trademark, or service mark. All such rights and privileges are vested in the patent, trademark, or service mark owner, and no other person may exercise such rights without express permission, authority, or license secured from the patent, trademark, or service mark owner.

Table of Contents

1	INTRODUCTION	1
2	OBJECT ATTRIBUTES.....	1
3	EPP COMMAND MAPPING.....	2
3.1	EPP Query Commands	2
3.1.1	EPP <check> Command.....	3
3.1.2	EPP <info> Command.....	4
3.1.3	EPP <transfer> Command.....	6
3.2	EPP Transform Commands	7
3.2.1	EPP <create> Command.....	7
3.2.2	EPP <delete> Command.....	8
3.2.3	EPP <renew> Command	9
3.2.4	EPP <transfer> Command.....	10
3.2.5	EPP <update> Command.....	11
4	FORMAL SYNTAX.....	12
5	REFERENCES.....	13

1 Introduction

This document describes a Whois Info extension for version 1.0 of the Extensible Provisioning Protocol (EPP). This mapping, an extension of the domain name mapping described in [EPP-D], is specified using the Extensible Markup Language (XML) 1.0 as described in [XML] and XML Schema notation as described in [XMLS-1] and [XMLS-2].

[EPP] provides a complete description of EPP command and response structures. A thorough understanding of the base protocol specification is necessary to understand the mapping described in this document.

XML is case sensitive. Unless stated otherwise, XML specifications and examples provided in this document MUST be interpreted in the character case presented to develop a conforming implementation.

2 Object Attributes

This extension adds additional elements to the domain name mapping described in [EPP-D]. Only new element descriptions are described here.

3 EPP Command Mapping

A detailed description of the EPP syntax and semantics can be found in [EPP]. The command mappings described here are specifically for use with the Whois Info Extension.

3.1 EPP Query Commands

EPP provides three commands to retrieve object information: <check> to determine if an object is known to the server, <info> to retrieve detailed information associated with an object, and <transfer> to retrieve object transfer status information.

3.1.1 EPP <check> Command

This extension does not add any elements to the EPP <check> command or <check> response described in [EPP-D].

3.1.2 EPP <info> Command

This extension defines additional elements for the EPP <info> command and response described in [EPP-D].

The EPP <info> command is used to retrieve information associated with a domain object. In addition to the EPP command elements described in [EPP-D], the command **MUST** contain an <extension> element. The <extension> element **MUST** contain a child <whoisInf:whoisInf> element that contains the following child element:

- A <whoisInf:flag> element that **MUST** contain a boolean value of “1” or “true” to indicate that additional whois information is desired in the response or a value of “0” or “false” to indicate that no additional whois information is desired in the response.

Example <info> command:

```
C:      <?xml version="1.0" encoding="UTF-8"?>
C:      <epp xmlns="urn:ietf:params:xml:ns:epp-1.0"
C:          xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
C:          xsi:schemaLocation="urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd">
C:          <command>
C:              <info>
C:                  <domain:info
C:                      xmlns:domain="urn:ietf:params:xml:ns:domain-1.0"
C:                      xsi:schemaLocation="urn:ietf:params:xml:ns:domain-1.0 domain-1.0.xsd">
C:                          <domain:name>example.com</domain:name>
C:                  </domain:info>
C:              </info>
C:              <extension>
C:                  <whoisInf:whoisInf
C:                      xmlns:whoisInf="http://www.verisign.com/epp/whoisInf-1.0"
C:                      xsi:schemaLocation="http://www.verisign.com/epp/whoisInf -1.0 whoisInf-
C:                      1.0.xsd">
C:                      <whoisInf:flag>1</whoisInf:flag>
C:                  </whoisInf:whoisInf>
C:              </extension>
C:              <clTRID>ABC-12345</clTRID>
C:          </command>
C:      </epp>
```

When an <info> command has been processed successfully, the EPP <infData> element **MUST** contain child elements as described in [EPP-D]. In addition to the EPP response element described in [EPP-D], the response **MUST** contain an <extension> element with a <whoisInf:whoisInfData> child element if the <whoisInf:whoisInf> command extension was included with a <whoisInf:flag> value of “1” or “true”. The <whoisInf:whoisInfData> element contains the following child elements:

- A <whoisInf:registrar> element that contains the full name of the sponsoring Registrar.
- An **OPTIONAL** <whoisInf:whoisServer> element that contains the sponsoring Registrar’s referral whois server name.
- An **OPTIONAL** <whoisInf:url> element that contains the sponsoring Registrar’s referral URL.

- An **OPTIONAL** <whoisInf:irisServer> element that contains the sponsoring Registrar's referral IRIS server name.

Example <info> response:

```
S: <?xml version="1.0" encoding="UTF-8"?>
S: <epp xmlns="urn:ietf:params:xml:ns:epp-1.0"
S:   xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
S:   xsi:schemaLocation="urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd">
S:   <response>
S:     <result code="1000">
S:       <msg>Command completed successfully</msg>
S:     </result>
S:     <resData>
S:       <domain:infData
S:         xmlns:domain="urn:ietf:params:xml:ns:domain-1.0"
S:         xsi:schemaLocation="urn:ietf:params:xml:ns:domain-1.0 domain-1.0.xsd">
S:         <domain:name>example.com</domain:name>
S:         <domain:roid>EXAMPLE1-VRSN</domain:roid>
S:         <domain:status s="ok"/>
S:         <domain:clID>ClientX</domain:clID>
S:         <domain:crID>ClientY</domain:crID>
S:         <domain:crDate>2005-11-11T18:09:52.0354Z</domain:crDate>
S:         <domain:authInfo>
S:           <domain:pw>2fooBAR</domain:pw>
S:         </domain:authInfo>
S:       </domain:infData>
S:     </resData>
S:     <extension>
S:       <whoisInf:whoisInfData
S:         xmlns:whoisInf="http://www.verisign.com/epp/whoisInf-1.0"
S:         xsi:schemaLocation="http://www.verisign.com/epp/whoisInf-1.0
S:           whoisInf-1.0.xsd">
S:         <whoisInf:registrar>Example Registrar Inc.</whoisInf:registrar>
S:         <whoisInf:whoisServer>whois.example.com</whoisInf:whoisServer>
S:         <whoisInf:url>http://www.example.com</whoisInf:url>
S:         <whoisInf:irisServer>iris.example.com</whoisInf:irisServer>
S:       </whoisInf:whoisInfData>
S:     </extension>
S:   </trID>
S:     <clTRID>ABC-12345</clTRID>
S:     <svTRID>54321-XYZ</svTRID>
S:   </trID>
S: </response>
S: </epp>
```


3.1.3 EPP <transfer> Command

This extension does not add any elements to the EPP <transfer> query command or <transfer> query response described in [EPP-D].

3.2 EPP Transform Commands

EPP provides five commands to transform objects: <create> to create an instance of an object, <delete> to delete an instance of an object, <renew> to extend the validity period of an object, <transfer> to manage object sponsorship changes, and <update> to change information associated with an object.

3.2.1 EPP <create> Command

This extension does not add any elements to the EPP <create> query command or <transfer> query response described in [EPP-D].

3.2.2 EPP <delete> Command

This extension does not add any elements to the EPP <delete> command or <delete> response described in [EPP-D].

3.2.3 EPP <renew> Command

This extension does not add any elements to the EPP <renew> command described in [EPP-D].

3.2.4 EPP <transfer> Command

This extension does not add any elements to the EPP <transfer> command described in [EPP-D].

3.2.5 EPP <update> Command

This extension does not add any elements to the EPP <update> command or <update> response described in [EPP-D].

4 Formal Syntax

An EPP object mapping is specified in XML Schema notation. The formal syntax presented here is a complete schema representation of the object mapping suitable for automated validation of EPP XML instances. The BEGIN and END tags are not part of the schema; they are used to note the beginning and ending of the schema for URI registration purposes.

```
<?xml version="1.0" encoding="UTF-8"?>

<schema targetNamespace="http://www.verisign.com/epp/whoisInf-1.0"
  xmlns:whoisInf="http://www.verisign.com/epp/whoisInf-1.0"
  xmlns:eppcom="urn:ietf:params:xml:ns:eppcom-1.0"
  xmlns="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">

  <import namespace="urn:ietf:params:xml:ns:eppcom-1.0"
    schemaLocation="eppcom-1.0.xsd"/>

  <annotation>
    <documentation>
      Extensible Provisioning Protocol v1.0
      extension schema for Whois Info
    </documentation>
  </annotation>

  <!--
Possible Whois Info extension root elements
-->
  <element name="whoisInf" type="whoisInf:whoisInfType"/>
  <element name="whoisInfData" type="whoisInf:whoisInfDataType"/>

  <!--
Child elements for the <whoisInf> extension which
is used as an extension to an info command.
-->
  <complexType name="whoisInfType">
    <sequence>
      <element name="flag" type="boolean"/>
    </sequence>
  </complexType>

  <!--
Child elements for the <whoisInfData> extension which
is used as an extension to the info response.
-->
  <complexType name="whoisInfDataType">
    <sequence>
      <element name="registrar" type="string"/>
      <element name="whoisServer" type="eppcom:labelType"
minOccurs="0"/>
      <element name="url" type="token" minOccurs="0"/>
      <element name="irisServer" type="eppcom:labelType"
minOccurs="0"/>
    </sequence>
  </complexType>

</schema>
```

5 References

[EPP] IETF RFC 3730: S. Hollenbeck: "Extensible Provisioning Protocol (EPP)", March 2004.

[EPP-D] IETF RFC 3731: S. Hollenbeck: "Extensible Provisioning Protocol Domain Name Mapping", March 2004.

[IETF-XML] M. Mealling: "The IETF XML Registry".

[ISO8601] ISO 8601:1988 (E): "Data elements and interchange formats -Information interchange - Representation of dates and times - The International Organization for Standardization".

[RFC2119] S. Bradner: "Key Words for Use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

[XML] Editors T. Bray et al.: "Extensible Markup Language (XML) 1.0 (Second Edition)", W3C Recommendation 6 October 2000.

[XMLS-1] Editors H. Thompson et al.: "XML Schema Part 1: Structures", W3C Recommendation 2 May 2001.

[XMLS-2] Editors P. Biron, A. Malhotra: "XML Schema Part 2: Datatypes", W3C Recommendation 2 May 2001.

[X3C-L] XML Schema Part 2: Datatypes, W3C Recommendation 02 May 2001.
<http://www.w3.org/TR/xmlschema-2/#language>