

**Palmpoint Recognition with
Three Dimensional Features**

Thesis Defense
M.Sc. in Software Technology

QING Pei, 11500811G
Department of Computing
The Hong Kong Polytechnic University

11 July, 2012

Acknowledgement

- David Zhang
- Lei Zhang
- Wei Li

2

Why?

What?

How?

Motivation

Why?

personal authentication

Motivation

personal authentication

- password
- most used
- but most easily subverted

5

6

Motivation

personal authentication

- smartcard
- more secure
- but will you carry dozens of smartcards with you everyday?

7

Motivation

personal authentication

- palmprint
- texture - almost fully explored
- geometry - not yet

10

Motivation

personal authentication

- biometrics
- fingerprint, palmprint, iris, face, voice
- code complex enough
- high availability

8

Motivation

personal authentication

- palmprint
- texture
- geometry

9

What?

Verification & Recognition

based on palmprint captures

12

Research Questions

- How much information lies the palmprint geometry?
- How to take advantage of the additional information?

13

Literature Review

- 2D techniques achieved high accuracy

Adams Kong, David Zhang, and Mohamed Kamel. A survey of palmprint recognition. *Pattern Recognition*, 42(7):1408–1418, July 2009.

14

Literature Review

- 3D devices are available

D Zhang, Guangming Lu, Wei Li, Lei Zhang, and Nan Luo. Three Dimensional Palmprint Recognition using Structured Light Imaging. In *Biometrics: Theory, Applications and Systems*, 2008. BTAS 2008. 2nd IEEE International Conference on, pages 1–6, 2008.

15

Literature Review

- Texture-based methods on 3D data
 - Mean Curvature Image
 - Gaussian Curvature Image

D Zhang, Guangming Lu, Wei Li, Lei Zhang, and Nan Luo. Palmprint Recognition Using 3-D Information. *Systems, Man, and Cybernetics, Part C: Applications and Reviews*. IEEE Transactions on, 39(5):505–519, 2009.

16

Literature Review

- Geometry-based methods on 3D data
 - Surface Type

D Zhang, Guangming Lu, Wei Li, Lei Zhang, and Nan Luo. Palmprint Recognition Using 3-D Information. *Systems, Man, and Cybernetics, Part C: Applications and Reviews*. IEEE Transactions on, 39(5):505–519, 2009.

17

Literature Review

- Fusion of texture and geometry features

W. Li, D Zhang, L. Zhang, G. Lu, and J. Yan. 3-D palmprint recognition with joint line and orientation features. *Systems, Man, and Cybernetics, Part C: Applications and Reviews*. IEEE Transactions on, 39(1):1–6, 2011.

18

How?

Method

- Data collection (regards to Wei Li)
- Data processing
- Recognition system

20

Data Collection


- Structural Light Imaging



21

Data Collection

- Structural Light Imaging



22

A Sample

- 768x576
single precision float depth matrix



23


Data Processing

- ROI extraction
- Feature extraction
- Dimension reduction
- Feature matching

24

Region of Interest

- 400x400, down-sample to 200x200



25

Maximum Depth

- Depth from a reference plane to the deepest point

28

Noise Cancellation

- Gradient Threshold

$$|\nabla D| = \sqrt{\left(\frac{\partial D}{\partial x}\right)^2 + \left(\frac{\partial D}{\partial y}\right)^2}$$

26

Maximum Depth

- Reference plane

$$d_r = \frac{1}{\sum_{i=R_s}^{R_e} \sum_{j=C_s}^{C_e} m_{ij}} \sum_{i=R_s}^{R_e} \sum_{j=C_s}^{C_e} (d_{ij})$$

29

Feature Extraction

- Maximum Depth
- Horizontal Cross-section Area
- Radial Line Length

27

Maximum Depth

- Deepest point

$$d_{max} = \max_{i=R_s}^{R_e} (\max_{j=C_s}^{C_e} (d_{ij}))$$

30

Maximum Depth


- Maximum Depth (MD)

$$MD = d_{max} - d_r$$

31

Horizontal Cross-section Area


- Contour view



32

Horizontal Cross-section Area

- Cut the ROI



33

Horizontal Cross-section Area

- Group pixels to N levels

$$G_{ij}^k = \begin{cases} 1 & \text{if } d_{ij} > h \cdot (N - k + 1)/N, \\ 0 & \text{otherwise} \end{cases}$$

$$k = 1, 2, \dots, N; i = 1, 2, \dots, 200; j = 1, 2, \dots, 200;$$

34


Horizontal Cross-section Area

- Stabilization: grow while connected

$$L^k = \begin{cases} G^1 & k = 1 \\ G^k \cap (L^{k-1} \oplus \Theta^{k-1}) & k = 2, 3, \dots, N \end{cases}$$

35

Horizontal Cross-section Area




36

Radial Line Length

- Finer description of the shape of HCA at each level
- Using the length of M line segments

37

Radial Line Length



38

Combined Feature Vector

- F consists of MD+HCA+RLL
- F has 1+N+NxM dimensions

39

Dimension Reduction

- Project F to a lower dimensional space
- Preserve as much information as possible

$$\tilde{F} = W^T F$$

40

Dimension Reduction

- Orthogonal Linear Discriminant Analysis

JP Ye. Characterization of a family of algorithms for generalized discriminant analysis on undersampled problems. Journal of Machine Learning Research, 6:489–502, 2005.

41

Feature Matching

- Coarse-level matching

$$Similarity = \|\tilde{F}_1 - \tilde{F}_2\| = \sum_{i=1}^T (f_i^1 - f_i^2)^2$$

42


Improved Matching

- Ranking Support Vector Machine

Thorsten Joachims. Optimizing search engines using clickthrough data. In KDD '02: Proceedings of the eighth ACM SIGKDD international conference on Knowledge discovery and data mining. ACM Request Permissions, July 2002.

Fine-matching Feature

- Mean Curvature Image



Experiment

- 8000 samples
- 4000 for training
- 4000 for testing
- Matlab

Optimizing Parameters

- Recall that we have a feature vector of $1+N \times M$ dimensions
- And we want to reduce the dimension to Γ


Optimizing Parameters

- Choosing N and M (by EER)

	M=8	M=16	M=32	M=64
N=4	14.3	19.15	14.35	14.07
N=8	14.2	16.3	12.32	12.54
N=16	18.11	18.35	15.21	14.11

Optimizing Parameters

- Choosing Γ




Performance Metrics

- Error rate
$$\text{error rate} = \frac{\text{number of false match}}{\text{total number of probe}} \times 100\%$$
- Penetration rate
$$\text{penetration rate} = \frac{\text{number of accessed template}}{\text{total number of template in the database}} \times 100\%$$

49

Performance Results



50

Speed

MCI only		
Process		Time (ms)
Feature extraction		112
Dimension reduction		0
Preprocess		0
MCI matching		0.86
Total (for one probe)		456

51

Speed

with Coarse-level matching

Process	Time (ms)
Feature extraction	136
Dimension reduction	0.1
Preprocess	0.5
MCI matching	0.86
Total (for one probe)	292.09

1.56X

52

Speed

with RSVM

Process	Time (ms)
Feature extraction	136
Dimension reduction	0.1
Preprocess	1.56
MCI matching	0.86
Total (for one probe)	240.86

1.9X

53

Discussion

54

Conclusions

- Geometric features extracted
- Matching process improved

55

Limitations

- 3D devices are *lower* in resolution (compared to 2D ones)
- possible, but not as cost effective

56

Limitations

- 3D depth values are more susceptible to movement than 2D textures
 - less stable
 - or less user-friendly

57

Limitations

- General biometrics authentication limitations

58

Future work

- Try different ROI
- Find geometric features with lower error rate
- Anti-counterfeiting considerations

59

Thank you.