Module Interface Specification for Measuring Microstructure Changes During Thermal Treatment

Team #30, ReSprint
Edwin Do
Joseph Braun
Timothy Chen
Abdul Nour Seddiki
Tyler Magarelli

 $January\ 18,\ 2023$

1 Revision History

Date	Developer	Notes
Jan 17, 2023	Timothy	Added Modules to Module Decomposition
	Chen	
Jan 18, 2023	Timothy	Added Current State Module
	Chen	
Jan 18, 2023	Timothy	Added File Output Module
	Chen	
Jan 18, 2023	Timothy	Added Graphical Output Module
	Chen	•
Jan 18 2023	Edwin Do	Added MIS info for UserInputValidation, HardwareInput-
		Validation, and Calculation Modules
Jan 18 2023	Edwin Do	Added state invariants

2 Symbols, Abbreviations and Acronyms

See SRS Documentation at here.

Contents

1	Rev	vision I	History			
2	Symbols, Abbreviations and Acronyms					
3	Introduction					
4	Not	ation				
5	Mo	dule D	Decomposition			
6	MIS	S of Cu	urrent State Module			
	6.1	Modul	${ m le}$			
	6.2	Uses				
		6.2.1	Imported Types			
		6.2.2	Imported Access Programs			
	6.3	Syntax	x			
		6.3.1	Exported Constants			
		6.3.2	Exported Access Programs			
	6.4	Seman	ntics			
		6.4.1	State Variables			
		6.4.2	State Invariant			
		6.4.3	Environment Variables			
		6.4.4	Assumptions			
		6.4.5	Access Routine Semantics			
		6.4.6	Local Functions			
7	MIS		leOutput Module			
	7.1	Modul	$ m le \ldots \ldots$			
	7.2	Uses				
		7.2.1	Imported Types			
		7.2.2	Imported Access Programs			
	7.3	•	x			
		7.3.1	Exported Constants			
		7.3.2	Exported Access Programs			
	7.4	Seman	ntics			
		7.4.1	State Variables			
		7.4.2	State Invariant			
		7.4.3	Environment Variables			
		7.4.4	Assumptions			
		7.4.5	Access Routine Semantics			
		7.4.6	Local Functions			

8	MIS	of Gr	raphical Output Module	7
	8.1	Modul	le	. 7
	8.2	Uses		. 7
		8.2.1	Imported Types	. 7
		8.2.2	Imported Access Programs	. 7
	8.3	Syntax	x	. 7
		8.3.1	Exported Constants	. 7
		8.3.2	Exported Access Programs	. 7
	8.4	Seman	ntics	. 7
		8.4.1	State Variables	. 7
		8.4.2	State Invariant	. 7
		8.4.3	Environment Variables	. 7
		8.4.4	Assumptions	. 8
		8.4.5	Access Routine Semantics	. 8
		8.4.6	Local Functions	
9	MIS	of Ca	alculation Module	9
	9.1		le	
	9.2			
		9.2.1	Imported Types	
		9.2.2	Imported Access Programs	
	9.3		X	
		9.3.1	Exported Constants	
		9.3.2	Exported Access Programs	
	9.4		ntics	
		9.4.1	State Variables	
		9.4.2	State Invariants	
		9.4.3	Environment Variables	
		9.4.4	Assumptions	
		9.4.5	Access Routine Semantics	
		9.4.6	Local Functions	
10	мтс	S of He	serInputValidation Module	12
10				
	10.2		Imported Types	
	10.3		X	
	10.5		Exported Constants	
			Exported Constants Exported Access Programs	
	10.4		ntics	
	10.4		State Variables	
			State Invariants	
			Environment Variables	. 12

	10.4.4 Assumptions	12
	10.4.5 Access Routine Semantics	13
	10.4.6 Local Functions	13
11 MIS	S of HardwareInputValidation Module	14
11.1	Module	14
11.2	Uses	14
	11.2.1 Imported Types	14
11.3	Syntax	14
	11.3.1 Exported Constants	14
	11.3.2 Exported Access Programs	14
11.4	Semantics	14
	11.4.1 State Variables	14
	11.4.2 State Invariants	14
	11.4.3 Environment Variables	14
	11.4.4 Assumptions	14
	11.4.5 Access Routine Semantics	15
	11.4.6 Local Functions	15
12 App	pendix	17

3 Introduction

The following document details the Module Interface Specifications for Measuring Microstructure Changes During Thermal Treatment. This project will allow the Materials Engineering lab at McMaster University, led by Dr. Zurob, to use a software capable of providing data on thermally treated metals. The data includes measurements of resistivity of the material as well as graphical representations and analysis.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at our GitHub repository.

4 Notation

[You should describe your notation. You can use what is below as a starting point. —SS]

The structure of the MIS for modules comes from Hoffman and Strooper (1995), with the addition that template modules have been adapted from Ghezzi et al. (2003). The mathematical notation comes from Chapter 3 of Hoffman and Strooper (1995). For instance, the symbol := is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1|c_2 \Rightarrow r_2|...|c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by Measuring Microstructure Changes During Thermal Treatment.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	N	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$

The specification of Measuring Microstructure Changes During Thermal Treatment uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, Measuring Microstructure Changes During Thermal Treatment uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding	
Behaviour-Hiding	Input Communication Module (??) Output Communication Module (??) Remote Access Module (??) Current State Module (6) FileOutput Module (7) Graphical Output Module (8)
Software Decision	Calculation Module (??) User Input Validation Module (??) Hardware Input Validation Module (??)

Table 1: Module Hierarchy

6 MIS of Current State Module

6.1 Module

Current State Module

6.2 Uses

6.2.1 Imported Types

 ${\bf Hardware Input:}\ (\ Voltage: real\ ;\ Time: real;\ Temperature: real;\ Current: real\)$

 $\label{thm:continuity} \textbf{UserInput:} \ (\ Sampling Rate: real; Sample Lengthgth: real; Sample Width: real; Filename: real; Sample Vidth: real; Filename: real; F$

string; Name: string; SampleName: string; Date: string)

6.2.2 Imported Access Programs

GetUserInput(): UserInput

GetHardwareInput(): HardwareInput

6.3 Syntax

6.3.1 Exported Constants

N/A

6.3.2 Exported Access Programs

Name	In	Out	Exceptions
StateInit()			
DisplayUserInfo()	string, string, string, string,		INVALID
	real, real, real		
DisplayHardwareState()	real, real, real		INVALID

6.4 Semantics

6.4.1 State Variables

N/A

6.4.2 State Invariant

6.4.3 Environment Variables

ApplicationWindow: the screen inferface where the information displayed to the user

6.4.4 Assumptions

StateInit() is called before any other access program

6.4.5 Access Routine Semantics

StateInit():

• transition: State Display is initialized on ApplicationWindow

• exception: none

DisplayUserInfo(Name, SampleName, Date, Filename, SamplingRate, SampleLength, SampleWidth):

- transition: Display Name, SampleName Date, Filename, SamplingRate, SampleLength, and SampleWidth on the ApplicationWindow
- exception: $exc := SamplingRate \notin \mathbb{R} \vee SamplingRate < 0 \vee SampleLength \notin \mathbb{R} \vee SampleLength < 0 \vee SampleWidth \notin \mathbb{R} \vee SampleWidth < 0 \Rightarrow INVALID$

DisplayHardwareState(Voltage, Current, Time, Temperature):

- transition: Display Voltage, Current, and Time on the ApplicationWindow
- exception: $exc := Voltage \notin \mathbb{R} \lor Voltage < 0 \lor Current \notin \mathbb{R} \lor Current < 0 \lor Time \notin \mathbb{R} \lor Time < 0 \lor Temperature \notin \mathbb{R} \Rightarrow INVALID$

6.4.6 Local Functions

7 MIS of FileOutput Module

7.1 Module

FileOutput Module

7.2 Uses

7.2.1 Imported Types

HardwareInput: (Voltage : real ; Time : real; Temperature : real; Current : real)
UserInput: (SamplingRate : real; SampleLength : real; SampleWidth : real; Filename : string Name : string; SampleName : string; Date : string)

7.2.2 Imported Access Programs

GetResistivity(): Real GetResistance(): Real GetUserInput(): UserInput

GetHardwareInput(): HardwareInput

7.3 Syntax

7.3.1 Exported Constants

N/A

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
FileInit()			
WriteUserInput()	string, string, string, real real,		INVALID
	real		
Write Sample Output ()	real, real, real, real, real	record	INVALID

7.4 Semantics

7.4.1 State Variables

N/A

7.4.2 State Invariant

7.4.3 Environment Variables

OutputFile: a file used to store data such as the user inputs and hardware outputs

7.4.4 Assumptions

FileInit() is called before any other access program.

7.4.5 Access Routine Semantics

FileInit():

• transition: Initializes an empty file

• exception: none

WriteUserInput(Name, SampleName, Date, SamplingRate, SampleLength, SampleWidth):

- transition: Write user input into the first line of the OutputFile
- exception: $exc := SamplingRate \notin \mathbb{R} \vee SamplingRate < 0 \vee SampleLength \notin \mathbb{R} \vee SampleLength < 0 | lorSampleWidth \notin \mathbb{R} \vee SampleWidth < 0 \Rightarrow INVALID$

WriteSampleOutput(Time, Temperature, Voltage, Current, Resistance, Resistivity):

- transition: Write each data set into the OutputFile at each time interval
- exception: $exc := Time \notin \mathbb{R} \lor Time < 0 \lor Temperature \notin \mathbb{R} \lor Voltage < 0 \lor Voltage \notin \mathbb{R} \lor Current < 0 \lor Current \notin \mathbb{R} \lor Resistance < 0 \lor Resistance \notin \mathbb{R} \lor Resistivity < 0 \lor Resistance \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

7.4.6 Local Functions

8 MIS of Graphical Output Module

8.1 Module

File Output Module

8.2 Uses

8.2.1 Imported Types

HardwareInput: (Voltage: real; Time: real; Temperature: real; Current: real)

8.2.2 Imported Access Programs

GetResistivity(): Real GetResistance(): Real GetHardwareInput(): HardwareInput

8.3 Syntax

8.3.1 Exported Constants

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
GraphInit()			
GraphTimeVResistance()	real, real		INVALID
GraphTimeVResistivity()	real, real		INVALID
GraphVoltageVResistence()	real, real		INVALID
GraphVoltageVResistivity()	real, real		INVALID
GraphTemperatureVResistence()	real, real		INVALID
GraphTemperatureVResistivity()	real, real		INVALID

8.4 Semantics

8.4.1 State Variables

N/A

8.4.2 State Invariant

N/A

8.4.3 Environment Variables

ApplicationWindow: the screen inferface where the information displayed to the user

8.4.4 Assumptions

GraphInit() is called before any other access program

8.4.5 Access Routine Semantics

GraphInit():

- transition: Graph is initialized on ApplicationWindow
- exception: none

GraphTimeVResistance(Time, Resistance):

- transition: Disaply graph of Time versus Resistance on ApplicationWindow
- exception: $exc := Time \notin \mathbb{R} \lor Time < 0 \lor Resistance \notin \mathbb{R} \lor Resistance < 0 \Rightarrow INVALID$

GraphTimeVResistivity(Time, Resistivity):

- transition: Display graph of Time versus Resistivity on Application Window
- exception: $exc := Time \notin \mathbb{R} \lor Time < 0 \lor Resistivity \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

GraphVoltageVResistance(Voltage, Resistance):

- transition: Display graph of Voltage versus Resistance on ApplicationWindow
- exception: $exc := Voltage \notin \mathbb{R} \lor Voltage < 0 \lor Resistance \notin \mathbb{R} \lor Resistance < 0 \Rightarrow INVALID$

GraphVoltageVResistivity(Voltage, Resistivity):

- transition: Display graph of Voltage versus Resistivity on ApplicationWindow
- exception: $exc := Voltage \notin \mathbb{R} \lor Voltage < 0 \lor Resistivity \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

GraphTemperatureVResistance(Temperature, Resistance):

- transition: Display graph of Temperature versus Resistance on ApplicationWindow
- exception: $exc := Temperature \notin \mathbb{R} \lor Resistance \notin \mathbb{R} \lor Resistance < 0 \Rightarrow INVALID$ GraphTemperatureVResistivity(Temperature, Resistivity):
 - transition: Display graph of Temperature versus Resistivity on ApplicationWindow
 - exception: $exc := Temperature \notin \mathbb{R} < Resistivity \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

8.4.6 Local Functions

9 MIS of Calculation Module

9.1 Module

Calculation

9.2 Uses

9.2.1 Imported Types

HardwareInput:

(Voltage: real; Time: real; Temperature: real; Current: real)

UserInput:

 $(\ Sampling Rate: real;\ Sample Length: real;\ Sample Width: real;\ Filename: string;$

Name: string; SampleName: string; Date: string)

9.2.2 Imported Access Programs

getHardwareInput(): HardwareInput

getUserInput(): UserInput

9.3 Syntax

9.3.1 Exported Constants

N/A

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
getResistance()	-	Real	INVALID
getResistivity()	-	Real	INVALID

9.4 Semantics

9.4.1 State Variables

Resistance: The calculated resistance value (real) Resistivity: The calculated resistivity value (real)

SampleArea: The calculated area of sample based on the length and width from user's input

9.4.2 State Invariants

Resistance ≥ 0 Resistivity ≥ 0 SampleArea ≥ 0

9.4.3 Environment Variables

N/A

9.4.4 Assumptions

We assume that the user may enter invalid values for inputs such as characters, empty spaces etc.. This will cause the program to throw and INVALID exception. This type of programmer error is also captured in the UserInputValidation Module to improve redundancy.

9.4.5 Access Routine Semantics

getResistance():

- transition: N/A
- output: out:= Resistance
- exception: $exc := Resistance \notin \mathbb{R} \lor Resistance < 0 \Rightarrow INVALID$

getResistivity():

- transition: N/A
- output: out := Resistivity
- exception: $exc := Resistivity \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

9.4.6 Local Functions

findSampleArea(SampleLength, SampleWidth)

• transition: SampleArea := SampleLength x SampleWidth

calcResistance(voltage, current):

- transition: Resistance := voltage/current
- exception: $exc := voltage \notin \mathbb{R} \lor voltage < 0$ $\lor current \notin \mathbb{R} \lor current < 0$ $\Rightarrow INVALID$

calc Resistivity (Resistance, Sample Area, Sample Length):

• transition: Resistivity := (resistance x SampleArea)/SampleLength

```
• exception: exc := voltage \notin \mathbb{R} \lor voltage < 0
 \lor current \notin \mathbb{R} \lor current < 0
 \Rightarrow INVALID
```

10 MIS of UserInputValidation Module

10.1 Module

UserInputValidation

10.2 Uses

10.2.1 Imported Types

UserInput:

(SamplingRate : real; SampleLength : real; SampleWidth : real; Filename : string; Name : string; SampleName : string; Date : string)

10.3 Syntax

10.3.1 Exported Constants

N/A

10.3.2 Exported Access Programs

Name	In	Out	Exceptions
getUserInput()	-	ADT (UserInput)	INVALID

10.4 Semantics

10.4.1 State Variables

N/A

10.4.2 State Invariants

N/A

10.4.3 Environment Variables

N/A

10.4.4 Assumptions

We assume that the user may enter invalid values for inputs such as characters, empty spaces etc.. This will cause the program to throw and INVALID exception.

10.4.5 Access Routine Semantics

getUserInput():

- output: out:= UserInput
- exception: $exc := validateFileData \neq TRUE \lor validateSampleData \neq TRUE \Rightarrow INVALID$

10.4.6 Local Functions

valdiateFileData(Filename, Date, Name):

- output: out:= TRUE
- exception: $exc := Filename.type \neq STRING \lor$ $Date.type \neq STRING \lor$ $Name.type \neq STRING$ $\Rightarrow INVALID$

validateSampleData(SamplingRate, SampleLength, SampleWidth):

- output: out:= TRUE
- exception: $exc := SamplingRate \notin \mathbb{R} \lor SamplingRate < 0 \lor SampleLength \notin \mathbb{R} \lor SampleLength < 0 \lor SampleWidth \notin \mathbb{R} \lor SampleWidth < 0 \Rightarrow INVALID$

11 MIS of HardwareInputValidation Module

11.1 Module

Hardware Input Validation

11.2 Uses

11.2.1 Imported Types

HardwareInput:

 $(\ Voltage: real\ ;\ Time: real;\ Temperature: real;\ Current: real\)$

11.3 Syntax

11.3.1 Exported Constants

N/A

11.3.2 Exported Access Programs

Name	In	Out	Exceptions
getHardwareInput()	-	ADT (HardwareInput)	INVALID

11.4 Semantics

11.4.1 State Variables

N/A

11.4.2 State Invariants

N/A

11.4.3 Environment Variables

N/A

11.4.4 Assumptions

11.4.5 Access Routine Semantics

getHardwareInput():

- output: out:= HardwareInput
- exception: $exc := validateParameters \neq TRUE \Rightarrow INVALID$

11.4.6 Local Functions

validateParameters(Voltage, Time, Current):

- \bullet output: out:= TRUE
- exception: $exc := Voltage < 0 \lor Time < 0 \lor Current < 0$ $\Rightarrow INVALID$

References

Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. Fundamentals of Software Engineering. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.

Daniel M. Hoffman and Paul A. Strooper. Software Design, Automated Testing, and Maintenance: A Practical Approach. International Thomson Computer Press, New York, NY, USA, 1995. URL http://citeseer.ist.psu.edu/428727.html.

12 Appendix

 $[{\bf Extra~information~if~required~-\!SS}]$