Module Interface Specification for Measuring Microstructure Changes During Thermal Treatment

Team #30, ReSprint
Edwin Do
Joseph Braun
Timothy Chen
Abdul Nour Seddiki
Tyler Magarelli

 $January\ 18,\ 2023$

1 Revision History

Date	Name	Notes
Jan 17, 2023	Timothy Chen	Added Modules to Module Decomposition
Jan 18, 2023	Timothy Chen	Added Current State Module
Jan 18, 2023	Timothy Chen	Added File Output Module
Jan 18, 2023	Timothy Chen	Added Graphical Output Module
Jan 18 2023	Edwin Do	Added MIS info for UserInputValidation, HardwareInput-Validation, and Calculation Modules
Jan 18 2023	Edwin Do	Added state invariants

2 Symbols, Abbreviations and Acronyms

See SRS Documentation at [give url —SS] [Also add any additional symbols, abbreviations or acronyms —SS]

Contents

1	Rev	vision History							
2	Symbols, Abbreviations and Acronyms								
3	Intr	roduction	-						
4	Not	cation	-						
5	Mo	dule Decomposition							
6	MIS	MIS of Input Communication Module							
	6.1	Module							
	6.2	Uses							
		6.2.1 Imported Types							
	6.3	Syntax							
		6.3.1 Exported Constants							
		6.3.2 Exported Access Programs							
	6.4	Semantics							
		6.4.1 State Variables							
		6.4.2 State Invariant							
		6.4.3 Environment Variables							
		6.4.4 Assumptions							
		6.4.5 Access Routine Semantics							
		6.4.6 Local Functions							
7	MIS	S of Output Communication Module							
	7.1	Module							
	7.2	Uses							
		7.2.1 Imported Types							
		7.2.2 Imported Access Programs							
	7.3	Syntax							
		7.3.1 Exported Constants							
		7.3.2 Exported Access Programs							
	7.4	Semantics							
	1.1	7.4.1 State Variables							
		7.4.2 State Invariant							
		7.4.3 Environment Variables							
		7.4.4 Assumptions							
		±							
		7.4.6 Local Functions							

8	MIS	of Re	emote Access Module	6
	8.1	Module	e	6
	8.2	Uses .		6
		8.2.1	Imported Types	6
	8.3	Syntax	[6
		8.3.1	Exported Constants	6
		8.3.2	Exported Access Programs	6
	8.4	Seman	tics	6
		8.4.1	State Variables	6
		8.4.2	State Invariant	6
		8.4.3	Environment Variables	6
		8.4.4	Assumptions	6
		8.4.5	Access Routine Semantics	6
		8.4.6	Local Functions	7
9	MIS		irrent State Module	8
	9.1		e	8
	9.2			8
		9.2.1	Imported Types	8
		9.2.2	Imported Access Programs	8
	9.3	Syntax	• • • • • • • • • • • • • • • • • • • •	8
		9.3.1	Exported Constants	8
		9.3.2	Exported Access Programs	8
	9.4	Seman	tics	8
		9.4.1	State Variables	8
		9.4.2	State Invariant	8
		9.4.3	Environment Variables	9
		9.4.4	Assumptions	9
		9.4.5	Access Routine Semantics	9
		9.4.6	Local Functions	9
10	NATO	C TO		1 0
10			*	10
				10
	10.2			10
			1 31	10
	10.0			10
	10.3			10
			1	10
	10.4		1	10
	10.4			10
				10
				10
		10 4 2	Environment Variables	11

	10.4.4 Assumptions	11
	10.4.5 Access Routine Semantics	11
	10.4.6 Local Functions	11
		12
	Module	12
11.2	Uses	12
	11.2.1 Imported Types	12
44.0	11.2.2 Imported Access Programs	12
11.3	Syntax	12
	11.3.1 Exported Constants	12
	1	12
11.4		12
	11.4.1 State Variables	12
	11.4.2 State Invariant	12
	11.4.3 Environment Variables	12
	11.4.4 Assumptions	13
	11.4.5 Access Routine Semantics	13
	11.4.6 Local Functions	13
12 MI	S of Calculation Module	14
12.1	Module	14
	Uses	14
	12.2.1 Imported Types	14
	12.2.2 Imported Access Programs	14
12.3	Syntax	14
	12.3.1 Exported Constants	14
	12.3.2 Exported Access Programs	14
12.4	Semantics	14
1-11	12.4.1 State Variables	14
	12.4.2 State Invariants	15
		15
	12.4.4 Assumptions	15
	12.4.5 Access Routine Semantics	15
	12.4.6 Local Functions	15
	12.4.0 Local I differential and the second and the	10
		17
	Module	17
13.2	Uses	17
	13.2.1 Imported Types	17
13.3	Syntax	17
	13.3.1 Exported Constants	17
	13.3.2 Exported Access Programs	17

13.4	Semantics	17
	13.4.1 State Variables	17
	13.4.2 State Invariants	17
	13.4.3 Environment Variables	17
	13.4.4 Assumptions	18
	13.4.5 Access Routine Semantics	18
	13.4.6 Local Functions	18
14 MIS	of HardwareInputValidation Module	19
14.1	Module	19
14.2	Uses	19
	14.2.1 Imported Types	19
14.3	Syntax	19
	14.3.1 Exported Constants	19
	14.3.2 Exported Access Programs	19
14.4	Semantics	19
	14.4.1 State Variables	19
	14.4.2 State Invariants	19
	14.4.3 Environment Variables	19
	14.4.4 Assumptions	19
	14.4.5 Access Routine Semantics	20
	14.4.6 Local Functions	20
15 App	endix	22

3 Introduction

The following document details the Module Interface Specifications for [Fill in your project name and description—SS]

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at [provide the url for your repo —SS]

4 Notation

[You should describe your notation. You can use what is below as a starting point. —SS]

The structure of the MIS for modules comes from Hoffman and Strooper (1995), with the addition that template modules have been adapted from Ghezzi et al. (2003). The mathematical notation comes from Chapter 3 of Hoffman and Strooper (1995). For instance, the symbol := is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | ... | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by Measuring Microstructure Changes During Thermal Treatment.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	N	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$

The specification of Measuring Microstructure Changes During Thermal Treatment uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, Measuring Microstructure Changes During Thermal Treatment uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding	
	Input Communication Module
	Output Communication Module
	Remote Access Module
Behaviour-Hiding	Current State Module
_	FileOutput Module
	Graphical Output Module
	Calculation Module
Software Decision	User Input Validation Module
	Hardware Input Validation Module

Table 1: Module Hierarchy

6 MIS of Input Communication Module

6.1 Module

Input Communication Module

6.2 Uses

6.2.1 Imported Types

HardwareInput: (Voltage: real; Time: real; Temperature: real; Current: real)
UserInput: (SamplingRate: real; SampleLengthgth: real; SampleWidth: real; Filename: string; Name: string; SampleName: string; Date: string)

6.3 Syntax

6.3.1 Exported Constants

N/A

6.3.2 Exported Access Programs

Name	In	Out Exceptions
passUserInput()		UserInput
		(ADT)
passHardwareInput()		HardwareInput(ADT)

6.4 Semantics

6.4.1 State Variables

N/A

6.4.2 State Invariant

N/A

6.4.3 Environment Variables

6.4.4 Assumptions

The UserInput and HardwareInput are received correctly and are going to be validated by the validation modules.

6.4.5 Access Routine Semantics

passUserInput():

• output: out:= UserInput

passHardwareInput():

• output: out:= HardwareInput

6.4.6 Local Functions

N/A

7 MIS of Output Communication Module

7.1 Module

Output Communication Module

7.2 Uses

7.2.1 Imported Types

HardwareInput: (Voltage: real; Time: real; Temperature: real; Current: real)
UserInput: (SamplingRate: real; SampleLengthgth: real; SampleWidth: real; Filename: string; Name: string; SampleName: string; Date: string)

7.2.2 Imported Access Programs

GetResistivity(): Real GetResistance(): Real GetUserInput(): UserInput

GetHardwareInput(): HardwareInput

7.3 Syntax

7.3.1 Exported Constants

7.3.2 Exported Access Programs

Name	In	Out Exceptions	
passUserInput()		UserInput	
(ADT)		(ADT)	
passHardwareInput()		HardwareInput(ADT)	
passResistivity()		Real	
passResistance()		Real	

7.4 Semantics

7.4.1 State Variables

N/A

7.4.2 State Invariant

N/A

7.4.3 Environment Variables

7.4.4 Assumptions

The values have been validated by the validation module.

7.4.5 Access Routine Semantics

passUserInput():

• output: out:= UserInput

passHardwareInput():

• output: out:= HardwareInput

passResistivity():

• output: out:= resisitivity (real)

passResistance():

• output: out:= resistance (real)

7.4.6 Local Functions

8 MIS of Remote Access Module

8.1 Module

Remote Access Module

8.2 Uses

8.2.1 Imported Types

userNameInput: string passwordInput: string

8.3 Syntax

8.3.1 Exported Constants

N/A

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
connect()	string, string		INVALID
$\operatorname{disconnect}()$			
stop()			

8.4 Semantics

8.4.1 State Variables

userName: string password: string

8.4.2 State Invariant

N/A

8.4.3 Environment Variables

8.4.4 Assumptions

connect() is called before any other routine

8.4.5 Access Routine Semantics

connect():

• transition: Connects to the application and user can view the ApplicationWindow

• exception: $exc := userNameInput \neq userName \lor passwordInput \neq password \Rightarrow INVALID$

disconnect():

- transition: Display message informing that the user has been disconnected from the application.
- exception: none

stop():

- transition: Display message that the stop was performed.
- exception: none

8.4.6 Local Functions

checkUserName(userNameInput):

- \bullet output: out := TRUE
- exception: none

checkUserName(passwordInput):

- output: out := TRUE
- exception: none

9 MIS of Current State Module

9.1 Module

Current State Module

9.2 Uses

9.2.1 Imported Types

 ${\bf Hardware Input:}\ (\ Voltage: real\ ;\ Time: real;\ Temperature: real;\ Current: real\)$

UserInput: (SamplingRate: real; SampleLengthgth: real; SampleWidth: real; Filename:

string; Name: string; SampleName: string; Date: string)

9.2.2 Imported Access Programs

GetUserInput(): UserInput

GetHardwareInput(): HardwareInput

9.3 Syntax

9.3.1 Exported Constants

N/A

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
StateInit()			
DisplayUserInfo()	string, string, string, string,		INVALID
	real, real, real		
${\bf Display Hardware State}()$	real, real, real		INVALID

9.4 Semantics

9.4.1 State Variables

N/A

9.4.2 State Invariant

9.4.3 Environment Variables

ApplicationWindow: the screen inferface where the information displayed to the user

9.4.4 Assumptions

StateInit() is called before any other access program

9.4.5 Access Routine Semantics

StateInit():

• transition: State Display is initialized on ApplicationWindow

• exception: none

DisplayUserInfo(Name, SampleName, Date, Filename, SamplingRate, SampleLength, SampleWidth):

- transition: Display Name, SampleName Date, Filename, SamplingRate, SampleLength, and SampleWidth on the ApplicationWindow
- exception: $exc := SamplingRate \notin \mathbb{R} \vee SamplingRate < 0 \vee SampleLength \notin \mathbb{R} \vee SampleLength < 0 \vee SampleWidth \notin \mathbb{R} \vee SampleWidth < 0 \Rightarrow INVALID$

DisplayHardwareState(Voltage, Current, Time, Temperature):

- transition: Display Voltage, Current, and Time on the ApplicationWindow
- exception: $exc := Voltage \notin \mathbb{R} \lor Voltage < 0 \lor Current \notin \mathbb{R} \lor Current < 0 \lor Time \notin \mathbb{R} \lor Time < 0 \lor Temperature \notin \mathbb{R} \Rightarrow INVALID$

9.4.6 Local Functions

10 MIS of FileOutput Module

10.1 Module

FileOutput Module

10.2 Uses

10.2.1 Imported Types

HardwareInput: (Voltage : real ; Time : real; Temperature : real; Current : real)
UserInput: (SamplingRate : real; SampleLength : real; SampleWidth : real; Filename : string Name : string; SampleName : string; Date : string)

10.2.2 Imported Access Programs

GetResistivity(): Real GetResistance(): Real GetUserInput(): UserInput

GetHardwareInput(): HardwareInput

10.3 Syntax

10.3.1 Exported Constants

N/A

10.3.2 Exported Access Programs

Name	In	Out	Exceptions
FileInit()			
WriteUserInput()	string, string, string, real real,		INVALID
	real		
${\bf Write Sample Output ()}$	real, real, real, real, real	record	INVALID

10.4 Semantics

10.4.1 State Variables

N/A

10.4.2 State Invariant

10.4.3 Environment Variables

OutputFile: a file used to store data such as the user inputs and hardware outputs

10.4.4 Assumptions

FileInit() is called before any other access program.

10.4.5 Access Routine Semantics

FileInit():

• transition: Initializes an empty file

• exception: none

WriteUserInput(Name, SampleName, Date, SamplingRate, SampleLength, SampleWidth):

- transition: Write user input into the first line of the OutputFile
- exception: $exc := SamplingRate \notin \mathbb{R} \vee SamplingRate < 0 \vee SampleLength \notin \mathbb{R} \vee SampleLength < 0 lorSampleWidth \notin \mathbb{R} \vee SampleWidth < 0 \Rightarrow INVALID$

WriteSampleOutput(Time, Temperature, Voltage, Current, Resistance, Resistivity):

- transition: Write each data set into the OutputFile at each time interval
- exception: $exc := Time \notin \mathbb{R} \lor Time < 0 \lor Temperature \notin \mathbb{R} \lor Voltage < 0 \lor Voltage \notin \mathbb{R} \lor Current < 0 \lor Current \notin \mathbb{R} \lor Resistance < 0 \lor Resistance \notin \mathbb{R} \lor Resistivity < 0 \lor Resistance \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

10.4.6 Local Functions

11 MIS of Graphical Output Module

11.1 Module

File Output Module

11.2 Uses

11.2.1 Imported Types

HardwareInput: (Voltage: real; Time: real; Temperature: real; Current: real)

11.2.2 Imported Access Programs

GetResistivity(): Real GetResistance(): Real GetHardwareInput(): HardwareInput

11.3 Syntax

11.3.1 Exported Constants

11.3.2 Exported Access Programs

Name	In	Out	Exceptions
GraphInit()			
GraphTimeVResistance()	real, real		INVALID
GraphTimeVResistivity()	real, real		INVALID
GraphVoltageVResistence()	real, real		INVALID
GraphVoltageVResistivity()	real, real		INVALID
GraphTemperatureVResistence()	real, real		INVALID
GraphTemperatureVResistivity()	real, real		INVALID

11.4 Semantics

11.4.1 State Variables

N/A

11.4.2 State Invariant

N/A

11.4.3 Environment Variables

ApplicationWindow: the screen inferface where the information displayed to the user

11.4.4 Assumptions

GraphInit() is called before any other access program

11.4.5 Access Routine Semantics

GraphInit():

- transition: Graph is initialized on ApplicationWindow
- exception: none

GraphTimeVResistance(Time, Resistance):

- transition: Disaply graph of Time versus Resistance on ApplicationWindow
- exception: $exc := Time \notin \mathbb{R} \lor Time < 0 \lor Resistance \notin \mathbb{R} \lor Resistance < 0 \Rightarrow INVALID$

GraphTimeVResistivity(Time, Resistivity):

- transition: Display graph of Time versus Resistivity on ApplicationWindow
- exception: $exc := Time \notin \mathbb{R} \lor Time < 0 \lor Resistivity \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

GraphVoltageVResistance(Voltage, Resistance):

- transition: Display graph of Voltage versus Resistance on ApplicationWindow
- exception: $exc := Voltage \notin \mathbb{R} \lor Voltage < 0 \lor Resistance \notin \mathbb{R} \lor Resistance < 0 \Rightarrow INVALID$

GraphVoltageVResistivity(Voltage, Resistivity):

- transition: Display graph of Voltage versus Resistivity on ApplicationWindow
- exception: $exc := Voltage \notin \mathbb{R} \lor Voltage < 0 \lor Resistivity \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

GraphTemperatureVResistance(Temperature, Resistance):

- transition: Display graph of Temperature versus Resistance on ApplicationWindow
- exception: $exc := Temperature \notin \mathbb{R} \lor Resistance \notin \mathbb{R} \lor Resistance < 0 \Rightarrow INVALID$ GraphTemperatureVResistivity(Temperature, Resistivity):
 - transition: Display graph of Temperature versus Resistivity on ApplicationWindow
 - exception: $exc := Temperature \notin \mathbb{R} < Resistivity \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

11.4.6 Local Functions

12 MIS of Calculation Module

[Use labels for cross-referencing —SS]

[You can reference SRS labels, such as R??.—SS]

[It is also possible to use LATEX for hypperlinks to external documents. —SS]

12.1 Module

Calculation

12.2 Uses

12.2.1 Imported Types

HardwareInput:

(Voltage: real; Time: real; Temperature: real; Current: real)

UserInput:

(SamplingRate : real; SampleLength : real; SampleWidth : real; Filename : string;

Name: string; SampleName: string; Date: string)

12.2.2 Imported Access Programs

getHardwareInput(): HardwareInput

getUserInput(): UserInput

12.3 Syntax

12.3.1 Exported Constants

N/A

12.3.2 Exported Access Programs

Name	In	Out	Exceptions
getResistance()	-	Real	INVALID
getResistivity()	-	Real	INVALID

12.4 Semantics

12.4.1 State Variables

Resistance: The calculated resistance value (real) Resistivity: The calculated resistivity value (real)

Sample Area: The calculated area of sample based on the length and width from user's input

12.4.2 State Invariants

Resistance ≥ 0 Resistivity ≥ 0 SampleArea ≥ 0

12.4.3 Environment Variables

N/A

12.4.4 Assumptions

We assume that the user may enter invalid values for inputs such as characters, empty spaces etc.. This will cause the program to throw and INVALID exception. This type of programmer error is also captured in the UserInputValidation Module to improve redundancy.

12.4.5 Access Routine Semantics

getResistance():

- transition: N/A
- output: out:= Resistance
- exception: $exc := Resistance \notin \mathbb{R} \lor Resistance < 0 \Rightarrow INVALID$

getResistivity():

- transition: N/A
- output: out := Resistivity
- exception: $exc := Resistivity \notin \mathbb{R} \lor Resistivity < 0 \Rightarrow INVALID$

12.4.6 Local Functions

find Sample Area (Sample Length, Sample Width)

 \bullet transition: SampleArea := SampleLength x SampleWidth

calcResistance(voltage, current):

- transition: Resistance := voltage/current
- exception: $exc := voltage \notin \mathbb{R} \lor voltage < 0$ $\lor current \notin \mathbb{R} \lor current < 0$ $\Rightarrow INVALID$

calc Resistivity (Resistance, Sample Area, Sample Length):

• transition: Resistivity := (resistance x SampleArea)/SampleLength

```
• exception: exc := voltage \notin \mathbb{R} \lor voltage < 0
 \lor current \notin \mathbb{R} \lor current < 0
 \Rightarrow INVALID
```

13 MIS of UserInputValidation Module

[Use labels for cross-referencing —SS]
[You can reference SRS labels, such as R??. —SS]
[It is also possible to use LATEX for hypperlinks to external documents. —SS]

13.1 Module

UserInputValidation

13.2 Uses

13.2.1 Imported Types

UserInput:

(SamplingRate : real; SampleLength : real; SampleWidth : real; Filename : string; Name : string; SampleName : string; Date : string)

13.3 Syntax

13.3.1 Exported Constants

N/A

13.3.2 Exported Access Programs

Name	In	Out	Exceptions
getUserInput()	-	ADT (UserInput)	INVALID

13.4 Semantics

13.4.1 State Variables

N/A

13.4.2 State Invariants

N/A

13.4.3 Environment Variables

13.4.4 Assumptions

We assume that the user may enter invalid values for inputs such as characters, empty spaces etc.. This will cause the program to throw and INVALID exception.

13.4.5 Access Routine Semantics

getUserInput():

- output: out:= UserInput
- exception: $exc := validateFileData \neq TRUE \lor validateSampleData \neq TRUE \Rightarrow INVALID$

13.4.6 Local Functions

valdiateFileData(Filename, Date, Name):

- output: out:= TRUE
- exception: $exc := Filename.type \neq STRING \lor$ $Date.type \neq STRING \lor$ $Name.type \neq STRING$ $\Rightarrow INVALID$

validateSampleData(SamplingRate, SampleLength, SampleWidth):

- output: out:= TRUE
- exception: $exc := SamplingRate \notin \mathbb{R} \lor SamplingRate < 0 \lor SampleLength \notin \mathbb{R} \lor SampleLength < 0 \lor SampleWidth \notin \mathbb{R} \lor SampleWidth < 0$ $\Rightarrow INVALID$

14 MIS of HardwareInputValidation Module

[Use labels for cross-referencing —SS]
[You can reference SRS labels, such as R??. —SS]
[It is also possible to use LATEX for hypperlinks to external documents. —SS]

14.1 Module

HardwareInputValidation

14.2 Uses

14.2.1 Imported Types

HardwareInput:

(Voltage: real; Time: real; Temperature: real; Current: real)

14.3 Syntax

14.3.1 Exported Constants

N/A

14.3.2 Exported Access Programs

Name	In	Out	Exceptions
getHardwareInput()	-	ADT (HardwareInput)	INVALID

14.4 Semantics

14.4.1 State Variables

N/A

14.4.2 State Invariants

N/A

14.4.3 Environment Variables

N/A

14.4.4 Assumptions

14.4.5 Access Routine Semantics

getHardwareInput():

- output: out:= HardwareInput
- exception: $exc := validateParameters \neq TRUE \Rightarrow INVALID$

14.4.6 Local Functions

validateParameters(Voltage, Time, Current):

- \bullet output: out:= TRUE
- exception: $exc := Voltage < 0 \lor Time < 0 \lor Current < 0$ $\Rightarrow INVALID$

References

Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. Fundamentals of Software Engineering. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.

Daniel M. Hoffman and Paul A. Strooper. Software Design, Automated Testing, and Maintenance: A Practical Approach. International Thomson Computer Press, New York, NY, USA, 1995. URL http://citeseer.ist.psu.edu/428727.html.

15 Appendix

 $[{\bf Extra~information~if~required~--SS}]$