Query Doctor

Same rows. Faster. Or the doctor *won't sign.*

Executes the original and the rewrite on Zetaris; signs only when the rows match. Hero: **2.11×** over 10 paired runs.

Case report hero-r1 — ACCEPTED

SPECIMEN · THE REWRITE DROPS THE STRUCK LINE

```
SELECT COUNT(1) AS n
FROM   TPCDS_DB.store_sales ss
~~LEFT JOIN TPCDS_DB.promotion p ON ss.ss_promo_sk = p.p_promo_sk~~
WHERE  ss.ss_customer_sk IS NULL
```

RESULTS VS REFERENCE · MEDIAN OF 3 ALTERNATING PAIRS



original	87cd00c5
rewrite	**87cd00c5**

ROW-IDENTICAL · 87CD00C5

Verified by **Verifier** — code, no model · 2.1× median, 3/3 pairs faster

landing + this deck
querydoc-flax.vercel.app

PROBLEM · WHO SIGNS OFF

Faster can still be *wrong*.

```
  SELECT COUNT(1) AS n
  FROM   TPCDS_DB.store_sales ss
- LEFT JOIN TPCDS_DB.promotion p
-   ON ss.ss_item_sk = p.p_item_sk
  WHERE  ss.ss_customer_sk IS NULL
```

original count	129,776
after the edit	129,752

Reviewers see one deleted line. Analytics engineers sign off on that diff before it merges.

SOLUTION

A model proposes. *Code decides.*

MODEL

Diagnoser

Reads the plan and the join key.

MODEL

Rewriter

One rewrite per hypothesis.

CODE

Verifier

Executes both, compares rows, times pairs.

1. original runs twice — deterministic?
2. same columns and types
3. 0 rows differ (or equal row hash)
4. ≥ 1.2×, saving > 1,782.9 ms, most pairs won


CODE

Orchestrator

Sequences, retries, remembers refusals.


WORKFLOW · ARCHITECTURE

Every rewrite passes *one gate.*



PRODUCT

The report a reviewer *signs*.



1 Verdict and stamp, first.

2 Measured bars: original vs rewrite.

3 Agent trace: every engine and model call.

THE MOMENT

One edit. Two keys. *Two verdicts.*

Case report hero-r1 ACCEPTED

```
LEFT JOIN TPCDS_DB.promotion p
  ON ss.ss_promo_sk = p.p_promo_sk
```

ON p_promo_sk — 300 of 300 distinct

fingerprint 87cd00c5 = 87cd00c5
2.1× median · 3/3 pairs faster

ROW-IDENTICAL · 87CD00C5

Case report hero-trap-r1 REFUSED

```
LEFT JOIN TPCDS_DB.promotion p
  ON ss.ss_item_sk = p.p_item_sk
```

ON p_item_sk — 291 of 300 distinct

fingerprint e51f9da7 ≠ 87cd00c5
first differing row 129752

REFUSED · ROW_DIFF

EVIDENCE

Measured on the engine, *not estimated.*


2.1×

live hero verdict

hero-r1 · 3/3 pairs
hero-r2 · 2.15×
fingerprint 87cd00c5

2.11×

bench, 10 alternating pairs



6 / 15

baseline changed rows

one model call, same Verifier
Query Doctor shipped: 0



ZETARIS + METERLESS

Zetaris runs it. *Meterless remembers it.*

Zetaris

10	`run_sql` — pre-check, key profile, diff, timing
1	`EXPLAIN FORMATTED` — the plan
JDBC	local platform, no MCP endpoint

Meterless

2	H-MEM `open` + `query` — the playbook
1	Markovian `chunk` — attempt hand-off
mock	Nightshift — default provider, not run live

NVIDIA Nemotron 3 Ultra · 2 calls (diagnose, rewrite)

counts from the recorded trace of hero-r1 · Nightshift: 16 mock-runtime tests

STACK

Small, tested, *runs keyless.*

TypeScript

Node 22 · API + UI on :8000

Java sidecar

one warm JDBC connection to Zetaris

DuckDB

sample engine · NYC TLC subset

286

tests · 26 files · no keys

Docker

one command, SAMPLE_MODE=true

Built with

Cursor: scaffold d3e823c
Claude Code: every other commit

WHAT WAS UNIQUE

It keeps the *wrong answers.*

ON THE PAGE

Refused rewrites stay, struck through, with the differing row.

IN MEMORY

A repeat refusal comes from the ledger, not re-run.

IN THE REPORT

"Identical on the current data" — not a proof.

1 hypothesis h1 · REJECT (ROW_DIFF)

Rewriter's note — model text ~~Removed unnecessary LEFT JOIN to promotion table since no promotion columns are referenced and the join cannot affect the row count of a LEFT JOIN with COUNT(1).~~

rows differ: 1 vs 1 — first differing row ["129752"] (rewrite only)

▸SQL — diff against the original

2 hypothesis h1 · REJECT (ROW_DIFF)

Rewriter's note — model text ~~Replace LEFT OUTER JOIN with LEFT SEMI JOIN to preserve row-count semantics while avoiding broadcast hash join overhead by eliminating duplicate matches from non-unique p_item_sk.~~

rows differ: 1 vs 1 — first differing row ["2853"] (rewrite only)

▸SQL — diff against the original

3 hypothesis h2 · REJECT (ROW_DIFF)

Rewriter's note — model text ~~Removed the redundant LEFT JOIN to promotion table since no promotion columns are used and the join cannot affect COUNT(1) result~~

refusal reused from ledger mem-11 — same original-result fingerprint; not re-run

▸SQL — diff against the original

FUTURE

Next: queries *we didn't write.*

- ☐ A query set not designed by us, and the baseline on Zetaris
- ☐ Re-record the hero through a live Nightshift runtime
- ☐ Zetaris MCP intake (`get_slow_queries`) when an endpoint exists
- ☐ Write-back of an approved rewrite

querydoc-flax.vercel.app
landing · deck · recorded runs