

# SciPy和科学计算

黄书剑



# SciPy生态系统



- **SciPy (pronounced “Sigh Pie”) is a Python-based ecosystem of open-source software for mathematics, science, and engineering.**



NumPy

Base N-dimensional  
array package



SciPy library

Fundamental library for  
scientific computing



Matplotlib

Comprehensive 2-D  
plotting

IP[y]:  
IPython

IPython

Enhanced interactive  
console



SymPy

Symbolic mathematics



pandas

Data structures &  
analysis

- 函数、极限、连续
- 一元函数微分学及其应用
- 一元函数积分学及其应用
  
- 无穷级数
- 多元函数微分学及其应用
- 多元函数积分学及其应用

- 多项式
  - 行列式
  - 线性方程组
  - 矩阵
  - 二次型
- 
- 线性空间
  - 线性变换
  - 欧几里得空间
  - 双线性函数与辛空间

- 随机变量及其分布
- 随机变量数字特征
- 集中不等式
- 参数估计
- 假设检验
- 回归分析与方差分析



# 最优化方法

---

- 凸集合
- 凸函数
- 凸优化问题
- 对偶性
- 凸函数优化
- 平滑函数优化
- 随机优化
- 分布式优化
- 在线优化

## SCIPY简介

- The SciPy library is one of the core packages that make up the SciPy stack. It provides many user-friendly and efficient numerical routines:

- numerical integration 数值积分
- interpolation 插值
- optimization 优化
- linear algebra 线性代数
- statistics 统计

## Subpackage

cluster

constants

fftpack

integrate

interpolate

io

linalg

ndimage

odr

optimize

signal

sparse

spatial

special

stats

## Description

Clustering algorithms

Physical and mathematical constants

Fast Fourier Transform routines

Integration and ordinary differential equation solvers

Interpolation and smoothing splines

Input and Output

Linear algebra

N-dimensional image processing

Orthogonal distance regression

Optimization and root-finding routines

Signal processing

Sparse matrices and associated routines

Spatial data structures and algorithms

Special functions

Statistical distributions and functions

与基于符号的计算不同，SciPy侧重于针对具体数值进行计算和求解







scipy中有哪些可以用来解方程的函数？请给我一个简单的列表



GitHub Copilot


在Python的SciPy库中，以下函数可以用来求解方程：

1. `fsolve`：用于求解非线性方程组的根。
2. `root`：用于求解非线性方程组的根，提供了更多的方法选项。
3. `brentq`、`brenth`、`ridder`、`bisect`、`newton`：这些函数用于求解一元方程的根。
4. `linprog`：用于求解线性规划问题。
5. `leastsq`：用于求解最小二乘问题。

这些函数都可以用来求解方程，但是它们的使用方法和适用场景各不相同，你需要根据你的具体问题来选择合适的函数。




请给我一个fsolve的示例

 GitHub Copilot



在Python的SciPy库中，`fsolve` 函数可以用来求解非线性方程组的根。以下是一个示例：



```
from scipy.optimize import fsolve
import numpy as np

def equations(vars):
    x, y = vars
    eq1 = x**2 + y**2 - 20
    eq2 = y - x**2
    return [eq1, eq2]

x_initial_guess = 1
y_initial_guess = 1
solution = fsolve(equations, (x_initial_guess, y_initial_guess))

print('Solution:', solution)
```

在这个例子中，我们定义了一个函数 `equations`，它返回了两个方程 `eq1` 和 `eq2`。然后我们使用 `fsolve` 函数求解了这两个方程的根。我们提供了一个初始猜测值 `(x_initial_guess, y_initial_guess)`，`fsolve` 函数使用这个初始猜测值开始求解过程。最后，我们打印出了方程的解。

# LINEAR ALGEBRA

# scipy.linalg



- See also [numpy.linalg](#) for more linear algebra functions. Note that although [scipy.linalg](#) imports most of them, identically named functions from [scipy.linalg](#) may offer more or slightly differing functionality.
  - 矩阵计算
  - 特征值
  - 矩阵分解

## Basics



<code>inv(a[, overwrite_a, check_finite])</code>	Compute the inverse of a matrix.
<code>solve(a, b[, sym_pos, lower, overwrite_a, ...])</code>	Solves the linear equation set $\mathbf{a} * \mathbf{x} = \mathbf{b}$ for the unknown $\mathbf{x}$ for square $\mathbf{a}$ matrix.
<code>solve_banded(l_and_u, ab, b[, overwrite_ab, ...])</code>	Solve the equation $\mathbf{a} \mathbf{x} = \mathbf{b}$ for $\mathbf{x}$ , assuming $\mathbf{a}$ is banded matrix.
<code>solveh_banded(ab, b[, overwrite_ab, ...])</code>	Solve equation $\mathbf{a} \mathbf{x} = \mathbf{b}$ .
<code>solve_circulant(c, b[, singular, tol, ...])</code>	Solve $\mathbf{C} \mathbf{x} = \mathbf{b}$ for $\mathbf{x}$ , where $\mathbf{C}$ is a circulant matrix.
<code>solve_triangular(a, b[, trans, lower, ...])</code>	Solve the equation $\mathbf{a} \mathbf{x} = \mathbf{b}$ for $\mathbf{x}$ , assuming $\mathbf{a}$ is a triangular matrix.
<code>solve_toeplitz(c_or_cr, b[, check_finite])</code>	Solve a Toeplitz system using Levinson Recursion
<code>matmul_toeplitz(c_or_cr, x[, check_finite, ...])</code>	Efficient Toeplitz Matrix-Matrix Multiplication using FFT
<code>det(a[, overwrite_a, check_finite])</code>	Compute the determinant of a matrix
<code>norm(a[, ord, axis, keepdims, check_finite])</code>	Matrix or vector norm.
<code>lstsq(a, b[, cond, overwrite_a, ...])</code>	Compute least-squares solution to equation $\mathbf{A} \mathbf{x} = \mathbf{b}$ .
<code>pinv(a[, cond, rcond, return_rank, check_finite])</code>	Compute the (Moore-Penrose) pseudo-inverse of a matrix.
<code>pinv2(a[, cond, rcond, return_rank, ...])</code>	Compute the (Moore-Penrose) pseudo-inverse of a matrix.
<code>pinvh(a[, cond, rcond, lower, return_rank, ...])</code>	Compute the (Moore-Penrose) pseudo-inverse of a Hermitian matrix.
<code>kron(a, b)</code>	Kronecker product.
<code>khatri_rao(a, b)</code>	Khatri-rao product
<code>tril(m[, k])</code>	Make a copy of a matrix with elements above the $k$ th diagonal zeroed.
<code>triu(m[, k])</code>	Make a copy of a matrix with elements below the $k$ th diagonal zeroed.
<code>orthogonal_procrustes(A, B[, check_finite])</code>	Compute the matrix solution of the orthogonal Procrustes problem.
<code>matrix_balance(A[, permute, scale, ...])</code>	Compute a diagonal similarity transformation for row/column balancing.
<code>subspace_angles(A, B)</code>	Compute the subspace angles between two matrices.
<code>LinAlgError</code>	Generic Python-exception-derived object raised by linalg functions.
<code>LinAlgWarning</code>	The warning emitted when a linear algebra related operation is close to fail conditions of the algorithm or loss of accuracy is expected.

## Eigenvalue Problems

`eig(a[, b, left, right, overwrite_a, ...])`

Solve an ordinary or generalized eigenvalue problem of a square matrix.

`eigvals(a[, b, overwrite_a, check_finite, ...])`

Compute eigenvalues from an ordinary or generalized eigenvalue problem.

`eigh(a[, b, lower, eigvals_only, ...])`

Solve a standard or generalized eigenvalue problem for a complex Hermitian or real symmetric matrix.

`eigvalsh(a[, b, lower, overwrite_a, ...])`

Solves a standard or generalized eigenvalue problem for a complex Hermitian or real symmetric matrix.

`eig_banded(a_band[, lower, eigvals_only, ...])`

Solve real symmetric or complex Hermitian band matrix eigenvalue problem.

`eigvals_banded(a_band[, lower, ...])`

Solve real symmetric or complex Hermitian band matrix eigenvalue problem.

`eigh_tridiagonal(d, e[, eigvals_only, ...])`

Solve eigenvalue problem for a real symmetric tridiagonal matrix.

`eigvalsh_tridiagonal(d, e[, select, ...])`

Solve eigenvalue problem for a real symmetric tridiagonal matrix.



## Decompositions

---

`lu(a[, permute_l, overwrite_a, check_finite])`

`lu_factor(a[, overwrite_a, check_finite])`

`lu_solve(lu_and_piv, b[, trans, ...])`

`svd(a[, full_matrices, compute_uv, ...])`

`svdvals(a[, overwrite_a, check_finite])`

`diagsvd(s, M, N)`

`orth(A[, rcond])`

`null_space(A[, rcond])`

`ldl(A[, lower, hermitian, overwrite_a, ...])`

`cholesky(a[, lower, overwrite_a, check_finite])`

`cholesky_banded(ab[, overwrite_ab, lower, ...])`

`cho_factor(a[, lower, overwrite_a, check_finite])`

`cho_solve(c_and_lower, b[, overwrite_b, ...])`

`cho_solve_banded(cb_and_lower, b[, ...])`

Compute pivoted LU decomposition of a matrix.

Compute pivoted LU decomposition of a matrix.

Solve an equation system,  $a x = b$ , given the LU factorization of a Singular Value Decomposition.

Compute singular values of a matrix.

Construct the sigma matrix in SVD from singular values and size M, N.

Construct an orthonormal basis for the range of A using SVD

Construct an orthonormal basis for the null space of A using SVD

Computes the LDLt or Bunch-Kaufman factorization of a symmetric/ hermitian matrix.

Compute the Cholesky decomposition of a matrix.

Cholesky decompose a banded Hermitian positive-definite matrix

Compute the Cholesky decomposition of a matrix, to use in cho\_solve

Solve the linear equations  $A x = b$ , given the Cholesky factorization of A.

Solve the linear equations  $A x = b$ , given the Cholesky factorization of the banded Hermitian A.



# 线性代数运算示例

- 求给定线性方程组的解

```
In [133]: a = np.array([[1, 3, 1], [2, 1, 3], [2, 2, 1]])  
...: b = np.array([10, 13, 9])  
...:  
...: x = linalg.solve(a, b)  
...: x  
Out[133]: array([1., 2., 3.] )
```





# 线性代数运算示例

- 求给定矩阵的相关特征
  - 行列式、秩
  - 特征值等

```
In [134]: A1 = np.arange(1,  
10).reshape(3, 3)
```

```
In [135]: A1
```

```
Out[135]:
```

```
array([[1, 2, 3],  
       [4, 5, 6],  
       [7, 8, 9]])
```

```
In [137]: linalg.det(A1)
```

```
Out[137]: 0.0
```

```
In [138]: np.linalg.matrix_rank(A1)
```

```
Out[138]: 2
```

```
In [139]: l, v = linalg.eig(A1)
```

```
In [140]: print(l)
```

```
[ 1.61168440e+01+0.j -1.11684397e+00+0.j  
 -9.75918483e-16+0.j]
```

```
In [141]: print(v)
```

```
[[-0.23197069 -0.78583024  0.40824829]  
 [-0.52532209 -0.08675134 -0.81649658]  
 [-0.8186735   0.61232756  0.40824829]]
```

# OPTIMIZATION



## scipy.optimize

- 包含通过各种算法进行最优化（求极值）的函数；包括非线性优化、线性规划、求根、曲线拟合等
  - minimize\_scalar, minimize
  - linprog
  - curve\_fit
  - root\_scalar, root

[https://scipy-lectures.org/advanced/mathematical\\_optimization/](https://scipy-lectures.org/advanced/mathematical_optimization/)

# Optimization



## Scalar functions optimization

`minimize_scalar`(fun[, bracket, bounds, ...]) Minimization of scalar function of one variable.

The `minimize_scalar` function supports the following methods:

- `minimize_scalar(method='brent')`
- `minimize_scalar(method='bounded')`
- `minimize_scalar(method='golden')`

## Local (multivariate) optimization

`minimize`(fun, x0[, args, method, jac, hess, ...]) Minimization of scalar function of one or more variables.

The `minimize` function supports the following methods:

- `minimize(method='Nelder-Mead')`
- `minimize(method='Powell')`
- `minimize(method='CG')`
- `minimize(method='BFGS')`
- `minimize(method='Newton-CG')`
- `minimize(method='L-BFGS-B')`
- `minimize(method='TNC')`
- `minimize(method='COBYLA')`
- `minimize(method='SLSQP')`
- `minimize(method='trust-constr')`
- `minimize(method='dogleg')`
- `minimize(method='trust-ncg')`
- `minimize(method='trust-krylov')`
- `minimize(method='trust-exact')`



---

## Least-squares and curve fitting

---

### Nonlinear least-squares

---

`least_squares`(fun, x0[, jac, bounds, ...]) Solve a nonlinear least-squares problem with bounds on the variables.

### Linear least-squares

---

`nnls`(A, b[, maxiter]) Solve  $\arg\min_{\mathbf{x} \geq 0} \|\mathbf{Ax} - \mathbf{b}\|_2$  for  $\mathbf{x} \geq 0$ .

`lsq_linear`(A, b[, bounds, method, tol, ...]) Solve a linear least-squares problem with bounds on the variables.

### Curve fitting

---

`curve_fit`(f, xdata, ydata[, p0, sigma, ...]) Use non-linear least squares to fit a function, f, to data.



## Root finding

---

### Scalar functions

---

<code>root_scalar(f[, args, method, bracket, ...])</code>	Find a root of a scalar function.
<code>brentq(f, a, b[, args, xtol, rtol, maxiter, ...])</code>	Find a root of a function in a bracketing interval using Brent's method.
<code>brenth(f, a, b[, args, xtol, rtol, maxiter, ...])</code>	Find a root of a function in a bracketing interval using Brent's method with hyperbolic extrapolation.
<code>ridder(f, a, b[, args, xtol, rtol, maxiter, ...])</code>	Find a root of a function in an interval using Ridder's method.
<code>bisect(f, a, b[, args, xtol, rtol, maxiter, ...])</code>	Find root of a function within an interval using bisection.
<code>newton(func, x0[, fprime, args, tol, ...])</code>	Find a zero of a real or complex function using the Newton-Raphson (or secant or Halley's) method.
<code>toms748(f, a, b[, args, k, xtol, rtol, ...])</code>	Find a zero using TOMS Algorithm 748 method.
<code>RootResults(root, iterations, ...)</code>	Represents the root finding result.

## Linear programming

---

`linprog(c[, A_ub, b_ub, A_eq, b_eq, bounds, ...])` Linear programming: minimize a linear objective function subject to linear equality and inequality constraints.


The `linprog` function supports the following methods:

- `linprog(method='simplex')`
- `linprog(method='interior-point')`
- `linprog(method='revised simplex')`
- `linprog(method='highs-ipm')`
- `linprog(method='highs-ds')`
- `linprog(method='highs')`

# 最优化示例



```
In [156]: from scipy import optimize as opt
In [157]: def objective_function(x):
...:     return 4 * x ** 4 - 3 * x + 1
...:
In [159]: res = opt.minimize_scalar(objective_function)
...: print(res)
fun: -0.2878035228724982
nfev: 16
nit: 12
success: True
x: 0.5723571222032383
```








# 方程求根示例

```
In [164]: def func(x):
...:     return x * 3 + 2 * np.cos(x) + 1
...:
In [165]: sol = opt.root(func, 0)
In [166]: print(sol)
fjac: array([[ -1.]])
fun: array([2.88657986e-15])
message: 'The solution converged.'
nfev: 8
qtf: array([-3.42632855e-09])
r: array([-4.43264413])
status: 1
success: True
x: array([-0.79851442])
```





## 规划问题示例

- 生产甲、乙、丙三种产品，可以获得利润，但消耗A、B两种资源。现已知A、B的资源总量，求利润最大的生产方案。

$$\max x_0 \cdot 45 + x_1 \cdot 20 + x_2 \cdot 45$$

$$\text{s.t. } x_0 \cdot 2 + x_1 + x_2 \cdot 3 \leq 100$$

$$x_0 \cdot 3 + x_1 \cdot 2 + x_2 \cdot 3 \leq 120$$

$$x_0, x_1, x_2 \geq 0$$

$$\min c^T x$$

optimize.linprog(...)

$$\text{s.t. } \begin{cases} Ax \leq b \\ Aeq * x = beq \\ lb \leq x \leq ub \end{cases}$$

	甲	乙	丙	总量
A	2	1	3	100
B	3	2	3	120
利润	45	20	45	



## \*规划问题示例

- 做100套钢架，用长2.8，1.5的钢条各一根和2.3的钢条两根，现有所有原料长度为7，通过切割得到所需钢条，求最少需要多少钢条（单位为米）。

$$\min x_0 + x_1 + x_2 + x_3 + x_4$$

$$\text{s.t. } x_0 + x_1 * 2 \geq 100$$

$$x_0 + x_2 * 2 + x_3 \geq 200$$

$$x_0 + x_2 + x_3 * 3 + x_4 * 4 \geq 100$$

$$\min c^T x$$

optimize.linprog(...)

$$\text{s.t. } \begin{cases} Ax \leq b \\ Aeq * x = beq \\ lb \leq x \leq ub \end{cases}$$

2.8	2.3	1.5	
1	1	1	x0
2	0	0	x1
0	2	1	x2
0	1	3	x3
0	0	4	x4

整数线性规划：变量取值为整数（分支定界法）

# NUMERICAL INTEGRATION



## Integrating functions, given function object

<code>quad(func, a, b[, args, full_output, ...])</code>	Compute a definite integral.
<code>quad_vec(f, a, b[, epsabs, epsrel, norm, ...])</code>	Adaptive integration of a vector-valued function.
<code>dblquad(func, a, b, gfun, hfun[, args, ...])</code>	Compute a double integral.
<code>tplquad(func, a, b, gfun, hfun, qfun, rfun)</code>	Compute a triple (definite) integral.
<code>nquad(func, ranges[, args, opts, full_output])</code>	Integration over multiple variables.
<code>fixed_quad(func, a, b[, args, n])</code>	Compute a definite integral using fixed-order Gaussian quadrature.
<code>quadrature(func, a, b[, args, tol, rtol, ...])</code>	Compute a definite integral using fixed-tolerance Gaussian quadrature.
<code>romberg(function, a, b[, args, tol, rtol, ...])</code>	Romberg integration of a callable function or method.
<code>quad_explain([output])</code>	Print extra information about <code>integrate.quad()</code> parameters and returns.
<code>newton_cotes(rn[, equal])</code>	Return weights and error coefficient for Newton-Cotes integration.
<code>IntegrationWarning</code>	Warning on issues during integration.
<code>AccuracyWarning</code>	



## Integrating functions, given fixed samples

---

`trapezoid(y[, x, dx, axis])`

Integrate along the given axis using the composite trapezoidal rule.

`cumulative_trapezoid(y[, x, dx, axis, initial])`

Cumulatively integrate  $y(x)$  using the composite trapezoidal rule.

`simpson(y[, x, dx, axis, even])`

Integrate  $y(x)$  using samples along the given axis and the composite Simpson's rule.


`romb(y[, dx, axis, show])`

Romberg integration using samples of a function.



## 数值积分示例

```
In [167]: from scipy import integrate
In [168]: f = lambda x: np.exp(-x**2)
In [169]: integrate.quad(f, 0, 5)
#return the integration results and estimated error
Out[169]: (0.8862269254513955, 2.3183115159980698e-14)
```





- 针对特定科学计算问题的数值求解
  - 线性代数
  - 最优化
  - 数值积分
  - .....