#### Structure for indexing texts

# Thierry Lecroq Thierry.Lecroq@univ-rouen.fr

Laboratoire d'Informatique, du Traitement de l'Information et des Systèmes.

International PhD School in Formal Languages and Applications

Tarragona, November 20th and 21st, 2006





#### Plan

- Introduction
- 2 Suffix Tree
- Suffix Automaton
- 4 Compact Suffix Automaton



#### **Plan**

- Introduction
- **Suffix Automaton**
- Compact Suffix Automaton





#### **Indexes**

- Pattern matching in static texts
- Basic operations
  - existence of patterns in the text
  - number of occurrences of patterns
  - list of positions of occurrences
- Other applications
  - finding repetitions in texts
  - finding regularities in texts
  - approximate matchings
  - . . .



### Implementation of indexes

suffix of text		
pattern		

#### Implementation

with efficient data structures

- Suffix Trees digital trees, PATRICIA tree (compact trees)
- Suffix Automata or DAWG's minimal automata, compact automata

with efficient algorithm

Suffix Arrays
 binary search in the ordered list of suffixes



Introduction

#### Efficient constructions

- Position tree, suffix tree [Weiner 1973], [McCreight, 1976], [Ukkonen, 1992] [Farach, 1997]
- Suffix DAWG, suffix automaton, factor automaton [Blumer et al., 1983], [Crochemore, 1984]
- Suffix array, PAT array [Manber, Myers, 1993], [Gonnet, 1987] [Kärkkäinen, Sanders, 2003] [Kim et al., 2003], [Ko, Aluru, 2003]
- Some other implementations of suffix trees [Andersson, Nilsson, 1993] [Irving, 1995] [Kärkkäinen, 1995], [Munro et al., 1999]
- For external memory (*SB-trees*) [Ferragina, Grossi, 1995]
- Compact suffix automaton [Crochemore, Vérin, 1997], [Inenaga et al., 2001]





#### **Suffixes**

 $\mathsf{Text}\ y \in \Sigma^*$ 

- Suff(y) = set of suffixes of y,
- card Suff(y) = |y| + 1

#### **Example**

Suff(ababbb)

$$rac{i}{y[i]}$$
 0 1 2 3 4 5  $rac{}{}$  b a b b

position

a	b	a	b	Ъ	b	0
	b	a	b	Ъ	b	1
		a	b	Ъ	b	2
			b	Ъ	b	3
				Ъ	b	4
					h	5

 $\varepsilon$  6 (empty string)



#### **Plan**

Introduction

- 2 Suffix Tree
- **Suffix Automaton**
- Compact Suffix Automaton



**Suffix Automaton** 



#### Trie of suffixes

Introduction


Text  $y \in \Sigma^*$ , Suff (y) set of suffixes of yT(y) =digital tree which branches are labeled by suffixes of y= tree-like deterministic automaton accepting Suff(y)

- Nodes identified with subwords of y
- Terminal nodes identified with suffixes of y, output = position of the suffix





#### Trie of suffixes







#### **Forks**

Introduction

Insertion of u = y[i ... n - 1] in the structure accepting longer suffixes


- **Head** of u: longest prefix y[i..k-1] of u occurring before i
- **Tail** of u: rest y[k ... n-1] of suffix u
- y = ababbb; head of abbb is ab; tail of abbb is bb
- Fork any node that has outdegree 2 at least, or that both has outdegre 1 and is terminal
- **Note**: the node associated with the head of u is a fork initial node is a fork iff y non empty



Laboratoire d'Informatique

de l'Information et des Systèmes

#### **Forks**



**Suffix Automaton** 



Suffix Automaton


#### **Suffix link**

- Function  $s_y$ , suffix link if node p identified with subword av,  $a \in \Sigma$ ,  $v \in \Sigma^*$  $s_{v}(p) = q$ , node identified with v
- Use creates shortcuts used to accelerate heads computations
- Useful for forks only undefined on initial node
- **Note**: if p is a fork, so is  $s_u(p)$



Laboratoire d'Informatique.

de l'Information et des Systèmes







#### **Suffix Tree**

Introduction


Text  $y \in \Sigma^*$  of length nS(y) suffix tree of y: compact trie accepting Suff(y)

- Definition tree obtained from the suffix trie of y by deleting all nodes having outdegree 1 that are not terminal
- Edges labeled by subwords of y instead of letters
- Number of nodes: no more than 2n (if n > 0) because all internal nodes have two children at least and there are at most n external nodes






#### **Suffix Tree**





Introduction

Labels represented by pairs (pos, Length)



- Requires to have y in main memory
- Size of S(y): O(n)

Laboratoire



Introduction

### Scheme of suffix tree construction

```
Suffix-tree(y)
     T \leftarrow \text{New-tree}()
  2 for i \leftarrow 0 to n-1 do
  3
            find fork of head of y[i ... n-1] using
               FAST-FIND from node s[r], and then SLOW-FIND
            k \leftarrow \text{position of tail of } y[i \dots n-1]
            if k < n then
                  q \leftarrow \text{New-state}()
                  Adi[fork] \leftarrow Adi[fork] \cup \{((k, n-k), q)\}
  8
                  output[q] \leftarrow i
  9
            else output[fork] \leftarrow i
 10
      return T
```


Adjacency-list representation of labeled arcs





### Straight insertion

 Insertion of suffix ababbb is done by letter comparisons from the initial node (current node)



- It leads to create node 3 which suffix link is still undefined.
- and node 4 associated with suffix ababbb at position 2
- Head is abab, tail is bb




**Suffix Automaton** 



Introduction

### **Straight insertion**




### Slow find

```
SLOW-FIND(p, k)
       while k < n and TARGET(p, y[k]) \neq NIL do
             q \leftarrow \text{Target}(p, y[k])
             (i,\ell) \leftarrow label(p,q)
             i \leftarrow i
  5
             do i \leftarrow i+1
                   k \leftarrow k + 1
             while i < j + \ell and k < n and y[i] = y[k]
  8
             if i < j + \ell then
  9
                    Adj[p] \leftarrow Adj[p] \setminus \{((j,\ell),q)\}
                    r \leftarrow \text{New-state}()
 10
 11
                   Adj[p] \leftarrow Adj[p] \cup \{((j, i - j), r)\}
                   Adj[r] \leftarrow Adj[r] \cup \{((j+i-j,\ell-i+j),q)\}
 12
 13
                   return (r, k)
 14
             p \leftarrow q
 15
       return (p, k)
```

### New suffix link


 $\bullet$  Computing  $s[3] = s_y(3)$  remains to find the node associated with bab



- Arc (0, (1,7), 2) is split into (0, (1,3), 5) and (5, (4,4), 2)
- Execution in constant time (here)
- In general, iteration in time proportional to the number of nodes along the path (and not proportional to the length of the string)



#### **New suffix link**




### Fast find

```
FAST-FIND(r, j, k)
       \triangleright computes TARGET(r, y[j ... k-1])
      if i \ge k then
             return r
       else q \leftarrow \text{Targer}(r, y[j])
  5
             (i', \ell) \leftarrow label(r, q)
  6
             if i + \ell \leq k then
                    return FAST-FIND(q, j + \ell, k)
             else Adj[r] \leftarrow Adj[r] \setminus \{((j',\ell),q)\}
  8
  9
                    p \leftarrow \text{New-state}()
                    Adi[r] \leftarrow Adi[r] \cup \{((j, k - j), p)\}
 10
                    Adi[p] \leftarrow Adi[p] \cup \{((j'+k-j,\ell-k+j),q)\}
 11
 12
                    return p
```

Introduction

#### **Next insertion**

End of insertion of suffix babbb




- Execution in constant time
- Head is bab, tail is bb





Laboratoire d'Informatique de Traitement


de l'Information et des Systèmes



Introduction

#### Scheme for insertion

• Scheme for the insertion of suffix  $y[i..n-1] = u \cdot v \cdot w \cdot z$ 



- It first computes p = Target(s[r], v) with Fast-Find (if necessary)
- then the fork of the current suffix with SLOW-FIND




### Complete algorithm

```
Suffix-tree(y)
       T \leftarrow \text{New-tree}()
  2 s[initial[T]] \leftarrow initial[T]
  3 (fork, k) \leftarrow (initial[T], 0)
       for i \leftarrow 0 to n-1 do
              k \leftarrow \max\{k, i\}
              if s[fork] = NIL then
                     r \leftarrow \mathsf{parent} \ \mathsf{of} \ \mathit{fork}
  8
                     (i, \ell) \leftarrow label(r, fork)
                     if r = initial[T] then
                           \ell \leftarrow \ell - 1
 10
 11
                     s[fork] \leftarrow \text{FAST-FIND}(s[r], k - \ell, k)
              (fork, k) \leftarrow \text{SLOW-FIND}(s[fork], k)
 12
 13
              if k < n then
 14
                     q \leftarrow \text{New-state}()
                     Adj[fork] \leftarrow Adj[fork] \cup \{((k, n - k), q)\}
15
 16
                     output[q] \leftarrow i
              else output[fork] \leftarrow i
 17
 18
       return T
```

### **Running time**

Scheme for insertion



- Main iteration increments i, which never decreases
- Iteration in FAST-FIND increments j, which never decreases
- Iteration in SLOW-FIND increments k, which never decreases
- Basic operations run in constant time or in time  $O(\log \operatorname{card} \Sigma)$

#### Theorem

Execution of Suffix-tree(y) = S(y) takes  $O(|y| \times \log \operatorname{card} \Sigma)$  time in the comparison model.



#### **Plan**

- Suffix Automaton
- Compact Suffix Automaton






Introduction

#### **Suffix Automaton**

Text  $y \in \Sigma^*$  of length n $\mathcal{A}(y) = \text{minimal deterministic automaton accepting } Suff(y)$ 

Minimization of the trie of suffixes



- ullet States are classes of factors (subwords) of y
- Size:


$$n+1 \leqslant \#states \leqslant 2n-1$$
  
 $n \leqslant \#arcs \leqslant 3n-4$ 




Introduction

#### Maximal size

Maximal number of states



Maximal number of arcs






#### Suffix link

Introduction

• Function  $f_y$ , suffix link let  $p = \text{Target}(initial[A], v_i), v \in \Sigma^+$  $f_u(p) = \text{Target}(initial[A], u,)$ , where u is the longest suffix of v occurring in a different right context




- s[1] = 0, s[2] = 1, s[3] = 3'', s[3''] = 3', s[3'] = 0, s[4] = 4'', s[4''] = 3', s[5] = 1, s[6] = 3'', s[7] = 4''.
- Suffix path example for state 7: (7, 4'', 3', 0), sequence of terminal states
- Use same but more efficient than suffix link in suffix trees





### One step (1)

ullet From  $\mathcal{A}(\mathtt{ccccbbccc})$  to  $\mathcal{A}(\mathtt{ccccbbcccd})$ 




• New arcs from states of the suffix path (9, 3, 2, 1, 0).





### One step (2)

Introduction



• Link 3 = s[9] and solid arc (3, c, 4) (not a shortcut) then, s[10] = TARGET(3, c) = 4



## One step (3)

• From A(ccccbbccc) to A(ccccbbcccb)

• 0 c 1 c 2 c 3 c 4 b 5 b 6 c 7 c 8 c 9

• b b b 5 c

• Link 3 = s[9], non-solid arc (3, b, 5), cccb suffix but ccccb not state 5 is cloned into 5'' = s[10] = s[5], s[5''] = 5' arcs (3, b, 5), (2, b, 5) et (1, b, 5) are redirected onto 5''




### **Operations on indexes**

#### Text y of length n

- Index implemented by suffix tree or suffix automaton of y memory space O(n), construction time  $O(n \times \log \operatorname{card} \Sigma)$
- String matching searching y for x of length m: time  $O(m \times \log \operatorname{card} \Sigma)$ number of occurrences of x in y: same complexity after O(n)preprocessing
- All occurrences finding all occurrences of x in y: time  $O(m \times \log \operatorname{card} \Sigma) + |output|)$
- Repetitions computing a longest subword of y occurring at least k times: time O(n)
- Marker computing a shortest subword of y occurring exactly once: time O(n)



### **Saving space**



#### **Plan**

- **Suffix Automaton**
- 4 Compact Suffix Automaton






### **Compact Suffix Automaton**

Text  $y \in \Sigma^*$  of length n

Introduction


 $A^{c}(y) = \text{compact minimal automaton accepting } Suff(y)$ 

• Compaction of A(y), or minimization of S(y)



y[i]b

• Linear size: O(n)





#### Direct construction of CSA

Suffix Automaton

Similar to both

- Suffix Tree construction
- Suffix Automaton construction
- Sequential addition of suffixes in the structure from the longest to the shortest
- Used features:
  - "slow-find" and "fast-find" procedures
  - suffix links
  - solid and non-solid arcs
  - state splitting
  - re-directions of arcs
- Complexity:  $O(n \log \operatorname{card} \Sigma)$  time, O(n) space 50% saved on space of Suffix Automaton





#### References



A. Andersson and S. Nilsson.

Introduction

Improved behavior of tries by adaptive branching.

Inf. Process. Lett., 46(6):295-300, 1993.



A. Apostolico et Z. Galil, editors. Pattern matching algorithms. Oxford University Press, 1997.



A. Blumer, J. Blumer, A. Ehrenfeucht, D. Haussler, and R. McConnel.

Linear size finite automata for the set of all subwords of a word: an outline of results.

Bull. Eur. Assoc. Theor. Comput. Sci., 21:12-20, 1983.



M. Crochemore.

Linear searching for a square in a word.

Bull. Eur. Assoc. Theor. Comput. Sci., 24:66-72, 1984.



M. Crochemore, C. Hancart and T. Lecroq. Algorithms on Strings. Cambridge University Press, 20017, to appear.



Introduction



#### References



M. Crochemore and T. Lecroq. Text Searching and Indexing. *Recent Advances in Formal Languages and Applications*, Series: Studies in Computational Intelligence, Volume 25, (2006), Z. Esik, C. Martin-Vide and V. Mitrana editors, pages 43-80, Springer Verlag.



M. Crochemore et W. Rytter. *Jewels of Stringology*. World Scientific, 2002.



M. Crochemore and R. Vérin.

Direct construction of compact directed acyclic word graphs.

In A. Apostolico and J. Hein, editors, *CPM*, LNCS 1264, pages 116–129, Aarhus, Denmark, 1997. Springer-Verlag, Berlin.



M. Farach.

Optimal suffix tree construction with large alphabets.

In FOCS, pages 137-143, Miami Beach, FL, 1997.







I aboratoir

P. Ferragina and R. Grossi.

The string B-tree: A new data structure for string search in external memory and its applications.

J. Assoc. Comput. Mach., 46(2):236–280, 1999.



G. H. Gonnet.

The PAT text searching system.

Report, Department of Computer Science, University of Waterloo, Ontario, 1987.



D. Gusfield. *Algorithms on strings, trees and sequences: computer science and computational biology*. Cambridge University Press, 1997.



S. Inenaga, H. Hoshino, A. Shinohara, M. Takeda, S. Arikawa, G. Mauri, and G. Payesi.

On-line construction of compact directed acyclic word graphs.

In A. Amir and G. M. Landau, editors, *CPM*, LNCS 2089, pages 169–180, Jerusalem, Israel, 2001. Springer-Verlag, Berlin.





#### References



R. W. Irving.

Introduction

Suffix binary search trees.

Technical report, University of Glasgow, Computing Science Department, 1996.



J. Kärkkäinen.

Suffix cactus: a cross between suffix tree and suffix array.

In Z. Galil and E. Ukkonen, editors, *CPM*, LNCS 937, pages 191–204, Espoo, Finland, 1995. Springer-Verlag, Berlin.



J. Kärkkäinen and P. Sanders.

Simple linear work suffix array construction.

In *ICALP*, LNCS 2719, pages 943–955, Eindhoven, The Netherlands, 2003. Springer-Verlag, Berlin.







I aboratoir

D. K. Kim, J. S. Sim, H. Park, and K. Park.

Linear-time construction of suffix arrays.

In R. A. Baeza-Yates, E. Chávez, and M. Crochemore, editors, CPM, LNCS 2676, pages 186-199, Morelia, Michocán, Mexico, 2003. Springer-Verlag, Berlin.



P. Ko and S. Aluru.

Space efficient linear time construction of suffix arrays.

In R. A. Baeza-Yates, E. Chávez, and M. Crochemore, editors, CPM, LNCS 2676, pages 200-210, Morelia, Michocán, Mexico, 2003. Springer-Verlag, Berlin.



U. Manber and G. Myers.

Suffix arrays: a new method for on-line string searches. SIAM J. Comput., 22(5):935-948, 1993.



E. M. McCreight.

A space-economical suffix tree construction algorithm.

J. Algorithms, 23(2):262-272, 1976.



Introduction



#### References



J. I. Munro, V. Raman, and S. S. Rao.

Space efficient suffix trees.

J. Algorithms, 39(2):205-222, 2001.



G. A. Stephen. String searching algorithms. World Scientific Press, 1994.



E. Ukkonen.

Approximate string matching with q-grams and maximal matches.

Theor. Comput. Sci., 92(1):191-212, 1992.



P. Weiner.

Linear pattern matching algorithm.

In *Proceedings of the 14th Annual IEEE Symposium on Switching and Automata Theory*, pages 1–11, Washington, DC, 1973.

